

5 cm

Note
 S/B = Station No 3 Ad
 S/B = Shaft

S/3F = No 3 Level

S/6A = No 6 Load Drive No 3 Ad

PLUMB LINE TRAVERSE SHEET

Station	Bearing	Red Bearing	C.D.	Dist.	N	S	E	W.	N	Totals	S	E	W.
3B 6 S/6A	74°35'	74°38'	N.E.	50.4	13.35		48.59		13.35			48.59	
S/A	256°55'	76°55'	S.W.	21.16		9.79		20.61	8.56			27.98	
S/B	215°25'	35°25'	S.W.	11.32		9.22		6.56			.66	21.42	
S/C (East Plumb line)	147°52'	32°08'	S.E.	12.21		10.34	6.49				11.40	27.91	Station at Plat No 3 Adir No 1 Plat Plumb line in shaft
S/3E	173°44'	6°16'	S.E.	14.22		14.16	1.55				25.16	29.96	Station at Plat No 3 Level
S/3F	131°21'	48°39'	SE	14.90		9.84	11.18				35.00	40.64	
S/3G	761°15'	18°45'	SE	162.45		153.83	52.93				188.93	92.47	along 2' cut
S/B 6 (West Plumb line) S/D	174°02'	5°52'	SE	12.09		12.01	1.23				12.67	22.65	Plumb line in shaft
S/C 16 S/D	252°16'	72°16'	S.W.	5.50		1.67		52.9			12.67	22.67	
S/3E	151°24'	28°36'	S.E.	14.25		12.48	6.80				22.15	29.47	Station at Plat No 3 Level No 3 Plat
S/3F	131°21'	48°39'	S.E.	14.90		9.84	11.18				34.99	40.65	

15-24

Wm Z Hatcher
 8/6/16