



- NOTE :
- 1 DRIVE SIZE IS 3.2m X 3.1m.
 - 2 ALL BOLTS SHOWN ARE 2.4m GROUDED DEFORMED BAR
 - 3 FINAL SHOTCRETE THICKNESS 50mm.
 - 4 ORDER OF SUPPORT INSTALLATION
(a) CONSTRUCTION SHOTCRETE SKIN
(b) GROUDED BAR
(c) MESH
(d) FINAL SHOTCRETE
 - 5 BOLT PATTERN SPACING IS 1.5m. ORIENTATION IS PERPENDICULAR TO DRIVE ADVANCE.
 - 6 WEEP HOLES 2m LONG WILL BE DRILLED THROUGH THE SHOTCRETE AS SHOWN. HOLES WILL BE DRILLED EVERY 10.0m ALONG DRIVE.
 - 7 FOR SETTING DETAILS, SEE DRAWING 01DM01 - 3004

**SECTION
LOOKING NORTH.**

REF. PLAN	GEOLOGY		SCALE 1:25	
	SURVEY		DOLPHIN MINE LOWER WEDGE OREBODY, DECLINE FAULT SEAL DRIVE PROFILE AND SUPPORT PATTERN	
	PLANNING			DRAWING NUMBER
	ROCK MEC.	<i>2/2</i>		01DM01 - 3002
	GRADE CON.			
	DRAFTING	<i>BJ Collis</i>		26-8-80
	T.S.S.	<i>agc</i>	27/8/80	