

0374_3138

5 cm

PRESSURE CELL

INSTALLATION N° 22 (14) LOCATION LOWER PIT STAGE, 2ND LIFT
 DATE 8.6.1980 220 228.97 East
 TYPE KYOWA BE-5KE 563 951.61 North
 UNIT N° BF 0591 -220.58 RL.
 CABLE LENGTH ≈ 30m
 ZERO STRESS READING 278 μ E
 SENSITIVITY 2497 μ E
 CALIBRATION CONSTANT 2000 kg/cm²
 ORIENTATION ≈ VERTICAL

Date	Day	Reading μ E	Δ Stress kPa	Stress kPa	Remarks	Date	Day	Reading μ E	Δ Stress kPa	Stress kPa	Remarks
19.6.81	360	535	154	50.4		4.5.82	676	500			
29.6.81	370	475		38.7		11.5.82	683	505			
13.7.81	384	500		43.6		14.5.82	686	510			
23.7.81	394	510		45.5		18.6.82	721	550			
31.7.81	402	515		46.5		23.6.82	726	510			
5.8.81	407	535		50.4		29.6.82	732	485	200		
10.8.81	412	525	160	48.5		8.7.82	741	495			
14.8.81	416	510		45.5		12.7.82	745	490			
21.8.81	423	519		47.3		22.7.82	755	500			
28.8.81	430	545		52.4		26.7.82	759	500			
1.9.81	434	530		49.4		2.8.82	766	525		+48.46	
11.9.81	444	550		53.4		9.8.82	773	640		+71.02	
14.9.81	447	540		51.4		30.8.82	794	587		+60.62	NEW READOUT SYSTEM IN USE FROM 30/8/82 25/9 to 24/10 this change
21.9.81	454	502		43.9		4 11 82		736 (-119/10)			
28.9.81	461	505		44.5		10 11 82		665			
9.10.81	472	540		51.4		11 11 82		641			
13.10.81	476	510	170	45.5		12 11 82		642			
23.10.81	486	505		44.5		18 11 82		682			
26.10.81	489	502		43.9		19 11 82		701			
4.11.81	498	500		43.6		22 11 82		627			
18.11.81	512	535	174	50.4		23 11 82		617			
4.12.81	528	510	176	45.5		24 11 82		614			
10.12.81	534	495				26 11 82		615			
17.12.81	541	505				1 12 82		612			
23.12.81	547	500				2 12 82		612			
4.1.82	559	500	180			3 12 82		615			
12.1.82	567	500				6 12 82		619			
18.1.82	573	490				7 12 82		608			
26.1.82	581	480	183			10 12 82		728		+88.29	
18.2.82	601	485	185			13 12 82		620			
26.2.82	609	550				15 12 82		700			
18.3.82	627	505				22 12 82		680			
23.3.82	634	485				24 12 82		684			
1.4.82	643	480				5 1 83		663			
6.4.82	648	480	190			10 1 83		602			
13.4.82	655	500	192			14 1 83		614			
19.4.82	661	520				2 2 83		630			
28.4.82	670	505				7 2 83		628		+68.67	