



PRESSURE CELL

INSTALLATION N° 23 (15) LOCATION LOWER PIT STAGE, 2ND LIFT
 DATE 8-6-1980 220 219.84 East
 TYPE KYOWA BE-5KE 563 944.59 North
 UNIT N° BE 9274 -220.27 m RL.
 CABLE LENGTH ≈ 30m
 ZERO STRESS READING 359 μE
 SENSITIVITY 2499 μE
 CALIBRATION CONSTANT 2000 kg/cm²
 ORIENTATION ≈ VERTICAL

Date	Day	Reading μE	Δ Stress kPa	Stress kPa	Remarks	Date	Day	Reading μE	Δ Stress kPa	Stress kPa	Remarks
29-6-81	370	620		51.2		11-5-82	683	655?			
13-7-81	384	640		55.1		14-5-82	686	660			
23-7-81	394	625		52.2		18-6-82	721	680			
31-7-81	402	630		53.2		23-6-82	726	640			
5-8-81	407	635		54.2		29-6-82	732	640	200		
10-8-81	412	635		54.2		8-7-82	741	640			
14-8-81	416	645		56.1		12-7-82	745	630			
21-8-81	423	650		57.1		22-7-82	755	625			
28-8-81	430	670		61.0		26-7-82	759	625			
1-9-81	434	650		57.1		2-8-82	766	660			
11-9-81	444	665		60.0		9-8-82	773	680		+62.98	
14-9-81	447	670		61.0		30-8-82	794	908		+68.47	NEW READOUT SYSTEM IN USE FROM 30/8/82
21-9-81	454	635		54.2		4 11 82		-9105 (kV)			25/9 to 24/10 Min. close
28-9-81	461	635		54.2		10 11 82		-770			
9-10-81	472	665		60.0		11 11 82		749			
13-10-81	476	645		56.1		16 11 82		3522			
23-10-81	486	645		56.1		18 11 82		809			
26-10-81	489	640		55.1		19 11 82		864			
4-11-81	498	635		54.2		22 11 82		744			
18-11-81	512	670 ¹⁷⁴		61.0		23 11 82		734			
4-12-81	528	640 ¹⁷⁶		55.1		24 11 82		730			
10-12-81	534	620				26 11 82		731			
17-12-81	541	630				1 12 82		730			
23-12-81	547	630				2 12 82		724		+71.61	
4-1-82	559	625				3 12 82		728			
12-1-82	567	640				6 12 82		733			
18-1-82	573	625				7 12 82		718			
26-1-82	581	610 ¹⁸³				10 12 82		730			
18-2-82	604	620 ¹⁸⁵				13 12 82		736			
26-2-82	609	685				22 12 82		817			
16-3-82	627	645				24 12 82		825			
23-3-82	634	625				5 1 83		806			
1-4-82	643	610				10 1 83		743			
6-4-82	648	620 ¹⁹⁰				14 1 83		752			
13-4-82	655	650 ¹⁹²				2 2 83		757			
19-4-82	661	670				7 2 83		758			
28-4-82	670	670				15-2-83		779			
4-5-82	676	660		+59.05		22-2-83		761		+78.87	