



PORE PRESSURE CELL

INSTALLATION N° 25 LOCATION LOWER PIT STAGE, 2ND LIFT
 DATE 8.6.1980 East
 TYPE KYOWA BP-2KC North
 UNIT N° YE 3086 R.L.
 CABLE LENGTH ≈ 30m
 ZERO STRESS READING -45 μE
 SENSITIVITY 1800 μE
 CALIBRATION CONSTANT 1111 kg/cm²
 ORIENTATION

Date	Day	Reading μE	Δ Stress kPa	Stress kPa	Remarks	Date	Day	Reading μE	Δ Stress kPa	Stress kPa	Remarks
28-9-81	461	45	168	9.8		4-11-82		66 (70) ^{KY}			25/3 to 24/10 Miss closure
9-10-81	472	85	169	4.2		10 11 82		-8			
13-10-81	476	35	170	8.7		11 11 82		-19			
23-10-81	486	40		9.3		15 11 82		-69			
26-10-81	489	30		8.2		16 11 82		-116			
4-11-81	498	30		8.2		19 11 82		-102			
8-11-81	512	60	174	11.4		22 11 82		-61			
4-12-81	528	40	176	9.3		23 11 82		-38			
10-12-81	534	35				24 11 82		-30			
17-12-81	541	20				26 11 82		-28			
23-12-81	547	20				1 12 82		-12			
4-1-82	559	25	180			2 12 82		16			
12-1-82	567	20				6 12 82		-16			
18-1-82	573	40				7 12 82		-13			
26-1-82	581	10	183			10 12 82		4			
18-2-82	601	0	185			13 12 82		4			
26-2-82	609	0				15 12 82		20			
16-3-82	627	10				21 12 82		33			
23-3-82	634	0				24 12 82		38			
1-4-82	643	35	189			5 1 83		30			
7-4-82	649	5	191			14 1 83		18			
13-4-82	655	15	192			2 2 83		25			
19-4-82	661	40				7 2 83		23			
28-4-82	670	25				15-2-83		24			
4-5-82	676	15				22-2-83		21			
11-5-82	683	30				4 3 83		21			
14-5-82	686	30				9 3 83		11			
18-6-82	721	20				14 3 83		22			+7.30
23-6-82	726	20				21 3 83		8			+5.77
29-6-82	732	30		+8.20		6.4.83		-19			+2.83
8-7-82	741	30				20 4 83		-24			
12-7-82	755	40		+9.30		21 4 83		-33			
22-7-82	NOT READING				SWITCH FAULTY	3 5 83		-42			+0.327
26-7-82	759	20				11 5 83		-58			-1.42
2-8-82	766	40				13 5 83		+32			
30-8-82	794	33			← NEW READOUT SYSTEM IN USE FROM 30/8/82	19 5 83		-64			
6-9-82	801	29				30 5 83		-82			
13-9-82	808	45				6.6.83		-84			-4.25