



UNIVERSAL WIRE EXTENSOMETER

NUMBERS : 60-64

INSTALLATION DETAILS

PILLAR S3759

BEARING ~135°

R.L.

DATE : 7-11-82

LOCATION :

SENSITIVITY .0092 mm/unit change.

DATE	DAY	NO. 60			NO. 61			NO. 62			NO. 63			NO. 64		
		V _{x100}	ΔV _{x100}	mm	V ₁₀₀	ΔV ₁₀₀	mm									
1.8.83		355			250			172			155			62		
9.8.83		306	-49		3764			147			123			25		
19.8.83		304			1013			-3093			122			24		
30.8.83		301	-54	-0.497	214	-36	-0.331	136	-36	-0.331	120	-35	-0.322	23	-39	-0.359
20.9.83		299			209			141			119			19		
11.10.83		294			199			131			115			13		
27.10.83		272			185			124			105			10		
8.11.83		266	-89	-0.819	178	-72	-0.662	118	-54	-0.497	102	-53	-0.487	9	-53	-0.487
24.11.83		262			173			117			99			5		
5.12.83		260			169			107			96			4		
10.4.84		261	-94		176	-74		119	-53		97	-58		-12	-74	
22.5.84		-1402			-1564			-3125			-1166			-1246		
		-1589			-3201			-3202			-3199			-3162		