



CO-ORDINATES						
POINT	N	E	R/L	LINE	DISTANCE	BEARING
A	10 464	40 387.3	F 885.1	A-B	15.2	090° 00'
B	10 464	40 402.5	F 887.0	B-C	28.2	180° 00'
C	10 435.8	40 402.5	F 887.0	C-D	14.4	270° 00'
D	10 447.5	40 442.0	F 889.6	D-E	16.0	180° 00'
E	10 447.5	40 427.6	F 897.7	E-F	10.0	270° 00'
F	10 431.5	40 427.6	F 897.7	F-G	23.8	0° 00'
G	10 431.5	40 417.4	F 895.0	G-H	4.5	270° 00'
H	10 455.5	40 417.4	F 891.0	H-I	4.5	270° 00'
I	10 431.5	40 412.9	F 895.0	TOTAL	99.6m	

U-CUT FLOOR BACK THE 2ND AND 3RD LIFTS MAY PASS OVER THE DECLINE PROVIDED COVER OF AT LEAST 7 METRES IS MAINTAINED. ORE BELOW 895m COULD BE OBTAINED BY SLOTTING UP FROM K39.

REVISIONS		APPROVAL	INITIALS	DATE
NO	DATE			

APPROVAL	INITIALS	DATE
TECHNICAL SERVICES SUPT.	W. J. ...	24/11/81
GENERAL MINING SUPT.
MINE SUPT.	Math D	23/11/81
SNR. SURVEYOR	B.H.L.	25/11/81
SNR. GEOLOGIST
PLANNING	AD7	18-11-81
ROCK MECHANICS	...	24.11.81

SCALE 1:250

notes: 1. While mining 2' x 3' lift, drain 246 and P47.
2. Pillar nos 'x' can be mined depending on grade.

LOCATION: BOLD HEAD MINE

SUBJECT: C1 P43 CUT AND FILL STOPE

ACCESS 10390N-10470N BETWEEN 887m AND 903m R.L. (WITH OPTION TO SLOT WESTERN SIDE TO 872m)

KIS KING ISLAND SCHEELITE
A Member of the Peabody Energy Group

GRASSY KING ISLAND

PRELIMINARY FINAL

PLAN NUMBER: 03BH04 - 1017