

Abstract

DELTA1 and DELTA2 are FORTRAN triangular variation plotting programs. The latter is used for plotting sand and gravel diagrams whereas DELTA1 is for general use.

OUTLINE OF PROGRAMS

The programs are written in FORTRAN for the Perkin-Elmer 6/16 and Complot DP-8 plotter. Program DELTA2 differs from DELTA1 only by the inclusion of program lines to produce additional lines used for sand and gravel resource plots (fig. 2).

Data is input as X, Y, and Z real positive values, which are normalised by the program prior to plotting.

Input is either from a previously compiled data file, or by direct entry at run time. Titling and labelling information may either be included in the data file or entered at run time.

A total of 16 different plot symbols may be used (fig. 1), and each point may be numbered if required. In addition to the plotter output a listing of the data may be printed with reference numbers corresponding with those used for labelling the plot points.

The scale of the plot is entered at run time, together with the offset from the right-hand margin of the plot paper (to make the best use of the plot paper). For publication the base of the triangle will normally be 148 mm, for one plot per page or 100 mm for two plots per page.

DATA FILE SPECIFICATIONS

Data files are best created using EDITOR as this permits the use of a format line which simplifies keyboarding. HLPTED gives full details for using EDITOR. The following outline gives the instructions for creating a new data file:

- | | | |
|------|---|---|
| (1) | AL DATA, 2, 1, 72 | Allocate output file |
| (2) | AS 0999 | Assign core buffer |
| (3) | AS 0422 | Assign printer |
| (4) | RU EDITOR | Run the editor |
| (5) | Wait for prompt
(C><IS><IL> LC=0) | |
| (6) | FL, RETURN | |
| (7) | CXXXXXXXXxYYYYYYyyZZZZZZzzMAL X-----Y-----Z-----+-----> | Type in format line |
| (8) | CR, RETURN | Enter input mode |
| (9) | Enter text | Terminate entry by] |
| (10) | EX, RETURN, 1, RETURN | Write to output file (wait for prompts) |
| (11) | PA, RETURN, CL | Exit program and close file |

The format line (see 7 above) consists of two parts, separated by a space. The left hand part is for numerical data (X, Y, Z) and codes; the right hand part is for text entry. The FORTRAN format is:

A1, 3F8.2, I2, I1, 1X, 32A1

The sequence of records and the code letters (col. 1 of each record) identifying the record type are:

- (1) File name (F)
- (2) Titling, labelling or data (T, X, Y, Z or blank)
- (3) End of file (E)

The various types of record are as follows:

- (1) FILENAME (F in col. 1). The name of the file is entered in cols. 30-44 under X-----Y-----Z.
- (2) TITLE OF PLOT (T in col. 1). The title to be printed under the plot diagram is entered in cols. 30 to 58, under X-----Y-----Z-----+----->
- (3) LABELLING OF AXES (X, Y or Z in col. 1). These records provide the labels for the apices of the triangle. Enter the appropriate code in col. 1 and the label in cols. 30-44, under X-----Y-----Z. To preserve alignment left justify the X label, centre the Y label and right justify the Z label. Text entered beyond col. 44 is ignored.
- (4) DATA (col. 1 must be blank). Enter X, Y and Z values in F8.2 format under XXXXXXxxYYYYYYyyZZZZZZzz in cols. 2-25. If required cols. 30-44 can be used to enter an identifier which will be included in the listing on the printer at run time. The plot symbol to be used is entered under MA (right justified) in cols. 26 and 27. Valid numbers are 0 to 15. 1 to 15 are as in MARKER, 0 is a dot, 15 is a circle. Enter a 1 under L (col. 28) if points are to be labelled with a number, otherwise leave this column blank. The labelling code may be overridden at run time.
- (5) END OF FILE. Enter E in col. 1 and the plotter restore code required in col. 28 (under L): this will normally be 2.

RUNNING THE PROGRAM

- (1) AC DATA, 1 Activate data file to LU 1 (or AS 0120 for VDT input).
- (2) AS 0899 Assign core buffer used for PWRITE.
- (3) AS 0912 Assign plotter. Ensure plotter is on line, etc.
- (4) AS 0422 Assign printer for listing (or AS 0420 to list on VDT).
- (5) RU DELTA1 (or RU DELTA2 for sand and gravel plots. Run program.
- (6) Enter distance in mm. from right hand of paper to base of triangle - valid values are 20 to 750.
- (7) Enter length of base of triangle required, normally 148 mm for publication use. The sum of this value and the offset entered under (6) may not exceed 900 mm.
- (8) Enter control code for labelling. Valid codes are zero (obey data file codes); 1 (override data file codes, label all points) or 2 (override data file codes, no point labelling).
- (9) Input file will now be read and a listing made on LU 4; the outline of the triangle will be drawn and the points plotted. If titling and labelling information has not been included in data file, this may be entered following the appropriate prompts.

If there is no input file, data must be entered from the VDT




Figure 1.

EXAMPLES OF PLOT SYMBOLS

35-5




Figure 2.

EXAMPLE OF TITLING FOR DELTA2