

1985/10. TASROCK - A computer-based catalogue for Tasmanian rocks

R.G. Richardson

Abstract

The program suite described is designed to provide a unified Tasmanian rock catalogue. Provision is included for searching the collections of a number of organisations, adding to the data, and producing a comprehensive manual.

INTRODUCTION

A number of organisations within Tasmania maintain rock collections (e.g. Hydro-Electric Commission, Department of Mines, Tasmanian Museum and Art Gallery, University of Tasmania) but there is no easy way of locating all specimens of a particular type or from a particular area. A committee from the Department of Mines and the University of Tasmania produced a coding sheet containing all required "basic" data, and a suite of FORTRAN 77 programs has been written to provide the required functions.

USING THE PROGRAMS

Data coding

Data are coded onto standard sheets (Appendix 1) using the current lists of standard abbreviations (printed using the program GUIDER), the following notes and the details in Appendix 2.

- (a) Registration number - up to 8 characters allowed.
- (b) Generic type - up to 2 characters in accordance with the standard list
- leave blank if not known
- (c) Age - up to 3 characters in accordance with the standard list
- leave blank if not known
- (d) Rock name - up to 10 characters in accordance with the standard list
- leave blank if not known
- (e) Rock unit - up to 8 characters in accordance with the standard list
- leave blank if not known
- (f) Location data - every attempt must be made to complete the fields for state and latitude/longitude or grid coordinates
- (g) Collector - up to 3 characters in accordance with the standard list
- leave blank if not known
- (h) Field number - up to 6 characters
- leave blank if not known
- (i) Year of collection - 4 characters
- leave blank if not known

- (j) Locality name - up to 12 characters
- leave blank if not known
- (k) Holder - 1 character in accordance with the standard list
- (l) Mineral name - up to 8 characters in accordance with the standard list
- leave blank if not known
- (m) Modifier - two sets of up to 4 characters in accordance with the standard list
- leave blank if not known
- (n) Treatment - four sets of up to 2 characters in accordance with the standard list
- leave blank if not known
- (o) Reference - up to four sets of 5 characters
- leave blank if not applicable
- (p) Extended reference - up to 40 characters
- leave blank if not applicable

Data entry

Data are input by typing ROCKADD. As the data will be entered for only one holder at a time, the program firstly requests the holder. Other data requested is in accordance with the coding forms. To terminate input type END in response to the request for registration number. At the end of input a proof-sheet is output and the data saved in file ROCKTMP.TMP. Corrections may be made to this file using the standard editing facilities and a new proof sheet printed and checked.

Data checking

Data are checked for validity of standard abbreviations by typing ROCKCHEK. Any departures from the standard abbreviations will be listed on the printer along with the line number in the ROCKTMP.TMP file and the column number on the line(s). Errors should be corrected then checked again.

Data merging

After checking, data are merged with the main file by typing ROCKMRGE.

Data sorting

Provided that there are not too many entries for a particular holder (32000) the entries for that particular holder may be sorted into ascending registration number order by typing ROCKSORT.

Data searching

The search phase is entered by typing ROCKSRCH. An entry will be retrieved only if the specified search options are matched.

The program requests the following data:

- (i) Send output to VDU - Y if entries found are to be listed on the VDU.
Provision exists for terminating the VDU listing if necessary.
- (ii) Send output to printer - Y if listing of retrieved entries is to be printed. If more than 1000 entries are found printing can be terminated at the 1000th entry.
- (iii) Search by registration number - Y to search only a range of registration numbers for a particular holder. Leave blank otherwise.
 - (a) Holder - reply with a valid holder abbreviation
 - (b) Starting registration number - a number valid for the holder selected, e.g. 1234 for the University, 77-12 for the Mines Department
 - (c) Finishing registration number - a number valid for the holder selected and greater than or equal to the starting number, e.g. 1287 for the University, 79-28 for the Mines Department.
- (iv) Generic type - one or more standard abbreviations on a line each abbreviation terminated by /. If this option is not required leave the line blank.
e.g. SE/ME/ sedimentary or metamorphic
- (v) Age - details as for generic type
- (vi) Rock name - details as for generic type
- (vii) Rock unit - details as for generic type
- (viii) State - details as for generic type
- (ix) Search by co-ordinates or latitude/longitude - C to search within an area of Tasmania specified by grid co-ordinates
 - L to search within an area (including Tasmania if necessary) specified by latitude and longitude
 - leave blank if neither is required
 - (a) If search by co-ordinates is specified the western, eastern, southern and northern boundaries are requested. The co-ordinates should be specified in metres with the assumed digit 5 on northings omitted.
 - (b) If search by latitude/longitude is specified the southern, northern, western and eastern boundaries are requested. The latitudes and longitudes are specified as on the input sheet.
- (x) Collector - details as for generic type

- (xi) Search by year - Y to search only a range of years of collection
 - leave blank otherwise
 - (a) Starting year - a four digit integer specifying the starting year
 - (b) Finishing year - a four digit integer specifying the finishing year and greater than or equal to the starting year
- (xii) Holder - details as for generic type
- (xiii) Mineral - details as for generic type
- (xiv) Modifier - details as for generic type
- (xv) Treatment - details as for generic type

A sample printout is given in Appendix 3.

Listing standard abbreviations

A list of standard abbreviations may be produced by typing GUIDER. A sample list is shown in Appendix 4.

THE PROGRAMS

ROCKADD (Appendix 5)

This program accepts data from the keyboard and copies it to a file in a format suitable for editing. Prompts are used to guide the user. The file created (ROCKTMP.TMP) may be edited using the standard editing facilities.

ROCKCHEK (Appendix 6)

This program checks the data in ROCKTMP.TMP against files of standard abbreviations to ensure that abbreviations used are valid. The program uses the following files:

- ROCKTYPE.DAT 50 character records. The first two characters are the abbreviation, the third is a blank and the remainder are the full description.
- ROCKAGES.DAT 50 character records. The first three characters are the abbreviation and the balance are as for ROCKTYPE.DAT.
- ROCKNAME.DAT 30 character records. The first ten characters are taken as the abbreviation.
- ROCKUNIT.DAT 30 character records. The first eight characters are taken as the abbreviation.
- COLECTOR.DAT 40 character records. The first three characters are the abbreviation and the balance are as for ROCKTYPE.DAT.
- MINERALS.DAT 30 character records. The first eight characters are taken as the abbreviation.
- MODIFIER.DAT 30 character records. The first four characters are the abbreviation and the balance are as for ROCKTYPE.DAT.

TRTMENT.DAT 50 character records. The first two characters are the abbreviation and the balance are as for ROCKTYPE.DAT.

ROCKMRGE (Appendix 7)

The data from ROCKTMP.TMP are read and added to the main data file (ROCCAT.DAT). Entries for the Department of Mines rock catalogue are prefixed with a code to indicate the year.

ROCKSORT (Appendix 8)

The data for a particular holder may be sorted into ascending registration number order provided that there are not too many (more than 32 000) entries for that holder.

ROCKSRCH (Appendix 9)

The data-base is searched for the occurrence of specified strings or numeric values using program SEARCHER. Output may be to the VDU, printer or both.

GUIDER (Appendix 10)

This program produces a guide to the abbreviations used within the data-base. With the exception of age and generic type abbreviations, the lists are ordered alphabetically. GUIDER uses all the files used by ROCKCHEK and in addition uses the 80 character record file INTRODUC.DAT.

[18 March 1985]

7/51

APPENDIX 2

Tasrock catalogue - computer entry sheet

1. REGISTRATION NUMBER:- eight (8) characters allowed - searchable

Mines Dept. 2 digits - up to 4 digits

e.g. 63 - 131

University

Entry No.

e.g. 12345

2. GENERIC TYPE:- two (2) characters allowed - searchable
- two (2) letters, e.g.

- IG - Igneous
- SE - Sedimentary
- ME - Metamorphic
- VO - Volcanic
- PY - Pyroclastic
- MS - Metasedimentary
- MI - Meta-igneous
- HY - Hydrothermal
- XE - Xenolith, xenocryst
- ML - Mineral
- OR - Ore
- GO - Gossan
- SO - Soil
- MC - Mineral concentrate
- VE - Vegetation, litter
- ET - Extraterrestrial

3. AGE:- three (3) characters allowed - searchable
- (2 or 3 common), e.g.

- DE Devonian
- JUL Lower (or Early Jurassic)
- MI Miocene
- OR Ordovician
- ORU Upper (or Late) Ordovician

(see Penny Green or R.S. Bottrill for full list)

4. ROCK NAME:- ten (10) characters allowed (not 11 as on first printing
of entry sheet) - searchable
- leave off last letters as necessary, e.g.

CONGLOMERA = CONGLOMERATE
GABBRO = ✓

5. ROCK UNIT:- eight (8) characters allowed - searchable
- leave off last letter as necessary

- BADGERHE (AD)
- BATHURST
- BURNIE
- CRIMSON
- DENISON
- DUNDAS
- ELDON
- FAULKNER
- GORDON
- JUNEE
- MATHINNA
- MT READ
- OONAH
- OWEN
- PARMEENE (R)
- ROCKYCAP (E)
- SMITHTON

6. STATE AND QUADRANGLE:- A = one (1) character, then B = five (5) characters

A 0 for Tas - then anticlockwise
1 = VIC, 2 = N.S.W. (including A.C.T.), 3 = QLD, 4 = N.T.,
5 = W.A., 6 = S.A. (A.C.T. = N.S.W.)

9 for overseas - then abbreviate country name, e.g.
CANDA = Canada (searchable)

B _____ insert quadrangle number for Tasmania using
1:50 000 sheets, if possible e.g.
7916S = Smithton

Use latitudes and longitudes for all areas outside Tasmania.

7. MAP CO-ORDINATES (searchable within Tasmania):-

Use metric co-ordinates, if available
[If in yards - put at bottom of sheet - will be converted in future]

Latitude and longitude used outside Tasmania (searchable everywhere).
Cross out N,S,E,W as appropriate.

For Metric co-ordinates - universal grid reference
use at least three (3) digits
i.e. 357...mE, 486...mN (The Nut, Stanley)
this will give location to nearest 1000 m. (The assumed digit 5
on northing is omitted)
[If more precise location is required use extra digits e.g. 3578...
4861.. to nearest 100 m]

8. COLLECTOR:- three (3) characters allowed

Use two (2) or three (3) as appropriate (searchable)
e.g.

F.A.	F. Ahmad	J.N.E.	J.N. Elliston
A.V.B.	A.V. Brown	R.J.F.	R.J. Ford
S.W.C.	S.W. Carey	D.I.G.	D.I. Groves

9. FIELD NUMBER:- six (6) characters

any combination of letters and numbers up to 6 (not searchable)
e.g. N56, CBDG42 etc.

Leave off later characters if necessary to preserve meaning
e.g. ROS PK7 = Rosny Park 7

10. YEAR OF COLLECTION:- four (4) characters, e.g. 1979 (searchable).

11. LOCALITY NAME:- twelve (12) characters (non-searchable)

abbreviate to preserve sense of description, e.g.
(i) 3 MLS E BLK STMP = 3 miles east of Black Stump
(ii) DELORAIN = ✓

12. HOLDER:- one (1) character (searchable)

M = Mines Dept., U = University, T = Tas. Museum, H = H.E.C.,
Q = Queen Victoria Museum, etc.

13. MINERAL NAME:- eight (8) characters allowed (searchable)

Leave off last letters if necessary, e.g.
CHALCOPY = Chalcopyrite RUTILE = ✓
MOLYBDEN = Molybdenite SCHEELIT = Scheelite

14. MODIFIER:- two (2) sets of four (4) characters allowed (searchable)
 - generally adjectives - abbreviate to preserve sense, e.g.
 ARG L = Argillaceous
 CAL C = Calcareous
 OPH C = Ophitic

If necessary use 2 x 4 characters, e.g.

GLOM PORP = Glomeroporphyritic

SUBT RACH = Subtrachytic

15. TREATMENT:- four (4) sets of two (2) characters (searchable)
 Choose from list below:-

AL	Atterberg limits	OT	oriented thin section
AP	acetate peel	PD	powdered specimens
CA	chemical analysis	PF	petrofabrics
CS	crushed specimen	PH	photo
DC	drill core	PM	probe mount
DE	density	PN	palynology
DP	doubly polished section	PR	polished hand specimen
DT	D.T.A.	PS	polished section
DX	X-ray disc	PT	polished thin section
FI	chips for fluid inclusion studies	PX	X-ray pill
GS	grain size analysis	PY	palaeontology
HM	heavy mineral separation	RE	resistivity
IS	isotope study	RO	hand specimen
LS	load strength	SU	susceptibility
MA	modal analysis	SV	seismic velocity
MS	mineral separation	TS	thin section

16. REFERENCE:- use up to four (4) sets of five (5) characters or write below - still under consideration - (must recognise journal and volume at least) e.g.

GEOL-SURV-BULL-61--- = Geological Survey Bulletin 61

JOURN, VOLC-, GEOTH, RES14 = Journal of Volcanology and Geothermal Research, vol. 14.

If in doubt write out full reference below 16.

APPENDIX 3
Sample of Printout

SEARCH OPTIONS ARE:
 GENERIC TYPE SE/ME/IG/
 AGE JU/
 ROCK NAME DOLERITE/BASALT/

10-10

REG NO	TYPIAGE	ROCK NAME	ROCKUNIT	ST	QUAD	COL	FLD NO	YEAR	LOCALITY	HLD	MINERAL	MOD1	MOD2	TREATMENT	REG NO	
REFERENCE					EXTRA REFERENCE				LOCATION							
56- 107	IG	JUL	DOLERITE			0	7916S	SWC	DOL1	1956	LAKES AREA	M			DC, DE, DX, PM	56- 107
	BULL GEOL SURV TAS27				TEST OF EXTRA REFERENCE						490000ME	350000MN				
56- 108	IG	JUL	DOLERITE			0		SWC	DOL1	1956	LAKES	M			DC, DE, DX, PM	56- 108
	TEST EXTEN DED REFNO				WITH LOW NUMBER						490000ME	350000MN				
57- 107	IG	JUL	DOLERITE			0	7914N	SWC	DOL2	1956	LAKES DSTRCT	M			DE, DC, DX, PM	57- 107
	BULL GEOL SURV TAS28				AND MORE REFERENCES						492000ME	355000MN				

15/01

11/51

APPENDIX 4

TASMANIAN ROCK CATALOGUE

GUIDE TO INFORMATION STORED

DATE 28 FEB 1985

INTRODUCTION

The abbreviations used in the Tasmanian rock catalogue (TASROK) are outlined in the following lists. Every attempt should be made to use the latest versions of the abbreviations. In the event of additional abbreviations being needed please contact the Mines Department to arrange an update and re-issue to participating groups.

12/51

REGISTRATION NUMBERS

FOR THE MINES DEPT. ROCK CATALOGUE
ASSUMED TO BE OF THE FORM 77-127

FOR THE MINES DEPT. MINERAL CATALOGUE
ASSUMED TO BE OF THE FORM 12345

FOR THE UNIVERSITY ASSUMED TO BE OF THE FORM
12345

GENERIC TYPE

	BLANK FOR NOT KNOWN
IG	IGNEOUS
SE	SEDIMENTARY
ME	METAMORPHIC
VO	VOLCANIC
PY	PYROCLASTIC
MS	METASEDIMENTARY
MI	METAIgneous
HY	HYDROTHERMAL
XE	XENOLITH, XENOCRYST
ML	MINERAL
OR	ORE
GO	GOSSAN
SO	SOIL
MC	MINERAL CONCENTRATE
VE	VEGETATION, LITTER
ET	EXTRATERRESTRIAL

AGE

	BLANKS FOR NOT KNOWN
DE	DEVONIAN
JUL	LOWER (OR EARLY) JURASSIC
MI	MIOCENE
OR	ORDOVICIAN
ORU	UPPER (OR LATE) ORDOVICIAN

ROCK NAMES

BLANKS

BASALT
CONGLOMERATE
DOLERITE
GABBRO
MUDSTONE
SANDSTONE

ROCK UNITS

BLANKS

BADGERHEAD
BATHURST
BURNIE
CRIMSON
DENISON
DUNDAS
ELDON
FAULKNER
GORDON
JUNEE
MATHINNA
MT READ
OONAH
OWEN
PARMEENER
ROCKYCAPE
SMITHTON

LOCATION DATA

STATE	
0	TASMANIA
1	VICTORIA
2	NEW SOUTH WALES (INCLUDING A. C. T.)
3	QUEENSLAND
4	NORTHERN TERRITORY
5	WESTERN AUSTRALIA
6	SOUTH AUSTRALIA
9	OVERSEAS

FOR ALL AREAS OUTSIDE TASMANIA
LATITUDE AND LONGITUDE ARE USED.

WITHIN TASMANIA THE AUSTRALIAN MAP GRID
IS USED WITH AT LEAST THREE (3) DIGITS
IN EACH COORDINATE. THE ASSUMED DIGIT 5 IN
NORTHINGS IS OMITTED

10-14

COLLECTORS

BLANKS=UNKNOWN	:	BLANKS=UNKNOWN
AB1 A V BROWN AND M P MC CLENAGHAN	:	FA F AHMAD
AVB A V BROWN	:	AB1 A V BROWN AND M P MC CLENAGHAN
DIG D I GROVES	:	AVB A V BROWN
FA F AHMAD	:	SWC S W CAREY
JNE J N ELLISTON	:	JNE J N ELLISTON
RJF R J FORD	:	RJF R J FORD
SWC S W CAREY	:	DIG D I GROVES

HOLDERS

PAGE 9

- M DEPARTMENT OF MINES (ROCK CATALOGUE)
P. O. BOX 56
ROSNY PARK
TASMANIA 7018
AUSTRALIA
- N DEPARTMENT OF MINES (MINERAL CATALOGUE)
P. O. BOX 56
ROSNY PARK
TASMANIA 7018
AUSTRALIA
- U GEOLOGY DEPARTMENT
UNIVERSITY OF TASMANIA
G. P. O. BOX 252C
HOBART
TASMANIA 7001
AUSTRALIA

10-15

MINERALS

PAGE 10

BLANKS
CHALCOPYRITE
MOLYBDENITE
RUTILE
SCHEELITE

15/51

MODIFIERS

	BLANKS		ARGL	ARGILLACEOUS
ARGL	ARGILLACEOUS			BLANKS
CALC	CALCAREOUS		CALC	CALCAREOUS
OPHC	OPHITIC		OPHC	OPHITIC
PORP	PORPHYRITIC		PORP	PORPHYRITIC

TREATMENTS

- BLANKS
- AL ATTERBURG LIMITS
- AP ACETATE PEEL
- CA CHEMICAL ANALYSIS
- CS CRUSHED SPECIMEN
- DC DRILL CORE
- DE DENSITY
- DP DOUBLY POLISHED SECTION
- DT D. T. A.
- DX X-RAY DISC
- FI CHIPS FOR FLUID INCLUSION STUDIES
- GS GRAIN SIZE ANALYSIS
- HM HEAVY MINERAL SEPARATION
- IS ISOTOPE STUDY
- LS LOAD STRENGTH
- MA MODAL ANALYSIS
- MS MINERAL SEPARATION
- OT ORIENTED THIN SECTION
- PD POWERED SPECIMEN
- PF PETROFABRICS
- PH PHOTO
- PM PROBE MOUNT
- PN PALYNOLOGY
- PR POLISHED HAND SPECIMEN
- PS POLISHED SECTION
- PT POLISHED THIN SECTION
- PX X-RAY PILL
- PY PALAEOLOGY
- RE RESISTIVITY
- RO HAND SPECIMEN
- SU SUSCEPTIBILITY
- SV SEISMIC VELOCITY
- TS THIN SECTION

17/51

APPENDIX 5

Program ROCKADD

```
*ROCKADD.CSS - FOR RUNNING ROCKADD
#IFX ROCKTMP.TMP; #WRITE ROCKTMP.TMP EXISTS; #CLEAR; #ENDC
* IF THE FILE IS STILL THERE DONT ALLOW ANY ADDING
L ROCKADD; AL ROCKTMP.TMP, IN, 80; AS 7, ROCKTMP.TMP; ST
PRI ROCKTMP.TMP; #WRITE FILE IS ROCKTMP.TMP; #EXIT
```

```

C ROCKADD. FTN - NEW ENTRIES FOR THE ROCK CATALOGUE
  REAL HOLD, AE, AN, AD, SPACE, AMINUS, TYPE, AGE, COLECT, ZERO, AT
  REAL HOLDER(6), REGNO(8), REGTMP(8), RNAME(3), RUNIT(2), QUAD(2),
  .   LOCN(12), FLDNUM(2), LOCATN(3), MINRL(2), MODIF(2),
  .   TRTMNT(4), REF1(3), REF2(3), REFEXT(10)
C REALS ARE ASSUMED 4 BYTES
  INTEGER IHOLD, I, K, KUP, IUP, J, JUP, ISTATE, IYEAR
  DATA HOLDER/1HH, 1HM, 1HN, 1HQ, 1HT, 1HU/, AE/1HE/, AN/1HN/, AD/1HD/,
  .   SPACE/1H /, AMINUS/1H-/, ZERO/1H0/
C
  OPEN(UNIT=4, FILE='CON:')
C OUTPUT TO TERMINAL ON LU 4
  OPEN(UNIT=5, FILE='CON:')
C INPUT FROM TERMINAL ON LU 5
C
C WRITES TWO 80 CHARACTER RECORDS PER INPUT FORM TO LU 7
C
  10 WRITE(4,100)
  100 FORMAT(' HOLDER'// H   H. E. C. '// M   MINES DEPT. ROCK CATALOGUE'//
  .   ' N   MINES DEPT. MINERAL CATALOGUE'//
  .   ' Q   QUEEN VICTORIA MUSEUM'// T   TASMANIAN MUSEUM'//
  .   ' U   UNIVERSITY OF TASMANIA')
  READ(5,101) HOLD
  101 FORMAT(A1)
C NOW CHECK THAT IT IS A VALID HOLDER AND GET THE HOLDER NUMBER
  DO 11 IHOLD=1,6
  IF (HOLD .EQ. HOLDER(IHOLD)) GOTO 12
C FOUND A MATCH
  11 CONTINUE
C IF FALL OUT NO MATCH
  GOTO 10
C NOW HAVE THE HOLDER NAME FOR THE BATCH SO START READING
C REGISTERED NUMBERS
C
  12 CONTINUE
C IHOLD IS THE HOLDER NUMBER
  WRITE(4,102)
  102 FORMAT(' REGISTRATION NUMBER - END TO FINISH')
  READ(5,103) REGNO
  103 FORMAT(8A1)
C NOW CHECK FOR THE END
  IF (REGNO(1) .EQ. AE .AND. REGNO(2) .EQ. AN .AND. REGNO(3) .EQ. AD)
  .   GOTO 280
C FINISH OFF DATA WHEN FIND END
C
C NOW GOTO THE RIGHT PLACE TO DECODE THE REGISTERED NUMBER ACCORDING TO IHOLD
  GOTO (201, 202, 205, 203, 204, 205), IHOLD
C USE SAME NUMBER SCHEME FOR UNIVERSITY AND MINES DEPT MINERALS
  201 GOTO 10
C DONT YET HAVE A FORMAT FOR THE H. E. C.
  202 CONTINUE
C THE MINES DEPT AS HOLDER - REG NO HAS FORM 67-1234
C MUST REMEMBER TO HAVE A WAY TO ENSURE THAT YEARS 19__ ARE
C LOWER IN VALUE THAN YEARS 20__
  DO 210 I=1,8
  IF (REGNO(I) .NE. SPACE) GOTO 211
C FIND THE FIRST NON-BLANK CHARACTER
  210 CONTINUE
  211 K=2

```

19/SI

```

C COUNTER FOR POSITION IN TEMPORARY ARRAY
  REGTMP(1)=SPACE
C ENSURE THAT THERE IS A SPACE FOR THE CODE FOR THE CENTURY WHICH
C IS ADDED IN ROCKMRGE.FTN
  REGTMP(K)=REGNO(I)
  K=K+1
  I=I+1
  REGTMP(K)=REGNO(I)
C NOW HAVE TRANSFERRED THE FIRST TWO CHARACTERS - THE YEAR CODE
  K=K+1
  REGTMP(K)=AMINUS
C NOW PUT THE MINUS THERE
C
C NOW COPY THE NUMBER FROM THE RIGHT HAND SIDE
  KUP=8
  IUP=8
  DO 212 J=1,8
  IF (REGNO(IUP) .NE. SPACE) GOTO 213
C FIND THE RIGHT-HAND MOST NON-BLANK
  IUP=IUP-1
212 CONTINUE
213 REGTMP(KUP)=REGNO(IUP)
  KUP=KUP-1
  IUP=IUP-1
  IF (REGNO(IUP) .NE. SPACE .AND. REGNO(IUP) .NE. AMINUS) GOTO 213
C SECOND HALF OF NUMBER MAY BE TERMINATED BY MINUS OR SPACE
  K=K+1
  IF (K .GT. KUP) GOTO 250
C NO BLANK FILL REQUIRED - MOST UNLIKELY
  DO 214 J=K, KUP
  REGTMP(J)=SPACE
214 CONTINUE
C FILLED WITH BLANKS
  GOTO 250
C NOW IN FORMAT I2, A1, I5
C
203 CONTINUE
C QUEEN VIC
  GOTO 10
C WE KNOW NOTHING
204 CONTINUE
C TAS MUSEUM
  GOTO 10
C WE DONT KNOW THIS EITHER
C
205 CONTINUE
C THE UNIVERSITY HAS NUMBERS ONLY SO
C WANT TO RIGHT JUSTIFY
  KUP=8
  JUP=8
  DO 220 J=1,8
  IF (REGNO(JUP) .NE. SPACE) GOTO 221
  JUP=JUP-1
220 CONTINUE
C LOOK FOR THE LAST NON-BLANK CHARACTER IN THE FIELD
221 CONTINUE
C NOW COPY UNTIL THE NEXT BLANK - STILL READING FROM RIGHT TO LEFT
  REGTMP(KUP)=REGNO(JUP)
  KUP=KUP-1
  JUP=JUP-1

```

```

      IF (JUP .EQ. 0) GOTO 222
      IF (REGNO(JUP) .NE. SPACE) GOTO 221
C GO BACK FOR THE NEXT CHARACTER ONLY IF THERE IS A NON-BLANK LEFT
222 CONTINUE
      IF (KUP .EQ. 0) GOTO 250
C HAVE FILLED REGTMP
      DO 223 J=1, KUP
      REGTMP(J)=SPACE
223 CONTINUE
C NOW IN I8 FORMAT
      GOTO 250
C
C
250 CONTINUE
C NOW GET THE OTHER BITS AND PIECES
      WRITE(4,104)
104 FORMAT(' TYPE')
      READ(5,105) TYPE
105 FORMAT(A2)
      WRITE(4,106)
106 FORMAT(' AGE')
      READ(5,107) AGE
107 FORMAT(A3)
      WRITE(4,108)
108 FORMAT(' ROCK NAME')
      READ(5,109) RNAME
109 FORMAT(2A4, A2)
      WRITE(4,110)
110 FORMAT(' ROCK UNIT')
      READ(5,111) RUNIT
111 FORMAT(2A4)
      WRITE(4,112)
112 FORMAT(' STATE CODE, QUAD OR COUNTRY')
      READ(5,113) ISTATE, QUAD
113 FORMAT(I1, A4, A1)
      IF (ISTATE .NE. 0) GOTO 260
C FOR ALL BUT TAS READ LAT AND LONG
      WRITE(4,114)
114 FORMAT(' COORDINATES')
      READ(5,115) LOCN
115 FORMAT(12A1)
      GOTO 265
C READ AS STRING OF 12 CHARACTERS
C
C NOW FOR LATS AND LONGS
260 WRITE(4,116)
116 FORMAT(' LAT & LONG')
      READ(5,117) (LOCN(I), I=2, 12)
117 FORMAT(11A1)
      LOCN(1)=SPACE
C PUT A LEADING SPACE IN THE LATS AND LONGS TO MAKE THEM THE SAME FIELD WIDTH
C THE COORDINATES
C
265 CONTINUE
      DO 266 I=2, 12
      IF (LOCN(I) .EQ. SPACE) LOCN(I)=ZERO
266 CONTINUE
C ZERO FILL TO ENSURE ALL TRAILING ZEROES ARE PRESENT BUT ENSURE
C THAT LEADING SPACE IN LTA/LONG IS NOT CHANGED
      WRITE(4,118)

```

```

118 FORMAT(' COLLECTOR')
    READ(5,119) COLECT
119 FORMAT(A3)
    WRITE(4,120)
120 FORMAT(' FIELD NO. ')
    READ(5,121) FLDNUM
121 FORMAT(A4,A2)
    WRITE(4,122)
122 FORMAT(' YEAR')
    READ(5,123) IYEAR
123 FORMAT(I4)
    WRITE(4,125)
125 FORMAT(' LOCALITY')
    READ(5,126) LOCATN
126 FORMAT(3A4)
    WRITE(4,127)
127 FORMAT(' HOLDER')
    READ(5,101) AT
C READ AND DISCARD THE HOLDER AS IT DOESNT CHANGE VERY OFTEN AND IS SET
C AT THE START OF THE PROGRAM
    WRITE(4,129)
129 FORMAT(' MINERAL')
    READ(5,130) MINRL
130 FORMAT(2A4)
    WRITE(4,131)
131 FORMAT(' MODIFIER')
    READ(5,132) MODIF
132 FORMAT(2A4)
    WRITE(4,133)
133 FORMAT(' TREATMENT')
    READ(5,134) TRTMNT
134 FORMAT(4A2)
    WRITE(4,135)
135 FORMAT(' REFERENCE 1')
    READ(5,136) REF1
136 FORMAT(2A4,A2)
    WRITE(4,137)
137 FORMAT(' REFERENCE 2')
    READ(5,136) REF2
    WRITE(4,138)
138 FORMAT(' EXTRA REFERENCES - 40 CHARS MAX')
    READ(5,139) REFEXT
139 FORMAT(10A4)
C END OF GETTING ONE FORM
C
    WRITE(7,150) REGTMP, TYPE, AGE, RNAME, RUNIT, ISTATE, QUAD, LOCN, COLECT,
    FLDNUM, IYEAR, LOCATN, HOLD, MINRL, MODIF, TRTMNT, REF1, REF2, REFEXT
150 FORMAT(8A1, A2, A3, 2A4, A2, 2A4, I1, A4, A1, 12A1, A3, A4, A2, I4, 3A4,
    A1, A4, 1X/A4, 2A4, 4A2, 2(2A4, A2), 10A4)
C WRITE TO OUTPUT FILE
    GOTO 12
C AND BACK AROUND
C
C NOW TO CLOSE OFF
200 CLOSE(UNIT=7, STATUS='KEEP')
C CLOSE OFF OR WRITE FILEMARK OR LOCK OR WHATEVER
    STOP
    END

```

22/51

APPENDIX 6

Program ROCKCHEK

```
*ROCKCHEK.CSS - FOR VERIFYING ROCKTMP.TMP DATA FILE  
L ROCKCHEK; AS 7, ROCKTMP.TMP, ERO; AS 6, PR:; ST  
$EXIT
```

C ROCKCHEK.FTN - TO CHECK ROCK CATALOGUE DATA FOR VALID ABBREVIATIONS
 C ASSUMES THAT THE PRINTER IS LU 6
 C ASSUMES THAT THE OUTPUT OF ROCKADD IS ON LU 7
 C ASSUMES THAT LU 4 MAY BE OPENED WITH A VARIETY OF FILE NAMES

```

REAL HOLD, TYPE, AGE, COLECT, ANAME1, ANAME2, ANAME3, AUNIT1, AUNIT2,
  MINRL1, MINRL2, MODIF1, MODIF2, TREAT
REAL REGNO(8), RNAME(3), RUNIT(2), QUAD(2),
  LOCN(12), FLDNUM(2), LOCATN(3), MINRL(2), MODIF(2),
  TRTMNT(4), REF1(3), REF2(3), REFEXT(10),
  TTYPE(30), TAGE(30), TNAME(3, 150), TUNIT(3, 30),
  TCLCT(150), TMINRL(2, 150), TMODIF(200), ATREAT(35)

```

C REALS ARE ASSUMED 4 BYTES
 INTEGER I, J, ISTATE, IYEAR, NTYPE, NAGE, NNAME, NUNIT, NCLCT, NMINRL,
 NMODIF, NTRTMT, LINE, LINEF, ICOL

```
REWIND 7
```

C ENSURE AT START OF DATA FILE
 OPEN(UNIT=4, FILE='ROCKTYPE.DAT', SHARE='ERO')
 NTYPE=1
 10 READ(4, 100, END=11) TTYPE(NTYPE)
 100 FORMAT(A2)
 NTYPE=NTYPE+1
 IF (NTYPE .GT. 30) STOP ' TOO MANY TYPES'
 GOTO 10
 11 NTYPE=NTYPE-1
 CLOSE(UNIT=4, STATUS='KEEP')

C READ THE CHOICE OF ROCK TYPES

```

OPEN(UNIT=4, FILE='ROCKAGES.DAT', SHARE='ERO')
NAGE=1
12 READ(4, 101, END=13) TAGE(NAGE)
101 FORMAT(A3)
NAGE=NAGE+1
IF (NAGE .GT. 30) STOP ' TOO MANY AGES'
GOTO 12
13 NAGE=NAGE-1
CLOSE(UNIT=4, STATUS='KEEP')

```

C READ THE CHOICE OF ROCK AGES

```

OPEN(UNIT=4, FILE='ROCKNAME.DAT', SHARE='ERO')
NNAME=1
14 READ(4, 102, END=15) TNAME(1, NNAME), TNAME(2, NNAME), TNAME(3, NNAME)
102 FORMAT(2A4, A2)
NNAME=NNAME+1
IF (NNAME .GT. 150) STOP ' TOO MANY NAMES'
GOTO 14
15 NNAME=NNAME-1
CLOSE(UNIT=4, STATUS='KEEP')

```

C READ THE CHOICE OF ROCK NAMES

```

OPEN(UNIT=4, FILE='ROCKUNIT.DAT', SHARE='ERO')
NUNIT=1
16 READ(4, 103, END=17) TUNIT(1, NUNIT), TUNIT(2, NUNIT)
103 FORMAT(2A4)
NUNIT=NUNIT+1
IF (NUNIT .GT. 30) STOP ' TOO MANY UNITS'
GOTO 16
17 NUNIT=NUNIT-1

```

```

CLOSE(UNIT=4, STATUS='KEEP')
C READ THE CHOICE OF ROCK UNITS
C
OPEN(UNIT=4, FILE='COLECTOR. DAT', SHARE='ERO')
NCLCT=1
18 READ(4, 104, END=19) TCLCT(NCLCT)
104 FORMAT(A3)
NCLCT=NCLCT+1
IF (NCLCT .GT. 150) STOP ' TOO MANY COLLECTORS'
GOTO 18
19 NCLCT=NCLCT-1
CLOSE(UNIT=4, STATUS='KEEP')
C READ THE CHOICE OF COLLECTORS
C
OPEN(UNIT=4, FILE='MINERALS. DAT', SHARE='ERO')
NMINRL=1
20 READ(4, 105, END=21) TMINRL(1, NMINRL), TMINRL(2, NMINRL)
105 FORMAT(2A4)
NMINRL=NMINRL+1
IF (NMINRL .GT. 150) STOP ' TOO MANY MINERALS'
GOTO 20
21 NMINRL=NMINRL-1
CLOSE(UNIT=4, STATUS='KEEP')
C READ THE CHOICE OF MINERALS
C
OPEN(UNIT=4, FILE='MODIFIER. DAT', SHARE='ERO')
NMODIF=1
22 READ(4, 106, END=23) TMODIF(NMODIF)
106 FORMAT(A4)
NMODIF=NMODIF+1
IF (NMODIF .GT. 200) STOP ' TOO MANY MODIFIERS'
GOTO 22
23 NMODIF=NMODIF-1
CLOSE (UNIT=4, STATUS='KEEP')
C READ THE CHOICE OF MODIFIERS
C
OPEN(UNIT=4, FILE='TRTMNT. DAT', SHARE='ERO')
NTRTMT=1
24 READ(4, 107, END=25) ATREAT(NTRTMT)
107 FORMAT(A2)
NTRTMT=NTRTMT+1
IF (NTRTMT .GT. 35) STOP ' TOO MANY TREATMENTS'
GOTO 24
25 NTRTMT=NTRTMT-1
CLOSE(UNIT=4, STATUS='KEEP')
C READ THE CHOICE OF TREATMENTS
C
C NOW FOR THE CHECKING
LINE=0
48 READ(7, 150, END=80) REGNO, TYPE, AGE, RNAME, RUNIT, ISTATE, QUAD, LOCN,
. COLECT, FLDNUM, IYEAR, LOCATN, HOLD, MINRL, MODIF, TRTMNT, REF1, REF2,
. REFEXT
150 FORMAT(8A1, A2, A3, 2A4, A2, 2A4, I1, A4, A1, 12A1, A3, A4, A2, I4, 3A4,
. A1, A4, 1X/A4, 2A4, 4A2, 2(2A4, A2), 10A4)
LINEF=LINE+1
LINE=LINE+2
C
DO 50 I=1, NTYPE
IF (TYPE .EQ. TTYPE(I)) GOTO 51
C FOUND IT

```

```

50 CONTINUE
  WRITE(6,200) TYPE,LINEF
200 FORMAT(' TYPE ERROR ',A2,' ON LINE',I4,' COLUMN 9')
51 CONTINUE
C CHECKED TYPES
C
  DO 52 I=1,NAGE
  IF (AGE .EQ. TAGE(I)) GOTO 53
52 CONTINUE
  WRITE(6,201) AGE,LINEF
201 FORMAT(' AGE ERROR ',A3,' ON LINE',I4,' COLUMN 11')
53 CONTINUE
C CHECKED AGES
C
  ANAME1=RNAME(1)
  ANAME2=RNAME(2)
  ANAME3=RNAME(3)
C SAVE ARRAY ACCESSES
  DO 54 I=1,NNAME
  IF (ANAME1 .NE. TNAME(1,I)) GOTO 54
  IF (ANAME2 .NE. TNAME(2,I)) GOTO 54
  IF (ANAME3 .EQ. TNAME(3,I)) GOTO 55
C A MATCH
54 CONTINUE
  WRITE(6,202) RNAME,LINEF
202 FORMAT(' ROCK NAME ERROR ',2A4,A2,' ON LINE',I4,' COLUMN 14')
55 CONTINUE
C CHECKED ROCK NAMES
C
  AUNIT1=RUNIT(1)
  AUNIT2=RUNIT(2)
  DO 56 I=1,NUNIT
  IF (AUNIT1 .NE. TUNIT(1,I)) GOTO 56
  IF (AUNIT2 .EQ. TUNIT(2,I)) GOTO 57
56 CONTINUE
  WRITE(6,203) RUNIT,LINEF
203 FORMAT(' ROCK UNIT ERROR ',2A4,' ON LINE',I4,' COLUMN 24')
57 CONTINUE
C CHECKED ROCK UNIT
C
  DO 58 I=1,NCLCT
  IF (COLECT .EQ. TCLCT(I)) GOTO 59
58 CONTINUE
  WRITE(6,204) COLECT,LINEF
204 FORMAT(' COLLECTOR ERROR ',A3,' ON LINE',I4,' COLUMN 50')
59 CONTINUE
C CHECKED COLLECTOR
C
  MINRL1=MINRL(1)
  MINRL2=MINRL(2)
  DO 60 I=1,NMINRL
  IF (MINRL1 .NE. TMINRL(1,I)) GOTO 60
  IF (MINRL2 .EQ. TMINRL(2,I)) GOTO 61
60 CONTINUE
  WRITE(6,205) MINRL,LINEF,LINE
205 FORMAT(' MINERAL ERROR ',2A4,' BETWEEN LINE',I4,' COLUMN 76',
          ' AND LINE',I4,' COLUMN 1')
61 CONTINUE
C CHECKED MINERALS
C

```

```

MODIF1=MODIF(1)
MODIF2=MODIF(2)
DO 62 I=1,NMODIF
IF (MODIF1 .EQ. TMODIF(I)) GOTO 63
62 CONTINUE
WRITE(6,206) MODIF1,LINE
206 FORMAT(' MODIFIER ERROR ',A4,' ON LINE',I4,' COLUMN 5')
63 CONTINUE
DO 64 I=1,NMODIF
IF (MODIF2 .EQ. TMODIF(I)) GOTO 65
64 CONTINUE
WRITE(6,207) MODIF2,LINE
207 FORMAT(' MODIFIER ERROR ',A4,' ON LINE',I4,' COLUMN 9')
65 CONTINUE
C CHECKED MODIFIERS
C
ICOL=11
DO 70 J=1,4
ICOL=ICOL+2
TREAT=TRTMNT(J)
DO 66 I=1,NTRTMT
IF (TREAT .EQ. ATREAT(I)) GOTO 70
66 CONTINUE
WRITE(6,208) TREAT,LINE,ICOL
208 FORMAT(' TREATMENT ERROR ',A2,' ON LINE',I4,' COLUMN',I3)
70 CONTINUE
C CHECKED TREATMENTS
C
C NOW GO AND GET THE NEXT ONE
GOTO 48
C
80 CONTINUE
C PREPARE TO CLOSE OFF
CLOSE(UNIT=7,STATUS='KEEP')
STOP
END

```

APPENDIX 7

Program ROCKMRGE

```
*ROCKMRGE.CSS - FOR PUTTING NEW ROCK DATA ON THE END OF ROCKDAT
L ROCKMRGE; REP ROCCAT.DAT, 0; AS 7, ROCCAT.DAT; AS 6, ROCKTMP.TMP, ERO
AL SYSF:ROCKMRGE.DAT, IN, 80/5/5; AS 4, SYSF:ROCKMRGE.DAT; ST
$IFE 0; DEL ROCKTMP.TMP; REP ROCCAT.DAT, FF00; DE SYSF:ROCKMRGE.DAT; $ENDC
$EXIT
```

```

C ROCKMRGE.FTN - FOR ADDING NEW ENTRIES TO THE END OF THE FILE
C WOULD PREFERABLY DONE USING SYSTEM UTILITIES
C MAIN FILE LU 7
C NEW DATA LU 6
C COMBINED DATA LU 4
C
  REAL A(159), ZERO, AM
C
  DATA ZERO/1H0/, AM/1HM/
C TO BE USED IN SETTING THE CENTURY CODE FOR THE MINES DEPT
C ROCK CATALOGUE
C ASSUMES FILES ARE OPEN
  10 READ(7,100,END=20) A
  100 FORMAT(79A1/80A1)
  WRITE(4,100) A
C READ AND WRITE ONE DATA SET - I. E. TWO RECORDS
  GOTO 10
C COPY ORIGINAL FILE
C
C NOW COPY THE NEW DATA CHANGING IT IF WE NEED TO AS WE GO
  20 CONTINUE
  READ(6,100,END=30) A
  IF (A(75) .EQ. AM) A(1)=ZERO
C FOR THE MINES DEPT. ROCK CATALOGUE NEED TO PUT IN THE
C CODE FOR THE CENTURY
C 0 FOR 19__ 1 FOR 20__ ETC.
  WRITE(4,100) A
  GOTO 20
C COPY NEW FILE
C
  30 REWIND 7
C REWIND OLD MAIN FILE
C
C NOW USE THE OPEN STATEMENT OR SOME OTHER DEVICE TO
C ENSURE THAT THE COMBINED FILE - LU 4 - IS WRITE PROTECTED
  OPEN(UNIT=4,SHARE='ERO')
  REWIND 4
  40 READ(4,100,END=50) A
  WRITE(7,100) A
  GOTO 40
C COPY THE COMBINED FILE BACK
C
  50 CONTINUE
  CLOSE(UNIT=7,STATUS='KEEP')
C CLOSE OFF THE NEW COMBINED FILE
  STOP
  END

```

29/51

APPENDIX 8

Program ROCKSORT

```

*ROCKSORT.CSS
* FOR SORTING ROCK CATALOGUE INTO REGISTERED NUMBER ORDER
PRE ETM
L ROCKSORT,10: AS 4,ROCCAT.DAT,ERO: AL SYSF:ROCTMP.DAT,IN,80/5/2
AS 5,CON:; AS 6,SYSF:ROCTMP.DAT; ST
$IFNE 0: $WRITE SORT ERROR: ENA ETM: $EXIT: $ENDC
$BUILD WCOPY.CMD
IN SYSF:ROCTMP.DAT
AL ROCCAT.DAT,IN,80/10/5
OUT ROCCAT.DAT
COPY *,*
REW I
REW 0
VERIFY *,*
END
$ENDB
REP SYSF:ROCTMP.DAT,FF00: REP ROCCAT.DAT,0: DE ROCCAT.DAT
L COPY32,50: ST ,COM=WCOPY.CMD,LI=NULL:,LO=NULL:
$IFNE 0: $WRITE SORT-COPY ERROR: ENA ETM: $EXIT: $ENDC
REP ROCCAT.DAT,FF00: REP SYSF:ROCTMP.DAT,0: DE SYSF:ROCTMP.DAT,WCOPY.CMD
ENA ETM: $EXIT

```

```

#TITL  ROCKSORT.FTN - SORT THE ROCK CATALOGUE
C INTO ASCENDING REGISTERED NUMBER ORDER
C USES FORTRAN 77 HEAVILY BUT COULD BE RE-WRITTEN
  CHARACTER*8  REGNO,REGNUM(32000)
  CHARACTER*1  HOLDER,HOLD,IA(159),IHOLD(6)
  INTEGER*2    FREC
  INTEGER*4    IREC,RECNUM(32000)
  EQUIVALENCE (IA(1),REGNO),(IA(75),HOLD)
C USED TO MAKE I/O SIMPLER
  DATA IHOLD/'H','M','N','Q','T','U'/
C USED TO CHECK TO SELECT A VALID ONE
C
C ASSUMES  LU 5 IS THE USER TERMINAL
C           LU 4 IS THE INPUT FILE
C           LU 6 IS THE OUTPUT FILE
C
C THE PROGRAM REQUESTS THE USER TO NOMINATE THE HOLDER WHOSE DATA IS
C TO BE SORTED.  THE INPUT DATA FILE IS SCANNED FOR A MATCHING HOLDER.
C NON-MATCHING DATA IS TRANSFERRED DIRECT TO THE OUTPUT FILE WHILST
C THE RECORD NUMBERS OF THE FIRST RECORD OF THE MATCHING DATA SETS
C ARE NOTED.  AFTER BEING SORTED THE DATA FROM THE HOLDER SPECIFIED
C WILL BE AT THE BACK OF THE FILE.
C
  10 WRITE(5,102)
  102 FORMAT(' HOLDER WHOSE DATA IS TO BE SORTED'/' H   H. E. C. '/
           ' M   MINES DEPT.  ROCK CATALOGUE'/'
           ' N   MINES DEPT.  MINERAL CATALOGUE'/'
           ' Q   QUEEN VICTORIA MUSEUM'/' T   TASMANIAN MUSEUM'/'
           ' U   UNIVERSITY OF TASMANIA'')
  READ(5,101) HOLDER
  101 FORMAT(A1)
C NOW CHECK THAT IT IS A VALID HOLDER AND GET THE HOLDER NUMBER
  DO 11 IH=1,6
  IF (HOLDER .EQ. IHOLD(IH)) GOTO 12
C FOUND A MATCH
  11 CONTINUE
C IF FALL OUT NO MATCH
  GOTO 10
C NOW HAVE THE HOLDER NAME FOR THE BATCH SO START READING
  12 CONTINUE
  OPEN(UNIT=4,ACCESS='DIRECT',RECL=80)
C OPEN THE INPUT FILE FOR DIRECT ACCESS TO ALLOW THE RANDOM
C READS AFTER THE BASIC SORT
  REWIND 4
  IREC=-1
C COUNTER FOR THE NUMBER OF RECORDS READ - NOTE THAT EACH DATA
C ENTRY CONSISTS OF TWO LOGICAL RECORDS AND IREC MUST BE
C INCREMENTED BY 2.
  FREC=0
C COUNTER FOR THE NUMBER OF RECORDS FOUND THAT MATCH THE SPECIFIED
C HOLDER
  15 READ(4,200,END=20) IA
  200 FORMAT(79A1/80A1)
C TWO RECORDS PER DATA ENTRY
  IREC=IREC+2
C INCREMENT THE RECORD NUMBER IN THE FILE
  IF (HOLD .NE. HOLDER) THEN
  WRITE(6,200) IA
  GOTO 15

```

```

ENDIF
C IF NOT THE RIGHT HOLDER SIMPLY COPY TO THE OUTPUT FILE
C
  FREC=FREC+1
C INCREMENT THE COUNTER FOR THE NUMBER OF FOUND RECORDS
  IF (FREC .GT. 32000) PAUSE 'MORE THAN 32000 ENTRIES SO CANCEL'
  REGNUM(FREC)=REGNO
  RECNUM(FREC)=IREC
  GOTO 15
C STORE THE REGISTRATION NUMBER AND THE RECORD NUMBER AND GO BACK
C FOR ANOTHER
C
C NOW TO SORT THE ONES WE HAVE FOUND
  20 CONTINUE
  IF (FREC .EQ. 0) STOP 'NO RECORDS'
  CALL BBSSTR(RECNUM, REGNUM, FREC)
C SORT INTO ASCENDING REG. NO. ORDER
  DO 30 I=1, FREC
  READ(4, 200, REC=RECNUM(I)) IA
  WRITE(6, 200) IA
  30 CONTINUE
C COPY IN NEW ORDER WHICH IS IN RECNUM AT THE END OF THE SORT
  CLOSE(UNIT=6, STATUS='KEEP')
  CLOSE(UNIT=4, STATUS='KEEP')
  END
  SUBROUTINE BBSSTR(IR, CVAR, N)
C SORT A NUMBER OF STRINGS INTO ASCENDING ORDER AND AT THE SAME TIME
C FOLLOW THE CHANGES WITH THE INDEX IR
  CHARACTER *8 CVAR(N), CTEMP
  INTEGER*4 IR(N), IT, IRI, IP1
  INTEGER*2 N
  LOGICAL NSWAP
  IF (N .LE. 1) RETURN
C NOTHING TO SORT
  NM1=N-1
  DO 30 J=1, NM1
  NSWAP=. TRUE.
  IRI=1
  DO 40 I=1, NM1
  IP1=I+1
  IF (CVAR(IRI) .LE. CVAR(IP1)) GOTO 40
  NSWAP=. FALSE.
  CTEMP=CVAR(IRI)
  IT=IR(IRI)
  CVAR(IRI)=CVAR(IP1)
  IR(IRI)=IR(IP1)
  CVAR(IP1)=CTEMP
  IR(IP1)=IT
  40 IRI=IP1
  IF (NSWAP) RETURN
  30 CONTINUE
  RETURN
  END

```

APPENDIX 9

Program ROCKSRCH

*ROCKSRCH.CSS - FOR SEARCHING THE ROCCAT.DAT FILE
L SEARCHER: AS 7, ROCCAT.DAT.ERD: AS 5, CON: AS 6, PR: ST
#EXIT

#NDEBUG

C SEARCHER.FTN - USE FOR SEARCHING THE ROCK CATALOGUE FILE
C ISSUES PROMPTS ON LU 5 AND PRINTS ON LU 6. IF DESIRED A SMALL NUMBER
C OF ENTRIES MAY BE LISTED TO LU 5.
C IF MORE THAN 1000 ENTRIES ARE FOUND THERE IS A CHANCE TO CUT OFF THE
C PRINTOUT AT THAT POINT.

CHARACTER*1 IYES, IY, HOLD, HOLDER(6), SREGNO(8), FREGNO(8), GTYPE(72),
RAGE(72), NAME(72), UNIT(72), STATE(72), IC, IL,
LATS(5), LATN(5), LONW(6), LONE(6), CLCT(72),
SHOLD(72), IMINRL(72), IMODIF(72), ITREAT(72),
ITAS, IA(159), SPACE, ZERO

CHARACTER*4 SYEAR, FYEAR, YEAR

CHARACTER*6 CORDW, CORDE, CORDS, CORDN, COORDE, COORDN

CHARACTER*8 SREGN, FREGN, REGNO

INTEGER ILATS, ILATN, ILONW, ILONE, IILAT, IILON, IHOLD, LINE, PAGE

REAL ANSWER(6)

REAL*8 ACORDE, ACORDN

LOGICAL RNO, LTYPE, LAGE, LNAME, LUNIT, LSTATE, SLOCN, LCOORD, LCLCT,

LYEAR, LHOLD, LMINRL, LMODIF, LTREAT, INTAS, FOUND, VDU, PRNTR

EQUIVALENCE (IA(1), REGNO), (IA(38), COORDE), (IA(44), COORDN),

(IA(59), YEAR)

C USED TO ALLOW USE OF THE FORTRAN 77 CHARACTER COMPARISONS
C CAN EASILY BE ADAPTED TO NON FORTRAN 77 WITH THE EXCEPTION
C OF REGNO WHICH WOULD REQUIRE A DIFFERENT SEARCHING PART FOR
C EACH HOLDER

DATA HOLDER/'H', 'M', 'N', 'Q', 'T', 'U'//, IY/'Y'//, IC/'C'//, IL/'L'//,
ITAS/'0'//, SPACE/' '//, ZERO/'0'//

C ASSUMES LU 5 IS THE USER CONSOLE

C ASSUMES LU 6 IS THE LINE PRINTER

C ASSUMES LU 7 IS THE MAIN DATA FILE

FOUND=. FALSE.

C USED TO DETERMINE IF ANY MATCHING DATA FOUND

WRITE(5, 90)

90 FORMAT(' SEND OUTPUT TO VDU?')

READ(5, 101) IYES

VDU=IYES .EQ. IY

C SEND OUTPUT TO THE VDU

WRITE(5, 91)

91 FORMAT(' SEND OUTPUT TO PRINTER?')

READ(5, 101) IYES

PRNTR=IYES .EQ. IY

C SEND OUTPUT TO PRINTER

LINE=0

PAGE=0

C USED TO KEEP COUNT OF LINES AND PAGES ON PRINTOUT

WRITE(5, 100)

100 FORMAT(' SEARCH BY REGISTRATION NUMBER?')

READ(5, 101) IYES

101 FORMAT(A1)

RNO=IYES .EQ. IY

IF (.NOT. RNO) GOTO 13

C

10 WRITE(5, 102)

102 FORMAT(' HOLDER'// H H. E. C. '//

' M MINES DEPT. ROCK CATALOGUE'//

' N MINES DEPT. MINERAL CATALOGUE'//

' Q QUEEN VICTORIA MUSEUM'// T TASMANIAN MUSEUM'//

' U UNIVERSITY OF TASMANIA')

READ(5, 101) HOLD

```

C NOW CHECK THAT IT IS A VALID HOLDER AND GET THE HOLDER NUMBER
  DO 11 IHOLD=1,6
  IF (HOLD .EQ. HOLDER(IHOLD)) GOTO 12
C FOUND A MATCH
  11 CONTINUE
C IF FALL OUT NO MATCH
  GOTO 10
C NOW HAVE THE HOLDER NAME FOR THE BATCH SO START READING
C REGISTERED NUMBERS
C
  12 CONTINUE
C IHOLD IS THE HOLDER NUMBER
  WRITE(5,104)
  104 FORMAT(' STARTING REGISTRATION NUMBER (USE - AS DELIMITER)')
  READ(5,105) SREGNO
  105 FORMAT(8A1)
  WRITE(5,106)
  106 FORMAT(' FINISHING REGISTRATION NUMBER (USE - AS DELIMITER)')
  READ(5,105) FREGNO
  CALL JUSTIF(SREGN,SREGNO,IHOLD)
  CALL JUSTIF(FREGN,FREGNO,IHOLD)
C JUSTIFY THE REGISTRATION NUMBER TO MATCH THE FORMAT USED BY ROCKADD
C AND RETURN IN FORTRAN 77 CHARACTER*8 FORMAT
C OTHER METHODS MAY BE REQUIRED HERE IF NOT FORTRAN77
  13 WRITE(5,107)
  107 FORMAT(' GENERIC TYPE')
  READ(5,108) GTYPE
  108 FORMAT(72A1)
  CALL YESRCH(LTYPE,GTYPE)
  WRITE(5,109)
  109 FORMAT(' AGE')
  READ(5,108) RAGE
  CALL YESRCH(LAGE,RAGE)
  WRITE(5,110)
  110 FORMAT(' ROCK NAME')
  READ(5,108) NAME
  CALL YESRCH(LNAME,NAME)
  WRITE(5,111)
  111 FORMAT(' ROCK UNIT')
  READ(5,108) UNIT
  CALL YESRCH(LUNIT,UNIT)
  WRITE(5,113)
  113 FORMAT(' STATE')
  READ(5,108) STATE
  CALL YESRCH(LSTATE,STATE)
  14 WRITE(5,114)
  114 FORMAT(' SEARCH BY (C)OORDINATES OR (L)AT/LONG//
    ' LEAVE BLANK FOR NEITHER')
  READ(5,101) IYES
  SLOCN=IYES .NE. SPACE
C IF NOT A SPACE THEN NEED TO LOOK FOR C OR L
  IF (.NOT. SLOCN) GOTO 16
C NOT WORRIED ABOUT COORDS OR LAT/LONG
  IF (IYES .NE. IC .AND. IYES .NE. IL) GOTO 14
C WASNT A VALID CHOICE
  LCOORD=IYES .EQ. IC
C TO INDICATE IF LOOKING FOR COORDS OR LAT/LONG
  IF (LCOORD) GOTO 15
C
C NOW GET LAT/LONG DATA

```

```

WRITE(5,115)
115 FORMAT(' SOUTHERNMOST LATITUDE')
READ(5,116) LATS
116 FORMAT(5A1)
WRITE(5,117)
117 FORMAT(' NORTHERNMOST LATITUDE')
READ(5,116) LATN
WRITE(5,118)
118 FORMAT(' WESTERNMOST LONGITUDE')
READ(5,119) LONW
119 FORMAT(6A1)
WRITE(5,120)
120 FORMAT(' EASTERNMOST LONGITUDE')
READ(5,119) LONE
C GET LATS AND LONGS AS DEGREES WITH + N,E - S,W
C USING ENCODE/DECODE ETC IN SUBROUTINE ILAT,ILON
  ILATS=ILAT(LATS)
  ILATN=ILAT(LATN)
  ILONW=ILON(LONW)
  ILONE=ILON(LONE)
C NOW DECIDE IF IT IS LIKELY TO FALL ON TAS.
C CHECK THE EDGES OF TAS AND THE AREA TO SEE IF THE AREA AND TAS COULD
C BE OVERLAPPED IN A SIMPLE MINDED WAY
C TAS HAS EDGES 143.75E,148.50E,39.50S,43.75S
  INTAS=ILONE .GE. 14345 .AND. ILONW .LE. 14830 .AND.
  ILATS .LE. -3930 .AND. ILATN .GE. -4345
C EASTERN EDGE IS EAST OF WEST OF TAS AND WESTERN EDGE IS WEST OF
C EASTERN EDGE OF TAS AND SOUTHERN EDGE IS SOUTH OF NORTHERN EDGE
C OF TAS AND NORTHERN EDGE IS NORTH OF SOUTHERN EDGE OF TAS
  GOTO 16
C GOT LATS AND LONGS AS SIGNED INTEGERS SO BRANCH ROUND
C
C
C NOW FOR COORDINATES
C ONCE AGAIN INVOKE FORTRAN 77 BY USING CHARACTER*6 FOR HOLDING
C THE COORDINATES
  15 WRITE(5,121)
  121 FORMAT(' WESTERNMOST EASTING IN METRES')
  READ(5,122) CORDW
  122 FORMAT(A6)
  WRITE(5,123)
  123 FORMAT(' EASTERNMOST EASTING IN METRES')
  READ(5,122) CORDE
  WRITE(5,124)
  124 FORMAT(' SOUTHERNMOST NORTHING IN METRES')
  READ(5,122) CORDS
  WRITE(5,125)
  125 FORMAT(' NORTHERNMOST NORTHING IN METRES')
  READ(5,122) CORDN
C FINISH READING COORDINATES
  DO 9 I=1,6
  IF (CORDW(I:I) .EQ. SPACE) CORDW(I:I)=ZERO
  IF (CORDE(I:I) .EQ. SPACE) CORDE(I:I)=ZERO
  IF (CORDS(I:I) .EQ. SPACE) CORDS(I:I)=ZERO
  IF (CORDN(I:I) .EQ. SPACE) CORDN(I:I)=ZERO
  9 CONTINUE
C ZERO FILL COORDS IF THEY HAVE NOT BEEN ZERO FILLED BY THE USER
C
C NOW FOR THE OTHER SEARCH OPTIONS
  16 WRITE(5,126)

```

```

126 FORMAT(' COLLECTOR')
  READ(5,108) CLCT
  CALL YESRCH(LCLCT,CLCT)
  WRITE(5,127)
127 FORMAT(' SEARCH BY YEAR? (Y OR N)')
  READ(5,101) IYES
  LYEAR=IYES .EQ. IY
  IF (.NOT. LYEAR) GOTO 8
C DONT ASK FOR YEAR IF NOT LOOKING FOR YEAR
  WRITE(5,128)
128 FORMAT(' STARTING YEAR')
  READ(5,129) SYEAR
129 FORMAT(A4)
C ANOTHER USE OF FORTRAN 77 ALTHOUGH A TRUE 32 BIT INTEGER WOULD BE OK
  WRITE(5,130)
130 FORMAT(' FINISHING YEAR')
  READ(5,129) FYEAR
  8 WRITE(5,131)
131 FORMAT(' HOLDER')
  READ(5,108) SHOLD
  CALL YESRCH(LHOLD,SHOLD)
  WRITE(5,132)
132 FORMAT(' MINERAL')
  READ(5,108) IMINRL
  CALL YESRCH(LMINRL,IMINRL)
  WRITE(5,133)
133 FORMAT(' MODIFIER')
  READ(5,108) IMODIF
  CALL YESRCH(LMODIF,IMODIF)
  WRITE(5,134)
134 FORMAT(' TREATMENT')
  READ(5,108) ITREAT
  CALL YESRCH(LTREAT,ITREAT)
C END OF GETTING OPTIONS
C
  IF (PRNTR) THEN
C IF OUTPUT TO PRINTER PRINT THE SEARCH OPTIONS
  WRITE(6,400)
400 FORMAT(' SEARCH OPTIONS ARE:')
  IF (RNO) WRITE(6,401) SREGNO,FREGNO
401 FORMAT(' STARTING REGISTRATION NUMBER',10X,8A1/
  ' FINISHING REGISTRATION NUMBER',10X,8A1)
  IF (LTYPE) WRITE(6,402) GTYPE
402 FORMAT(' GENERIC TYPE',10X,72A1)
  IF (LAGE) WRITE(6,403) RAGE
403 FORMAT(' AGE',10X,72A1)
  IF (LNAME) WRITE(6,404) NAME
404 FORMAT(' ROCK NAME',10X,72A1)
  IF (LUNIT) WRITE(6,405) UNIT
405 FORMAT(' ROCK UNIT',10X,72A1)
  IF (LSTATE) WRITE(6,406) STATE
406 FORMAT(' STATE',10X,72A1)
  IF (SLOCN .AND. LCOORD) WRITE(6,407) CORDW,CORDE,CORDS,CORDN
407 FORMAT(' COORDINATE LIMITS',10X,2(A6,'ME '),2(A6,'MN '))
  IF (SLOCN .AND. .NOT. LCOORD) WRITE(6,408) LATS,LATN,LONW,LONE
408 FORMAT(' LAT/LONG LIMITS',10X,2(5A1,1X),2(6A1,1X))
  IF (LCLCT) WRITE(6,409) CLCT
409 FORMAT(' COLLECTOR',10X,72A1)
  IF (LYEAR) WRITE(6,410) SYEAR,FYEAR
410 FORMAT(' YEAR RANGE',10X,A4,'-',A4)

```

```

      IF (LHOLD) WRITE(6,411) SHOLD
411  FORMAT(' HOLDER',10X,72A1)
      IF (LMINRL) WRITE(6,412) IMINRL
412  FORMAT(' MINERAL',10X,72A1)
      IF (LMODIF) WRITE(6,413) IMODIF
413  FORMAT(' MODIFIER',10X,72A1)
      IF (LTREAT) WRITE(6,414) ITREAT
414  FORMAT(' TREATMENT',10X,72A1)
      ENDIF
C HAVE NOW PRINTED OPTIONS
C
C NOW FOR THE SEARCH
  17 READ(7,200,END=40) IA
  200 FORMAT(79A1/80A1)
      IF (.NOT. RNO) GOTO 18
      IF (IA(75) .NE. HOLD) GOTO 17
C NOT THE RIGHT HOLDER FOR THE SORT OF REGISTRATION NUMBER
C SPECIFIED
C
      IF (REGNO .LT. SREGN .OR. REGNO .GT. FREGN) GOTO 17
C USE FORTRAN 77 STRING COMPARISON HERE TO MAKE LIFE EASIER
C FOR THE MINES DEPT. - OTHERS WILL NEED EITHER FORTRAN 77
C OR A DIFFERENT APPROACH
C
  18 CONTINUE
      IF (.NOT. LTYPE) GOTO 19
      IF (ISITIN(GTYPE, IA, 9, 10) .EQ. 0) GOTO 17
C CHECK GENERIC TYPE
  19 CONTINUE
      IF (.NOT. LAGE) GOTO 20
      IF (ISITIN(RAGE, IA, 11, 13) .EQ. 0) GOTO 17
C CHECK AGE
  20 CONTINUE
      IF (.NOT. LNAME) GOTO 21
      IF (ISITIN(NAME, IA, 14, 23) .EQ. 0) GOTO 17
C CHECK ROCK NAME
  21 CONTINUE
      IF (.NOT. LUNIT) GOTO 22
      IF (ISITIN(UNIT, IA, 24, 31) .EQ. 0) GOTO 17
C CHECK ROCK UNIT
  22 CONTINUE
      IF (.NOT. LSTATE) GOTO 23
      IF (ISITIN(STATE, IA, 32, 32) .EQ. 0) GOTO 17
C CHECK STATE
  23 CONTINUE
      IF (.NOT. SLOCN) GOTO 26
      IF (LCOORD) GOTO 25
C DEAL WITH SEARCH BY LAT/LONG FIRST
C
C LOOK TO SEE IF TAS COULD BE INVOLVED AND IF SO CONVERT TAS COORDS
C TO LAT AND LONG
      IF (IA(32) .NE. ITAS) GOTO 24
C NOT IN TAS SO DATA MUST ALREADY BE LAT/LONG
C
      IF (.NOT. INTAS) GOTO 17
C THE AREA DOES NOT INCLUDE TAS SO GO AND GET ANOTHER DATA SET
C NOW LOOK MORE CLOSELY BY CONVERTING TO LATS AND LONGS
C USE FORTRAN 77 CHARACTER VARIABLES
      ENCODE(BUFF, 135) COORDE
  135 FORMAT(A6, '. 0')

```

```

      DECODE(BUFF,136) ACORDE
136  FORMAT(F8.1)
      ENCODE(BUFF,135) COORDN
      DECODE(BUFF,136) ACORDN
C NOW HAVE THE COORDINATES IN DOUBLE PRECISION READY FOR PASSING TO GEOGRF
      CALL GEOGRF(ACORDE,ACORDN,ANSWER)
      IILAT=-(ANSWER(1)*100.0+ANSWER(2)+(ANSWER(3)/60.0))
      IF (IILAT .LT. ILATS .OR. IILAT .GT. ILATN) GOTO 17
      IILON=ANSWER(4)*100.0+ANSWER(5)+(ANSWER(6)/60.0)
      IF (IILON .LT. ILOW .OR. IILON .GT. ILONE) GOTO 17
      GOTO 26
      24 CONTINUE
C NOW LOOK FOR ALL BUT TAS
      IILAT=ILAT(IA(39))
      IF (IILAT .LT. ILATS .OR. IILAT .GT. ILATN) GOTO 17
      IILON=ILON(IA(44))
      IF (IILON .LT. ILOW .OR. IILON .GT. ILONE) GOTO 17
C CHECK LAT/LONG
      GOTO 26
C NOW FOR THE COORDS
      25 CONTINUE
C USE FORTRAN 77 CHARACTER VARIABLES HERE
      IF (IA(32) .NE. ITAS) GOTO 17
C NOT IN TAS SO NOT COORDS
      IF (COORDN .GT. CORDN .OR. COORDN .LT. CORDS) GOTO 17
      IF (COORDE .GT. CORDE .OR. COORDE .LT. CORDW) GOTO 17
C CHECK COORDS OF TAS USING FORTRAN 77 CHARACTER VARIABLES
      26 CONTINUE
      IF (.NOT. LCLCT) GOTO 27
      IF (ISITIN(CLCT,IA,50,52) .EQ. 0) GOTO 17
C CHECKED COLLECTOR
      27 CONTINUE
      IF (.NOT. LYEAR) GOTO 28
C USE FORTRAN 77 CHARACTER VARIABLES HERE
      IF (YEAR .LT. SYEAR .OR. YEAR .GT. FYEAR) GOTO 17
C CHECKED YEAR
      28 CONTINUE
      IF (.NOT. LHOLD) GOTO 29
      IF (ISITIN(SHOLD,IA,75,75) .EQ. 0) GOTO 17
C CHECKED HOLDER
      29 CONTINUE
      IF (.NOT. LMINRL) GOTO 30
      IF (ISITIN(IMINRL,IA,76,83) .EQ. 0) GOTO 17
C CHECKED MINERAL
      30 CONTINUE
      IF (.NOT. LMODIF) GOTO 31
      IF (ISITIN(IMODIF,IA,84,87) .EQ. 0 .AND. ISITIN(IMODIF,IA,88,91)
          .EQ. 0) GOTO 17
C CHECKED BOTH MODIFIERS
      31 CONTINUE
      IF (.NOT. LTREAT) GOTO 32
      IF (ISITIN(ITREAT,IA,92,93) .EQ. 0 .AND. ISITIN(ITREAT,IA,94,95)
          .EQ. 0 .AND. ISITIN(ITREAT,IA,96,97) .EQ. 0 .AND.
          ISITIN(ITREAT,IA,98,99) .EQ. 0) GOTO 17
C CHECKED ALL FOUR TREATMENTS
      32 CONTINUE
C
C IF GET TO HERE HAVE SATISFIED ALL THE CHECKS
      IA(1)=' '
C MASK OUT THE CODE FOR YEARS 19__ AND 20__ UNTIL NEEDED

```

```

IF (.NOT. VDU) GOTO 33
WRITE(5,300) IA
300 FORMAT(///1X,'REG NO',5X,8A1/
1X,'TYPE',7X,2A1/
1X,'AGE',8X,3A1/
1X,'ROCK NAME ',10A1/
1X,'ROCK UNIT ',8A1/
1X,'STATE, QUAD ',A1,1X,5A1/
1X,'COORDS OR'//
1X,'LAT/LONG',3X,6A1,1X,6A1/
1X,'COLLECTOR',2X,3A1/
1X,'FIELD NO',3X,6A1/
1X,'YEAR',7X,4A1/
1X,'LOCALITY',3X,12A1/
1X,'HOLDER',5X,A1/
1X,'MINERAL',4X,8A1/
1X,'MODIFIER',3X,4A1,1X,4A1/
1X,'TREATMENT',2X,4(2A1,1X)/
1X,'REFERENCE',2X,10A1/12X,10A1/12X,40A1/
1X,'OUTPUT MORE TO VDU?')
READ(5,101) IYES
VDU=IYES.EQ.IY
C RESET VDU OPTION IF DONT WANT MORE OUTPUT
33 CONTINUE
IF (.NOT. PRNTR .AND. .NOT. VDU) GOTO 40
C IF ENDED UP NOT WANTING ANY OUTPUT WHY BOTHER LOOKING ANY MORE
IF (.NOT. PRNTR) GOTO 17
C OFF TO THE READ IF ONLY VDU OUTPUT
IF (MOD(LINE,18) .EQ. 0) CALL HEAD(PAGE)
LINE=LINE+1
WRITE(6,301) (IA(I),I=1,37),(IA(I),I=50,99),(IA(I),I=1,8)
301 FORMAT(1X,8A1,' ',1X,2A1,' ',3A1,' ',10A1,' ',8A1,' ',
1X,A1,' ',5A1,' ',3A1,' ',6A1,' ',4A1,' ',12A1,' ',
2X,A1,' ',8A1,' ',2(4A1,' '),3(2A1,' '),2A1,' ',8A1)
C WRITE THE FIRST LINE
C
C NOW USE DIFFERENT FORMATS FOR LAT/LONG AND COORDS
IF (IA(38) .EQ. SPACE) GOTO 34
C DEAL WITH COORDS FIRST WHICH DONT HAVE SPACE FILL AT THE FRONT
WRITE(6,302) (IA(I),I=100,159),(IA(I),I=38,49)
302 FORMAT(9X,2(10A1,1X),' ',40A1,' ',6A1,'ME ',6A1,'MN'//)
GOTO 35
C
C NOW FOR LAT/LONG
34 WRITE(6,303) (IA(I),I=100,159),(IA(I),I=39,49)
303 FORMAT(9X,2(10A1,1X),' ',40A1,' ',2A1,'D',2A1,'M ',A1,
2X,3A1,'D',2A1,'M ',A1//)
35 CONTINUE
FOUND=.TRUE.
C REMEMBER THAT HAVE FOUND AT LEAST ONE ENTRY AND WRITTEN IT TO THE
IF (LINE .NE. 1000) GOTO 17
WRITE(5,304)
304 FORMAT(' 1000 ENTRIES SENT TO PRINTER - DO YOU'
' WANT TO SEND MORE?')
READ(5,101) IYES
IF (IYES .NE. IY) GOTO 40
GOTO 17
C IF DONT WANT MORE STOP OTHERWISE READ ANOTHER ENTRY
C PRINTER
C

```

```

C NOW CLOSE OFF
  40 CONTINUE
    CLOSE(UNIT=7, STATUS='KEEP')
    IF (FOUND) WRITE(6, 306)
  306 FORMAT(1X)
    STOP
    END
    SUBROUTINE GEOGRF(EAST, NORTH, ANSWER)
    DOUBLE PRECISION NORTH, EAST
    REAL ANSWER(6)
    DOUBLE PRECISION TMD1, ORTH, DEG, TMD2, CON, Q1, DOG, SIND, COSD,
      TAND, TANSQ, SINSEC, C, D, DTAN, R, P, PCUBE, POR, PFIVE, P1, P2, P3, P4,
      P5, GLAT, TEMPL, DLONG, DC, SLO, SLA
    DOUBLE PRECISION VAL(16), Q(5)
    INTEGER*2 I, IDLA, MLA, IDLO, MLO
C CONVERTS AMG GRID COORDS (IN METRES) TO LATS AND LONGS
C INPUT OF NORTH COORDINATE EXCLUDES LEADING 5 FOR USE IN TASMANIA
C E. G. 5326446.014 BECOMES 326446.014
    VAL(1)=9.833D-06
    VAL(2)=1.1117334878D05
    VAL(3)=3.4906585D-02
    VAL(4)=6.981317D-02
    VAL(5)=1.04719755D-01
    VAL(6)=9.008D-06
    VAL(7)=1.745329252D-02
    VAL(8)=0.66945418546D-02
    VAL(9)=1.99840032D-08
    VAL(10)=23.96162303D-20
    VAL(11)=5.9928028794D-14
    VAL(12)=119.76019192D-26
    VAL(13)=2.9964014397D-14
    VAL(14)=14.970023989D-26
    VAL(15)=6.3354611409D06
    VAL(16)=1.60389546D04
C
    ORTH=NORTH+5.0D06
C ADD THE LEADING 5 TO THE NORTH COORDINATE
    TMD1=1.0D07-ORTH
    DEG=VAL(1)*TMD1
C
    DO 10 I=1, 10
      TMD2=VAL(2)*DEG-VAL(16)*DSIN(VAL(3)*DEG)+
        16.83310D00*DSIN(VAL(4)*DEG)-0.0218D00*DSIN(VAL(5)*DEG)
      CON=TMD1-0.9996D00*TMD2
      IF (DABS(CON) .LT. 1.0D-03) GOTO 14
      DEG=DEG+VAL(6)*CON
  10 CONTINUE
    GOTO 16
C
  14 CONTINUE
    Q1=(EAST-500000.0D00)*1.0D-06
    Q(1)=Q1
    DO 11 I=2, 5
      Q(I)=Q(I-1)*Q1
  11 CONTINUE
    DOG=VAL(7)*DEG
    SIND=DSIN(DOG)
    COSD=DCOS(DOG)
    TAND=SIND/COSD
    TANSQ=TAND*TAND

```

```

SINSEC=0.48481368111D-05
C=1.0D00-VAL(8)*SIND*SIND
D=0.27777777778D01
DTAN=D*TAND
R=VAL(15)/C**1.5
P=637816.0D01/C**0.5
PCUBE=P**3
POR=P/R
PFIVE=PCUBE*P*P
P1=DTAN/(VAL(9)*R*P*SINSEC)
P2=DTAN*(5.0D00+3.0D00*TANSQ)/(VAL(10)*R*PCUBE*SINSEC)
P3=D/(P*COSD*SINSEC*.9996D-02)
P4=D*(POR+2.0D00*TANSQ)/(VAL(11)*PCUBE*SINSEC*COSD)
P5=D*(5.0D00+TANSQ*(28.0D00+24.0D00*TANSQ))/(VAL(12)*
COSD*PFIVE*SINSEC)
GLAT=DEG-P1*Q(2)+P2*Q(4)
TEMPL=P3*Q1-P4*Q(3)+P5*Q(5)
DLONG=TEMPL+7.0D00
CALL DECDEG(DLONG, IDLO, MLO, SLO)
IDLO=IDLO+140
CALL DECDEG(GLAT, IDLA, MLA, SLA)
GOTO 18
16 CONTINUE
WRITE(5,100)
100 FORMAT(' ***** GEOGRAPHICAL ERROR *****')
STOP 9998
18 CONTINUE
ANSWER(1)=IDLA
ANSWER(2)=MLA
ANSWER(3)=SLA
ANSWER(4)=IDLO
ANSWER(5)=MLO
ANSWER(6)=SLO
C STORE LAT AND LONG READY TO RETURN
RETURN
END
SUBROUTINE DECDEG(ANGLE, IDEG, MIN, SEC)
DOUBLE PRECISION ANGLE, SEC
INTEGER*2 IDEG, MIN
DOUBLE PRECISION DEGI, RMIN
IDEG=IFIX(SNGL(ANGLE))
DEGI=IDEG
ANGLE=60.0D00*(ANGLE-DEGI)
MIN=IFIX(SNGL(ANGLE))
RMIN=MIN
SEC=60.0D00*(ANGLE-RMIN)
RETURN
END
SUBROUTINE JUSTIF(REGN, REGNO, IHOLD)
C FOR SETTING UP REGISTRATION NUMBERS IN THE FORMAT USED BY ROCKADD
C USES FORTRAN 77 CHARACTER VARIABLES
CHARACTER*1 REGNO(8), SPACE, AMINUS
CHARACTER*8 REGN
INTEGER IHOLD, I, K, KUP, IUP, J, JUP
DATA SPACE/' ', AMINUS/'-'
GOTO (201, 202, 205, 203, 204, 205), IHOLD
201 RETURN
C DONT YET HAVE A FORMAT FOR THE H. E. C.
202 CONTINUE
C THE MINES DEPT AS HOLDER - REG NO HAS FORM 67-1234

```

```

DO 210 I=1,8
  IF (REGNO(I) .NE. SPACE) GOTO 211
C FIND THE FIRST NON-BLANK CHARACTER
210 CONTINUE
211 K=2
C COUNTER FOR POSITION IN TEMPORARY ARRAY
  REGN(1:1)='0'
C INITIALLY SET UP WITH THE CODE FOR THE YEARS 19__ . LATER ON
C WILL NEED TO REMOVE THIS WITH THE YEARS 20__ AND REQUEST
C EXTRA DIGIT IN SEARCHES
  REGN(K:K)=REGNO(I)
  K=K+1
  I=I+1
  REGN(K:K)=REGNO(I)
C NOW HAVE TRANSFERRED THE FIRST TWO CHARACTERS - THE YEAR CODE
  K=K+1
  REGN(K:K)=AMINUS
C NOW PUT THE MINUS THERE
C
C NOW COPY THE NUMBER FROM THE RIGHT HAND SIDE
  KUP=8
  IUP=8
  DO 212 J=1,8
    IF (REGNO(IUP) .NE. SPACE) GOTO 213
C FIND THE RIGHT-HAND MOST NON-BLANK
  IUP=IUP-1
212 CONTINUE
213 REGN(KUP:KUP)=REGNO(IUP)
  KUP=KUP-1
  IUP=IUP-1
  IF (REGNO(IUP) .NE. SPACE .AND. REGNO(IUP) .NE. AMINUS) GOTO 213
C SECOND HALF OF NUMBER MAY BE TERMINATED BY MINUS OR SPACE
  K=K+1
  IF (K .GT. KUP) GOTO 250
C NO BLANK FILL REQUIRED - MOST UNLIKELY
  DO 214 J=K,KUP
    REGN(J:J)=SPACE
214 CONTINUE
C FILLED WITH BLANKS
  GOTO 250
C NOW IN FORMAT I2, A1, I5
C
203 CONTINUE
C QUEEN VIC
  RETURN
C WE KNOW NOTHING
204 CONTINUE
C TAS MUSEUM
  RETURN
C WE DONT KNOW THIS EITHER
C
205 CONTINUE
C THE UNIVERSITY AND MINES MINERAL CATALOGUE HAVE NUMBERS ONLY SO
C WANT TO RIGHT JUSTIFY
  KUP=8
  JUP=8
  DO 220 J=1,8
    IF (REGNO(JUP) .NE. SPACE) GOTO 221
  JUP=JUP-1
220 CONTINUE

```

```

C LOOK FOR THE LAST NON-BLANK CHARACTER IN THE FIELD
221 CONTINUE
C NOW COPY UNTIL THE NEXT BLANK - STILL READING FROM RIGHT TO LEFT
  REGN(KUP:KUP)=REGNO(JUP)
  KUP=KUP-1
  JUP=JUP-1
  IF (JUP .EQ. 0) GOTO 222
  IF (REGNO(JUP) .NE. SPACE) GOTO 221
C GO BACK FOR THE NEXT CHARACTER ONLY IF THERE IS A NON-BLANK LEFT
222 CONTINUE
  IF (KUP .EQ. 0) GOTO 250
C HAVE FILLED REGTMP
  DO 223 J=1, KUP
  REGN(J:J)=SPACE
223 CONTINUE
C NOW IN I8 FORMAT
  GOTO 250
C
C
250 CONTINUE
  RETURN
  END
  SUBROUTINE YESRCH(SRCH, VARIAB)
  LOGICAL SRCH
  CHARACTER*1 VARIAB(72)
  SRCH=VARIAB(1) .NE. ' ' .OR. VARIAB(2) .NE. ' '
C USE FORTRAN 77 CHARACTER COMPARISON
C SRCH IS TRUE IF THERE IS A STRING SPECIFIED TO SEARCH FOR
C AND FALSE OTHERWISE
  RETURN
  END
  INTEGER FUNCTION ILAT(LAT)
C TO CONVERT FROM FORTRAN 77 CHARACTER VARIABLE TO INTEGER VARIABLE
C LAT IS OF THE FORM 4330S
  INTEGER I
  CHARACTER*1 LAT(5)
  REAL BUFF(2)
  ENCODE(BUFF,100) (LAT(I), I=1, 4)
100 FORMAT(4A1)
  DECODE(BUFF,101) ILAT
101 FORMAT(I4)
  IF (LAT(5) .EQ. 'S') ILAT=-ILAT
C MAKE NEGATIVE FOR SOUTH
  RETURN
  END
  INTEGER FUNCTION ILON(LON)
C TO CONVERT FROM FORTRAN 77 CHARACTER VARIABLE TO INTEGER VARIABLE
  INTEGER I
  CHARACTER*1 LON(6)
  REAL BUFF(2)
  ENCODE(BUFF,100) (LON(I), I=1, 5)
100 FORMAT(5A1)
  DECODE(BUFF,101) ILON
101 FORMAT(I5)
  IF (LON(6) .EQ. 'W') ILON=-ILON
C MAKE NEGATIVE IF WEST
  RETURN
  END
  INTEGER FUNCTION ISITIN(AKEYS, A, IS, IE)
C SEARCH FOR CHARACTERS IN FIELDS IS TO IE OF A STARTING AT FIELD

```

```

C IS FOR MATCHING WITH STRINGS IN AKEYS. THE STRINGS IN AKEYS
C ARE STORED AS STRING1/STRING2/ . . /STRINGN/ WITH A SPACE FOLLOWING
C A / ACTING AS A TERMINATOR.
C ISITIN TAKES A VALUE OF 1 IF ANY OF THE STRINGS MATCH AND ZERO
C OTHERWISE.
C BASED ON A ROUTINE ORIGINALLY WRITTEN BY R. J. G. LEWIS, TAS UNI
C USES CAHRACTER*1 FOR FORTRAN 77 BUT COULD EQUALLY WELL USE A1 FORMAT
C FOR ANY TYPE OF VARIABLE
CHARACTER*1 A(72), AKEYS(72), AEND, SPACE
INTEGER IS, IE, I, IBASE, KEYST
AEND='/'
SPACE=' '
KEYST=1
8 IBASE=IS-1
DO 10 I=KEYST,72
IF (AKEYS(I) .EQ. AEND) GOTO 12
C FOUND A MATCH IF HIT A /
IF (AKEYS(I) .NE. A(IBASE+1)) GOTO 14
IBASE=IBASE+1
IF (IBASE .GE. IE) GOTO 12
C HAVE FOUND A MATCH TO THE END OF THE FIELD
10 CONTINUE
12 ISITIN=1
RETURN
C FOUND SO RETURN
14 CONTINUE
I=I+1
DO 16 KEYST=I,72
IF (AKEYS(KEYST) .EQ. AEND) GOTO 18
C SCAN FOR A /
16 CONTINUE
ISITIN=0
RETURN
C DID NOT FIND /
18 KEYST=KEYST+1
IF (AKEYS(KEYST) .NE. SPACE) GOTO 8
C NOT / SO BACK ROUND
ISITIN=0
RETURN
END
SUBROUTINE HEAD(PAGE)
C TO HEAD UP A PAGE
INTEGER PAGE
PAGE=PAGE+1
WRITE(6,100) PAGE
100 FORMAT(1H1,120X,'PAGE',I4/2X,'REG NO !TYP!PAGE! ROCK NAME!',
. 'ROCKUNIT!ST! QUAD!COL!FLD NO!YEAR! LOCALITY !',
. 'HLD! MINERAL!MOD1!MOD2! TREATMENT ! REG NO'/
16X,'REFERENCE',6X,'!',12X,'EXTRA REFERENCE',
. 13X,'! LOCATION'/1X,118('-'))
RETURN
END

```

45/51

APPENDIX 10
Program GUIDER

```
* GUIDER.CSS  
* FOR RUNNING GUIDER  
L GUIDER; AS 6.PR.; ST  
$EXIT
```

C GUIDER. FTM - FOR PRINTING THE GUIDE TO THE ROCK CATALOGUE
C PROGRAMS

INTEGER IDATE(3), IMNTH(12), A(20), LINE, PAGE
INTEGER*2 IRA(200), IRB(200), IA(25), IIA(25)
CHARACTER*30 ROCK(30), MINRL(150)
CHARACTER*3 ICLCT(150), TCLCT(150)
CHARACTER*35 COLECT(150)
CHARACTER*4 IMODIF(200)
CHARACTER*24 AMODIF(200)
EQUIVALENCE (A(1), IA(1)), (A(1), IIA(1)), (A(1), IRA(1)),
 (ROCK(1), MINRL(1)), (ROCK(1), COLECT(1)),
 (ROCK(1), AMODIF(1))

C TO SAVE SPACE
DATA IMNTH/'JAN', 'FEB', 'MAR', 'APR', 'MAY', 'JUN', 'JUL',
 'AUG', 'SEP', 'OCT', 'NOV', 'DEC'/
CALL DATE(IDATE)
IDATE(1)=IDATE(1)+1900

C PUT THE CENTURY IN
WRITE(6,100) IDATE(2), IMNTH(IDATE(3)), IDATE(1)
100 FORMAT(/////30X, 'TASMANIAN ROCK CATALOGUE'/30X, 24('-')
 /////30X, 'GUIDE TO INFORMATION STORED'/////35X,
 'DATE', I3, 1X, A3, I5)

C WRITE TITLE PAGE AND DATE
C
PAGE=1

C PAGE COUNTER
CALL HEAD(LINE, PAGE)
C HEADS PAGE, RESET LINE COUNTER AND INCREMENTS PAGE COUNTER
WRITE(6,103)
103 FORMAT(34X, 'INTRODUCTION'/34X, 12('-'))
LINE=LINE+2
OPEN(UNIT=4, FILE='INTRODUC. DAT', SHARE='ERO')
10 READ(4,104,END=11) A
104 FORMAT(20A4)
IF (LINE .GT. 55) THEN
CALL HEAD(LINE, PAGE)
WRITE(6,103)
LINE=LINE+2
ENDIF

C HEAD UP A NEW PAGE AS NEEDED
WRITE(6,105) A
105 FORMAT(1X, 20A4)
LINE=LINE+1
GOTO 10

C GET NEXT LINE OF INTRODUCTION
11 CLOSE(UNIT=4, STATUS='KEEP')

C
CALL HEAD(LINE, PAGE)
WRITE(6,106)
106 FORMAT(30X, 'REGISTRATION NUMBERS'/30X, 20('-')//
 15X, 'FOR THE MINES DEPT. ROCK CATALOGUE'//
 15X, 'ASSUMED TO BE OF THE FORM 77-127'//
 15X, 'FOR THE MINES DEPT. MINERAL CATALOGUE'//
 15X, 'ASSUMED TO BE OF THE FORM 12345'//
 15X, 'FOR THE UNIVERSITY ASSUMED TO BE OF THE FORM'//
 15X, '12345')

C
CALL HEAD(LINE, PAGE)
WRITE(6,107)

```

107 FORMAT(15X, 'GENERIC TYPE'/15X, 12(' - '))
    LINE=LINE+2
    OPEN(UNIT=4, FILE='ROCKTYPE. DAT', SHARE='ERO')
12 READ(4, 930, END=13) IA
930 FORMAT(25A2)
    IF (LINE .GT. 55) THEN
    CALL HEAD(LINE, PAGE)
    WRITE(6, 107)
    LINE=LINE+2
    ENDIF
    WRITE(6, 931) IA
931 FORMAT(10X, 25A2)
    LINE=LINE+1
    GOTO 12
CC COPY GENERIC TYPE AND LET USER KEEP THIS FILE IN ORDER
13 CLOSE(UNIT=4, STATUS='KEEP')
C
    CALL HEAD(LINE, PAGE)
    WRITE(6, 108)
108 FORMAT(20X, 'AGE'/20X, ' --- ')
    LINE=LINE+2
    OPEN(UNIT=4, FILE='ROCKAGES. DAT', SHARE='ERO')
14 READ(4, 930, END=15) IA
    IF (LINE .GT. 55) THEN
    CALL HEAD(LINE, PAGE)
    WRITE(6, 108)
    LINE=LINE+2
    ENDIF
    WRITE(6, 931) IA
    LINE=LINE+1
    GOTO 14
C COPY AGES IN CHRONOLGICAL ORDER NOT ALPHABETICAL ORDER
15 CLOSE(UNIT=4, STATUS='KEEP')
    CALL HEAD(LINE, PAGE)
    WRITE(6, 109)
109 FORMAT(30X, 'ROCK NAMES'/30X, 10(' - '))
    LINE=LINE+2
    NVAR=1
C COUNTER FOR NUMBER OF ENTRIES TO BE SORTED
    OPEN(UNIT=4, FILE='ROCKNAME. DAT', SHARE='ERO')
16 READ(4, 110, END=17) ROCK(NVAR)
110 FORMAT(A30)
    IRA(NVAR)=NVAR
C INITIALISE THE INDEX FOR THE SORT
    NVAR=NVAR+1
    IF (NVAR .GT. 30) STOP 'TOO MANY ROCK NAMES'
    GOTO 16
C READ AND STORE MORE
17 CLOSE(UNIT=4, STATUS='KEEP')
    NVAR=NVAR-1
C HAD A VALUES OF 1 MORE THAN THE NUMBER READ
    CALL ALFSRT(IRA, ROCK, NVAR, 10)
    DO 18 I=1, NVAR
    IF (LINE .GT. 55) THEN
    CALL HEAD(LINE, PAGE)
    WRITE(6, 109)
    LINE=LINE+1
    ENDIF
    WRITE(6, 111) ROCK(IRA(I))
111 FORMAT(30X, A30)

```

```

LINE=LINE+1
18 CONTINUE
C SORTED AND PRINTED ROCK NAMES
C
CALL HEAD(LINE, PAGE)
WRITE(6, 112)
112 FORMAT(30X, 'ROCK UNITS'/30X, 10(' - '))
LINE=LINE+2
NVAR=1
OPEN(UNIT=4, FILE='ROCKUNIT. DAT', SHARE='ERO')
19 READ(4, 110, END=20) ROCK(NVAR)
IRA(NVAR)=NVAR
NVAR=NVAR+1
IF (NVAR .GT. 30) STOP 'TOO MANY ROCK UNITS'
GOTO 19

```

```

C ROUND FOR MORE
20 CLOSE(UNIT=4, STATUS='KEEP')
NVAR=NVAR-1
CALL ALFSRT(IRA, ROCK, NVAR, 8)
DO 21 I=1, NVAR
IF (LINE .GT. 55) THEN
CALL HEAD(LINE, PAGE)
WRITE(6, 112)
LINE=LINE+2
ENDIF
WRITE(6, 111) ROCK(IRA(I))
LINE=LINE+1

```

```

21 CONTINUE
C SORTED AND PRINTED ROCK UNITS

```

```

C
CALL HEAD(LINE, PAGE)
WRITE(6, 113)
113 FORMAT(15X, 'LOCATION DATA'/15X, 13(' - '))
WRITE(6, 114)
114 FORMAT(' STATE' /
. / 0 TASMANIA' /
. / 1 VICTORIA' /
. / 2 NEW SOUTH WALES (INCLUDING A. C. T.)' /
. / 3 QUEENSLAND' /
. / 4 NORTHERN TERRITORY' /
. / 5 WESTERN AUSTRALIA' /
. / 6 SOUTH AUSTRALIA' /
. / 9 OVERSEAS' / /)
WRITE(6, 115)
115 FORMAT(' FOR ALL AREAS OUTSIDE TASMANIA' /
. / LATITUDE AND LONGITUDE ARE USED. ' / /
. / WITHIN TASMANIA THE AUSTRALIAN MAP GRID' /
. / IS USED WITH AT LEAST THREE (3) DIGITS' /
. / IN EACH COORDINATE. THE ASSUMED DIGIT 5 IN' /
. / NORTHINGS IS OMITTED')

```

```

C
CALL HEAD(LINE, PAGE)
WRITE(6, 116)
116 FORMAT(35X, 'COLLECTORS'/35X, 10(' - '))
LINE=LINE+2
NVAR=1
OPEN(UNIT=4, FILE='COLECTOR. DAT', SHARE='ERO')
22 READ(4, 117, END=26) ICLCT(NVAR), COLECT(NVAR)
117 FORMAT(A3, 2X, A35)
IRA(NVAR)=NVAR

```

IRB(NVAR)=NVAR

C NOW REVERSE ICLCT TO PUT THE LETTER STANDING FOR THE SURNAME FIRST
C AND STRIP OFF ANY NUMERIC CHARACTERS THAT MAY APPEAR

K=3
J=1
DO 24 I=1,3
IF (ICLCT(NVAR)(K:K) .GE. '0' .AND. ICLCT(NVAR)(K:K) .LE. '9'
.OR. ICLCT(NVAR)(K:K) .EQ. ' ') GOTO 23

C SKIP NUMERIC VALUES
TCLCT(NVAR)(J:J)=ICLCT(NVAR)(K:K)
J=J+1

23 K=K-1
24 CONTINUE
IF (J .NE. 4) THEN
DO 25 I=J,3

TCLCT(NVAR)(I:I)=' '
25 CONTINUE

C FILL WITH BLANKS
ENDIF
NVAR=NVAR+1
IF (NVAR .GT. 150) STOP ' TOO MANY COLLECTORS '
GOTO 22

C BACK ROUND

C
26 CLOSE(UNIT=4, STATUS='KEEP')
NVAR=NVAR-1
CALL ALFSRT(IRA, ICLCT, NVAR, 3)
CALL ALFSRT(IRB, TCLCT, NVAR, 3)
DO 27 I=1, NVAR
IF (LINE .GT. 55) THEN
CALL HEAD(LINE, PAGE)
WRITE(6, 116)
LINE=LINE+2
ENDIF
WRITE(6, 118) ICLCT(IRA(I)), COLECT(IRA(I)), ICLCT(IRB(I)),
COLECT(IRB(I))

118 FORMAT(1X, A3, 2X, A35, 2X, ' ', 2X, A3, 2X, A35)
LINE=LINE+1

27 CONTINUE

C SORTED AND PRINTED COLLECTORS

C
CALL HEAD(LINE, PAGE)
WRITE(6, 119)
119 FORMAT(15X, 'HOLDERS'/15X, 7(' - '))
WRITE(6, 122)
122 FORMAT(1X, 'M', 6X, 'DEPARTMENT OF MINES (ROCK CATALOGUE)'/
8X, 'P. O. BOX 56'/8X, 'ROSNY PARK'/
8X, 'TASMANIA 7018'/8X, 'AUSTRALIA'//
WRITE(6, 123)
123 FORMAT(1X, 'N', 6X, 'DEPARTMENT OF MINES (MINERAL CATALOGUE)'/
8X, 'P. O. BOX 56'/8X, 'ROSNY PARK'/
8X, 'TASMANIA 7018'/8X, 'AUSTRALIA'//
WRITE(6, 126)
126 FORMAT(1X, 'U', 6X, 'GEOLOGY DEPARTMENT'/
8X, 'UNIVERSITY OF TASMANIA'/
8X, 'G. P. O. BOX 252C'/8X, 'HOBART'/
8X, 'TASMANIA 7001'/8X, 'AUSTRALIA'//

C LIST HOLDERS

C

```

CALL HEAD(LINE, PAGE)
WRITE(6, 130)
130 FORMAT(30X, 'MINERALS'/30X, 8(' - '))
LINE=LINE+2
NVAR=1
OPEN(UNIT=4, FILE='MINERALS. DAT', SHARE='ERO')
28 READ(4, 110, END=29) MINRL(NVAR)
IRA(NVAR)=NVAR
NVAR=NVAR+1
IF (NVAR .GT. 150) STOP 'TOO MANY MINERALS'
GOTO 28
C READ AND STORE ANOTHER MINERAL
29 CLOSE(UNIT=4, STATUS='KEEP')
NVAR=NVAR-1
CALL ALFSRT(IRA, MINRL, NVAR, 8)
DO 30 I=1, NVAR
IF (LINE .GT. 55) THEN
CALL HEAD(LINE, PAGE)
WRITE(6, 130)
LINE=LINE+2
ENDIF
WRITE(6, 111) MINRL(IRA(I))
LINE=LINE+1
30 CONTINUE
C SORTED AND PRINTED MINERALS
C
CALL HEAD(LINE, PAGE)
WRITE(6, 131)
131 FORMAT(29X, 'MODIFIERS'/29X, 9(' - '))
LINE=LINE+2
OPEN(UNIT=4, FILE='MODIFIER. DAT', SHARE='ERO')
NVAR=1
31 READ(4, 132, END=32) IMODIF(NVAR), AMODIF(NVAR)
132 FORMAT(A4, 2X, A24)
IRA(NVAR)=NVAR
IRB(NVAR)=NVAR
NVAR=NVAR+1
IF (NVAR .GT. 200) STOP 'TOO MANY MODIFIERS'
GOTO 31
C BACK ROUND
32 CLOSE(UNIT=4, STATUS='KEEP')
NVAR=NVAR-1
CALL ALFSRT(IRA, IMODIF, NVAR, 4)
CALL ALFSRT(IRB, AMODIF, NVAR, 24)
DO 33 I=1, NVAR
IF (LINE .GT. 55) THEN
CALL HEAD(LINE, PAGE)
WRITE(6, 131)
LINE=LINE+2
ENDIF
WRITE(6, 133) IMODIF(IRA(I)), AMODIF(IRA(I)), IMODIF(IRB(I)),
AMODIF(IRB(I))
133 FORMAT(1X, A4, 2X, A24, 2X, ' | ', 2X, A4, 2X, A24)
LINE=LINE+1
33 CONTINUE
C SORT AND PRINT MODIFIERS
C
CALL HEAD(LINE, PAGE)
WRITE(6, 134)
134 FORMAT(20X, 'TREATMENTS'/20X, 10(' - '))

```

```

LINE=LINE+2
OPEN(UNIT=4, FILE='TRTMENT. DAT', SHARE='ERO')
35 READ(4, 950, END=36) IIA
950 FORMAT(25A2)
IF (LINE .GT. 55) THEN
CALL HEAD(LINE, PAGE)
WRITE(6, 134)
LINE=LINE+2
ENDIF
WRITE(6, 951) IIA
951 FORMAT(10X, 25A2)
LINE=LINE+1
GOTO 35
C BACK ROUND
C
36 CLOSE(UNIT=4, STATUS='KEEP')
WRITE(6, 135)
135 FORMAT(1X)
STOP
END
SUBROUTINE ALFSRT(IR, CVAR, NVAR, NCHAR)
INTEGER NVAR, NCHAR, NLEN
CHARACTER*(*) CVAR(NVAR)
INTEGER*2 IR(NVAR)
LOGICAL NSWAP
IF (NVAR .LE. 1) RETURN
C NOTHING TO SORT
NM1=NVAR-1
DO 30 J=1, NM1
NSWAP=. TRUE.
IRI=IR(1)
DO 40 I=1, NM1
IP1=I+1
IRIP1=IR(IP1)
IF (CVAR(IRI)(1:NCHAR) .LE. CVAR(IRIP1)(1:NCHAR)) GOTO 40
NSWAP=. FALSE.
IR(I)=IRIP1
IR(IP1)=IRI
IRIP1=IRI
40 IRI=IRIP1
IF (NSWAP) RETURN
30 CONTINUE
RETURN
END
SUBROUTINE HEAD(LINE, PAGE)
INTEGER LINE, PAGE
LINE=0
WRITE(6, 100) PAGE
100 FORMAT(1H1/70X, 'PAGE', I3)
PAGE=PAGE+1
RETURN
END

```