

1985/34. CARS - A computer assisted records system (Revision 4)

R.G. Richardson

Abstract

The program suite described is used for adding entries to a data-base of Engineering Geology correspondence, sorting the data-base, and searching it. The data are entered in a simple fill-in-the spaces manner and part or all of the details entered may be searched. The new revision simplifies searching by area.

USING THE PROGRAMS

The programs are run on the Geological Survey Perkin-Elmer mini-computer, and it is assumed that the user is familiar with the standard data editing facilities.

Data-base maintenance

Data are put into a standard format (Appendix 1) before entry. Input is commenced by typing RECADD and continues until END is typed in response to the name prompt. Data are entered left justified in response to prompts, with the category and geology numbers being entered as either one or two digits on the same line.

At the end of input, a proof-sheet is output and the data saved in file RECTEMP.TMP. Any corrections should be made to this file using the standard editing facilities and a new proof sheet then printed and checked.

The new data in RECTEMP.TMP must be added to the end of the existing data-base by typing RECMERGE. To ensure that the file remains in records reference number order, it should be sorted periodically using the RECSORT command. As sorting is a slow process it should not be carried out more often than necessary.

Data-base searching

The search phase is entered by typing RECSRCH. An entry will be retrieved only if one value in each search option specified is found.

The program requests the following data:

- (i) Search type - F for a search on specified option values
- R for a search between a range of records reference numbers. If R is specified, the starting and ending record reference numbers are specified. e.g. 1234/78.
- (ii) Name - one or more names on a single line, each name terminated by /. If a search by name is not required leave the line blank. e.g. BROWN/JONES/SMITH/
- (iii) Job location - details as for name.
- (iv) Agency name - details as for name.
- (v) Agency type - one or more agency numbers on a single line, each terminated by /. If a search by agency type

is not required leave the line blank.

e.g. 0/ find agency type 0
0/2 find agency types 0 or 2

- (vi) Year - one or more years on a single line, each terminated by a /. Leave blank if not required.
e.g. 82/ only year 1982
75/76/77/78/79/80/ years 1975 to 1980 inclusive.
- (vii) Geologist - details as for name. e.g. PRW/WCC/DJJ/
- (viii) Search also non-specified area/subject material - leave blank if this material is not to be included in a search by area.
- Y for searching material that may be of a general or non-area specific nature when searching by area. The map reference must be 0 0.
e.g. if this is the only search option specified a list of general reports is produced.
e.g. a search for work done by geologist CJK on landslides in north-east Tasmania (search by area) may have this option specified to detect any general work done by CJK on landslides as well.
- (ix) Search by area - leave blank for no search by area.
- Y for finding entries inside a specified area. Entries on the boundary of the area will not be found. The program prompts for the number of vertices. If 2 is entered a simple rectangle parallel to the grid may be entered by specifying the co-ordinates of any two diagonally opposite corners. Otherwise the program prompts for the vertex co-ordinates. Co-ordinates should be in the same form as used on the input sheets.
- (x) Category - one or more category numbers on a single line, each group terminated by /. Leave blank if not required.
e.g. 0/2/ groundwater or expansive soils
12/4 slope stability and expansive soils or miscellaneous.
- (xi) Geology - one or more geology numbers on a single line, each group terminated by /. Leave blank if not required.
e.g. 0/9/ Quaternary or granite
17/ Tertiary sediments and Tertiary basalt.
- (xii) Screen listing required - Y if required, N otherwise.
At the end of each screen a choice is made as to whether to list any more data on the screen or not.
- (xiii) Printout required - Y if the number of entries found can be realistically printed.
- N if the number of entries found is too great to want them printed.

THE PROGRAMS

RECADD (Appendix 2)

This program accepts data from the keyboard and copies it to a file in a format suitable for editing. Prompts are used to guide the user. The file created (RECTEMP.TMP) is then edited using the standard edit facilities.

RECMERGE (Appendix 3)

The data from RECTEMP.TMP are converted to the format of the data-base. The data-base is copied to a temporary work file and the new data are added to the end of this. The combined file is then copied back to the original data-base file.

RECSORT (Appendix 4)

The data are sorted into ascending records reference number order and written to a temporary file in the new order. The temporary file is then copied back to the original data-base file.

RECSRCH (Appendix 5)

The data-base is searched for the occurrence of specified strings and a point-in-polygon algorithm is used to locate data from within a specified area.

[15 July 1985]

APPENDIX 1

Data input sheet

CARS (COMPUTER ASSISTED RECORDS SYSTEM)

NAME: _____ (24)
JOB LOCATION: _____ (36)
AGENCY: _____ (24)

GOVERNMENT PROFESSIONAL INDIVIDUAL

RECORDS REFERENCE NO.: _____ / _____

GEOLOGIST: _____ (3)

AMG MAP REFERENCE: _____ 5 _____ (9)

CATEGORY:*

- GROUNDWATER
- SLOPE STABILITY
- EXPANSIVE SOILS
- FOUNDATION INVESTIGATION
- MISCELLANEOUS

GEOLOGY:*

Qu Tert.Sed. Triassic Permian L-Pal
 C Pre-C Tb Jdl Granite

*Cross two (2) maximum

CARS (COMPUTER ASSISTED RECORDS SYSTEM)

NAME: _____ (24)
JOB LOCATION: _____ (36)
AGENCY: _____ (24)

GOVERNMENT PROFESSIONAL INDIVIDUAL

RECORDS REFERENCE NO.: _____ / _____

GEOLOGIST: _____ (3)

AMG MAP REFERENCE: _____ 5 _____ (9)

CATEGORY:*

- GROUNDWATER
- SLOPE STABILITY
- EXPANSIVE SOILS
- FOUNDATION INVESTIGATION
- MISCELLANEOUS

GEOLOGY:*

Qu Tert.Sed. Triassic Permian L-Pal
 C Pre-C Tb Jdl Granite

*Cross two (2) maximum

APPENDIX 2
Program RECADD

```
*RECADD. CSS
*FOR RUNNING RECADD AND PRINTING A PROOF SHEET
$IFX RECTEMP. TMP: $WRITE ** CHECK LAST MERGE: $EXIT: $ENDC
PRE ETM: AL RECTEMP. TMP, IN, 106
* SET UP THE OUTPUT FILE
L RECADD, 3: AS 6, RECTEMP. TMP: * LOAD PROG AND SET LU 6
TENPFILE 3, IN, 80: ST
PRINT RECTEMP. TMP
$WRITE FILE IS RECTEMP. TMP: ENA ETM: $EXIT
```

6/38

```

*TITL RECADD.FTN - ADD LETTERS TO THE RECORDS FILE
C TAKES KEYBOARD INPUT AND PREPARES A PROOF SHEET
  CHARACTER*1 BUFF(9)
  INTEGER*4 MAPREF
  CHARACTER*24 NAME
  CHARACTER*36 LOCATN
  CHARACTER*24 AGNAME
  INTEGER*2 AGNO, RECNO, RECYR
  CHARACTER*3 GEOLST
  CHARACTER*2 CATG, GEOL
C INPUT IS NAME, LOCATION, AGENCY NAME, AGENCY TYPE(AGNO),
C RECORDS FILE NO (RECNO/RECYR), GEOLOGIST,
C CATEGORY(UP TO 2), GEOLOGY (UP TO 2)
C
  OPEN(UNIT=5, FILE='CON:')
C SET THE CONSOLE UP AS LU 5 FOR INPUT
C THE OUTPUT IS TO LU 6
  10 WRITE(5,100)
  100 FORMAT(' NAME OR END')
  READ(5,200) NAME
  200 FORMAT(A24)
  IF (INDEX(NAME, 'END') .NE. 0) GOTO 20
C RECOGNISE END BY HAVING END ON ITS OWN AND PRINT PROOF SHEET
  WRITE(5,101)
  101 FORMAT(' LOCATION')
  READ(5,201) LOCATN
  201 FORMAT(A36)
  WRITE(5,102)
  102 FORMAT(' AGENCY')
  READ(5,202) AGNAME
  202 FORMAT(A24)
  WRITE(5,103)
  103 FORMAT(' AGENCY TYPE')
  READ(5,*) AGNO
  11 WRITE(5,104)
  104 FORMAT(' RECORDS REF NO')
  READ(5,109) BUFF
  109 FORMAT(9A1)
  DO 12 I=1,9
  IF (BUFF(I) .EQ. '/') BUFF(I)=' '
  12 CONTINUE
C CHANGE / TO , TO COPE WITH FREE FORMAT READ
  REWIND 3
  WRITE(3,109) BUFF
  REWIND 3
  READ(3,*,END=11,ERR=11) RECNO, RECYR
  WRITE(5,105)
  105 FORMAT(' GEOLOGIST')
  READ(5,203) GEOLST
  203 FORMAT(A3)
  WRITE(5,106)
  106 FORMAT(' MAP REF')
  READ(5,*) MAPREF
  WRITE(5,107)
  107 FORMAT(' CATEGORY')
  READ(5,204) CATG
  204 FORMAT(A2)
  WRITE(5,108)
  108 FORMAT(' GEOLOGY')

```

```
      READ(5,204) GEOL
C READ ONE COMPLETE DATA SHEET
C
C 50 WRITE TO OUTPUT FILE
      WRITE(6,300) NAME, LOCATN, AGNAME, AGNO, RECNO, RECYR, GEOLST, MAPREF,
      CATG, GEOL
300 FORMAT(1X, '@', A24, '@', A36, '@', A24, '@', I1, '@', I5, '//',
      I2, '@', A3, '@', I9, 2('@', A2), '@')
C WRITE WITH DELIMITERS AFTER EACH FIELD
      GOTO 10
C BACK AROUND
C
C OTHERWISE CLOSE UP AND STOP
      20 CONTINUE
      CLOSE(UNIT=6, STATUS='KEEP')
      END
```

APPENDIX 3

Program RECMERGE

```

*RECMERGE. CSS
* FOR MERGING CORRECTED FILE WITH MAIN FILE
PRE ETM: XDE MRGTMP. TMP: *DELETE SCRATCH FILE
AL MRGTMP. TMP, IN, 88: L RECMERGE, 10: * AL SCRATCH FILE AND LOAD PROG
REP RECTEMP. TMP, FF00: AS 6, RECTEMP. TMP, ERO: AS 4, MRGTMP. TMP: ST
$IFNE 0: $WRITE TRANSLATE ERROR: ENA ETM: $EXIT: $ENDC
REP MRGTMP. TMP, FF00
$BUILD COPY. CMD
IN JOBREC. DAT
AL TEMP: TEMP. DAT, IN, 88/6/5
OUT TEMP: TEMP. DAT
COPY *, *
IN MRGTMP. TMP
COPY *, *
END
$ENDB
L COPY32, 50: ST , COM=COPY. CMD, LI=NULL: , LO=NULL:
$IFNE 0: $WRITE COPY-MERGE ERROR: ENA ETM: $EXIT: $ENDC
REP JOBREC. DAT, 0: REP TEMP: TEMP. DAT, FF00
DE COPY. CMD, JOBREC. DAT
$BUILD COPY. CMD
IN TEMP: TEMP. DAT
AL JOBREC. DAT, IN, 88/10/3
OUT JOBREC. DAT
COPY *, *
REW I
REW 0
VERIFY *, *
END
$ENDB
L COPY32, 50: ST , COM=COPY. CMD, LI=NULL: , LO=NULL:
$IFNE 0: $WRITE COPY BACK FAILED: ENA ETM: $EXIT: $ENDC
REP JOBREC. DAT, FF00: REP TEMP: TEMP. DAT, 0: REP RECTEMP. TMP, 0
REP MRGTMP. TMP, 0
DE COPY. CMD, MRGTMP. TMP, RECTEMP. TMP, TEMP: TEMP. DAT
ENA ETM
$EXIT

```

```

$TITL  RECMERGE.FTN - CONVERT PROOF FILE TO MASTER FILE FORMAT
C
      INTEGER*4 NORTH
      INTEGER*2 EAST
C SPLIT MAPREF INTO THE RELEVANT PARTS NOW
      CHARACTER*24 NAME
      CHARACTER*36 LOCATN
      CHARACTER*24 AGNAME
      INTEGER*2 RECNO, RECYR
      CHARACTER*3 GEOLST
      CHARACTER*2 CATG, GEOL
      CHARACTER*1 AGNO, BUFF(102)
C AS FOR RECADD.FTN
C
C NOW SET UP EQUIVALENCE
      EQUIVALENCE (BUFF(1), NAME), (BUFF(25), LOCATN), (BUFF(61), AGNAME),
      . (BUFF(85), RECNO), (BUFF(87), RECYR), (BUFF(89), GEOLST),
      . (BUFF(92), AGNO), (BUFF(93), CATG), (BUFF(95), GEOL),
      . (BUFF(97), EAST), (BUFF(99), NORTH)
C THIS IS USED TO ALLOW BINARY OUTPUT FOR FASTER ACCESS
C
      OPEN(UNIT=4, FORM='BINARY', RECL=102)
C OPEN THE OUTPUT FILE FOR BINARY OUTPUT
      10 READ(6, 300, END=20) NAME, LOCATN, AGNAME, AGNO, RECNO, RECYR,
      . GEOLST, EAST, NORTH, CATG, GEOL
      300 FORMAT(2X, A24, 1X, A36, 1X, A24, 1X, A1, 1X, I5, 1X, I2, 1X, A3,
      . 1X, I4, I5, 2(1X, A2))
      WRITE(4) BUFF
C BINARY WRITE TO OUTPUT FILE
      GOTO 10
C BACK ROUND
C
C AT END
      20 CONTINUE
      CLOSE(UNIT=4, STATUS='KEEP')
      CLOSE(UNIT=6, STATUS='KEEP')
      END

```

10/38

APPENDIX 4

Program RECSORT

```
*RECSORT.CSS
* FOR SORTING JOB FILE INTO CHRONOLOGICAL ORDER
PRE ETM
L RECSORT,10: AS 4, JOBREC.DAT,ERO: AL TEMP:TEMP.DAT,IN,88/5/2
AS 6,TEMP:TEMP.DAT: ST
$IFNE 0: $WRITE SORT ERROR: ENA ETM: $EXIT: $ENDC
$BUILD COPY.CMD
IN TEMP:TEMP.DAT
AL JOBREC.DAT,IN,88/10/5
OUT JOBREC.DAT
COPY *,*
REW I
REW 0
VERIFY *,*
END
$ENDB
REP TEMP:TEMP.DAT,FF00: REP JOBREC.DAT,0: DE JOBREC.DAT
L COPY32,50: ST ,COM=COPY.CMD,LI=NULL:,LO=NULL:
$IFNE 0: $WRITE SORT-COPY ERROR: ENA ETM: $EXIT: $ENDC
REP JOBREC.DAT,FF00: REP TEMP:TEMP.DAT,0: DE TEMP:TEMP.DAT,COPY.CMD
ENA ETM: $EXIT
```

```

$TITL RECSORT.FTN - SORT THE JOB FILE INTO CALENDAR ORDER
C
      INTEGER*4 NORTH
      INTEGER*2 EAST
C SPLIT MAPREF INTO THE RELEVANT PARTS NOW
      CHARACTER*24 NAME
      CHARACTER*36 LOCATN
      CHARACTER*24 AGNAME
      INTEGER*2 RECNO, RECYR
      CHARACTER*3 GEOLST
      CHARACTER*2 CATG, GEOL
      CHARACTER*1 AGNO, BUFF(102)
C AS FOR RECADD.FTN
C
C FOLLOWING ARE FOR THE SORT
      INTEGER*2 INDEX(8000)
      INTEGER*4 IA(8000)
C ALLOW FOR 8000 ENTRIES
C
C NOW SET UP EQUIVALENCE
      EQUIVALENCE (BUFF(1), NAME), (BUFF(25), LOCATN), (BUFF(61), AGNAME),
      . (BUFF(85), RECNO), (BUFF(87), RECYR), (BUFF(89), GEOLST),
      . (BUFF(92), AGNO), (BUFF(93), CATG), (BUFF(95), GEOL),
      . (BUFF(97), EAST), (BUFF(99), NORTH)
C THIS IS USED TO ALLOW BINARY OUTPUT FOR FASTER ACCESS
C
      OPEN(UNIT=4, FORM='BINARY', ACCESS='DIRECT', RECL=102)
C OPEN THE INPUT FILE FOR RANDOM AND SEQUENTIAL ACCESS
      REWIND 4
      IREC=0
C COUNTER FOR NUMBER OF RECORDS
      10 READ(4, END=20) BUFF
      IREC=IREC+1
      IF (IREC .GT. 8000) STOP 'MORE THAN 8000 ENTRIES'
      INDEX(IREC)=IREC
C FILL SORT INDEX
      IA(IREC)=RECNO+(RECYR*100000)
C COMBINE RECNO AND RECYR TO GET CHRONOLOGICAL NUMER
      GOTO 10
C BACK AROUND
C
C NOW FOR THE WORK
      20 CONTINUE
      IF (IREC .EQ. 0) STOP 'NO RECORDS'
      CALL BUBSTI(INDEX, IA, 1, IREC)
C SORT INTO ASCENDING NUMBER - I. E. CHRON ORDER
      OPEN(UNIT=6, FORM='BINARY', RECL=102)
C OPEN OUTPUT FILE
      DO 30 I=1, IREC
      READ(4, REC=INDEX(I)) BUFF
      WRITE(6) BUFF
C COPY TO NEW ORDER
      30 CONTINUE
      CLOSE(UNIT=6, STATUS='KEEP')
      CLOSE(UNIT=4, STATUS='KEEP')
      END
      SUBROUTINE BUBSTI(IR, IA, IBASE, N)
      INTEGER*4 IA(N)

```

```
INTEGER*2 IR(N)
LOGICAL NSWAP
IF (N .LE. 1) RETURN
C NOTHING TO SORT
NM1=N-1
DO 30 J=IBASE,NM1
NSWAP=. TRUE.
IRI=IR(1)
DO 40 I=IBASE,NM1
IP1=I+1
IRIP1=IR(IP1)
IF (IA(IRI) .LE. IA(IRIP1)) GOTO 40
NSWAP=. FALSE.
IR(I)=IRIP1
IR(IP1)=IRI
IRIP1=IRI
40 IRI=IRIP1
IF (NSWAP) RETURN
30 CONTINUE
RETURN
END
```

APPENDIX 5
Program RECSRCH

```
*RECSRCH.CSS - SEARCH THE JOB FILE  
L RECSRCH.10: AS 4.JOBREC.DAT,ERO: XAL SYSF:ENGJOBS.TMP,IN.132/3/2  
AS 6.SYSF:ENGJOBS.TMP; REW 6: AS 5.CON:; TEMPFIL 3,IN.80; ST  
*IFX SYSF:ENGJOBS.TMP; PRI SYSF:ENGJOBS.TMP,DEL: #ENDO: #EXIT
```

*TITL RECSRCH.FTN - SEARCH JOB FILE

C

INTEGER*4 NORTH
INTEGER*2 EAST, FCOUNT, SCOUNT
REAL*4 ALINE(124)

C USED WHEN COPYING FROM OUTPUT FILE TO SCREEN

C SPLIT MAPREF INTO THE RELEVANT PARTS NOW

CHARACTER*24 NAME
CHARACTER*36 LOCATN
CHARACTER*24 AGNAME
INTEGER*2 RECNO, RECYR
CHARACTER*3 GEOLST
CHARACTER*2 CATG, GEOL
CHARACTER*1 AGNO, BUFF(102), AREGN

C AS FOR RECADD.FTN

C

C NOW SET UP EQUIVALENCE

EQUIVALENCE (BUFF(1), NAME), (BUFF(25), LOCATN), (BUFF(61), AGNAME),
(BUFF(85), RECNO), (BUFF(87), RECYR), (BUFF(89), GEOLST),
(BUFF(92), AGNO), (BUFF(93), CATG), (BUFF(95), GEOL),
(BUFF(97), EAST), (BUFF(99), NORTH)

C THIS IS USED TO ALLOW BINARY OUTPUT FOR FASTER ACCESS

C

CHARACTER*80 SNAME, SLOCN, SAGNAM, SAGNO, SYEAR, SGEOLT, SCAT, SGEOL
INTEGER*2 IYR(30), RNSTA, YRSTA, RNSTO, YRSTO, STYPE
INTEGER*2 FFEED

C USED TO PUT FORM FEEDS INTO OUTPUT FILE

REAL X(100), Y(100), YINTVL(100), RSLOPE(100)
INTEGER*2 SWATH(100, 25)

C ABOVE 2 LINES USED FOR FSTJDN POINT IN POLYGON SEARCH

LOGICAL NOTIN, INOUT
DATA FFEED/3072/

C THE FORM FEED CHARACTER IN A1

OPEN(UNIT=4, FORM='BINARY', RECL=102)

C OPEN THE INPUT FILE

10 WRITE(5, 100)
100 FORMAT(' SEARCHING JOB RECORDS'// DO YOU NEED A'
' FULL SEARCH (F) OR RECORDS NO. SEARCH (R)?')
READ(5, 200) STYPE
200 FORMAT(A1)
IF (STYPE .EQ. 'R') GOTO 30

C WANT SEARCH ON RECORDS NUMBER

IF (STYPE .NE. 'F') GOTO 10

C PROMPT AGAIN IF NOT ONE OF THE TWO DESIRED OPTIONS

C

C NOW FOR A FULL SEARCH

WRITE(6, 400)
400 FORMAT(' SEARCH OPTIONS ARE:')
WRITE(5, 101)
101 FORMAT(' FOR EACH OPTION ENTER EITHER A BLANK LINE OR'
' THE DESIRED VALUES FOR THE OPTION, EACH TERMINATED BY'
' A //' E. G. FRED/BILL/TOM/SMITH//')
WRITE(5, 102)
102 FORMAT(' NAME?')
READ(5, 201) SNAME
201 FORMAT(A80)
IF (SNAME(1:1) .NE. ' ') WRITE(6, 401) SNAME
401 FORMAT(' NAME', 10X, A80)
WRITE(5, 103)

```

103 FORMAT(' JOB LOCATION?')
   READ(5,201) SLOCN
   IF (SLOCN(1:1) .NE. '/') WRITE (6,402) SLOCN
402 FORMAT(' JOB LOCATION',10X,A80)
   WRITE(5,104)
104 FORMAT(' AGENCY NAME?')
   READ(5,201) SAGNAM
   IF (SAGNAM(1:1) .NE. '/') WRITE(6,403) SAGNAM
403 FORMAT(' AGENCY NAME',10X,A80)
   WRITE(5,105)
105 FORMAT(' AGENCY TYPE (0,1,2)?')
   READ(5,201) SAGNO
   IF (SAGNO(1:1) .NE. '/') WRITE(6,404) SAGNO
404 FORMAT(' AGENCY NO.',10X,A80)
   WRITE(5,106)
106 FORMAT(' YEAR?')
   READ(5,201) SYEAR
   NYEAR=0
C COUNTER FOR NUMBER OF YEAR OPTIONS INPUT
   IF (SYEAR(1:2) .EQ. '/') GOTO 21
C NO YEAR SEARCH DESIRED
   WRITE(6,405) SYEAR
405 FORMAT(' YEAR',10X,A80)
   ILAST=1
C COUNT POSITION ALONG INPUT LINE
   20 ICHAR=INDEX(SYEAR(ILAST:80), '/')
C LOOK FOR / AS TERMINATOR OF A YEAR
   IF (ICHR .EQ. 0) GOTO 21
C NO MORE /
   ENCODE(BUFF,300) SYEAR(ILAST:ILAST+1)
300 FORMAT(A2)
   NYEAR=NYEAR+1
   DECODE(BUFF,301) IYR(NYEAR)
301 FORMAT(I2)
C CONVERTED TO AN INTEGER
   ILAST=ILAST+ICHR
C POSITION TO AFTER THE /
   IF (ILAST .NE. 79) GOTO 20
C ROUND FOR NEXT YEAR
C
C NOW GET THE NEXT SEARCH OPTION
   21 CONTINUE
   WRITE(5,107)
107 FORMAT(' GEOLOGIST?')
   READ(5,201) SGEOLT
   IF (SGEOLT(1:1) .NE. '/') WRITE(6,406) SGEOLT
406 FORMAT(' GEOLOGIST',10X,A80)
   WRITE(5,416)
416 FORMAT(' SEARCH ALSO NON-SPECIFIED AREA/SUBJECT MATERIAL (Y)')
   READ(5,200) AREGN
   IF (AREGN .EQ. 'Y') WRITE(6,417)
417 FORMAT(' SEARCHING ALSO NON-SPECIFIED AREA/SUBJECT MATERIAL')
   WRITE(5,108)
108 FORMAT(' SEARCH FOR SITES WITHIN A SPECIFIED AREA (Y)?')
   READ(5,200) STYPE
   IF (STYPE .EQ. 'Y') GOTO 23
C WANT TO READ COORDS
   NCOORD=0
   GOTO 26
C DONT WANT TO SEARCH FOR SITES IN AN AREA

```

```

C
  23 CONTINUE
C READ VERTICES
  WRITE(5,109)
109 FORMAT(' NUMBER OF VERTICES OF AREA?'/
  ' ENTER 2 TO SPECIFY A RECTANGLE')
  READ(5,*) NCOORD
  IF (NCOORD .LT. 2) GOTO 23
C NEED AT LEAST 3 VERTICES TO DEFINE AN AREA
  IF (NCOORD .EQ. 2) THEN
    WRITE(5,515)
515 FORMAT(' ENTER COORDS OF TWO DIAGONALLY OPPOSITE CORNERS OF ',
  ' THE RECTANGLE'/' ONE PER LINE IN THE FORM EASTNORTH')
  ELSE
    WRITE(5,110)
110 FORMAT(' ENTER VERTEX COORDS IN CLOCKWISE ORDER'/'
  ' ONE PER LINE IN FORM EASTNORTH')
  ENDIF
  IXMAX=-999999999
  IXMIN=-IXMAX
  IYMAX=IXMAX
  IYMIN=IXMIN
C USE THESE TO STORE THE RANGE OF THE AREA
  DO 24 I=1,NCOORD
    READ(5,303) IX,IY
303 FORMAT(I4,I5)
C GET INTO 100'S OF METRES EAST AND NORTH
    IXMAX=MAX0(IX,IXMAX)
    IXMIN=MIN0(IX,IXMIN)
    IYMAX=MAX0(IY,IYMAX)
    IYMIN=MIN0(IY,IYMIN)
C FIND THE RANGE
    X(I)=IX*0.1
    Y(I)=IY*0.1
C CONVERT TO KM BEFORE STORING
  24 CONTINUE
  IF (NCOORD .GT. 2) THEN
    IF (X(1) .NE. X(NCOORD) .OR. Y(1) .NE. Y(NCOORD)) THEN
      NCOORD=NCOORD+1
      X(NCOORD)=X(1)
      Y(NCOORD)=Y(1)
C CLOSE AREA
    ENDIF
    WRITE(6,407)
407 FORMAT(' AREA COORDINATES (KM)')
    WRITE(6,408) (X(I),Y(I),I=1,NCOORD)
408 FORMAT(20X,4(F14.2,F9.2))
    NCOORD=NCOORD-1
C ROUTINE FOR LOCATING POINTS DOESNT REQUIRE CLOSURE
  CALL PREPLY(X,Y,NCOORD,YINTVL,INTVLS,SWATH,RSLOPE)
C CUT THE SEARCH AREA UP INTO SWATHS
  ELSE
    WRITE(6,516) IXMIN,IXMAX,IYMIN,IYMAX
516 FORMAT(' SEARCH RECTANGLE FROM',I5,'00ME TO',I5,'00ME AND FROM',
  I6,'00MN TO',I6,'00MN')
  ENDIF
C
  26 CONTINUE
  WRITE(5,111)
111 FORMAT(' CATEGORY (0-5)?')

```

```

      READ(5,201) SCAT
      IF(SCAT(1:1) .NE. ' ') WRITE(6,409) SCAT
409  FORMAT(' CATEGORY',10X,A80)
      WRITE(5,112)
112  FORMAT(' GEOLOGY (0-9)?')
      READ(5,201) SGEOL
      IF (SGEOL(1:1) .NE. ' ') WRITE(6,410) SGEOL
410  FORMAT(' GEOLOGY',10X,A80)
C END OF OPTION INPUT
C
C*****
C NOW FOR THE SEARCH
      FCOUNT=0
C COUNTER FOR NUMBER OF FOUND ENTRIES
      27 READ(4,END=40) BUFF
C READ ONE ENTRY
      IF (NOTIN(SNAME,NAME)) GOTO 27
C NOT THE RIGHT NAME
      IF(NOTIN(SLOCN,LOCATN)) GOTO 27
C NOT THE RIGHT LOCATION
      IF(NOTIN(SAGNAM,AGNAME)) GOTO 27
C NOT THE AGENCY
      IF (SAGNO(1:1) .NE. ' ' .AND. INDEX(SAGNO,AGNO) .EQ. 0) GOTO 27
C NOT THE DESIRED AGENCY NUMBER
      IF (NYEAR .NE. 0) THEN
          DO 28 I=1,NYEAR
              IF (IYR(I) .EQ. RECYR) GOTO 29
          28 CONTINUE
              GOTO 27
C NOT FOUND SO FALL OUT
          29 CONTINUE
      ENDIF
C LOOKED FOR YEAR
      IF (NOTIN(SGEOLT,GEOLST)) GOTO 27
C NOT THE GEOLOGIST
      IF (AREGN .EQ. 'Y') THEN
          IF (EAST .EQ. 0 .AND. NORTH .EQ. 0) GOTO 41
C IF FOUND A GENERAL REPORT DONT ALSO DO A COORDINATE SEARCH
          IF (NCOORD .EQ. 0) GOTO 27
C IF NOT CHECKING COORDS AS WELL AND IT WASNT A GENERAL GO BACK ROUND
          ENDIF
C NOT AN AREA OR SUBJECT SPECIFIC REPORT
          IF (NCOORD .NE. 0) THEN
              IF (EAST .LT. IXMIN .OR. EAST .GT. IXMAX) GOTO 27
              IF (NORTH .LT. IYMIN .OR. NORTH .GT. IYMAX) GOTO 27
C CANT POSSIBLY BE IN AREA
              IF (NCOORD .GT. 2) THEN
                  XTMP=EAST*0.1
                  YTMP=NORTH*0.1
C CONVERT TO KM
                  IF (.NOT. INOUT(XTMP,YTMP,X,Y,YINTVL,INTVLS,SWATH,RSLOPE))
                      GOTO 27
C NOT IN THE SPECIFIED AREA
              ENDIF
C FOR THE SIMPLE RECTANGLE DONT NEED THE POLYGON SEARCH
          ENDIF
          41 IF (NOTIN(SCAT,CATG)) GOTO 27
C NOT RIGHT CATEGORY
          IF (NOTIN(SGEOL,GEOL)) GOTO 27
C NOT RIGHT GEOLOGY

```

```

C IF FINALLY GET TO HERE HAVE FOUND AN ENTRY THAT MATCHES THE
C SEARCH OPTIONS
C
  IF (MOD(FCOUNT,53) .EQ. 0) CALL HEAD
C HEAD PAGE
  FCOUNT=FCOUNT+1
C INCREMENT FOUND ENTRY COUNTER
  WRITE(6,412) NAME, LOCATN, AGNAME, AGNO, RECNO, RECYR, GEOLST, EAST,
    NORTH, CATG, GEOL
412 FORMAT(A24, ' ', A36, ' ', A24, ' ', 2X, A1, ' ', ' ', I5, ' ', I2,
  ' ', ' ', 1X, A3, ' ', ' ', 2I5, ' ', ' ', 1X, A2, 1X, ' ', 1X, A2)
  GOTO 27
C BACK AROUND
C
C*****
C NOW FOR THE CASE OF SEARCHING ONLY ON A RANGE OF RECORD NOS
  30 CONTINUE
  WRITE(5,113)
113 FORMAT(' ENTER STARTING RECORD NO. IN FORM NNNNN/YR')
  CALL RNOIN(RNSTA, YRSTA)
  WRITE(5,114)
114 FORMAT(' ENTER ENDING RECORDS NUMBER')
  CALL RNOIN(RNSTO, YRSTO)
  IF (YRSTA .GT. YRSTO .OR. YRSTA .EQ. YRSTO .AND.
    RNSTA .GT. RNSTO) GOTO 30
C NOT IN CHRONOLOGICAL SEQUENCE
  WRITE(6,413) RNSTA, YRSTA, RNSTO, YRSTO
413 FORMAT(' SEARCHING RECORDS NUMBERS FROM',
  I6, ' ', I2, ' TO', I6, ' ', I2)
  FCOUNT=0
  31 READ(4,END=40) BUFF
  IF (RECYR .LT. YRSTA .OR. RECYR .GT. YRSTO) GOTO 31
C NOT IN THE YEAR RANGE
  IF (RECYR .EQ. YRSTA .AND. RECNO .LT. RNSTA) GOTO 31
C IN STARTING YEAR BUT BEFORE NUMBER REQUIRED
  IF (RECYR .EQ. YRSTO .AND. RECNO .GT. RNSTO) GOTO 31
C IN ENDING YEAR BUT AFTER THE RANGE OF INTEREST
  IF (MOD(FCOUNT,53) .EQ. 0) CALL HEAD
C HEAD UP PAGE
  FCOUNT=FCOUNT+1
  WRITE(6,412) NAME, LOCATN, AGNAME, AGNO, RECNO, RECYR, GEOLST,
    EAST, NORTH, CATG, GEOL
  GOTO 31
C ROUND AGAIN
C
C NOW AT THE END OF THE RUN
  40 CONTINUE
  WRITE(6,414) FFEED
414 FORMAT(1A1,
  ' // AGENCY TYPE'
  ' //      0 GOVT.          1 PROF.          2 INDIV. ///'
  ' // CATEGORY'
  ' //      0 GROUNDWATER    1 SLOPE          2 EXPANSIVE'
  ' //                                STABILITY        SOILS'
  ' //      3 FOUNDATION    4 MISCELLANEOUS'
  ' //                                INVESTIGATION'//
  ' // GEOLOGY'
  ' //      0 QUATERNARY     1 TERTIARY        2 TRIASSIC'
  ' //                                SEDIMENTS'
  ' //      3 PERMIAN        4 LOWER          5 CAMBRIAN'

```

```

. //          PALAEOZOIC/
. //          6 PRECAMBRIAN    7 TERTIARY    8 JURASSIC/
. //          BASALT          9 GRANITE/
. //          DOLERITE/
C NOW DECIDE IF IT IS GOING TO BE PUT OUT ON THE SCREEN
WRITE(5,115) FCOUNT
1:15 FORMAT(I7, ' RECORDS WERE FOUND'// DO YOU WANT A',
' SCREEN LISTING (Y OR N)?')
READ(5,200) STYPE
IF (STYPE .EQ. 'N') GOTO 47
C NO SCREEN LIST WANTED
REWIND (6)
C BACK TO THE START
SCOUNT=0
C COUNTER FOR NUMBER OF LINES ON SCREEN
45 READ(6,415) ALINE
4:15 FORMAT(2A4,124A1)
IF (ALINE(1) .EQ. ' AGE' .AND. ALINE(2) .EQ. 'NCY ') GOTO 47
C TEST FOR THE END OF THE ENTRIES
WRITE(5,116) ALINE
1:16 FORMAT(1X,2A4,54A1/8X,70A1)
SCOUNT=SCOUNT+1
IF (SCOUNT .LT. 10) GOTO 45
C ALLOW 10 ENTRIES PER SCREENFULL
SCOUNT=0
C RESET
WRITE(5,117)
1:17 FORMAT(' LIST MORE ENTRIES ON SCREEN (Y OR N)?')
READ(5,200) STYPE
IF (STYPE .EQ. 'Y') GOTO 45
C ROUND AGAIN FOR ANOTHER SCREEN FULL
47 WRITE(5,118)
1:18 FORMAT(' DO YOU WANT A PRINTOUT (Y OR N)?')
READ(5,200) STYPE
IF (STYPE .NE. 'Y' .OR. FCOUNT .EQ. 0) THEN
CLOSE(UNIT=6, STATUS='DELETE')
STOP
C CLOSE FILE AND DELETE IT THEN STOP
ENDIF
CLOSE(UNIT=6, STATUS='KEEP')
STOP
END
LOGICAL FUNCTION NOTIN(SSTRNG, RSTRNG)
C SSTRNG CONTAINS A SERIES OF STRINGS TERMINATED BY /
C E. G. FRED/BILL/TOM/
C AND RSTRNG IS SEARCHED FOR THE OCCURENCE OF ONE OF THESE STRINGS
C IF ONE IS FOUND TO MATCH NOTIN IS .FALSE.
C IF STRNG IS EMPTY NOTIN IS .FALSE.
CHARACTER*80 SSTRNG
CHARACTER* (*) RSTRNG
NOTIN=.FALSE.
IF (SSTRNG(1:1) .EQ. ' ') RETURN
C NO NEED TO LOOK
ILAST=1
C COUNTER FOR POSITION IN SSTRNG
20 ICHAR=INDEX(SSTRNG(ILAST:80), '/')
C LOOK FOR / AS TERMINATOR OF STRING
IF (ICHR .EQ. 0) GOTO 25
C HAVENT FOUND A MATCH BY THE END OF THE LINE
IF (INDEX(RSTRNG, SSTRNG(ILAST:ILAST+ICHR-2)) .NE. 0) RETURN

```

```

C LOOK BETWEEN /S IN SSTRNG AND IF FIND A MATCH RETURN
  ILAST=ILAST+ICHR
C POSITION AFTER THE /
  IF (ILAST .LE. 79) GOTO 20
C BACK ROUND IF NOT AT END OF LINE
C
C ELSE END
  25 CONTINUE
  NOTIN=. TRUE.
C NO MATCH
  RETURN
  END
  SUBROUTINE HEAD
C HEAD UP PAGES FROM SEARCH
  INTEGER*2 FFEED
  DATA FFEED/3072/
C USED TO PUT FORM FEEDS IN OUTPUT FILE
  WRITE(6,100) FFEED
100 FORMAT(1A1/9X, 'NAME', 11X, '1', 11X, 'JOB LOCATION', 12X, '1', 13X,
. 'AGENCY', 10X, '1 RECORDS | INIT| MAPREF |',
. ' CAT| GEOL'/24X, '1', 36X, '1', 10X, 'NAME', 10X, '1',
. ' NO |', 4X, 'NO', 3X, '1', 5X, '1', 11X, '1', 4X, '1'/1X,
. 130(' '))
  RETURN
  END
  SUBROUTINE RNOIN(RNO, RYR)
C USE TO READ RECORDS NO AND YEAR AND AVOID HAVING TO MANUALLY
C REPLACE / WITH , IN 1234/76
  INTEGER*2 RNO, RYR
  CHARACTER*1 BUFF(9)
  READ(5, 115) BUFF
115 FORMAT(9A1)
  DO 10 I=1,9
  IF (BUFF(I) .EQ. '/') BUFF(I)=','
  10 CONTINUE
  REWIND 3
  WRITE(3, 115) BUFF
  REWIND 3
  READ(3, *) RNO, RYR
C PUT OUT TO TEMPORARY FILES AND READ BACK IN IN FREE FORMAT
  RETURN
  END

```

```

#TITL FSTJDN.FTN - POINT IN POLYGON
C PROGRAM COLLECTION FASTJORDAN
C SALOMON, K. B., 1978. AN EFFICIENT POINT-IN-POLYGON ALGORITHM
C COMPUTERS AND GEOSCIENCES, V4, NO. 2, P. 173-178
C
C USE BY READING VERTICES OF POLYGON IN ORDER (BUT NOT CLOSING IT)
C AND CALLING PREPLY ONCE BEFORE THE SEARCH IS BEGUN. THE ACTUAL
C SEARCHING IS DONE BY MEANS OF THE LOGICAL FUNCTION INOUT.
C

```

```

  SUBROUTINE PREPLY(X, Y, NUVERT, YINTVL, INTVLS, SWATH, RSLOPE)
C
C*****
C THIS ROUTINE PREPARES THE POLYGON CONSISTING OF THE NUVERT VERTICES
C (X(I),Y(I)) BY FIRST SORTING THE SEGMENT Y-END POINTS INTO
C DECREASING ORDER AND FORMING AN INTERVAL FOR EACH CONSECUTIVE PAIR:
C (YINTVL(I),YINTVL(I+1)), I=1,INTVLS. THIS IS PERFORMED BY CALLING
C SORT.
C THE CODE CONSISTING OF THE DO 100 AND DO 200 LOOPS CONSTRUCTS,

```

C FOR EACH INTERVAL I, THE LIST OF SEGMENTS TO BE TESTED BY INOUT.
 C THIS LIST IS PLACED IN THE I-TH ROW OF SWATH. THE FIRST ENTRY,
 C SWATH(I,1), WILL BE SET TO THE NUMBER OF SEGMENTS IN THE ROW. NOTE
 C THAT AS YINTVL CONTAINS NO REDUNDANCIES, I. E. YINTVL(I) IS STRICTLY
 C GREATER THAN YINTVL(I+1), NO HORIZONTAL SEGMENTS WILL BE PLACED IN
 C THE LIST.
 C THE CODE CONSISTING OF THE DO 300 LOOP ESTABLISHES THE
 C RECIPROCAL SLOPE FOR EACH NON-HORIZONTAL SEGMENT. THIS IS TO BE
 C USED BY INOUT. FINALLY, THE SEGMENTS WITHIN A ROW OF SWATH ARE
 C ORDERED FROM LEFT-TO-RIGHT.

C
 C*****

```

C
  INTEGER*2 SWATH(100,25)
  REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
  CALL SORT(Y,NUVERT,YINTVL,INTVLS)
  IF (INTVLS .LE. 0) GOTO 400
  X(NUVERT+1)=X(1)
  Y(NUVERT+1)=Y(1)
  DO 100 I=1,INTVLS
100 SWATH(I,1)=0
  DO 200 I=1,INTVLS
    DO 200 J=1,NUVERT
      IF (Y(J).GE.YINTVL(I) .AND. YINTVL(I+1).GE.Y(J+1) .OR.
*      Y(J+1).GE.YINTVL(I) .AND. YINTVL(I+1).GE.Y(J))
*      CALL INCLUD(SWATH,I,J)
200 CONTINUE
  DO 300 I=1,NUVERT
  IF (Y(I).EQ.Y(I+1)) GOTO 300
  RSLOPE(I)=(X(I+1)-X(I))/(Y(I+1)-Y(I))
300 CONTINUE
  CALL ORDER(X,Y,YINTVL,INTVLS,SWATH,RSLOPE)
  RETURN
400 WRITE(7,401)
401 FORMAT(' ***** PREP OF POLYGON ABORTED SINCE NO INTERVALS',
* ' CONSTRUCTED')
  STOP
  END
  SUBROUTINE SORT(Y,NUVERT,YINTVL,INTVLS)

```

C
 C*****

C ROUTINE ESTABLISHES THE INTERVALS OF THE Y-AXIS DEFINED BY THE
 C ENDPOINTS OF THE POLYGON'S SEGMENTS. THE DO 100 LOOP INITIALISES
 C YSORT FROM THE SEGMENT Y-END POINTS. THE DO 200 LOOPS SORT YSORT
 C INTO DESCENDING ORDER. THE DO 300 LOOP ELIMINATES REDUNDANCIES IN
 C YSORT AND PLACES IRREDUNDANT SORTED Y'S INTO YINTVL. IT ALSO SETS
 C INTVLS TO THE TRUE NUMBER OF Y INTERVALS. JUST PRIOR TO RETURNING
 C A FINAL INTERVAL EXTENDING TO '-INFINITY' IS ESTABLISHED.

C
 C*****

```

C
  REAL Y(100),YINTVL(100),YSORT(100)
  INTEGER*2 UPPER
  DO 100 I=1,NUVERT
100 YSORT(I)=Y(I)
  UPPER=NUVERT-1
  DO 200 I=1,UPPER
    IPLS1=I+1
    DO 200 J=IPLS1,NUVERT

```

```

      IF (YSORT(I).GE.YSORT(J)) GOTO 200
      TEMP=YSORT(I)
      YSORT(I)=YSORT(J)
      YSORT(J)=TEMP
200  CONTINUE
      YINTVL(1)=YSORT(1)
      INTVLS=0
      DO 300 I=1,UPPER
        IF (YSORT(I).EQ.YSORT(I+1)) GOTO 300
        INTVLS=INTVLS+1
        YINTVL(INTVLS+1)=YSORT(I+1)
300  CONTINUE
      YINTVL(INTVLS+2)=-1.0E75
      RETURN
      END
      SUBROUTINE INCLUD(SWATH,I,J)

```

C
 C*****
 C ROUTINE PLACES THE J-TH POLYGON SEGMENT INTO THE NEXT AVAILABLE
 C LOCATION IN ROW I OF SWATH.
 C
 C*****
 C

```

      INTEGER*2 SWATH(100,25),POINTR
      SWATH(I,1)=SWATH(I,1)+1
      POINTR=SWATH(I,1)
      SWATH(I,POINTR+1)=J
      RETURN
      END
      SUBROUTINE ORDER(X,Y,YINTVL,INTVLS,SWATH,RSLOPE)

```

C
 C*****
 C FOR EACH INTERVAL, A HORIZONTAL LINE IS PASSED THROUGH THE MIDDLE
 C (Y_{MID}) OF THE INTERVAL. THE DO 100 LOOP PLACES THE X-INTERSECTION
 C OF EACH SEGMENT IN THIS SWATH SO THAT THESE INTERSECTIONS OCCUR
 C FROM LEFT-TO-RIGHT.
 C
 C*****
 C

```

      REAL X(100),Y(100),YINTVL(100),RSLOPE(100),XINTSC(25)
      INTEGER*2 SWATH(100,25),POINTR,SEGNO,UPPER
      LOGICAL VERTSG
      DO 200 INTVAL=1,INTVLS
        NMBSEG=SWATH(INTVAL,1)
        YMID=(YINTVL(INTVAL)+YINTVL(INTVAL+1))/2.0
        DO 100 POINTR=1,NMBSEG
          SEGNO=SWATH(INTVAL,POINTR+1)
          VERTSG=ABS(X(SEGNO+1)-X(SEGNO)) .LT. 1.0E-5
          IF (VERTSG) XINTSC(POINTR)=X(SEGNO)
          IF (.NOT. VERTSG) XINTSC(POINTR)=X(SEGNO)+
*                               RSLOPE(SEGNO)*(YMID-Y(SEGNO))

```

```

100  CONTINUE
      IF (NMBSEG.LT.2 .OR. MOD(NMBSEG,2).NE.0) GOTO 300
      UPPER=NMBSEG-1
      DO 200 I=1,UPPER
        IPLS1=I+1
        DO 200 J=IPLS1,NMBSEG
          IF (XINTSC(I).LE.XINTSC(J)) GOTO 200
          TEMP=XINTSC(I)

```

```

XINTSC(I)=XINTSC(J)
XINTSC(J)=TEMP
ITEMP=SWATH(INTVAL,I+1)
SWATH(INTVAL,I+1)=SWATH(INTVAL,J+1)
SWATH(INTVAL,J+1)=ITEMP

```

```

200 CONTINUE
RETURN

```

```

300 WRITE(7,301) INTVAL
301 FORMAT(' ** PREP OF POLYGON ABORTED. INTERVAL ',IS,
* ' HAS EITHER LESS THAN TWO SEGMENTS OR AN ODD NUMBER OF THEM')
STOP
END
LOGICAL FUNCTION INOUT(XP,YP,X,Y,YINTVL,INTVLS,SWATH,RSLOPE)

```

C
C*****
C

C THE FOUR LINES ENCLOSED IN DASHES DETERMINE THE INTERVAL CONTAINING
C YP. THE DO 400 LOOP CONTINUES UNTIL THE FIRST SEGMENT WITHIN THE
C INTERVAL FALL TO THE LEFT OF (XP,YP). IN THIS EVENT, INOUT IS SET
C TRUE. IFF AN EVEN NUMBER OF SEGMENTS HAS BEEN TESTED.

C
C*****
C

```

REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
INTEGER*2 SWATH(100,25),SEGNO
INOUT=.FALSE.

```

C-----

```

INTVAL=0
100 INTVAL=INTVAL+1
IF (YINTVL(INTVAL) .GT. YP) GOTO 100
INTVAL=INTVAL-1

```

C-----

```

300 IF (INTVAL.LT.1 .OR. INTVAL.GT.INTVLS) RETURN
NMBSEG=SWATH(INTVAL,1)+1
DO 400 I=2,NMBSEG
SEGNO=SWATH(INTVAL,I)
IF (XP-X(SEGNO).LE.(YP-Y(SEGNO))*RSLOPE(SEGNO)) GOTO 500
400 CONTINUE
RETURN
500 INOUT=MOD(I,2) .EQ. 1
RETURN
END

```

\$TITL WATSRCH.FTN - SEARCH WATER BORE FILE

```

C
INTEGER*2 QUADS, EAST, CARDS, AOK, IBASE, FCCOUNT, FOUND(5000)
LOGICAL CHANGE, CHGE
REAL*4 DEPSTR, ANUM(2), SWL, CHEM(17)
INTEGER*4 NORTH, TDSC, CONDF
CHARACTER*24 NAME
CHARACTER*30 LOCATN
CHARACTER*8 DRILCO, PROMPT(17)
INTEGER*2 CARD, QUAD, YEAR, TOTDEP, CASDEP, YIELD, ANAL, INANAL, RECCNT
CHARACTER*3 GEOLST
CHARACTER*2 GEOL

```

```

C INPUT IS OWNER, LOACTION, DRILL CO., QUADRANGLE NO., CARD NO.,
C YEAR, GEOLOGIST, MAPREF, TOTAL DEPTH, CASING DEPTH,
C DEPTH STRUCK, STANDING WATER LEVEL, YIELD, CONDUCTIVITY (FIELD
C MEASUREMENT), NO. OF ANALYSES OF WATER SAMPLES, GEOLOGY
C (UP TO 2). IF THERE HAS BEEN AN ANALYSIS MADE THEN ONE
C ANALYSIS IN THE FORM-
C PH, CONDUCTIVITY, CO3, HCO3, CL, SO4,
C SiO2, CA, MG, FE, AL, K, NA, TDS(LAB),
C ALKALINITY, PERM. HARDNESS,
C TEMP. HARDNESS.
C (THESE ARE EQUIVALENT TO CHEM(17))

```

```

CHARACTER*1 BUFF(108)
EQUIVALENC (BUFF(1), NAME), (BUFF(25), LOCATN), (BUFF(55), DRILCO),
. (BUFF(65), TDSC), (BUFF(69), CONDF), (BUFF(73), NORTH),
. (BUFF(77), DEPSTR), (BUFF(81), SWL), (BUFF(85), GEOLST),
. (BUFF(89), TOTDEP), (BUFF(91), CASDEP), (BUFF(93), YEAR),
. (BUFF(95), YIELD), (BUFF(97), QUAD), (BUFF(99), CARD),
. (BUFF(101), ANAL), (BUFF(103), GEOL), (BUFF(105), INANAL),
. (BUFF(107), EAST)

```

```

INTEGER*2 FFEED
C USED TO PUT FORM FEEDS INTO OUTPUT FILE
REAL X(100), Y(100), YINTVL(100), RSLOPE(100)
INTEGER*2 SWATH(100, 25)

```

```

C ABOVE 2 LINES USED FOR FSTJDN POINT IN POLYGON SEARCH
LOGICAL NOTIN, INOUT, SANAL, STDM, SYM, STDC, SCDF, SCH(14), IER
REAL*4 CHMAX(14), CHMIN(14), YMIN, YMAX
INTEGER*2 IQUAD(30), IYR(30), NQUAD, NYEAR, ITDMIN, ITDMAX,
. YLMIN, YLMAX, STYPE
INTEGER*4 TDCMIN, TDCMAX, CDFMIN, CDFMAX
CHARACTER*80 SNAME, SLOCN, SQUAD, SYEAR, SGEOL, SGEOLT
DATA FFEED/3072/

```

```

C THE FORM FEED CHARACTER IN A1
DATA PROMPT/'PH', 'CONDUCT', 'CO3', 'HCO3', 'CL', 'SO4', 'SiO2',
. 'Ca', 'Mg', 'Fe', 'Al', 'K', 'Na', 'TDS(Lab)', 'Alk', 'P Hard',
. 'T Hard'/

```

```

C USED FOR PROMPTS
OPEN(UNIT=4, FORM='BINARY', ACCESS='DIRECT', RECL=108, SHARE='ERO')

```

```

C OPEN THE WATMAIN.DAT FILE
OPEN(UNIT=2, FORM='BINARY', ACCESS='DIRECT', RECL=68, SHARE='ERO')

```

```

C OPEN WATANAL.DAT FILE
WRITE(5, 101)
101 FORMAT(' FOR CHARACTER OPTIONS ENTER EITHER A BLANK LINE OR/'
. ' THE DESIRED VALUES FOR THE OPTION, EACH TERMINATED BY/'
. ' A //' ' E.G. FRED/BILL/TOM/SMITH// ' FOR NUMERIC OPTIONS',
. ' ENTER EITHER THE RANGE REQUESTED// OR A BLANK LINE')
WRITE(5, 102)

```

102 FORMAT(' OWNER?')

```

      READ(5,201) SNAME
201 FORMAT(A80)
      WRITE(5,103)
103 FORMAT(' LOCATION?')
      READ(5,201) SLOCN
      WRITE(5,104)
104 FORMAT(' QUADRANGLE NO. ?')
      READ(5,201) SQUAD
      CALL NMERIC(SQUAD, IQUAD, NQUAD)
      WRITE(5,106)
106 FORMAT(' YEAR?')
      READ(5,201) SYEAR
      NYEAR=0
C COUNTER FOR NUMBER OF YEAR OPTIONS INPUT
      IF (SYEAR(1:2) .EQ. ' ') GOTO 21
C NO YEAR SEARCH DESIRED
      CALL NMERIC(SYEAR, IYR, NYEAR)
C
C NOW GET THE NEXT SEARCH OPTION
21 CONTINUE
      WRITE(5,107)
107 FORMAT(' GEOLOGIST?')
      READ(5,201) SGEOLT
      WRITE(5,108)
108 FORMAT(' SEARCH FOR SITES WITHIN A SPECIFIED AREA (Y)?')
      READ(5,200) STYPE
      IF (STYPE .EQ. 'Y') GOTO 23
C WANT TO READ COORDS
      NCOORD=0
      GOTO 26
C DONT WANT TO SEARCH FOR SITES IN AN AREA
C
23 CONTINUE
C READ VERTICES
      WRITE(5,109)
109 FORMAT(' NUMBER OF VERTICES OF AREA?/'
           ' ENTER 2 TO SPECIFY A RECTANGLE')
      READ(5,*) NCOORD
      IF (NCOORD .LT. 2) GOTO 23
C NEED AT LEAST 3 VERTICES TO DEFINE AN AREA
      IF (NCOORD .EQ. 2) THEN
        WRITE(5,515)
515 FORMAT(' ENTER COORDS OF TWO DIAGONALLY OPPOSITE CORNERS OF '
           ' THE RECTANGLE/' ONE PER LINE IN THE FORM EASTNORTH')
        ELSE
          WRITE(5,110)
110 FORMAT(' ENTER VERTEX COORDS IN CLOCKWISE ORDER/'
           ' ONE PER LINE IN FORM EASTNORTH')
        ENDIF
        IXMAX=-999999999
        IXMIN=-IXMAX
        IYMAX=IXMAX
        IYMIN=IXMIN
C USE THESE TO STORE THE RANGE OF THE AREA
        DO 24 I=1, NCOORD
          READ(5,503) IX, IY
503 FORMAT(I4, I5)
C GET INTO 100'S OF METRES EAST AND NORTH
        IXMAX=MAX0(IX, IXMAX)
        IXMIN=MIN0(IX, IXMIN)

```

```

      IYMAX=MAX0(IY,IYMAX)
      IYMIN=MIN0(IY,IYMIN)
C FIND THE RANGE
      X(I)=IX*0.1
      Y(I)=IY*0.1
C CONVERT TO KM BEFORE STORING
      24 CONTINUE
      IF (NCOORD .GT. 2) THEN
      IF (X(1) .NE. X(NCOORD) .OR. Y(1) .NE. Y(NCOORD)) THEN
      NCOORD=NCOORD+1
      X(NCOORD)=X(1)
      Y(NCOORD)=Y(1)
C CLOSE AREA
      ENDIF
      NCOORD=NCOORD-1
C ROUTINE FOR LOCATING POINTS DOESNT REQUIRE CLOSURE
      CALL PREPLY(X,Y,NCOORD,YINTVL,INTVLS,SWATH,RSLOPE)
C CUT THE SEARCH AREA UP INTO SWATHS
      ENDIF
C
      26 CONTINUE
      WRITE(5,105)
105 FORMAT(' TOTAL DEPTH RANGE - MIN,MAX (REAL)')
      CALL RANGE(ANUM,IER,5)
      TDMIN=ANUM(1)
      TDMAX=ANUM(2)
      ITDMIN=TDMIN*10.0+0.1
      ITDMAX=TDMAX*10.0+0.1
      STDM=ITDMAX .GE. ITDMIN .AND. ITDMAX .NE. 0
      WRITE(5,111)
111 FORMAT(' YIELD RANGE - MIN,MAX (REAL)')
      CALL RANGE(ANUM,IER,5)
      YMIN=ANUM(1)
      YMAX=ANUM(2)
      YLMIN=YMIN*100.0+0.1
      YLMAX=YMAX*100.0+0.1
      SYM=YLMAX .GE. YLMIN .AND. YLMAX .NE. 0
      WRITE(5,121)
121 FORMAT(' CONDUCTIVITY (FIELD) RANGE - MIN,MAX (INTEGER)')
      CALL RANGE(ANUM,IER,5)
      CDFMIN=ANUM(1)
      CDFMAX=ANUM(2)
      SCDF=CDFMAX .GE. CDFMIN .AND. CDFMAX .NE. 0
      WRITE(5,113)
113 FORMAT(' TDS RANGE - MIN,MAX (INTEGER)')
      CALL RANGE(ANUM,IER,5)
      TDCMIN=ANUM(1)
      TDCMAX=ANUM(2)
      STDC=TDCMAX .GE. TDCMIN .AND. TDCMAX .NE. 0
      WRITE(5,112)
112 FORMAT(' GEOLOGY (0-9)?')
      READ(5,201) SGEOL
      WRITE(5,114)
114 FORMAT(' SEARCH ON ANALYSIS (Y OR N)?')
      READ(5,200) STYPE
200 FORMAT(A1)
      SANAL=STYPE .EQ. 'Y'
      IF (SANAL) THEN
      DO 20 I=1,14
      WRITE(5,115) PROMPT(I)

```

```

1:15 FORMAT(' RANGE MIN, MAX FOR ',A8)
CALL RANGE(ANUM, IER, 5)
CHMIN(I)=ANUM(1)
CHMAX(I)=ANUM(2)
SCH(I)=CHMAX(I) .GE. CHMIN(I) .AND. CHMAX(I) .NE. 0
20 CONTINUE
ENDIF
IF (.NOT. STDC .AND. SCH(14)) THEN
C LOOKING FOR TDS SO MAKE IT LOOK AT THE FRONT OF THE VIRTUAL
C CARD TO SAVE TIME RUSHING OFF TO GET THE BACK OF THE CARD
STDC=. TRUE.
TDCMIN=CHMIN(14)
TDCMAX=CHMAX(14)
ENDIF
C STORED RANGE FOR TDS
C END OF OPTION INPUT
C
C*****
C NOW FOR THE SEARCH
FCOUNT=0
C COUNTER FOR NUMBER OF FOUND ENTRIES
RECCNT=0
C COUNTER FOR POSITION IN WATMAIN.DAT
27 READ(4,END=40) BUFF
C READ ONE ENTRY
RECCNT=RECCNT+1
C READ ONE MORE RECORD FROM WATMAIN
IF (SANEL .AND. ANAL .EQ. 0) GOTO 27
C SEARCHING BY ANALYSIS BUT THERE IS NO ANALYSIS
IF (NOTIN(SNAME,NAME)) GOTO 27
C NOT THE RIGHT NAME
IF(NOTIN(SLOCN,LOCATN)) GOTO 27
C NOT THE RIGHT LOCATION
IF (NQAD .NE. 0) THEN
DO 32 I=1,NQAD
IF (IQAD(I) .EQ. QUAD) GOTO 25
32 CONTINUE
GOTO 27
C NOT FOUND SO FALL OUT
25 CONTINUE
ENDIF
C END LOOK FOR QUADRANGLE
IF (NYEAR .NE. 0) THEN
DO 28 I=1,NYEAR
IF (IYR(I) .EQ. YEAR) GOTO 29
28 CONTINUE
GOTO 27
C NOT FOUND SO FALL OUT
29 CONTINUE
ENDIF
C LOOKED FOR YEAR
IF (NOTIN(SGEOLT,GEOLST)) GOTO 27
C NOT THE GEOLOGIST
IF (NCOORD .NE. 0) THEN
IF (EAST .LT. IXMIN .OR. EAST .GT. IXMAX) GOTO 27
IF (NORTH .LT. IYMIN .OR. NORTH .GT. IYMAX) GOTO 27
C CANT POSSIBLY BE IN AREA
IF (NCOORD .GT. 2) THEN
XTMP=EAST*0.1
YTMP=NORTH*0.1

```

```

C CONVERT TO KM
  IF (.NOT. INOUT(XTMP, YTMP, X, Y, YINTVL, INTVLS, SWATH, RSLOPE))
    GOTO 27
C NOT IN THE SPECIFIED AREA
  ENDIF
C FOR THE SIMPLE RECTANGLE DONT NEED THE POLYGON SEARCH
  ENDIF
  IF (STDM) THEN
    IF (TOTDEP .LT. ITDMIN .OR. TOTDEP .GT. ITDMAX) GOTO 27
  ENDIF
C CHECK FOR TOTAL DEPTH IN RANGE
  IF (SYM) THEN
    IF (YIELD .LT. YLMIN .OR. YIELD .GT. YLMAX) GOTO 27
  ENDIF
C CHECK YIELD IN RANGE
  IF (SCDF) THEN
    IF (CONDF .LT. CDFMIN .OR. CONDF .GT. CDFMAX) GOTO 27
  ENDIF
C CHECK FIELD CONDUCTIVITY
  IF (STDC) THEN
    IF (TDSC .LT. TDCMIN .OR. TDSC .GT. TDCMAX) GOTO 27
  ENDIF
C CHECK TDS
  IF (NOTIN(SGEOL, GEOL)) GOTO 27
C NOT RIGHT GEOLOGY
  IF (SANAL) THEN
    DO 30 I=1,13
C ONLY 13 AS HAVE LOOKED AT TDS ON FRONT OF CARD
    IF (SCH(I)) THEN
      IF (CHEM(I) .LT. CHMIN(I) .OR. CHEM(I) .GT. CHMAX(I)) GOTO 27
C THAT PARTICULAR ITEM NOT IN RANGE
    ENDIF
    30 CONTINUE
C GO ROUND ONE ITEM AT A TIME
  ENDIF
C BEEN THROUGH ANALYSIS
C IF FINALLY GET TO HERE HAVE FOUND AN ENTRY THAT MATCHES THE
C SEARCH OPTIONS
C
C PUT RECORD NUMBER INTO STORAGE
  FCOUNT=FCOUNT+1
C NO. OF FOUND ENTRIES
  IF (FCOUNT .EQ. 5001) STOP 'SEEK HELP - 5000 ENTRY ERROR'
  FOUND(FCOUNT)=RECCNT
C STORE REC NO IN WATMAIN.DAT
  GOTO 27
C BACK ROUND
C BACK AROUND
C
C
C NOW AT THE END OF THE RUN
  40 CONTINUE
C NOW DECIDE IF IT IS GOING TO BE PUT OUT ON THE SCREEN
  WRITE(5,123) FCOUNT
  123 FORMAT(I7, ' RECORDS WERE FOUND'// ' DO YOU WANT A'
    ' SCREEN LISTING (Y OR N)?')
  READ(5,200) STYPE
  IF (FCOUNT .EQ. 0) STOP
C NO ENTRIES FOUND SO EXIT ASAP
  IF (STYPE .EQ. 'N') GOTO 47

```

```

C NO SCREEN LIST WANTED
C
C TO SCREEN LIST USE DIRECT I/O
  SCOUNT=0
C NO. OF ENTRIES SENT TO SCREEN
  DO 41 I=1,FCOUNT
  READ(4,REC=FOUND(I)) BUFF
  TOTDP=TOTDEP*0.1
  CASDP=CASDEP*0.1
  AYIELD=YIELD*0.01
C CONVERT BACK TO LITRES/SEC FROM HUNDREDTHS OF LITRES/SEC
C AND BACK TO METRES FROM DECIMETRES
  IF (TDSC .GT. 0) THEN
  WRITE(5,116) NAME, LOCATN, DRILCO, QUAD, CARD, YEAR, GEOLST, EAST,
    NORTH, TOTDP, CASDP, DEPSTR, SWL, AYIELD, CONDF, TDSC, ANAL, GEOL
116 FORMAT(1X, A24, ' ', A30, ' ', A8, 2(' ', I3)/5X, I2, ' ',
    A3, ' ', I4, I5, ' ', 4(F5.1, 'm'),
    F5.2, '1/s', I5, ' ', I5, 'mg/1', I2, ' ', A2)
  ELSE
  WRITE(5,122) NAME, LOCATN, DRILCO, QUAD, CARD, YEAR, GEOLST, EAST,
    NORTH, TOTDP, CASDP, DEPSTR, SWL, AYIELD, CONDF, ANAL, GEOL
122 FORMAT(1X, A24, ' ', A30, ' ', A8, 2(' ', I3)/5X, I2, ' ',
    A3, ' ', I4, I5, ' ', 4(F5.1, 'm'),
    F5.2, '1/s', I5, ' ', 5X, 'mg/1', I2, ' ', A2)
  ENDIF
  SCOUNT=SCOUNT+1
  IF (SCOUNT .LT. 10) GOTO 41
C ALLOW 10 ENTRIES PER SCREENFULL
  SCOUNT=0
C RESET
  WRITE(5,117)
117 FORMAT(' LIST MORE ENTRIES ON SCREEN (Y OR N)?')
  READ(5,200) STYPE
  IF (STYPE .EQ. 'N') GOTO 47
C ROUND AGAIN FOR ANOTHER SCREEN FULL
  41 CONTINUE
  47 WRITE(5,118)
118 FORMAT(' DO YOU WANT A PRINTOUT (Y OR N)?')
  READ(5,200) STYPE
  IF (STYPE .NE. 'Y') STOP
C STOP IF NOTHING FOUND
C
C OTHERWISE WRITE TO PRINTER
C FIRST WRITE THE SEARCH OPTIONS
  WRITE(6,400)
400 FORMAT(' SEARCH OPTIONS ARE:')
  IF (SNAME(1:1) .NE. ' ') WRITE(6,401) SNAME
401 FORMAT(' NAME',10X,A80)
  IF (SLOCN(1:1) .NE. ' ') WRITE (6,402) SLOCN
402 FORMAT(' LOCATION',10X,A80)
  IF (NQUAD .NE. 0) WRITE(6,403) SQUAD
403 FORMAT(' QUADRANGLE NO.',10X,A80)
  IF (NYEAR .NE. 0) WRITE(6,405) SYEAR
405 FORMAT(' YEAR',10X,A80)
  IF (SGEOLT(1:1) .NE. ' ') WRITE(6,406) SGEOLT
406 FORMAT(' GEOLOGIST',10X,A80)
  IF (NCOORD .NE. 0) THEN
  IF (NCOORD .GT. 2) THEN
  WRITE(6,407)
407 FORMAT(' AREA COORDINATES (KM)')

```

```

NCOORD=NCOORD+1
C ROUTINE FOR LOCATING POINTS DOESNT REQUIRE CLOSURE
WRITE(6,408) (X(I),Y(I),I=1,NCOORD)
408 FORMAT(20X,4(F14.2,F9.2))
C ROUTINE FOR LOCATING POINTS DOESNT REQUIRE CLOSURE
ELSE
WRITE(6,516) IXMIN,IXMAX,IYMIN,IYMAX
516 FORMAT(' SEARCH RECTANGLE FROM',I5,' @0ME TO',I5,' @0ME AND FROM',
I6,' @0MN TO',I6,' @0MN')
ENDIF
ENDIF
IF (STDM) WRITE(6,409) TDMIN,TDMAX
409 FORMAT(' TOTAL DEPTH RANGE',F6.1,' TO',F6.1)
IF (SYM) WRITE(6,411) YMIN,YMAX
411 FORMAT(' YIELD RANGE',F6.2,' TO',F6.2)
IF (SCDF) WRITE(6,412) CDFMIN,CDFMAX
412 FORMAT(' CONDUCTIVITY (FIELD) RANGE',I6,' TO',I6)
IF (STDC) WRITE(6,413) TDCMIN,TDCMAX
413 FORMAT(' TDS RANGE',I6,' TO',I6)
IF (SGEOL(1:1) .NE. ' ') WRITE(6,410) SGEOL
410 FORMAT(' GEOLOGY',10X,A80)
DO 35 I=1,13
IF (SCH(I)) WRITE(6,414) PROMPT(I),CHMIN(I),CHMAX(I)
414 FORMAT(' RANGE FOR ',A8,' IS',F7.1,' TO',F7.1)
35 CONTINUE
LINE=0
C COUNTER FOR NUMBER OF LINES PRINTED
WRITE(5,119)
119 FORMAT(' PRINT ANALYSIS WHERE AVAILABLE (Y OR N)?')
READ(5,200) STYPE
IF (STYPE .NE. 'Y') THEN
C USE DIFFERENT FORMAT IF NOT WORRIED ABOUT ANALYSIS
DO 42 I=1,FCOUNT
READ(4,REC=FOUND(I)) BUFF
AYIELD=YIELD*0.01
TOTDP=TOTDEP*0.1
CASDP=CASDEP*0.1
C CONVERT TO LITRES/SEC AND METRES
IF (MOD(LINE,53) .EQ. 0) CALL HEAD
C HEAD PAGE
LINE=LINE+1
IF (TDSC .GT. 0) THEN
WRITE(6,300) NAME,LOCATN,DRILCO,QUAD,CARD,YEAR,GEOLST,EAST,
NORTH,TOTDP,CASDP,DEPSTR,SWL,AYIELD,CONDF,TDSC,ANAL,GEOL
300 FORMAT(1X,A22,' ',A27,' ',A8,' ',I2,' ',I3,' ',I2,' ',
A3,' ',I4,I5,4(' ',F5.1),' ',F5.2,' ',I5,' ',I5,
' ',I2,' ',A2)
ELSE
WRITE(6,301) NAME,LOCATN,DRILCO,QUAD,CARD,YEAR,GEOLST,EAST,
NORTH,TOTDP,CASDP,DEPSTR,SWL,AYIELD,CONDF,ANAL,GEOL
301 FORMAT(1X,A22,' ',A27,' ',A8,' ',I2,' ',I3,' ',I2,' ',
A3,' ',I4,I5,4(' ',F5.1),' ',F5.2,' ',I5,' ',I5,
' ',I2,' ',A2)
ENDIF
C USE DIFFERENT FORMAT IF THERE IS NO TDS
42 CONTINUE
ELSE
DO 43 I=1,FCOUNT
READ(4,REC=FOUND(I)) BUFF
C READ THE BASIC DATA

```

```

RYIELD=YIELD*0.01
TOTDP=TOTDEP*0.1
CASDP=CASDEP*0.1
C CONVERT BACK TO LITRES/SEC AND METRES
IF (ANAL .NE. 0) THEN
  READ(2,REC=INANAL) CHEM
  IF (MOD(LINE,55) .EQ. 0) CALL HEAD2
C HEAD PAGE
  LINE=LINE+5
  IF (TDSC .GT. 0) THEN
    WRITE(6,302) NAME,LOCATN,EAST,NORTH,QUAD,CARD,GEOLST,GEOL,YEAR,
      TOTDP,DEPSTR,SWL,CASDP,RYIELD,TDSC,CONDF,ANAL,
      DRILCO
302 FORMAT(' OWNER: ',A24,' LOCN: ',A30,' AMG: ',I2I5,
  ' QUAD: ',I3,' CARD: ',I3,' INIT: ',A3,' GEOLOGY: ',A2,' YR: ',I3
  ' DEPTH: -TOTAL: ',F5.1,' STRUCK: ',F5.1,' SWL: ',F5.1,
  ' CASING: ',F5.1,' YIELD: ',F5.2,' TDS: ',I5,
  ' COND(FIELD): ',I6,' ANALYSES: ',I2,' DRILL CO: ',A8)
  ELSE
    WRITE(6,303) NAME,LOCATN,EAST,NORTH,QUAD,CARD,GEOLST,GEOL,YEAR,
      TOTDP,DEPSTR,SWL,CASDP,RYIELD,CONDF,ANAL,
      DRILCO
303 FORMAT(' OWNER: ',A24,' LOCN: ',A30,' AMG: ',I2I5,
  ' QUAD: ',I3,' CARD: ',I3,' INIT: ',A3,' GEOLOGY: ',A2,' YR: ',I3
  ' DEPTH: -TOTAL: ',F5.1,' STRUCK: ',F5.1,' SWL: ',F5.1,
  ' CASING: ',F5.1,' YIELD: ',F5.2,' TDS: ',I5X,
  ' COND(FIELD): ',I6,' ANALYSES: ',I2,' DRILL CO: ',A8)
  ENDIF
  WRITE(6,304) CHEM
304 FORMAT(' pH: ',F4.1,' CONDUCTIVITY: ',F7.1,' CO3: ',F7.1,
  ' HCO3: ',F7.1,' Cl: ',F7.1,' SO4: ',F7.1,' SiO2: ',F7.1,
  ' Ca: ',F7.1,' Mg: ',F7.1,' Fe: ',F7.1,' Al: ',F7.1,
  ' K: ',F7.1,' Na: ',F7.1,' TDS: ',F7.1,' Alk: ',F7.1,
  ' TOT OR PERM HARDNESS: ',F7.1,' TEMP HARDNESS: ',F7.1)
  ELSE
    IF (MOD(LINE,54) .EQ. 0) CALL HEAD2
    LINE=LINE+3
C HEAD PAGE
    IF (TDSC .GE. 0) THEN
      WRITE(6,302) NAME,LOCATN,EAST,NORTH,QUAD,CARD,GEOLST,GEOL,YEAR,
        TOTDP,DEPSTR,SWL,CASDP,RYIELD,TDSC,CONDF,ANAL,
        DRILCO
    ELSE
      WRITE(6,303) NAME,LOCATN,EAST,NORTH,QUAD,CARD,GEOLST,GEOL,YEAR,
        TOTDP,DEPSTR,SWL,CASDP,RYIELD,CONDF,ANAL,
        DRILCO
    ENDIF
  ENDIF
  WRITE(6,305)
305 FORMAT(1X)
  43 CONTINUE
  ENDIF
C END PRINT EITHER CLOSE SPACED SHORT LIST OR FULL LIST
  WRITE(6,415) FFEED
415 FORMAT(1A1,
  ' // ALL DEPTHS IN METRES'//
  ' // ALL ANALYSES IN mg/l'//
  ' // ALL CONDUCTIVITIES IN uS/cm'//
  ' // ALL YIELDS IN l/sec'//
  ' // GEOLOGY'

```

```

. //      0 COASTAL          1 QUATERNARY          2 TERTIARY'
. //      SANDS              ALLUVIUM              SEDIMENTS'
. //      3 TRIASSIC         4 PERMIAN            5 MATHINNA'
. //                                     SEDIMENTS'
. //      6 ORDOVICIAN       7 GORDON             8 CAMBRIAN'
. //                                     LIMESTONE'
. //      9 PRECAMBRIAN      A PRECAMBRIAN        B TERTIARY'
. //                                     DOLOMITE             BASALT'
. //      C JURASSIC         D GRANITE'
. //      DOLERITE'
WRITE(6, 416)
416 FORMAT(1X)
STOP
END
SUBROUTINE NNERIC(STRING, IVAR, NVAR)
CHARACTER* (*) STRING
INTEGER*2 IVAR(2), NVAR
NVAR=0
ILAST=1
C COUNT POSITION ALONG INPUT LINE
  20 ICHAR=INDEX(STRING(ILAST:80), '/')
C LOOK FOR / AS TERMINATOR OF A STRING
  IF (ICHR .EQ. 0) GOTO 21
C NO MORE /
  ENCODE(BUFF, 300) STRING(ILAST:ILAST+1)
  300 FORMAT(A2)
  NNVAR=NNVAR+1
  DECODE(BUFF, 301) IVAR(NVAR)
  301 FORMAT(I2)
C CONVERTED TO AN INTEGER
  ILAST=ILAST+ICHR
C POSITION TO AFTER THE /
  IF (ILAST .NE. 79) GOTO 20
C ROUND FOR NEXT IVAR
  21 RETURN
END
LOGICAL FUNCTION NOTIN(SSTRNG, RSTRNG)
C SSTRNG CONTAINS A SERIES OF STRINGS TERMINATED BY /
C E. G. FRED/BILL/TOM/
C AND RSTRNG IS SEARCHED FOR THE OCCURENCE OF ONE OF THESE STRINGS
C IF ONE IS FOUND TO MATCH NOTIN IS .FALSE.
C IF STRNG IS EMPTY NOTIN IS .FALSE.
  CHARACTER*80 SSTRNG
  CHARACTER* (*) RSTRNG
  NOTIN=.FALSE.
  IF (SSTRNG(1:1) .EQ. '/') RETURN
C NO NEED TO LOOK
  ILAST=1
C COUNTER FOR POSITION IN SSTRNG
  20 ICHAR=INDEX(SSTRNG(ILAST:80), '/')
C LOOK FOR / AS TERMINATOR OF STRING
  IF (ICHR .EQ. 0) GOTO 25
C HAVENT FOUND A MATCH BY THE END OF THE LINE
  IF (INDEX(RSTRNG, SSTRNG(ILAST:ILAST+ICHR-2)) .NE. 0) RETURN
C LOOK BETWEEN /S IN SSTRNG AND IF FIND A MATCH RETURN
  ILAST=ILAST+ICHR
C POSITION AFTER THE /
  IF (ILAST .LE. 79) GOTO 20
C BACK ROUND IF NOT AT END OF LINE
C

```

```

C ELSE END
  25 CONTINUE
    NOTIN=. TRUE.
C NO MATCH
  RETURN
  END
  SUBROUTINE HEAD
C HEAD UP PAGES FROM SEARCH
  INTEGER*2 FFEED
  DATA FFEED/3072/
C USED TO PUT FORM FEEDS IN OUTPUT FILE
  WRITE(6,100) FFEED
100 FORMAT(1A1/9X, 'OWNER', 9X, '1', 9X, 'LOCATION', 10X, '1 DRILCO 1',
. 2X, 'CARD', 'INIT', 9X, '1 TOT 1 CAS 1DEPTH', 11X, '1FIELD', 5X, '1',
. 'ANI', /23X, '1', 27X, '1', 8X, 'QUAD ↑ YEAR ↑ 1 MAPREF ',
. '1 DEP 1 DEP 1 STR 1 SWL 1 YLD 1COND 1 TDS 1ALIGED',
. /1X, 131(' '))
  RETURN
  END
  SUBROUTINE RNOIN(RNO, RYR)
C USE TO READ RECORDS NO AND YEAR AND AVOID HAVING TO MANUALLY
C REPLACE / WITH , IN 1234/76
  INTEGER*2 RNO, RYR
  CHARACTER*1 BUFF(9)
  READ(5,115) BUFF
115 FORMAT(9A1)
  DO 10 I=1,9
    IF (BUFF(I) .EQ. '/') BUFF(I)=','
  10 CONTINUE
  REWIND 3
  WRITE(3,115) BUFF
  REWIND 3
  READ(3,*) RNO, RYR
C PUT OUT TO TEMPORARY FILES AND READ BACK IN IN FREE FORMAT
  RETURN
  END
  SUBROUTINE HEAD2
C PUT A FORM FEED AT THE HEAD OF THE PAGE
  INTEGER*2 FFEED
  DATA FFEED/3072/
  WRITE(6,100) FFEED
100 FORMAT(A1)
  RETURN
  END
$TITL RANGE - FREE FORMAT OF 2 POSITIVE REALS SEPARATED BY , OR -
  SUBROUTINE RANGE(ANUM, IER, ILUN)
C A ROUTINE FOR INPUTTING 2 REAL VALUES IN ANUM.
C THE INPUT FILE IS SCANNED UNTIL 2 VALUES ARE READ OR THERE IS AN
C END OF LINE. NUMBERS ON THE SAME LINE MAY BE SEPARATED BY , OR -.
C THE ROUTINE REQUIRES POSITIVE NUMBERS. THE MAXIMUM LENGTH IS 80 CHAR
C ANUM(2) REAL
C ILUN INTEGER*4
C IER LOGICAL
C IER IS TRUE IF THERE IS AN ERROR OR EOF
C COUNT IS THE ACTUAL NUMBER OF VALUES SUCCESSFULLY TRANSFERRED
C USES ENCODE TO REFORMAT SUITABLE FOR F10.0
C
  REAL ANUM(2)
  INTEGER*2 A(10), ALINE(80), PLUS, MINUS,
. DPOINT, AL, K, I, J, IBOT, ZERO, NINE, POINT

```

```

INTEGER*4 ILUN,COUNT
REAL*4 BUFF(4)
LOGICAL IER
DATA PLUS/'1H+/',MINUS/'1H-/',DPOINT/'1H. /',ZERO/'1H0/',NINE/'1H9'/
IER=.TRUE.
COUNT=0
C USED TO KEEP TRACK OF NUMBER OF VALUES FOUND
  READ(ILUN,100,END=101,ERR=101) ALINE
  100 FORMAT(80A1)
C READ IN CHARACTER FORMAT - 80 CHARS
  IBOT=1
C USED OT MOVE STEADILY ALONG THE LINE
  29 CONTINUE
C TO HERE TO LOOK FURTHER ALONG A LINE
  IF (IBOT .GE. 81) GOTO 28
  DO 10 I=IBOT,80
  AL=ALINE(I)
  IF (AL .EQ. PLUS .OR. AL .EQ. DPOINT
    .OR. (AL .GE. ZERO .AND. AL .LE. NINE)) GOTO 20
C LOOK FOR +,.,0,1,2,3,4,5,6,7,8,9 AS THE START OF A NUMBER
  10 CONTINUE
C IF FALL THROUGH HERE ARE AT THE END OF A LINE
  GOTO 28
C ONLY ONE NUMBER ON LINE WHEN SHOULD BE 2 SO SET BOTH TO 0
C
C NOW COPY THE NUMBER TO ITS END
  20 K=0
C COUNTER FOR A ARRAY
  POINT=0
C ENSURE HAVE ONE AND ONLY ONE DECIMAL POINT
  DO 11 J=I,80
  AL=ALINE(J)
  IF (AL .EQ. DPOINT .AND. POINT .EQ. 1) GOTO 21
C FIND A SECOND DEC PT SO AT THE END OF THE NUMBER
  IF (AL .EQ. DPOINT) POINT=1
C FOUND A DECIMAL POINT
  IF (AL .NE. PLUS .AND. AL .NE. DPOINT
    .AND. (AL .LT. ZERO .OR. AL .GT. NINE)) GOTO 21
C TERMINATE NUMBER BY NOT A +,.,0,1,2,3,4,5,6,7,8,9
  K=K+1
  IF (K .GE. 11) GOTO 101
C TOO MANY CHARACTERS
  A(K)=AL
  11 CONTINUE
C AT END OF NUMBER
  J=81
  21 IBOT=J
C NOTE SCAN START FOR NEXT NUMBER
  IF (POINT .EQ. 1) GOTO 22
C ALREADY HAVE A DECIMAL POINT
  K=K+1
  A(K)=DPOINT
C ADD A DECIMAL POINT IF NEEDED
C
C AND WRITE TO BUFFER AND REFORMAT
  22 IF (K .EQ. 10) GOTO 24
C NUMBER IS 10 CHARACTERS LONG
  K=K+1
  DO 23 I=K,10
  A(I)=ZERO

```

```

23 CONTINUE
C FILL WITH ZEROES
24 CONTINUE
  ENCODE(BUFF,100) (A(I), I=1, 10)
  DECODE(BUFF,111) ATMP
111 FORMAT(F10.0)
C HAVE THE NUMBER
  COUNT=COUNT+1
  ANUM(COUNT)=ATMP
  IF (COUNT .LT. 2) GOTO 29
  IER=.FALSE.
101 RETURN
28 ANUM(1)=0.
  ANUM(2)=0.
  GOTO 101
END

```

```

$TITL FSTJDN.FTN - POINT IN POLYGON
C PROGRAM COLLECTION FASTJORDAN
C SALOMON, K. B., 1978. AN EFFICIENT POINT-IN-POLYGON ALGORITHM
C COMPUTERS AND GEOSCIENCES, V4, NO. 2, P. 173-178

```

```

C USE BY READING VERTICES OF POLYGON IN ORDER (BUT NOT CLOSING IT)
C AND CALLING PREPLY ONCE BEFORE THE SEARCH IS BEGUN. THE ACTUAL
C SEARCHING IS DONE BY MEANS OF THE LOGICAL FUNCTION INOUT.

```

```

SUBROUTINE PREPLY(X, Y, NUVERT, YINTVL, INTVLS, SWATH, RSLOPE)

```

```

C*****
C THIS ROUTINE PREPARES THE POLYGON CONSISTING OF THE NUVERT VERTICES
C (X(I), Y(I)) BY FIRST SORTING THE SEGMENT Y-END POINTS INTO
C DECREASING ORDER AND FORMING AN INTERVAL FOR EACH CONSECUTIVE PAIR:
C (YINTVL(I), YINTVL(I+1)), I=1, INTVLS. THIS IS PERFORMED BY CALLING
C SORT.
C THE CODE CONSISTING OF THE DO 100 AND DO 200 LOOPS CONSTRUCTS,
C FOR EACH INTERVAL I, THE LIST OF SEGMENTS TO BE TESTED BY INOUT.
C THIS LIST IS PLACED IN THE I-TH ROW OF SWATH. THE FIRST ENTRY,
C SWATH(I,1), WILL BE SET TO THE NUMBER OF SEGMENTS IN THE ROW. NOTE
C THAT AS YINTVL CONTAINS NO REDUNDANCIES, I. E. YINTVL(I) IS STRICTLY
C GREATER THAN YINTVL(I+1), NO HORIZONTAL SEGMENTS WILL BE PLACED IN
C THE LIST.
C THE CODE CONSISTING OF THE DO 300 LOOP ESTABLISHES THE
C RECIPROCAL SLOPE FOR EACH NON-HORIZONTAL SEGMENT. THIS IS TO BE
C USED BY INOUT. FINALLY, THE SEGMENTS WITHIN A ROW OF SWATH ARE
C ORDERED FROM LEFT-TO-RIGHT.

```

```

C*****

```

```

  INTEGER*2 SWATH(100,25)
  REAL X(100), Y(100), YINTVL(100), RSLOPE(100)
  CALL SORT(Y, NUVERT, YINTVL, INTVLS)
  IF (INTVLS .LE. 0) GOTO 400
  X(NUVERT+1)=X(1)
  Y(NUVERT+1)=Y(1)
  DO 100 I=1, INTVLS
100 SWATH(I,1)=0
  DO 200 I=1, INTVLS
  DO 200 J=1, NUVERT
  IF (Y(J).GE. YINTVL(I) .AND. YINTVL(I+1).GE. Y(J+1) .OR.
*   Y(J+1).GE. YINTVL(I) .AND. YINTVL(I+1).GE. Y(J))
*   CALL INCLUD(SWATH, I, J)

```

```

200 CONTINUE
  DO 300 I=1, NUVERT
  IF (Y(I).EQ.Y(I+1)) GOTO 300
  RSLOPE(I)=(X(I+1)-X(I))/(Y(I+1)-Y(I))
300 CONTINUE
  CALL ORDER(X, Y, YINTVL, INTVLS, SWATH, RSLOPE)
  RETURN
400 WRITE(7, 401)
401 FORMAT(' ***** PREP OF POLYGON ABORTED SINCE NO INTERVALS',
* ' CONSTRUCTED')
  STOP
  END
  SUBROUTINE SORT(Y, NUVERT, YINTVL, INTVLS)

```

C
C*****
C
C ROUTINE ESTABLISHES THE INTERVALS OF THE Y-AXIS DEFINED BY THE
C ENDPOINTS OF THE POLYGON'S SEGMENTS. THE DO 100 LOOP INITIALISES
C YSORT FROM THE SEGMENT Y-END POINTS. THE DO 200 LOOPS SORT YSORT
C INTO DESCENDING ORDER. THE DO 300 LOOP ELIMINATES REDUNDANCIES IN
C YSORT AND PLACES IRREDUNDANT SORTED Y'S INTO YINTVL. IT ALSO SETS
C INTVLS TO THE TRUE NUMBER OF Y INTERVALS. JUST PRIOR TO RETURNING
C A FINAL INTERVAL EXTENDING TO '-INFINITY' IS ESTABLISHED.
C
C*****
C

```

  REAL Y(100), YINTVL(100), YSORT(100)
  INTEGER*2 UPPER
  DO 100 I=1, NUVERT
100 YSORT(I)=Y(I)
  UPPER=NUVERT-1
  DO 200 I=1, UPPER
  IPLS1=I+1
  DO 200 J=IPLS1, NUVERT
  IF (YSORT(I).GE.YSORT(J)) GOTO 200
  TEMP=YSORT(I)
  YSORT(I)=YSORT(J)
  YSORT(J)=TEMP
200 CONTINUE
  YINTVL(1)=YSORT(1)
  INTVLS=0
  DO 300 I=1, UPPER
  IF (YSORT(I).EQ.YSORT(I+1)) GOTO 300
  INTVLS=INTVLS+1
  YINTVL(INTVLS+1)=YSORT(I+1)
300 CONTINUE
  YINTVL(INTVLS+2)=-1.0E75
  RETURN
  END
  SUBROUTINE INCLUD(SWATH, I, J)

```

C
C*****
C ROUTINE PLACES THE J-TH POLYGON SEGMENT INTO THE NEXT AVAILABLE
C LOCATION IN ROW I OF SWATH.
C
C*****
C

```

  INTEGER*2 SWATH(100, 25), POINTR
  SWATH(I, 1)=SWATH(I, 1)+1
  POINTR=SWATH(I, 1)

```

```

SWATH(I, POINTR+1)=J
RETURN
END
SUBROUTINE ORDER(X, Y, YINTVL, INTVLS, SWATH, RSLOPE)

```

```

C
C*****
C
C FOR EACH INTERVAL, A HORIZONTAL LINE IS PASSED THROUGH THE MIDDLE
C (YMID) OF THE INTERVAL. THE DO 100 LOOP PLACES THE X-INTERSECTION
C OF EACH SEGMENT IN THIS SWATH SO THAT THESE INTERSECTIONS OCCUR
C FROM LEFT-TO-RIGHT.
C
C*****
C

```

```

REAL X(100), Y(100), YINTVL(100), RSLOPE(100), XINTSC(25)
INTEGER*2 SWATH(100, 25), POINTR, SEGNO, UPPER
LOGICAL VERTSG
DO 200 INTVAL=1, INTVLS
  NMBSEG=SWATH(INTVAL, 1)
  YMID=(YINTVL(INTVAL)+YINTVL(INTVAL+1))/2.0
  DO 100 POINTR=1, NMBSEG
    SEGNO=SWATH(INTVAL, POINTR+1)
    VERTSG=ABS(X(SEGNO+1)-X(SEGNO)) .LT. 1.0E-5
    IF (VERTSG) XINTSC(POINTR)=X(SEGNO)
    IF (.NOT. VERTSG) XINTSC(POINTR)=X(SEGNO)+
      RSLOPE(SEGNO)*(YMID-Y(SEGNO))

```

```

*
100 CONTINUE
IF (NMBSEG.LT.2 .OR. MOD(NMBSEG, 2).NE.0) GOTO 300
UPPER=NMBSEG-1
DO 200 I=1, UPPER
  IPLS1=I+1
  DO 200 J=IPLS1, NMBSEG
    IF (XINTSC(I).LE.XINTSC(J)) GOTO 200
    TEMP=XINTSC(I)
    XINTSC(I)=XINTSC(J)
    XINTSC(J)=TEMP
    ITEMP=SWATH(INTVAL, J+1)
    SWATH(INTVAL, I+1)=SWATH(INTVAL, J+1)
    SWATH(INTVAL, J+1)=ITEMP

```

```

200 CONTINUE
RETURN
300 WRITE(7, 301) INTVAL
301 FORMAT(' ** PREP OF POLYGON ABORTED. INTERVAL ', I5/
  * ' HAS EITHER LESS THAN TWO SEGMENTS OR AN ODD NUMBER OF THEM')
STOP
END
LOGICAL FUNCTION INOUT(XP, YP, X, Y, YINTVL, INTVLS, SWATH, RSLOPE)

```

```

C
C*****
C
C THE FOUR LINES ENCLOSED IN DASHES DETERMINE THE INTERVAL CONTAINING
C YP. THE DO 400 LOOP CONTINUES UNTIL THE FIRST SEGMENT WITHIN THE
C INTERVAL FALL TO THE LEFT OF (XP, YP). IN THIS EVENT, INOUT IS SET
C .TRUE. IFF AN EVEN NUMBER OF SEGMENTS HAS BEEN TESTED.
C
C*****
C
REAL X(100), Y(100), YINTVL(100), RSLOPE(100)
INTEGER*2 SWATH(100, 25), SEGNO
INOUT=.FALSE.

```

```
C-----  
      INTVAL=0  
100  INTVAL=INTVAL+1  
      IF (YINTVL(INTVAL) .GT. YP) GOTO 100  
      INTVAL=INTVAL-1  
C-----  
300  IF (INTVAL .LT. 1 .OR. INTVAL .GT. INTVLS) RETURN  
      NMBSEG=SWATH(INTVAL,1)+1  
      DO 400 I=2,NMBSEG  
          SEGNO=SWATH(INTVAL,I)  
          IF (XP-X(SEGNO) .LE. (YP-Y(SEGNO))*RSLOPE(SEGNO)) GOTO 500  
400  CONTINUE  
      RETURN  
500  INOUT=MOD(I,2) .EQ. 1  
      RETURN  
      END
```