

UR1986-58

1986/58. CONMAT - The Tasmanian construction materials register.

R. G. Richardson

Abstract

The program suite described is used for adding entries to a register of construction materials, changing entries, sorting the register, and searching. The data are entered onto coding forms and all the details, except the reference number, can be searched.

INTRODUCTION

Data on several thousand sources of Tasmanian construction materials are held by the Department of Mines in the construction materials register. To search through the data on the basis of one or more parameters using the existing manual system is extremely difficult and time consuming.

The programs used for CONMAT are written in FORTRAN 77 and are run on the Geological Survey Perkin-Elmer mini-computer. It is assumed that the user is familiar with the operating system and the standard editing facilities. Any grain size analyses that have been processed through the SEDSAM programs (Hudspeth, 1986) may be retrieved and printed during the search. Appendix 1 shows an input coding form.

USING THE PROGRAMS

Data-base maintenance

Data are input by typing CONADD. This program regards field data as consisting of production, reserves, operational status, rock name, rock unit, age, colour, generic environment, extractability, collector and year. Test data are assumed to consist of geophysics, drilling, test and laboratory. The program tests as many options as possible for valid data. The program requests the following:

- (i) Reference number - the reference number in the register. The first two digits of the reference number are the quadrangle.
 - to finish input type END here
 - e.g. 01072
 - 75123
- (ii) Map sheet - the 1:50 000 sheet number
 - e.g. 83142
- (iii) AMG co-ordinates - the AMG co-ordinates of the site to the nearest 100 m.
 - e.g. EQ123456
- (iv) Occupier - the occupier's name (up to 20 characters).
- (v) Mineral lease - the mineral lease number.
- (vi) Locality - a description of the locality (up to 12 characters).
- (vii) Land tenure - a one-digit code to indicate the land tenure.

- (viii) Land use - a one-digit code to indicate the land use allowed by the planning authority.
- (ix) Report - a reference to any report (up to 12 characters).
- (x) Annual Production - annual production ($m^3 \times 10^3$)
- (xi) Total production - total production ($m^3 \times 10^3$)
- (xii) Reserves - a one-digit code to indicate the estimated reserves.
- (xiii) Operational status - a one-digit code to indicate the operational status of the site.
- (xiv) Rock name - the dominant rock type involved (up to 10 characters)
- (xv) Rock unit - the stratigraphic name of the rock unit (up to 8 characters)
- (xvi) Age - the geological age of the material (up to 3 characters)
- (xvii) Colour - up to two one-digit codes to indicate the colour.
- (xviii) Generic environment - up to two one-character codes to indicate the generic environment.
- (xix) Extractability - a one-digit code to indicate the method of extraction.
- (xx) Data collected by/year - the data collector and year. The year must be a four digit integer.
- (xxi) If there is no test data type N here - prompts (xxii) to (xxv) will not be issued.
- (xxii) Geophysics - up to two one-digit codes to indicate geophysical testing methods.
- (xxiii) Drilling - up to two one-digit codes to indicate drilling techniques used in testing.
- (xxiv) Tests - a series of prompts for test types. Type Y if this test type was performed.
- (xxv) Laboratory - a one-digit code to indicate the testing laboratory.
- (xxvi) Soil classification symbol - a five-character soil classification.
- (xxvii) Use - up to six one-character codes to indicate uses for the material.
- (xxviii) Quality - a one-digit code to indicate the quality of the material.
- (xxix) Standard - a one-digit code to indicate the standard to which testing has been performed.

At the end of input, a proof-sheet is output and the data saved in file CONTEMP.TMP. Corrections may be made to this file using the standard editing facilities, and a new proof-sheet then printed and checked.

The new data in CONTEMP.TMP must be added to the end of the existing data-base by typing CONMERGE. To ensure that the file remains in reference number order it should be sorted periodically using the CONSORT command.

Data may be changed by typing CONCHGE. The program requests:

- (i) Reference number - the reference number of the entry to be altered
- type END if no further alterations are to be made
- (ii) A series of opportunities to alter particular data values follows.

Data-base searching

The search phase is entered by typing CONSRCH. An entry will be retrieved only if the specified search options are matched.

The program requests the following data:

- (i) Quadrangle - one or more quadrangle numbers on a single line, each terminated by a /. Leave blank if not required.
e.g. 01/27/33/
- (ii) Map sheet - as for quadrangle.
- (iii) Search by area - leave blank for no search by area
- Y for finding entries inside a specified area. Entries on the boundary of the area will not be found. The program prompts for the number of vertices. If 2 is entered a simple rectangle parallel to the grid may be entered by specifying the co-ordinates of any two diagonally opposite corners. Otherwise the program requires the co-ordinates of the vertices of the area in clockwise order.
- (iv) Occupier - details as for quadrangle.
- (v) Mineral lease - one or more mineral lease numbers on a single line each terminated by a ;. Leave blank if not required
e.g. 1234P/M;107P/M;
- (vi) Land tenure - one or more land tenure codes on a single line, each terminated by a /. Leave blank if not required.
e.g. 1/2/
- (vii) Land use - details as for land tenure.
- (viii) Search on field data - type Y to search field data. Leave blank otherwise.
- (ix) Annual Production range - blank if not used
- minimum and maximum if looking for certain ranges.

- (x) Total production range - details as for annual production range.
- (xi) Reserves - details as for land tenure.
- (xii) Operation status - details as for land tenure.
- (xiii) Rock name - details as for quadrangle.
- (xiv) Rock unit - details as for quadrangle.
- (xv) Age - details as for quadrangle.
- (xvi) Colour - one or more colour codes on a single line, each group terminated by a /. Leave blank if not required.
 e.g. 2/5/ white or yellow
 04/ light and grey
- (xvii) Generic environment - details as for colour.
- (xviii) Extractability - details as for land tenure.
- (xix) Collector - details as for quadrangle.
- (xx) Range of years - details as for annual production range.
- (xxi) Search on test data - type Y to search test data. Leave blank otherwise.
- (xxii) Geophysics - details as for colour.
- (xxiii) Drilling - details as for colour.
- (xxiv) Test - type Y if a particular test is required. Leave blank otherwise.
- (xxv) Print grain size analysis results - type Y to print available grain size analysis results for entries retrieved. Leave blank otherwise.
- (xxvi) Laboratory - details as for land tenure.
- (xxvii) Soil classification symbol - details as for quadrangle.
- (xxviii) Use - details as for colour.
- (xxix) Quality - details as for land tenure.
- (xxx) Standard - details as for land tenure.
- (xxxi) Listing option - 1 Full listing on the printer
 2 Full listing on screen with option of printing
 3 Abbreviated listing to printer
- (xxxii) Print this entry - Y if an entry on the screen is to be printed.
- (xxxiii) Stop searching - N if no more entries are to be searched.

(xxxiv) Printer only - Y if further entries are to go only to the printer.

(xxxv) Print found entries - Y to print the found entries.

Sample outputs for options 1 and 3 are shown in Appendices 2 and 3.

THE PROGRAMS

CONADD (Appendix 4)

This program accepts data from the keyboard and copies it to a file in a format suitable for editing. Prompts are used to guide the user and some verification is performed. The file created (CONTEMP.TMP) may then be edited using the standard edit facilities.

CONMERGE (Appendix 5)

The data from CONTEMP.TMP are read and the basic data converted to the format of the data-base and put in file CONIND.DAT.

CONSORT (Appendix 6)

The data are sorted into ascending reference number order using a temporary work file. An index file for use by CONCHGE is created.

CONCHGE (Appendix 7)

This pair of programs allows users to change entries in the data-base.

CONSRCH (Appendix 8)

The data base is searched for the occurrence of specified strings or values and a point-in-polygon algorithm is used to locate data from within a specified area.

REFERENCE

HUDSPETH, J.W. 1986. SEDSAM: A FORTRAN program for size of sediment analysis (Revision 2). *Unpubl. Rep. Dep. Mines Tasm.* 1986/57.

[16 September 1986]

CONSTRUCTIONAL MATERIALS REGISTER - INPUT DATA SHEET

GENERAL DATA

Reference No. (5) -----

Map sheet (1:50 000) (5) -----

AHG Co-ordinates (8) -----

Occupier (20) -----

Mineral Lease (7) -----

Locality (12) -----

Land tenure (1) National Park State Forest Crown land
 Cons. Area Freehold Other

Planning Authority (1) Quarrying permitted Quarrying not permitted Quarrying discretionary
 Land Use

Report (12) -----

FIELD DATA

Production (4) ----- (annual)

(m³ x 10³) (4) ----- (total)

Reserves m³ (1) Not determined 10³-10⁴ 10⁶-10⁹
 <10³ 10⁴-10⁶ >10⁹

Operational Status (1) fully operational abandoned
 occasionally new area

Rock name (10) -----

Rock unit (8) -----

Age (3) -----

Colour (2) Light Black Brown
 Dark Grey Red
 White Yellow Mottled

Generic-environment (2) Igneous - intrusive Alluvial
 - volcanic Dune
 Sedimentary Beach
 Metamorphic Offshore
 Duricrust Furnace slag
 Residual Mine waste
 Colluvial Fly ash

Extractability (1) Backhoe
 Excavator
 Bulldozer (D9)
 Blasting required

Data collected by /year (7) -----

TEST DATA

Geophysics (2) E.M. Seismic Resistivity
 Gravity Magnetic

Drilling (2) Auger Diamond Rotary
 Churn Percussion Test Pits

Test (1) each (tick for yes)

Grain size analysis	<input type="checkbox"/>
Atterberg limits	<input type="checkbox"/>
Strength properties	<input type="checkbox"/>
Petrology	<input type="checkbox"/>
Chemical analysis	<input type="checkbox"/>
X-ray diffraction	<input type="checkbox"/>
Ceramic	<input type="checkbox"/>
Other	<input type="checkbox"/>

Laboratory (1) Department of Mines
 Department of Main Roads
 H.E.C.
 Other

Unified soil classification symbol (5) -----

Use (6) -----

A	Crushed aggregate	N	Sand - mortar
	Natural aggregate:	O	- filtration
B	Road - sub base	P	- foundry
C	- base course	Q	- glass
D	- admixture	R	- brick
E	- sealed road	S	- bedding
F	- unsealed road	T	Clay - brick
G	- hot mix sand	U	- earthenware
H	Concrete	V	- porcelain
	- coarse aggregate		
I	- fine aggregate	W	- filler
J	- pipe	X	Building stone
K	- block	Y	Heavy mineral
L	- tile	Z	Silica
M	Light-weight aggregate		

Quality Marginal
 Satisfactory
 Excellent

Standard British standard
 Australian standard
 NAASRA
 ASTM
 Other

58-6

Data input sheet

APPENDIX 1

6/54

APPENDIX 2

Sample output, Option 1

SEARCH OPTIONS ARE:

QUADRANGLE 83/
 OCCUPIER SORELL/DMR/
 GRAIN SIZE ANALYSIS MUST HAVE BEEN DONE
 GRAIN SIZE ANALYSES TO BE PRINTED

TASMANIAN CONSTRUCTION MATERIALS REGISTER

58-7

REF: 83001 MAP: 84123 COORDS: 544252639 OCCUPIER: SORELL COUNCIL LEASE: LOCAL: PENNA TEN: CL USE:
 REPORT: ANN PROD'N: 0 TOT: 3 RES: SML STAT: ABN ROCKNAME: DOLERITE UNIT: AGE: JU
 COLOUR: , GEN TYPE: IN,RE EXTRACT'N: DZ COLLECTOR: RAM YEAR: 1979 GEOPHYS: , DRILL: ,
 TEST: GS,AL, , , , , LAB: DMR SOIL CLASS: GW-GC USES: RS,RU, , , , QUALITY: S STANDARD: RA

REF: 83003 MAP: 84123 COORDS: 544352657 OCCUPIER: DMR LEASE: LOCAL: SORELL TEN: CL USE:
 REPORT: ANN PROD'N: 0 TOT: 14 RES: MED STAT: ABN ROCKNAME: DOLERITE UNIT: AGE: JU
 COLOUR: , GEN TYPE: IN, EXTRACT'N: DZ COLLECTOR: RAM YEAR: 1979 GEOPHYS: , DRILL: ,
 TEST: GS,AL, , , , , LAB: DMR SOIL CLASS: GC USES: RS, , , , , QUALITY: M STANDARD: RA

REF: 83005 MAP: 84123 COORDS: 556652548 OCCUPIER: SORELL COUNCIL LEASE: LOCAL: CARLTON TEN: FH USE:
 REPORT: ANN PROD'N: 0 TOT: 25 RES: MED STAT: OCC ROCKNAME: DOLERITEG UNIT: AGE: JU
 COLOUR: , GEN TYPE: IN,RE EXTRACT'N: DZ COLLECTOR: RAM YEAR: 1979 GEOPHYS: , DRILL: ,
 TEST: GS,AL, , , , , LAB: DMR SOIL CLASS: GW-GC USES: RS,RB,RU, , , , QUALITY: S STANDARD: RA

REF: 83013 MAP: 84123 COORDS: 555552656 OCCUPIER: DMR LEASE: LOCAL: WATTLE HILL TEN: CL USE:
 REPORT: ANN PROD'N: 0 TOT: 8 RES: MED STAT: OCC ROCKNAME: DOLERITE UNIT: AGE: JU
 COLOUR: , GEN TYPE: IN, EXTRACT'N: DZ COLLECTOR: RAM YEAR: 1979 GEOPHYS: , DRILL: ,
 TEST: GS,AL, , , , , LAB: DOM SOIL CLASS: GW-SC USES: RS,RW, , , , QUALITY: M STANDARD: RA

GRAIN SIZE ANALYSES

REF NO

83001

PHI= -5.229 PERCENT= 0.000
 PHI= -4.728 PERCENT= 7.000
 PHI= -4.248 PERCENT= 14.000
 PHI= -3.252 PERCENT= 36.000
 PHI= -2.251 PERCENT= 47.000
 PHI= -1.239 PERCENT= 60.000
 PHI= 1.234 PERCENT= 82.000
 PHI= 3.737 PERCENT= 91.000
 MEAN= -1.183

CALCULATIONS ARE FOR INCLUDED FRACTION

NO SORTING, SKEWNESS OR KURTOSIS CALCULATED
 L.L.= 37.000 P.I.= 17.000 L.S.= 10.000
 DUST RATIO= 0.500

83003

PHI= -5.229 PERCENT= 0.000
 PHI= -4.728 PERCENT= 8.000
 PHI= -4.248 PERCENT= 25.000
 PHI= -3.252 PERCENT= 38.000
 PHI= -2.251 PERCENT= 45.000
 PHI= -1.239 PERCENT= 52.000
 PHI= 1.234 PERCENT= 74.000
 PHI= 3.737 PERCENT= 84.000
 MEAN= -0.383

CALCULATIONS ARE FOR INCLUDED FRACTION

NO SORTING, SKEWNESS OR KURTOSIS CALCULATED
 L.L.= 48.000 P.I.= 31.000 L.S.= 15.000
 DUST RATIO= 0.615

83013

PHI= -5.229 PERCENT= 0.000
 PHI= -4.728 PERCENT= 3.000
 PHI= -4.248 PERCENT= 3.000
 PHI= -3.252 PERCENT= 11.000
 PHI= -2.251 PERCENT= 29.000
 PHI= -1.239 PERCENT= 62.000
 PHI= 1.234 PERCENT= 84.000
 PHI= 3.737 PERCENT= 91.000
 MEAN= -0.870

CALCULATIONS ARE FOR INCLUDED FRACTION

NO SORTING, SKEWNESS OR KURTOSIS CALCULATED
 L.L.= 42.000 P.I.= 24.000 L.S.= 20.000
 DUST RATIO= 0.563

LAND TENURE

0 NP NATIONAL PARK	1 CA CONSERVATION AREA	2 SF STATE FOREST
3 FH FREE-HOLD	4 CL CROWN LAND	5 OT OTHER

PLANNING AUTHORITY LAND USE

1 QP QUARRYING PERMITTED	2 QN QUARRYING NOT PERMITTED	3 QD QUARRYING DISCRETIONARY
--------------------------	------------------------------	------------------------------

RESERVES

0 NOT NOT DETERMINED	1 NIL <1 000	2 SML 1 000-10 000
3 MED 10 000-1 000 000	4 LGE 1 000 000-1 000 000 000	5 VST >1 000 000 000

OPERATIONAL STATUS

0 FOP FULLY OPERATIONAL	1 OCC OCCASIONAL	2 ABN ABANDONED
3 NEW NEW AREA		

COLOUR

0 LT LIGHT	1 DK DARK	2 WH WHITE
3 BK BLACK	4 GR GREY	5 YL YELLOW
6 BR BROWN	7 RD RED	8 MO MOTTLED

GENERIC ENVIRONMENT

0 IN IGNEOUS INTRUSIVE	1 VO IGNEOUS VOLCANIC	2 SE SEDIMENTARY
3 ME METAMORPHIC	4 DU DURICRUST	5 RE RESIDUAL
6 CO COLLUVIAL	7 AL ALLUVIAL	8 DN DUNE
9 BC BEACH	A OS OFFSHORE	B FS FURNACE SLAG
C MW MINE WASTE	D FA FLY ASH	

EXTRACTABILITY

0 BH BACKHOE	1 EX EXCAVATOR	2 DZ BULLDOZER (D9)
3 BL BLASTING		

GEOPHYSICS

0 EM ELECTROMAGNETICS	1 GR GRAVITY	2 SV SEISMIC VELOCITY
3 MG MAGNETICS	4 RE RESISTIVITY	

DRILLING

0 AU AUGER	1 CH CHURN	2 DI DIAMOND
3 PC PERCUSSION	4 RO ROTARY	5 TP TEST PIT

TESTING

GS GRAIN SIZE ANALYSIS	AL ATTERBERG LIMITS	SP STRENGTH PROPERTIES
PE PETROLOGY	CA CHEMICAL ANALYSIS	XR X-RAY DIFFRACTION
CR CERAMIC	OT OTHER	

LABORATORY

0 DOM DEPARTMENT OF MINES	1 DMR DEPARTMENT OF MAIN ROADS	2 HEC HYDRO-ELECTRIC COMMISSION
---------------------------	--------------------------------	---------------------------------

USE

A CA	CRUSHED AGGREGATE	B RS	ROAD SUB-BASE	C RB	ROAD BASE COURSE
D RA	ROAD ADMIXTURE	E RW	ROAD WEARING (SEALED)	F RU	ROAD UNSEALED
G RH	ROAD HOTMIX SAND	H CC	CONCRETE COARSE AGGREGATE	I CF	CONCRETE FINE AGGREGATE
J CP	CONCRETE PIPE	K CB	CONCRETE BLOCK	L CT	CONCRETE TILE
M LW	LIGHT WEIGHT AGGREGATE	N SM	SAND MORTAR	O SF	SAND FILTRATION
P SN	SAND FOUNDRY	Q SG	SAND GLASS	R SB	SAND BRICK
S SD	SAND BEDDING	T BC	BRICK CLAY	U EC	EARTHENWARE CLAY
V PC	PORCELAIN CLAY	W FC	FILTER CLAY	X BS	BUILDING STONE
Y HM	HEAVY MINERAL	Z SI	SILICA		

QUALITY

0 M	MARGINAL	1 S	SATISFACTORY	2 E	EXCELLENT
-----	----------	-----	--------------	-----	-----------

TESTING STANDARD

0 BS	BRITISH STANDARD	1 AS	AUSTRALIAN STANDARD	2 RA	NAASRA
3 AM	ASTM	4 OT	OTHER		

APPENDIX 3
Sample output, Option 3

SEARCH OPTIONS ARE:
 QUADRANGLE 83/
 OCCUPIER SORELL/DMR/
 GRAIN SIZE ANALYSIS MUST HAVE BEEN DONE
 GRAIN SIZE ANALYSES TO BE PRINTED

58-11

TASMANIAN CONSTRUCTION MATERIALS REGISTER

REFNO	CO-ORDS	LOCALITY	OCCUPIER	IM LEASE	LAND	TE	US	RES	OPS	COL	EX	USCS	USES	TESTS			
														QU	GP	DR	LA
83001	544252639	PENNA	SORELL COUNCIL		CL	SML	ABN			DZ	GW-GC	RS,RU,		S	N	N	Y
83003	544352657	SORELL	DMR		CL	MED	ABN			DZ	GC	RS,		M	N	N	Y
83005	556652548	CARLTON	SORELL COUNCIL		FH	MED	OCC			DZ	GW-GC	RS,RB,RU,		S	N	N	Y
83013	555552656	WATTLE HILL	DMR		CL	MED	OCC			DZ	GW-SC	RS,RW,		M	N	N	Y

LAND TENURE

0 NP NATIONAL PARK	1 CA CONSERVATION AREA	2 SF STATE FOREST
3 FH FREE-HOLD	4 CL CROWN LAND	5 OT OTHER

PLANNING AUTHORITY LAND USE

1 QP QUARRYING PERMITTED	2 QN QUARRYING NOT PERMITTED	3 QD QUARRYING DISCRETIONARY
--------------------------	------------------------------	------------------------------

RESERVES

0 NOT NOT DETERMINED	1 NIL <1 000	2 SML 1 000-10 000
3 MED 10 000-1 000 000	4 LGE 1 000 000-1 000 000 000	5 VST >1 000 000 000

OPERATIONAL STATUS

0 FOP FULLY OPERATIONAL	1 OCC OCCASIONAL	2 ABN ABANDONED
3 NEW NEW AREA		

COLOUR

0 LT LIGHT	1 DK DARK	2 WH WHITE
3 BK BLACK	4 GR GREY	5 YL YELLOW
6 BR BROWN	7 RD RED	8 MD MOTTLED

GENERIC ENVIRONMENT

0 IN IGNEOUS INTRUSIVE	1 VO IGNEOUS VOLCANIC	2 SE SEDIMENTARY
3 ME METAMORPHIC	4 DU DURICRUST	5 RE RESIDUAL
6 CO COLLUVIAL	7 AL ALLUVIAL	8 DN DUNE
9 BC BEACH	A OS OFFSHORE	B FS FURNACE SLAG
C MW MINE WASTE	D FA FLY ASH	

EXTRACTABILITY

0 BH BACKHOE	1 EX EXCAVATOR	2 DZ BULLDOZER (D9)
3 BL BLASTING		

GEOPHYSICS

0 EM ELECTROMAGNETICS	1 GR GRAVITY	2 SV SEISMIC VELOCITY
3 MG MAGNETICS	4 RE RESISTIVITY	

DRILLING

0 AU AUGER	1 CH CHURN	2 DI DIAMOND
3 PC PERCUSSION	4 RO ROTARY	5 TP TEST PIT

TESTING

GS GRAIN SIZE ANALYSIS	AL ATTERBERG LIMITS	SP STRENGTH PROPERTIES
PE PETROLOGY	CA CHEMICAL ANALYSIS	XR X-RAY DIFFRACTION
CR CERAMIC	OT OTHER	

LABORATORY

0 DOM DEPARTMENT OF MINES	1 DMR DEPARTMENT OF MAIN ROADS	2 HEC HYDRO-ELECTRIC COMMISSION
---------------------------	--------------------------------	---------------------------------

USE

A CA	CRUSHED AGGREGATE	B RS	ROAD SUB-BASE	C RB	ROAD BASE COURSE
D RA	ROAD ADMIXTURE	E RW	ROAD WEARING (SEALED)	F RU	ROAD UNSEALED
G RH	ROAD HOTMIX SAND	H CC	CONCRETE COARSE AGGREGATE	I CF	CONCRETE FINE AGGREGATE
J CP	CONCRETE PIPE	K CB	CONCRETE BLOCK	L CT	CONCRETE TILE
M LW	LIGHT WEIGHT AGGREGATE	N SM	SAND MORTAR	O SF	SAND FILTRATION
P SN	SAND FOUNDRY	Q SG	SAND GLASS	R SB	SAND BRICK
S SD	SAND BEDDING	T BC	BRICK CLAY	U EC	EARTHENWARE CLAY
V FC	PORCELAIN CLAY	W FC	FILTER CLAY	X BS	BUILDING STONE
Y HM	HEAVY MINERAL	Z SI	SILICA		

QUALITY

0 M	MARGINAL	1 S	SATISFACTORY	2 E	EXCELLENT
-----	----------	-----	--------------	-----	-----------

TESTING STANDARD

0 BS	BRITISH STANDARD	1 AS	AUSTRALIAN STANDARD	2 RA	NAASRA
3 AM	ASTM	4 OT	OTHER		

Program CONADD

```

#TITL CONADD.FTN - ADD CONSTRUCTION MATERIALS TO REGISTER
  INTEGER*2 IBELL, ANNUAL, TOTAL
  CHARACTER*1 TENURE, LANDUSE, RESERVE, STATUS, EXTRACT, TEST, GRAIN,
  .   ATTBG, STRONG, PETROL, CHEM, XRD, CERAM, OTHERTEST, LAB,
  .   QUALITY, STANDARD
  CHARACTER*2 COLOUR, GENERIC, GEOPHYS, DRILL
  CHARACTER*3 AGE
  CHARACTER*5 REFNO, SHEET, CLASS
  CHARACTER*6 USE
  CHARACTER*7 LEASE, YEAR
  CHARACTER*8 UNIT, MAPREF
  CHARACTER*10 ROCK
  CHARACTER*12 LOCAL, REPORT
  CHARACTER*20 OCCUPY
  LOGICAL UNPRINT
  DATA IBELL/1792/

C
C INPUT IS REF NO, MAP SHEET, CO-ORDINATES, OCCUPIER, LEASE, LOCALITY,
C   LAND TENURE, LAND USE, REPORT, PRODUCTION ANNUAL,
C   PRODUCTION TOTAL, RESERVES, OPERATIONAL STATUS, ROCK NAME,
C   ROCK UNIT, AGE, COLOUR, GENERIC ENVIRONMENT, EXTRACTABILITY,
C   DATA COLLECTOR, YEAR, TEST TYPES, UNIFIED SOIL CLASSIFICATION
C   SYMBOL, USE, QUALITY, STANDARD FOR TESTING
C
      OPEN (UNIT=5, FILE='CON:')
C OPEN THE CONSOLE
C
      20 WRITE(5,100)
      100 FORMAT(' REF NO (TYPE END TO FINISH)')
      READ(5,200) REFNO
      200 FORMAT(A5)
      IF (REFNO .EQ. 'END ') GOTO 50
C END OF INPUT SO CLOSE FILES
      DO 21 I=1,5
      IF (REFNO(I:I) .GT. '9' .OR. REFNO(I:I) .LT. '0') THEN
      WRITE(5,101) IBELL
      101 FORMAT(1X,A1,' REF NO MUST HAVE FIVE NUMERIC CHARACTERS')
      GOTO 20
      ENDIF
C REFNO IS OF FORM 01001 OR 75023
      21 CONTINUE
      CALL ALPHA5(SHEET, 'MAP SHEET')
      22 CALL ALPHA8(MAPREF, 'CO-ORDINATES')
C NOW CHECK FOR VALID MAPREF
      IF (MAPREF(1:1) .LT. 'B' .OR. MAPREF(1:1) .GT. 'F') THEN
C MUST HAVE EAST OF B,C,D,E,F
      WRITE(5,104) IBELL
      104 FORMAT(1X,A1,' COORDINATES INCORRECT - FORM IS E0123456')
      GOTO 22
      ENDIF
      IF (MAPREF(2:2) .LT. 'M' .OR. MAPREF(2:2) .GT. 'S'
      .   .OR. MAPREF(2:2) .EQ. '0') THEN
C MUST HAVE NORTH OF M,N,P,Q,R,S
      WRITE(5,104)
      GOTO 22
      ENDIF

```

```

C CHECK FOR VALID MAP COORDINATES
C
C END OF MAP COORDS
  CALL ALPHA20(OCCUPY,'OCCUPIER')
  CALL ALPHA7(LEASE,'LEASE')
  CALL ALPHA12(LOCAL,'LOCALITY')
  CALL NUMB1(TENURE,'TENURE','0','5')
  CALL NUMB1(LANDUSE,'LAND USE','1','3')
  CALL ALPHA12(REPORT,'REPORT')
C
C NOW FIELD DATA
  WRITE(5,110)
110 FORMAT(' ANNUAL PRODUCTION - MUST NOT BE BLANK')
  READ(5,*) ANNUAL
  WRITE(5,111)
111 FORMAT(' TOTAL PRODUCTION - MUST NOT BE BLANK')
  READ(5,*) TOTAL
  CALL NUMB1(RESERVE,'RESERVES','0','5')
  CALL NUMB1(STATUS,'STATUS','0','3')
  CALL ALPHA10(ROCK,'ROCK NAME')
  CALL ALPHAS(UNIT,'ROCK UNIT')
  CALL ALPHA3(AGE,'AGE')
  CALL NUMB2(COLOUR,'COLOUR','0','8')
  CALL NUMB2(GENERIC,'GEN ENVIRONMENT','0','9')
  CALL NUMB1(EXTRACT,'EXTRACTABILITY','0','3')
 23 WRITE(5,120)
120 FORMAT(' COLLECTED • YEAR')
  READ(5,203) YEAR
203 FORMAT(A7)
  IF (UNPRINT(YEAR,7)) THEN
  WRITE(5,121) IBELL
121 FORMAT(1X,A1,' KEYING ERROR - REENTER COLLECTED • YEAR')
  GOTO 23
  ENDIF
C NOW CHECK FOR 4 FIGURE YEAR IN 1800,1900 OR 2000 SERIES
  K=7
  DO 30 I=1,7
  IF (ICHAR(YEAR(K:K)) .LE. ICHAR('9') .AND.
  . ICHAR(YEAR(K:K)) .GE. ICHAR('0')) GOTO 31
C FOUND THE LAST NUMERIC CHARACTER
  K=K-1
 30 CONTINUE
  I=10
C IF FALL THROUGH HAVENT FOUND NUMERIC CHARACTERS
 31 IF (I .NE. 10) THEN
  ITMP=CTOI(YEAR(K-3:K),J)
C GET THE FOUR DIGIT YEAR
  ELSE
  ITMP=0
  ENDIF
  IF (ITMP .LT. 1800 .OR. ITMP .GT. 2000) THEN
  WRITE(5,121) IBELL
  GOTO 23
  ENDIF
  WRITE(5,122)
122 FORMAT(' IF THERE IS NO TEST DATA TYPE N HERE')
  READ(5,205) TEST
205 FORMAT(A1)
  IF (TEST .EQ. 'N') THEN
  GEOPHYS=' '

```

```

DRILL=' '
GRAIN=' '
ATTBG=' '
STRONG=' '
PETROL=' '
CHEM=' '
XRD=' '
CERAM=' '
OTHERTEST=' '
LAB=' '
ELSE
CALL NUMB2(GEOPHYS, 'GEOPHYSICS', '0', '4')
CALL NUMB2(DRILL, 'DRILLING', '0', '5')
CALL ALPHA1(GRAIN, 'GRAIN SIZE ANAL')
CALL ALPHA1(ATTBG, 'ATTERBERG LIMIT')
CALL ALPHA1(STRONG, 'STRENGTH PROP')
CALL ALPHA1(PETROL, 'PETROLOGY')
CALL ALPHA1(CHEM, 'CHEMICAL ANAL')
CALL ALPHA1(XRD, 'X-RAY')
CALL ALPHA1(CERAM, 'CERAMIC')
CALL ALPHA1(OTHERTEST, 'OTHER TEST')
CALL NUMB1(LAB, 'LABORATORY', '0', '3')
ENDIF
CALL ALPHA5(CLASS, 'SOIL CLASSIFICATION')
CALL NUMB6(USE, 'USE', 'A', 'Z')
CALL NUMB1(QUALITY, 'QUALITY', '0', '2')
CALL NUMB1(STANDARD, 'STANDARD', '0', '4')
C READ ALL INPUT DATA
C
C NOW OUTPUT TO PROOF SHEET
WRITE(6, 400) REFNO, SHEET, MAPREF, OCCUPY, LEASE, LOCAL, TENURE,
. LANDUSE, REPORT, ANNUAL, TOTAL, RESERVE, STATUS, ROCK,
. UNIT, AGE, COLOUR, GENERIC, EXTRACT, YEAR, GEOPHYS, DRILL,
. GRAIN, ATTBG, STRONG, PETROL, CHEM, XRD, CERAM, OTHERTEST,
. LAB, CLASS, USE, QUALITY, STANDARD
400 FORMAT(1X, 2(A5, '@'), A8, '@', A20, '@', A7, '@', A12, '@', A1, '@', A1/
. 6X, '@', A12, '@', 2(I4, '@'), 2(A1, '@'), A10, '@', A8, '@', A3, '@',
. 2(A2, '@'), A1/6X, '@', A7, '@', 2(A2, '@'), 9(A1, '@'), A5, '@',
. A6, '@', 2(A1, '@'))
C WRITE WITH DELIMITERS AFTER EACH FIELD AND REFNO ON ITS OWN
GOTO 20
C BACK ROUND
C
C OTHERWISE STOP
50 CLOSE(UNIT=6, STATUS='KEEP')
STOP
END

#INCLUDE ALPHA1.FTN
SUBROUTINE ALPHA1(SVAR, PROMPT)
CHARACTER * (*) PROMPT
CHARACTER *1 SVAR
LOGICAL UNPRINT
INTEGER*2 IBELL
DATA IBELL/1792/
WRITE(5, 100) PROMPT
100 FORMAT(1X, C20)
10 READ(5, 101) SVAR
101 FORMAT(A1)
IF (.NOT. UNPRINT(SVAR, 1)) RETURN

```

```

C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
  WRITE(5,102) IBELL,PROMPT
  102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
  GOTO 10
  END

```

```

$INCLUDE ALPHA3.FTN
  SUBROUTINE ALPHA3(SVAR,PROMPT)
  CHARACTER * (*) PROMPT
  CHARACTER *3 SVAR
  LOGICAL UNPRINT
  INTEGER*2 IBELL
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
  100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
  101 FORMAT(A3)
  IF (.NOT. UNPRINT(SVAR,3)) RETURN

```

```

C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
  WRITE(5,102) IBELL,PROMPT
  102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
  GOTO 10
  END

```

```

$INCLUDE ALPHA5.FTN
  SUBROUTINE ALPHA5(SVAR,PROMPT)
  CHARACTER * (*) PROMPT
  CHARACTER *5 SVAR
  LOGICAL UNPRINT
  INTEGER*2 IBELL
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
  100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
  101 FORMAT(A5)
  IF (.NOT. UNPRINT(SVAR,5)) RETURN

```

```

C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
  WRITE(5,102) IBELL,PROMPT
  102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
  GOTO 10
  END

```

```

$INCLUDE ALPHA7.FTN
  SUBROUTINE ALPHA7(SVAR,PROMPT)
  CHARACTER * (*) PROMPT
  CHARACTER *7 SVAR
  LOGICAL UNPRINT
  INTEGER*2 IBELL
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
  100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
  101 FORMAT(A7)
  IF (.NOT. UNPRINT(SVAR,7)) RETURN

```

```

C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
  WRITE(5,102) IBELL,PROMPT
  102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
  GOTO 10
  END

```

```

$INCLUDE ALPHA8.FTN
  SUBROUTINE ALPHA8(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *8 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A8)
    IF (.NOT. UNPRINT(SVAR,8)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
  END

```

```

$INCLUDE ALPHA10.FTN
  SUBROUTINE ALPHA10(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *10 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A10)
    IF (.NOT. UNPRINT(SVAR,10)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
  END

```

```

$INCLUDE ALPHA12.FTN
  SUBROUTINE ALPHA12(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *12 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A12)
    IF (.NOT. UNPRINT(SVAR,12)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
  END

```

```

$INCLUDE ALPHA20.FTN
  SUBROUTINE ALPHA20(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *20 SVAR
    LOGICAL UNPRINT

```

```

    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A20)
    IF (.NOT. UNPRINT(SVAR,20)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
    END

$INCLUDE NUMB1.FTN
    SUBROUTINE NUMB1(SVAR,PROMPT,LOW,UP)
    CHARACTER *(*) PROMPT
    CHARACTER*1 SVAR
    CHARACTER*1 UP,LOW
    INTEGER*2 IBELL
    LOGICAL UNPRINT
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A1)
    IF (UNPRINT(SVAR,1)) THEN
        WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
        GOTO 10
    ENDIF
    IF (SVAR .EQ. ' ' .OR.
        . (SVAR .GE. LOW .AND. SVAR .LE. UP)) GOTO 11
C VALID CHARACTER
    WRITE(5,102) IBELL,PROMPT
    GOTO 10
11 CONTINUE
    RETURN
    END

$INCLUDE CONNUMB2.FTN
    SUBROUTINE NUMB2(SVAR,PROMPT,LOW,UP)
    CHARACTER *(*) PROMPT
    CHARACTER*2 SVAR
    CHARACTER*1 UP,LOW
    INTEGER*2 IBELL
    LOGICAL UNPRINT
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A2)
    IF (UNPRINT(SVAR,2)) THEN
        WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
        GOTO 10
    ENDIF
    IF (PROMPT .NE. 'GEN ENVIRONMENT') THEN
        DO 11 I=1,2
            IF (SVAR(I:I) .EQ. ' ' .OR.
                . (SVAR(I:I) .GE. LOW .AND. SVAR(I:I) .LE. UP)) GOTO 11

```

```

C VALID CHARACTER
  WRITE(5,102) IBELL,PROMPT
  GOTO 10
11 CONTINUE
  ELSE
  DO 12 I=1,2
  IF(SVAR(I:I) .EQ. ' ' .OR.
    . ((SVAR(I:I) .GE. '0' .AND. SVAR(I:I) .LE. '9') .OR.
    . (SVAR(I:I) .GE. 'A' .AND. SVAR(I:I) .LE. 'D')) GOTO 12

```

```

C VALID CHARACTER FOR GENERIC ENVIRONMENT
  WRITE(5,102) IBELL,PROMPT
  GOTO 10
12 CONTINUE
  ENDIF
  RETURN
  END

```

```

$INCLUDE NUMB6.FTN
  SUBROUTINE NUMB6(SVAR,PROMPT,LOW,UP)
  CHARACTER *(*) PROMPT
  CHARACTER*6 SVAR
  CHARACTER*1 UP,LOW
  INTEGER*2 IBELL
  LOGICAL UNPRINT
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
101 FORMAT(A6)
  IF (UNPRINT(SVAR,6)) THEN
  WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
  GOTO 10
  ENDIF
  DO 11 I=1,6
  IF (SVAR(I:I) .EQ. ' ' .OR.
    . (SVAR(I:I) .GE. LOW .AND. SVAR(I:I) .LE. UP)) GOTO 11

```

```

C VALID CHARACTER
  WRITE(5,102) IBELL,PROMPT
  GOTO 10
11 CONTINUE
  RETURN
  END

```

```

$INCLUDE UNPRINT.FTN
  LOGICAL FUNCTION UNPRINT(SVAR,NCHAR)
  CHARACTER* (*) SVAR
  DO 10 I=1,NCHAR
  IF (SVAR(I:I) .LT. ' ') THEN
  UNPRINT=.TRUE.
  RETURN
  ENDIF
10 CONTINUE
  UNPRINT=.FALSE.
  RETURN
  END

```

Program CONMERGE

```

$TITL CONMERGE.FTN - MERGE CONSTRUCTION MATERIALS INTO REGISTER
CHARACTER*4 MREFE,MREFN
CHARACTER*7 YEAR
CHARACTER*8 MAPREF
INTEGER*2 ANNUAL,TOTAL,IYEAR,EAST
INTEGER*4 NORTH
CHARACTER*1 TENURE, LANDUSE, RESERVE, STATUS, EXTRACT, TEST, GRAIN,
.   ATTBG, STRONG, PETROL, CHEM, XRD, CERAM, OTHERTEST, LAB,
.   QUALITY, STANDARD
CHARACTER*2 COLOUR, GENERIC, GEOPHYS, DRILL
CHARACTER*3 AGE, COLLECT
CHARACTER*5 REFNO, SHEET, CLASS
CHARACTER*6 USE
CHARACTER*7 LEASE
CHARACTER*8 UNIT
CHARACTER*10 ROCK
CHARACTER*12 LOCAL, REPORT
CHARACTER*20 OCCUPY
C
CHARACTER*1 BUFF(132)
C BUFFER ARRAY TO ALLOW BINARY WRITE
EQUIVALENCE (BUFF(1), OCCUPY), (BUFF(21), LOCAL), (BUFF(33), REPORT),
.   (BUFF(45), ROCK), (BUFF(55), UNIT), (BUFF(63), LEASE),
.   (BUFF(70), USE), (BUFF(76), REFNO), (BUFF(81), SHEET),
.   (BUFF(86), CLASS), (BUFF(91), NORTH), (BUFF(95), AGE),
.   (BUFF(98), COLLECT), (BUFF(101), COLOUR),
.   (BUFF(103), GENERIC), (BUFF(105), GEOPHYS),
.   (BUFF(107), DRILL), (BUFF(109), ANNUAL), (BUFF(111), TOTAL),
.   (BUFF(113), IYEAR), (BUFF(115), EAST), (BUFF(117), TENURE),
.   (BUFF(118), LANDUSE), (BUFF(119), RESERVE), (BUFF(120), STATUS),
.   (BUFF(121), EXTRACT),
.   (BUFF(122), GRAIN), (BUFF(123), ATTBG), (BUFF(124), STRONG),
.   (BUFF(125), PETROL), (BUFF(126), CHEM), (BUFF(127), XRD),
.   (BUFF(128), CERAM), (BUFF(129), OTHERTEST), (BUFF(130), LAB),
.   (BUFF(131), QUALITY), (BUFF(132), STANDARD)
C USED FOR BINARY OUTPUT FOR FASTER ACCESS
C
OPEN(UNIT=4, FORM='BINARY', RECL=132)
C OPEN THE OUTPUT FILE FOR BINARY OPERATIONS
10 READ(6, 400, END=20) REFNO, SHEET, MAPREF, OCCUPY, LEASE, LOCAL, TENURE,
.   LANDUSE, REPORT, ANNUAL, TOTAL, RESERVE, STATUS, ROCK,
.   UNIT, AGE, COLOUR, GENERIC, EXTRACT, YEAR, GEOPHYS, DRILL,
.   GRAIN, ATTBG, STRONG, PETROL, CHEM, XRD, CERAM, OTHERTEST,
.   LAB, CLASS, USE, QUALITY, STANDARD
400 FORMAT(1X, 2(A5, 1X), A8, 1X, A20, 1X, A7, 1X, A12, 1X, A1, 1X, A1/
.   6X, 1X, A12, 1X, 2(I4, 1X), 2(A1, 1X), A10, 1X, A8, 1X, A3, 1X,
.   2(A2, 1X), A1/6X, 1X, A7, 1X, 2(A2, 1X), 9(A1, 1X), A5, 1X,
.   A6, 1X, 2(A1, 1X))
C READ BACK IN IN SAME FORMAT
C
C NOW RETRIEVE AMG COORDINATES, THE YEAR AND THE COLLECTOR
C THEN PUT THE APPROPRIATE VALUES IN THE YES/NO TEST BOXES
C
ITMP=ICHAR(MAPREF(1:1))
MREFE(1:1)=CHAR(ITMP-16)
ITMP=ICHAR(MAPREF(2:2))

```

```

      IF (ITMP .GT. 78) ITMP=ITMP-1
      MREFN(1:1)=CHAR(ITMP-28)
      MREFE(2:4)=MAPREF(3:5)
      MREFN(2:4)=MAPREF(6:8)
      EAST=CTOI(MREFE,J)
      NORTH=CTOI(MREFN,J)
      NORTH=NORTH+50000
C ABOVE CODE FROM GRID2.FTN GRID CONVERSION PROGRAM BY E.L. MARTIN
C NOW HAVE EAST AND NORTH SEPARATELY
C
C NOW FOR YEAR AND COLLECTOR
      K=7
      DO 25 I=1,7
        IF (YEAR(K:K) .LE. '9' .AND. YEAR(K:K) .GE. '0') GOTO 26
C FOUND THE LAST NUMERIC CHARACTER
      K=K-1
      25 CONTINUE
      26 IYEAR=CTOI(YEAR(K-3:K),J)
C CONVERT TO INTEGER
C
      COLLECT=' '
C FILL THE COLLECTOR WITH BLANKS
      IF (K .GT. 4) COLLECT(1:K-4)=YEAR(1:K-4)
C COPY THE COLLECTOR
C
C NOW FOR ALL THE TESTS
      IF (GRAIN .NE. ' ') GRAIN='1'
      IF (ATTBG .NE. ' ') ATTBG='1'
      IF (STRONG .NE. ' ') STRONG='1'
      IF (PETROL .NE. ' ') PETROL='1'
      IF (CHEM .NE. ' ') CHEM='1'
      IF (XRD .NE. ' ') XRD='1'
      IF (CERAM .NE. ' ') CERAM='1'
      IF (OTHERTEST .NE. ' ') OTHERTEST='1'
C THE TESTS ARE SET TO 1 IF CONDUCTED
C
C NOW WRITE OUT
      WRITE(4) BUFF
C BINARY WRITE TO OUTPUT FILE
      GOTO 10
C BACK ROUND
C
C AT END
      20 CLOSE(UNIT=4,STATUS='KEEP')
      CLOSE(UNIT=6,STATUS='KEEP')
      END

```

APPENDIX 6

Program CONSORT

```
*TITL CONSORT.FTN - SORT THE CONSTRUCTION MATERIAL REGISTER
```

```

C
  INTEGER*2 INDEX(8000), IQUAD(98), LQUAD, JQUAD
  INTEGER*4 IA(8000)
  INTEGER*2 ANNUAL, TOTAL, IYEAR, EAST
  INTEGER*4 NORTH
  CHARACTER*1 TENURE, LANDUSE, RESERVE, STATUS, EXTRACT, TEST, GRAIN,
  .   ATTBG, STRONG, PETROL, CHEM, XRD, CERAM, OTHERTEST, LAB,
  .   QUALITY, STANDARD
  CHARACTER*2 COLOUR, GENERIC, GEOPHYS, DRILL
  CHARACTER*3 AGE, COLLECT
  CHARACTER*5 REFNO, SHEET, CLASS
  CHARACTER*6 USE
  CHARACTER*7 LEASE
  CHARACTER*8 UNIT
  CHARACTER*10 ROCK
  CHARACTER*12 LOCAL, REPORT
  CHARACTER*20 OCCUPY

C
  CHARACTER*1 BUFF(132)
C BUFFER ARRAY TO ALLOW BINARY WRITE
  EQUIVALENCE (BUFF(1), OCCUPY), (BUFF(21), LOCAL), (BUFF(33), REPORT),
  .   (BUFF(45), ROCK), (BUFF(55), UNIT), (BUFF(63), LEASE),
  .   (BUFF(70), USE), (BUFF(76), REFNO), (BUFF(81), SHEET),
  .   (BUFF(86), CLASS), (BUFF(91), NORTH), (BUFF(95), AGE),
  .   (BUFF(98), COLLECT), (BUFF(101), COLOUR),
  .   (BUFF(103), GENERIC), (BUFF(105), GEOPHYS),
  .   (BUFF(107), DRILL), (BUFF(109), ANNUAL), (BUFF(111), TOTAL),
  .   (BUFF(113), IYEAR), (BUFF(115), EAST), (BUFF(117), TENURE),
  .   (BUFF(118), LANDUSE), (BUFF(119), RESERVE), (BUFF(120), STATUS),
  .   (BUFF(121), EXTRACT),
  .   (BUFF(122), GRAIN), (BUFF(123), ATTBG), (BUFF(124), STRONG),
  .   (BUFF(125), PETROL), (BUFF(126), CHEM), (BUFF(127), XRD),
  .   (BUFF(128), CERAM), (BUFF(129), OTHERTEST), (BUFF(130), LAB),
  .   (BUFF(131), QUALITY), (BUFF(132), STANDARD)

C USED FOR BINARY OUTPUT FOR FASTER ACCESS
C
  OPEN(UNIT=4, FORM='BINARY', ACCESS='DIRECT', RECL=132)
C OPEN THE INPUT FILE FOR BINARY, RANDOM AND SEQUENTIAL OPERATIONS
  REWIND 4
  DO 8 I=1,98
    IQUAD(I)=0
  8 CONTINUE
C FILL THE INDEX FOR THE STARTING RECORD OF EACH QUADRANGLE WITH 0
  LQUAD=0
C USED TO REMEMBER THE LAST QUADRANGLE
  IREC=0
C COUNTER FOR NUMBER OF RECORDS
  10 READ(4,END=20) BUFF
    IREC=IREC+1
    IF (IREC .GT. 8000) STOP 'MORE THAN 8000 ENTRIES'
    INDEX(IREC)=IREC
C FILL SORT INDEX
  IA(IREC)=CTOI(REFNO, I)
C CONVERT REFNO TO INTEGER AND STORE IN IA
  GOTO 10

```

24/5A

```

C BACK ROUND
C
C NOW FOR THE WORK
  20 CONTINUE
    IF (IREC .EQ. 0) STOP 'NO RECORDS'
    CALL BUBSTI4(INDEX, IA, 1, IREC)
C SORT INTO ASCENDING NUMBER - I.E. REFNO ORDER
  OPEN(UNIT=6, FORM='BINARY', RECL=132)
C OPEN OUTPUT FILE
  DO 30 I=1, IREC
    READ(4, REC=INDEX(I)) BUFF
    WRITE(6) BUFF
C COPY TO NEW ORDER
C
C NOW CHECK TO SEE IF IT WAS THE START OF A QUADRANGLE
  JQUAD=CTOI(REFNO(1:2), K)
C THE QUADRANGLE PART OF THE REFERENCE NO
  IF (JQUAD .GT. LQUAD) THEN
C HAVE A NEW AND LARGER QUADRANGLE NUMBER
  LQUAD=JQUAD
C SAVE AS THE NEW LAST QUAD NO
  IQUAD(JQUAD)=I
C NOW SAVE THE RECORD NUMBER
  ENDIF
  30 CONTINUE
    CLOSE(UNIT=6, STATUS='KEEP')
    CLOSE(UNIT=4, STATUS='KEEP')
    OPEN(UNIT=6, FILE='CONQUAD.IND', FORM='BINARY', RECL=2)
    DO 35 I=1, 98
C NOT 98 QUADS BUT FOR SIMPLICITY USE NUMBERS THAT DONT EXIST AS WELL
    WRITE(6) IQUAD(I)
  35 CONTINUE
C THE INDEX IS WRITTEN TO A BINARY FILE
  END

```

```

SUBROUTINE BUBSTI4(IR, IA, IBASE, N)
  INTEGER*4 IA(N)
  INTEGER*2 IR(N)
  LOGICAL NSWAP
  IF (N .LE. 1) RETURN

```

```

C NOTHING TO SORT
  NM1=N-1
  DO 30 J=IBASE, NM1
    NSWAP=.TRUE.
    IRI=IR(1)
    DO 40 I=IBASE, NM1
      IP1=I+1
      IRIP1=IR(IP1)
      IF (IA(IRI) .LE. IA(IRIP1)) GOTO 40
      NSWAP=.FALSE.
      IR(I)=IRIP1
      IR(IP1)=IRI
      IRIP1=IRI
  40 IRI=IRIP1
  IF (NSWAP) RETURN
  30 CONTINUE
  RETURN
END

```

Program CONCHGE

\$TITL CONCHGE.FTN - CHANGE DETAILS IN THE CONSTRUCTION MATERIALS REGISTER
C

INTEGER*2 IQUAD(98), IRECNO, IBELL

C THE ARRAY TO STORE THE STARTING RECORD FOR EACH QUADRANGLE AND THE
C COUNTER FOR THE ENTRY NUMBER TO BE REPLACED IN THE UPDATE

LOGICAL CHGE, CHANGE

INTEGER*2 ANNUAL, TOTAL, IYEAR, EAST

INTEGER*4 NORTH

CHARACTER*1 TENURE, LANDUSE, RESERVE, STATUS, EXTRACT, TEST, GRAIN,

. ATTBG, STRONG, PETROL, CHEM, %RD, CERAM, OTHERTEST, LAB,

. QUALITY, STANDARD

CHARACTER*2 COLOUR, GENERIC, GEOPHYS, DRILL

CHARACTER*3 AGE, COLLECT

CHARACTER*4 MREFE, MREFN

CHARACTER*5 REFNO, SHEET, CLASS, REFNO1

CHARACTER*6 USE

CHARACTER*7 LEASE

CHARACTER*8 UNIT, MAPREF

CHARACTER*10 ROCK

CHARACTER*12 LOCAL, REPORT

CHARACTER*20 OCCUPY

C

CHARACTER*1 BUFF(132), BUFF2(134)

C BUFFER ARRAY TO ALLOW BINARY WRITE

EQUIVALENCE (BUFF(1), OCCUPY), (BUFF(21), LOCAL), (BUFF(33), REPORT),

. (BUFF(45), ROCK), (BUFF(55), UNIT), (BUFF(63), LEASE),

. (BUFF(70), USE), (BUFF(76), REFNO), (BUFF(81), SHEET),

. (BUFF(86), CLASS), (BUFF(91), NORTH), (BUFF(95), AGE),

. (BUFF(98), COLLECT), (BUFF(101), COLOUR),

. (BUFF(103), GENERIC), (BUFF(105), GEOPHYS),

. (BUFF(107), DRILL), (BUFF(109), ANNUAL), (BUFF(111), TOTAL),

. (BUFF(113), IYEAR), (BUFF(115), EAST), (BUFF(117), TENURE),

. (BUFF(118), LANDUSE), (BUFF(119), RESERVE), (BUFF(120), STATUS),

. (BUFF(121), EXTRACT),

. (BUFF(122), GRAIN), (BUFF(123), ATTBG), (BUFF(124), STRONG),

. (BUFF(125), PETROL), (BUFF(126), CHEM), (BUFF(127), %RD),

. (BUFF(128), CERAM), (BUFF(129), OTHERTEST), (BUFF(130), LAB),

. (BUFF(131), QUALITY), (BUFF(132), STANDARD)

C USED FOR BINARY OUTPUT FOR FASTER ACCESS

EQUIVALENCE (BUFF2(1), IRECNO), (BUFF2(3), BUFF(1))

C USED TO ADD THE RECORD NUMBER TO THE ENTRIES TO BE UPDATED

DATA IBELL/1792/

C

OPEN(UNIT=4, FORM='BINARY', ACCESS='DIRECT', RECL=132)

C OPEN THE INPUT FILE FOR BINARY, RANDOM AND SEQUENTIAL OPERATIONS

REWIND 4

OPEN(UNIT=3, FILE='CONQUAD.IND', RECL=2, FORM='BINARY', SHARE='ERO')

C OPEN THE FILE WITH THE INDEX TO THE QUADRANGLES

DO 8 I=1, 98

READ(3) IQUAD(I)

8 CONTINUE

CLOSE(UNIT=3, STATUS='KEEP')

C READ THE STARTS OF THE QUADRANGLES AND CLOSE THE FILE

C

OPEN(UNIT=6, FORM='BINARY', RECL=134)

C OPEN THE FILE TO HOLD THE CHANGED RECORDS

```

CHGE=.FALSE.
C USED TO DECIDE WHEN THE OUTPUT LISTING NEEDS HEADING
  OPEN(UNIT=5,FILE='CON:')
C OPEN THE CONSOLE
  OPEN(UNIT=3,FILE='PR:')
C OPEN THE PRINTER FOR OUTPUT
  10 WRITE(5,100)
  100 FORMAT(' REF NO (TYPE END TO FINISH)')
  READ(5,200) REFNO1
  200 FORMAT(A5)
  IF (REFNO1 .EQ. 'END ') GOTO 50
C THE END OF THE CHANGES
  DO 11 I=1,5
  IF (REFNO1(I:I) .GT. '9' .OR. REFNO1(I:I) .LT. '0') THEN
  WRITE(5,101) IBELL
  101 FORMAT(1X,A1,' REF NO MUST HAVE FIVE NUMERIC CHARACTERS')
  GOTO 10
  ENDF
  11 CONTINUE
  IF (IQUAD(CTOI(REFNO1(1:2),K)) .EQ. 0) THEN
  12 WRITE(5,102) IBELL
  102 FORMAT(1X,A1,' REF NO NOT VALID')
  GOTO 10
  ENDF
C NOW READY TO START LOOKING FOR A REFNO1
C
  IBASE=IQUAD(CTOI(REFNO1(1:2),K))
C THE FIRST ENTRY HAVING THIS QUADRANGLE NUMBER
  IF (IBASE .NE. 1) THEN
C IF NOT THE FIRST RECORD
  READ(4,REC=IBASE-1) BUFF
C POSITION THE FILE ONE RECORD BEFORE THE FIRST RECORD OF THE QUADRANGLE
  ELSE
  REWIND 4
C IF IBASE IS THE FIRST RECORD REWIND THE FILE
  ENDF
C
C NOW SCAN THE FILE LOOKING FOR THE ENTRY
  13 READ(4,END=12) BUFF
C IF HIT END HAVE INVALID REF NO
  IF (REFNO .GT. REFNO1) GOTO 12
C REFNO'S ARE IN ASCENDING ORDER SO IF THE ONE ON FILE IS BIGGER
C HAVE INVALID REFNO
  IF (REFNO .LT. REFNO1) THEN
  IBASE=IBASE+1
  GOTO 13
C INCREMENT RECORD COUNTER AND BACK ROUND
  ENDF
C
C IF GET TO HERE HAVE FOUND A MATCHING REF NO
  WRITE(5,103) REFNO,SHEET,OCCUPY,LEASE
  103 FORMAT(1X,A5,2X,A5,2X,A20,2X,A7/' OK ?'/
  . ' TYPE Y IF THIS IS TO BE CHANGED')
  READ(5,201) AOK
  201 FORMAT(A1)
  IF (AOK .NE. 'Y') GOTO 10
C BACK FOR ANOTHER REF NO
C
C NOW OFFER THE CHANGES
  IF (CHANGE('MAP SHEET')) CALL ALPHA5(SHEET,'MAP SHEET')

```

```

      IF (CHANGE('COORDS')) THEN
14 CALL ALPHA8(MAPREF,'COORDS')
C NOW CHECK FOR VALID MAPREF
  IF (MAPREF(1:1) .LT. 'B' .OR. MAPREF(1:1) .GT. 'F') THEN
    WRITE(5,104) IBELL
104 FORMAT(1X,A1,' COORDINATES INCORRECT - FORM IS EQ123456')
    GOTO 14
  ENDIF
  IF (MAPREF(2:2) .LT. 'M' .OR. MAPREF(2:2) .GT. 'S'
    .OR. MAPREF(2:2) .EQ. '0') THEN
    WRITE(5,104)
    GOTO 14
  ENDIF
C CHECK FOR VALID MAP COORDINATES
  ENDIF
C END OF MAP COORDS
  IF (CHANGE('OCCUPIER')) CALL ALPHA20(OCCUPY,'OCCUPIER')
  IF (CHANGE('LEASE')) CALL ALPHA7(LEASE,'LEASE')
  IF (CHANGE('LOCALITY')) CALL ALPHA12(LOCAL,'LOCALITY')
  IF (CHANGE('TENURE')) CALL NUMB1(TENURE,'TENURE','0','5')
  IF (CHANGE('LAND USE')) CALL NUMB1(LANDUSE,'LAND USE','1','3')
  IF (CHANGE('REPORT')) CALL ALPHA12(REPORT,'REPORT')
  WRITE(5,105)
105 FORMAT(' TO ALTER THE FIELD DATA TYPE Y HERE')
  READ(5,201) AOK
  IF (AOK .EQ. 'Y') THEN
    IF (CHANGE('ANNUAL PRODUCTION')) CALL INT2(ANNUAL,
      'ANNUAL PRODUCTION')
    IF (CHANGE('TOTAL PRODUCTION')) CALL INT2(TOTAL,
      'TOTAL PRODUCTION')
    IF (CHANGE('RESERVES')) CALL NUMB1(RESERVE,'RESERVES','0','5')
    IF (CHANGE('STATUS')) CALL NUMB1(STATUS,'STATUS','0','3')
    IF (CHANGE('ROCK NAME')) CALL ALPHA10(ROCK,'ROCK NAME')
    IF (CHANGE('ROCK UNIT')) CALL ALPHA8(UNIT,'ROCK UNIT')
    IF (CHANGE('AGE')) CALL ALPHA3(AGE,'AGE')
    IF (CHANGE('COLOUR')) CALL NUMB2(COLOUR,'COLOUR','0','8')
    IF (CHANGE('GEN ENVIRONMENT')) CALL NUMB2(GENERIC,
      'GEN ENVIRONMENT','0','9')
    IF (CHANGE('EXTRACTIBILITY')) CALL NUMB1(EXTRACT,
      'EXTRACTIBILITY','0','3')
    IF (CHANGE('COLLECTOR')) CALL ALPHA3(COLLECT,'COLLECTOR')
    IF (CHANGE('YEAR')) CALL INT2(IYEAR,'YEAR')
  ENDIF
C END OF DEALING WITH FIELD DATA IF REQUIRED
C
C
C
  WRITE(5,106)
106 FORMAT(' TO CHANGE TEST DATA TYPE Y HERE')
  READ(5,201) AOK
  IF (AOK .EQ. 'Y') THEN
C CHANGE THE TEST DATA
  IF (CHANGE('GEOPHYSICS')) CALL NUMB2(GEOPHYS,'GEOPHYSICS',
    '0','4')
  IF (CHANGE('DRILLING')) CALL NUMB2(DRILL,'DRILLING','0','5')
  IF (CHANGE('GRAIN SIZE ANAL')) CALL ALPHA1(GRAIN,
    'GRAIN SIZE ANAL')
  IF (CHANGE('ATTERBERG LIM')) CALL ALPHA1(ATTBG,
    'ATTERBERG LIM')
  IF (CHANGE('STRENGTH PROP')) CALL ALPHA1(STRONG,

```

20/51

```

. 'STRENGTH PROP')
IF (CHANGE('PETROLOGY')) CALL ALPHA1(PETROL,'PETROLOGY')
IF (CHANGE('CHEMICAL ANAL')) CALL ALPHA1(CHEM,
. 'CHEMICAL ANAL')
IF (CHANGE('XRD')) CALL ALPHA1(XRD,'XRD')
IF (CHANGE('CERAMIC')) CALL ALPHA1(CERAM,'CERAMIC')
IF (CHANGE('OTHER')) CALL ALPHA1(OTHERTEST,
. 'OTHER')
IF (CHANGE('LABORATORY')) CALL NUMB1(LAB,'LABORATORY','0','3')
ENDIF
C END OF CHANGING TEST DETAILS
C
C
C
IF (CHANGE('SOIL CLASSIFICATION')) CALL ALPHA5(CLASS,
. 'SOIL CLASSIFICATION')
IF (CHANGE('USE')) CALL NUMB6(USE,'USE','A','Z')
IF (CHANGE('QUALITY')) CALL NUMB1(QUALITY,'QUALITY','0','2')
IF (CHANGE('STANDARD')) CALL NUMB1(STANDARD,'STANDARD',
. '0','4')
C
C END READING CHANGES
C
IRECNO=IBASE
C NOTE THE RECORD NUMBER
IF (.NOT. CHGE) THEN
WRITE (3,300)
300 FORMAT(' THE FOLLOWING CHANGES ARE BEING MADE'//)
CHGE=.TRUE.
ENDIF
C HEAD UP ONLY ON THE FIRST TIME
WRITE (3,301) REFNO,SHEET,MAPREF,OCCUPY,LEASE,LOCAL,TENURE,
. LANDUSE,REPORT,ANNUAL,TOTAL,RESERVE,STATUS,ROCK,
. UNIT,AGE,COLOUR,GENERIC,EXTRACT,COLLECT,IYEAR,GEOFYS,DRILL,
. GRAIN,ATTBG,STRONG,PETROL,CHEM,XRD,CERAM,OTHERTEST,
. LAB,CLASS,USE,QUALITY,STANDARD
301 FORMAT(1X,2(A5,'@'),A8,'@',A20,'@',A7,'@',A12,'@',A1,'@',A1/
. 6X,'@',A12,'@',2(I4,'@'),2(A1,'@'),A10,'@',A8,'@',A3,'@',
. 2(A2,'@'),A1/6X,'@',A3,I4,'@',2(A2,'@'),9(A1,'@'),A5,'@',
. A6,'@',2(A1,'@'))
C WRITE WITH DELIMITERS AFTER EACH FIELD AND REFNO ON ITS OWN
C
C NOW RETRIEVE AMG COORDINATES
C
ITMP=ICHAR(MAPREF(1:1))
MREFE(1:1)=CHAR(ITMP-16)
ITMP=ICHAR(MAPREF(2:2))
IF (ITMP.GT.78) ITMP=ITMP-1
MREFN(1:1)=CHAR(ITMP-28)
MREFE(2:4)=MAPREF(3:5)
MREFN(2:4)=MAPREF(6:8)
EAST=CTOI(MREFE,J)
NORTH=CTOI(MREFN,J)
NORTH=NORTH+50000
C ABOVE CODE FROM GRID2.FTN GRID CONVERSION PROGRAM BY E.L. MARTIN
C NOW HAVE EAST AND NORTH SEPARATELY
C
WRITE(6) BUFF2
C WRITE OUT TO THE FILE TO HOLD THE UPDATES
GOTO 10

```

C BACK ROUND AGAIN
C
C
C

50 CONTINUE
CLOSE(UNIT=4,STATUS='KEEP')
CLOSE(UNIT=6,STATUS='KEEP')
WRITE(3,302)
302 FORMAT(1X//)

C CLOSE ALL FILES ETC UP
END

LOGICAL FUNCTION CHANGE(STRING)
CHARACTER* (*) STRING
WRITE(5,100) STRING
100 FORMAT(' TO CHANGE ',C20/' TYPE Y HERE')
READ(5,102) AOK
102 FORMAT(A1)
CHANGE=AOK .EQ. 'Y'
RETURN
END

#INCLUDE ALPHA1.FTN
SUBROUTINE ALPHA1(SVAR,PROMPT)
CHARACTER * (*) PROMPT
CHARACTER *1 SVAR
LOGICAL UNPRINT
INTEGER*2 IBELL
DATA IBELL/1792/
WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
10 READ(5,101) SVAR
101 FORMAT(A1)
IF (.NOT. UNPRINT(SVAR,1)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
GOTO 10
END

#INCLUDE ALPHA3.FTN
SUBROUTINE ALPHA3(SVAR,PROMPT)
CHARACTER * (*) PROMPT
CHARACTER *3 SVAR
LOGICAL UNPRINT
INTEGER*2 IBELL
DATA IBELL/1792/
WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
10 READ(5,101) SVAR
101 FORMAT(A3)
IF (.NOT. UNPRINT(SVAR,3)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
GOTO 10
END

```

$INCLUDE ALPHAS.FTN
  SUBROUTINE ALPHAS(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *5 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
    10  READ(5,101) SVAR
101  FORMAT(A5)
    IF (.NOT. UNPRINT(SVAR,5)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102  FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
    END

```

```

$INCLUDE ALPHA7.FTN
  SUBROUTINE ALPHA7(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *7 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
    10  READ(5,101) SVAR
101  FORMAT(A7)
    IF (.NOT. UNPRINT(SVAR,7)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102  FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
    END

```

```

$INCLUDE ALPHAS.FTN
  SUBROUTINE ALPHAS(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *8 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
    10  READ(5,101) SVAR
101  FORMAT(A8)
    IF (.NOT. UNPRINT(SVAR,8)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102  FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
    END

```

```

$INCLUDE ALPHA10.FTN
  SUBROUTINE ALPHA10(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *10 SVAR
    LOGICAL UNPRINT

```

```

      INTEGER*2 IBELL
      DATA IBELL/1792/
      WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
      10  READ(5,101) SVAR
101  FORMAT(A10)
      IF (.NOT. UNPRINT(SVAR,10)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
      WRITE(5,102) IBELL,PROMPT
102  FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
      GOTO 10
      END

```

```

$INCLUDE ALPHA12.FTN
      SUBROUTINE ALPHA12(SVAR,PROMPT)
      CHARACTER * (*) PROMPT
      CHARACTER *12 SVAR
      LOGICAL UNPRINT
      INTEGER*2 IBELL
      DATA IBELL/1792/
      WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
      10  READ(5,101) SVAR
101  FORMAT(A12)
      IF (.NOT. UNPRINT(SVAR,12)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
      WRITE(5,102) IBELL,PROMPT
102  FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
      GOTO 10
      END

```

```

$INCLUDE ALPHA20.FTN
      SUBROUTINE ALPHA20(SVAR,PROMPT)
      CHARACTER * (*) PROMPT
      CHARACTER *20 SVAR
      LOGICAL UNPRINT
      INTEGER*2 IBELL
      DATA IBELL/1792/
      WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
      10  READ(5,101) SVAR
101  FORMAT(A20)
      IF (.NOT. UNPRINT(SVAR,20)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
      WRITE(5,102) IBELL,PROMPT
102  FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
      GOTO 10
      END

```

```

$INCLUDE INT2.FTN
      SUBROUTINE INT2(IVAR,PROMPT)
      CHARACTER * (*) PROMPT
      INTEGER*2 IVAR
      WRITE(5,100) PROMPT
100  FORMAT(1X,C20)
      READ(5,*) IVAR
      RETURN
      END

```

```

$INCLUDE NUMB1.FTN
  SUBROUTINE NUMB1(SVAR,PROMPT,LOW,UP)
  CHARACTER *(*) PROMPT
  CHARACTER*1 SVAR
  CHARACTER*1 UP,LOW
  INTEGER*2 IBELL
  LOGICAL UNPRINT
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
101 FORMAT(A1)
  IF (UNPRINT(SVAR,1)) THEN
  WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
  GOTO 10
  ENDIF
  IF (SVAR .EQ. ' ' .OR.
  . (SVAR .GE. LOW .AND. SVAR .LE. UP)) GOTO 11
C VALID CHARACTER
  WRITE(5,102) IBELL,PROMPT
  GOTO 10
  11 CONTINUE
  RETURN
  END

```

```

$INCLUDE CONNUMB2.FTN
  SUBROUTINE NUMB2(SVAR,PROMPT,LOW,UP)
  CHARACTER *(*) PROMPT
  CHARACTER*2 SVAR
  CHARACTER*1 UP,LOW
  INTEGER*2 IBELL
  LOGICAL UNPRINT
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
101 FORMAT(A2)
  IF (UNPRINT(SVAR,2)) THEN
  WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
  GOTO 10
  ENDIF
  IF (PROMPT .NE. 'GEN ENVIRONMENT') THEN
  DO 11 I=1,2
  IF (SVAR(I:I) .EQ. ' ' .OR.
  . (SVAR(I:I) .GE. LOW .AND. SVAR(I:I) .LE. UP)) GOTO 11
C VALID CHARACTER
  WRITE(5,102) IBELL,PROMPT
  GOTO 10
  11 CONTINUE
  ELSE
  DO 12 I=1,2
  IF (SVAR(I:I) .EQ. ' ' .OR.
  . ((SVAR(I:I) .GE. '0' .AND. SVAR(I:I) .LE. '9') .OR.
  . (SVAR(I:I) .GE. 'A' .AND. SVAR(I:I) .LE. 'D')))) GOTO 12
C VALID CHARACTER FOR GENERIC ENVIRONMENT
  WRITE(5,102) IBELL,PROMPT
  GOTO 10

```

```

12 CONTINUE
   ENDIF
   RETURN
   END

```

```

$INCLUDE NUMB6.FTN
  SUBROUTINE NUMB6(SVAR,PROMPT,LOW,UP)
  CHARACTER*(*) PROMPT
  CHARACTER*6 SVAR
  CHARACTER*1 UP,LOW
  INTEGER*2 IBELL
  LOGICAL UNPRINT
  DATA IBELL/1792/
  WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
  10 READ(5,101) SVAR
101 FORMAT(A6)
  IF (UNPRINT(SVAR,6)) THEN
  WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
  GOTO 10
  ENDIF
  DO 11 I=1,6
  IF (SVAR(I:I) .EQ. ' ' .OR.
  . (SVAR(I:I) .GE. LOW .AND. SVAR(I:I) .LE. UP)) GOTO 11
C VALID CHARACTER
  WRITE(5,102) IBELL,PROMPT
  GOTO 10
  11 CONTINUE
  RETURN
  END

```

```

$INCLUDE UNPRINT.FTN
  LOGICAL FUNCTION UNPRINT(SVAR,NCHAR)
  CHARACTER*(*) SVAR
  DO 10 I=1,NCHAR
  IF (SVAR(I:I) .LT. ' ') THEN
  UNPRINT=.TRUE.
  RETURN
  ENDIF
  10 CONTINUE
  UNPRINT=.FALSE.
  RETURN
  END

```

```

$TITL CONCHGE2.FTN - PUT CHANGES INTO CONMAT REGISTER MAIN FILE
C
  INTEGER*2 IRECNO
C THE COUNTER FOR THE ENTRY NUMBER TO BE REPLACED IN THE UPDATE
  INTEGER*2 ANNUAL,TOTAL,IYEAR,EAST
  INTEGER*4 NORTH
  CHARACTER*1 TENURE,LANDUSE,RESERVE,STATUS,EXTRACT,TEST,GRAIN,
  . ATTBG,STRONG,PETROL,CHEM,XRD,CERAM,OTHERTEST,LAB,
  . QUALITY,STANDARD
  CHARACTER*2 COLOUR,GENERIC,GEOPHYS,DRILL
  CHARACTER*3 AGE,COLLECT
  CHARACTER*5 REFNO,SHEET,CLASS,REFNO1
  CHARACTER*6 USE
  CHARACTER*7 LEASE
  CHARACTER*8 UNIT

```

CHARACTER*10 ROCK
CHARACTER*12 LOCAL,REPORT
CHARACTER*20 OCCUPY

C CHARACTER*1 BUFF(132),BUFF2(134)
C BUFFER ARRAY TO ALLOW BINARY WRITE
EQUIVALENCE (BUFF(1),OCCUPY),(BUFF(21),LOCAL),(BUFF(33),REPORT),
. (BUFF(45),ROCK),(BUFF(55),UNIT),(BUFF(63),LEASE),
. (BUFF(70),USE),(BUFF(76),REFNO),(BUFF(81),SHEET),
. (BUFF(86),CLASS),(BUFF(91),NORTH),(BUFF(95),AGE),
. (BUFF(98),COLLECT),(BUFF(101),COLOUR),
. (BUFF(103),GENERIC),(BUFF(105),GEOPHYS),
. (BUFF(107),DRILL),(BUFF(109),ANNUAL),(BUFF(111),TOTAL),
. (BUFF(113),IYEAR),(BUFF(115),EAST),(BUFF(117),TENURE),
. (BUFF(118),LANDUSE),(BUFF(119),RESERVE),(BUFF(120),STATUS),
. (BUFF(121),EXTRACT),
. (BUFF(122),GRAIN),(BUFF(123),ATTBG),(BUFF(124),STRONG),
. (BUFF(125),PETROL),(BUFF(126),CHEM),(BUFF(127),%RD),
. (BUFF(128),CERAM),(BUFF(129),OTHERTEST),(BUFF(130),LAB),
. (BUFF(131),QUALITY),(BUFF(132),STANDARD)

C USED FOR BINARY OUTPUT FOR FASTER ACCESS
EQUIVALENCE (BUFF2(1),IRECNO),(BUFF2(3),BUFF(1))
C USED TO ADD THE RECORD NUMBER TO THE ENTRIES TO BE UPDATED
C

OPEN(UNIT=4,FORM='BINARY',SHARE='ERO',RECL=132)
C OPEN THE INPUT FILE FOR BINARY SEQUENTIAL OPERATIONS
C

OPEN(UNIT=3,FORM='BINARY',RECL=134)
REWIND 3

C OPEN THE UPDATE FILE AND REWIND IT
OPEN(UNIT=6,FORM='BINARY',ACCESS='DIRECT',RECL=132)
C OPEN THE OUTPUT FILE FOR SEQUENTIAL AND DIRECT BINARY
C

C COPY MAIN FILE TO OUTPUT FILE
10 READ(4,END=11) BUFF
WRITE(6) BUFF
GOTO 10

C COPY ONE RECORD AT A TIME TO THE END
C
11 CONTINUE

C
CLOSE(UNIT=4,STATUS='KEEP')

C NOW UPDATE THE COPY OF THE MAIN FILE ON LU 6 FROM LU 3
C

20 READ(3,END=21) BUFF2
WRITE(6,REC=IRECNO) BUFF
GOTO 20

C BACK ROUND
C

21 CONTINUE

C AT THE END
CLOSE(UNIT=3,STATUS='KEEP')
CLOSE(UNIT=6,STATUS='KEEP')
END

Program CONSRCH

```

$TITL CONSRCH.FTN - SEARCH THE CONSTRUCTION MATERIAL REGISTER
INTEGER*2 ANNUAL,TOTAL,IYEAR,EAST
INTEGER*4 NORTH,FCOUNT
CHARACTER*1 TENURE,LANDUSE,RESERVE,STATUS,EXTRACT,TEST,GRAIN,
.   ATTBG,STRONG,PETROL,CHEM,XRD,CERAM,OTHERTEST,LAB,
.   QUALITY,STANDARD
CHARACTER*2 COLOUR,GENERIC,GEOPHYS,DRILL
CHARACTER*3 AGE,COLLECT
CHARACTER*5 REFNO,SHEET,CLASS
CHARACTER*6 USE
CHARACTER*7 LEASE
CHARACTER*8 UNIT
CHARACTER*10 ROCK
CHARACTER*12 LOCAL,REPORT
CHARACTER*20 OCCUPY

C
CHARACTER*1 BUFF(132)
C BUFFER ARRAY TO ALLOW BINARY WRITE
EQUIVALENCE (BUFF(1),OCCUPY),(BUFF(21),LOCAL),(BUFF(33),REPORT),
.   (BUFF(45),ROCK),(BUFF(55),UNIT),(BUFF(63),LEASE),
.   (BUFF(70),USE),(BUFF(76),REFNO),(BUFF(81),SHEET),
.   (BUFF(86),CLASS),(BUFF(91),NORTH),(BUFF(95),AGE),
.   (BUFF(98),COLLECT),(BUFF(101),COLOUR),
.   (BUFF(103),GENERIC),(BUFF(105),GEOPHYS),
.   (BUFF(107),DRILL),(BUFF(109),ANNUAL),(BUFF(111),TOTAL),
.   (BUFF(113),IYEAR),(BUFF(115),EAST),(BUFF(117),TENURE),
.   (BUFF(118),LANDUSE),(BUFF(119),RESERVE),(BUFF(120),STATUS),
.   (BUFF(121),EXTRACT),
.   (BUFF(122),GRAIN),(BUFF(123),ATTBG),(BUFF(124),STRONG),
.   (BUFF(125),PETROL),(BUFF(126),CHEM),(BUFF(127),XRD),
.   (BUFF(128),CERAM),(BUFF(129),OTHERTEST),(BUFF(130),LAB),
.   (BUFF(131),QUALITY),(BUFF(132),STANDARD)
C USED FOR BINARY OUTPUT FOR FASTER ACCESS
C
REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
INTEGER*2 SWATH(100,25)
C ABOVE 2 LINES USED FOR FSTJDN POINT IN POLYGON SEARCH
C
LOGICAL NOTIN,INOUT,SEMIN
CHARACTER*1 ITYPE,SFIELD,STEST,SGRAIN,GRANAL,SATTBG,SSTRONG,
.   SPETROL,SCHEM,SXRD,SCERAM,SOOTHERTEST
INTEGER*2 BANNUAL,EANNUAL,BTOTAL,ETOTAL,BYEAR,EYEAR,FFEED
CHARACTER*4 SANNUAL,FANNUAL,STOTAL,FTOTAL,SYEAR,FYEAR
CHARACTER*80 SQUAD,SMAP,SOCCUPY,SLEASE,SLOCN,STEN,SLANDUSE,
.   SRESERVE,SSTATUS,SROCK,SUNIT,SAGE,SCOLOUR,SGENERIC,SLAB,
.   SEXTRACT,SCOLLECT,SGEOPHYS,SDRILL,SUSE,SQUALITY,SSTANDARD,
.   SCLASS
C THE ABOVE ARE USED TO READ SEARCH OPTIONS INTO
CHARACTER*1 ARSRCH,AUSE,NG,ND,NT,APRINT
CHARACTER*1 NQUAL,MNQUAL(3)
CHARACTER*2 NTEN,MNTEN(6),NLUSE,MNLUSE(3),NCOL1,NCOL2,MNCOL(9),
.   NEXTRACT,MNEXTRACT(4),NUSE(6),MNUSE(26),NGEN1,NGEN2,MNGEN(14),
.   NGP1,NGP2,MNGP(5),NDRILL1,NDRILL2,MNDRILL(6),
.   NSTD,MNSTD(5),NTEST(8)
CHARACTER*3 NRES,MNRES(6),NSTAT,MNSTAT(4),NLAB,MNLAB(4)
CHARACTER*5 GSRCH(4000)

```

34/5A

```

DATA MN TEN/'NP', 'CA', 'SF', 'FH', 'CL', 'OT' /
DATA MN LUSE/'QP', 'QN', 'QD' /
DATA MN RES/'NOT', 'NIL', 'SML', 'MED', 'LGE', 'VST' /
DATA MN STAT/'FOP', 'OCC', 'ABN', 'NEW' /
DATA MN COL/'LT', 'DK', 'WH', 'BK', 'GR', 'YL', 'BR', 'RD', 'MO' /
DATA MN EXTRACT/'BH', 'EX', 'DZ', 'BL' /
DATA MN USE/'CA', 'RS', 'RB', 'RA', 'RW', 'RU', 'RH', 'CC', 'CF',
. 'CP', 'CB', 'CT', 'LW', 'SM', 'SF', 'SN', 'SG', 'SB', 'SD', 'BD',
. 'EC', 'PC', 'FC', 'BS', 'HM', 'SI' /
DATA MN QUAL/'M', 'S', 'E' /
DATA MN GEN/'IN', 'VO', 'SE', 'ME', 'DU', 'RE', 'CO', 'AL', 'DN',
. 'BC', 'OS', 'FS', 'MW', 'FA' /
DATA MN GF/'EM', 'GR', 'SV', 'MG', 'RE' /
DATA MN DRILL/'AU', 'CH', 'DI', 'PC', 'RO', 'TP' /
DATA MN LAB/'DOM', 'DMR', 'HEC', 'OTH' /
DATA MN STD/'BS', 'AS', 'RA', 'AM', 'OT' /

```

C THE ABOVE ARE USED IN THE EXPANSION OF NUMERIC CODES TO
C MNEMONICS
C
C
C

```
DATA FFEED/3072/
```

```

C THE FORM FEED CHARACTER
OPEN(UNIT=4,FORM='BINARY',RECL=132)
C OPEN THE INPUT FILE FOR BINARY SEQUENTIAL OPERATIONS
REWIND 4
WRITE(5,100)
100 FORMAT(' SEARCHING CONSTRUCTION MATERIAL REGISTER')
C NOW FOR A FULL SEARCH
WRITE(6,300)
300 FORMAT(' SEARCH OPTIONS ARE:')
WRITE(5,101)
101 FORMAT(' FOR EACH OPTION ENTER EITHER A BLANK LINE OR'/
. ' THE DESIRED VALUES FOR THE OPTION, EACH TERMINATED BY'
. ', ' A //' ' E.G. FRED/BILL/TOM/SMITH/')
WRITE(5,102)
102 FORMAT(' QUADRANGLE?')
READ(5,201) SQUAD
201 FORMAT(A80)
IF (SQUAD(1:1) .NE. ' ') WRITE(6,301) SQUAD
301 FORMAT(' QUADRANGLE',10X,A80)
WRITE(5,103)
103 FORMAT(' MAP SHEET?')
READ(5,201) SMAP
IF (SMAP(1:1) .NE. ' ') WRITE(6,302) SMAP
302 FORMAT(' MAP SHEET',10X,A80)
WRITE(5,104)
104 FORMAT(' SEARCH FOR SITES WITHIN A SPECIFIED AREA (Y)?')
READ(5,202) ITYPE
202 FORMAT(A1)
IF (ITYPE .EQ. 'Y') GOTO 10
C WANT TO READ COORDS
NCOORD=0
GOTO 12
C DONT WANT TO SEARCH FOR SITES IN AN AREA
C
10 CONTINUE
C READ VERTICES
WRITE(5,105)
105 FORMAT(' NUMBER OF VERTICES OF AREA?') /

```

```

. ' ENTER 2 TO SPECIFY A RECTANGLE' )
  READ(5,*) NCOORD
  IF (NCOORD .LT. 2) GOTO 10
C NEED AT LEAST 3 VERTICES TO DEFINE AN AREA
  IF (NCOORD .EQ. 2) THEN
    WRITE(5,106)
  106 FORMAT(' ENTER COORDS OF TWO DIAGONALLY OPPOSITE CORNERS OF ',
. ' THE RECTANGLE'/' ONE PER LINE IN THE FORM EASTNORTH' )
  ELSE
    WRITE(5,107)
  107 FORMAT(' ENTER VERTEX COORDS IN CLOCKWISE ORDER' /
. ' ONE PER LINE IN FORM EASTNORTH' )
  ENDIF
  IXMAX=-999999999
  IXMIN=-IXMAX
  IYMAX=IXMAX
  IYMIN=IXMIN
C USE THESE TO STORE THE RANGE OF THE AREA
  DO 11 I=1,NCOORD
    READ(5,203) IX,IY
  203 FORMAT(I4,I5)
C GET INTO 100'S OF METRES EAST AND NORTH
  IXMAX=MAX0(IX,IXMAX)
  IXMIN=MIN0(IX,IXMIN)
  IYMAX=MAX0(IY,IYMAX)
  IYMIN=MIN0(IY,IYMIN)
C FIND THE RANGE
  X(I)=IX*0.1
  Y(I)=IY*0.1
C CONVERT TO KM BEFORE STORING
  11 CONTINUE
  IF (NCOORD .GT. 2) THEN
    IF (X(1) .NE. X(NCOORD) .OR. Y(1) .NE. Y(NCOORD)) THEN
      NCOORD=NCOORD+1
      X(NCOORD)=X(1)
      Y(NCOORD)=Y(1)
C CLOSE AREA
    ENDIF
    WRITE(6,303)
  303 FORMAT(' AREA COORDINATES (KM)')
    WRITE(6,304) (X(I),Y(I),I=1,NCOORD)
  304 FORMAT(20X,4(F14.2,F9.2))
    NCOORD=NCOORD-1
C ROUTINE FOR LOCATING POINTS DOESNT REQUIRE CLOSURE
  CALL PREPLY(X,Y,NCOORD,YINTVL,INTVLS,SWATH,RSLOPE)
C CUT THE SEARCH AREA UP INTO SWATHS
  ELSE
    WRITE(6,305) IXMIN,IXMAX,IYMIN,IYMAX
  305 FORMAT(' SEARCH RECTANGLE FROM',I5,'00ME TO',I5,'00ME AND FROM',
. I6,'00MN TO',I6,'00MN')
  ENDIF
C
  12 CONTINUE
  WRITE(5,108)
  108 FORMAT(' OCCUPIER?')
  READ(5,201) SOCCUPY
  IF (SOCCUPY(1:1) .NE. ' ') WRITE (6,306) SOCCUPY
  306 FORMAT(' OCCUPIER',10X,A80)
  WRITE(5,109)
  109 FORMAT(' MINERAL LEASE (USE ; TO SEPARATE OPTIONS HERE)?')

```

```

READ(5,201) SLEASE
IF (SLEASE(1:1) .NE. ' ') WRITE(6,307) SLEASE
307 FORMAT(' MINERAL LEASE',10%,A80)
WRITE(5,110)
110 FORMAT(' LOCALITY?')
READ(5,201) SLOCN
IF (SLOCN(1:1) .NE. ' ') WRITE (6,308) SLOCN
308 FORMAT(' LOCALITY',10%,A80)
WRITE(5,111)
111 FORMAT(' LAND TENURE (0-5)?')
READ(5,201) STEN
IF (STEN(1:1) .NE. ' ') WRITE(6,309) STEN
309 FORMAT(' LAND TENURE',10%,A80)
WRITE(5,112)
112 FORMAT(' LAND USE (1-3)?')
READ(5,201) SLANDUSE
IF (SLANDUSE(1:1) .NE. ' ') WRITE(6,310) SLANDUSE
310 FORMAT(' LAND USE',10%,A80)
WRITE(5,113)
113 FORMAT(' TO SEARCH THE FIELD DATA TYPE Y HERE')
READ(5,202) SFIELD

```

C
C

```

IF (SFIELD .NE. ' ') THEN
C SKIP ROUND FIELD DATA IF NOT NEEDED
WRITE(5,114)
114 FORMAT(' RANGE OF ANNUAL PRODUCTION' /
. ' ENTER START OF RANGE')
READ(5,204) SANNUAL
204 FORMAT(A4)
IF (SANNUAL .NE. ' ') THEN
WRITE(5,115)
115 FORMAT(' ENTER END OF RANGE')
READ(5,204) FANNUAL
WRITE(6,311) SANNUAL,FANNUAL
311 FORMAT(' LOOKING FOR ANNUAL PRODUCTION BETWEEN ',A4,' AND ',
. A4)
BANNUAL=CTOI(SANNUAL,K)
EANNUAL=CTOI(FANNUAL,K)
ENDIF
WRITE(5,116)
116 FORMAT(' RANGE OF TOTAL PRODUCTION' /
. ' ENTER START OF RANGE')
READ(5,204) STOTAL
IF (STOTAL .NE. ' ') THEN
WRITE(5,117)
117 FORMAT(' ENTER END OF RANGE')
READ(5,204) FTOTAL
WRITE(6,312) STOTAL,FTOTAL
312 FORMAT(' LOOKING FOR TOTAL PRODUCTION BETWEEN ',A4,' AND ',
. A4)
BTOTAL=CTOI(STOTAL,K)
ETOTAL=CTOI(FTOTAL,K)
ENDIF
WRITE(5,118)
118 FORMAT(' RESERVES (0-5)?')
READ(5,201) SRESERVE
IF (SRESERVE(1:1) .NE. ' ') WRITE (6,313) SRESERVE
313 FORMAT(' RESERVES',10%,A80)
WRITE(5,119)

```

```

119 FORMAT(' OPERATIONAL STATUS (0-3)?')
    READ(5,201) SSTATUS
    IF (SSTATUS(1:1) .NE. ' ') WRITE (6,314) SSTATUS
314 FORMAT(' OPERATIONAL STATUS',10%,A80)
    WRITE(5,120)
120 FORMAT(' ROCK NAME?')
    READ(5,201) SROCK
    IF (SROCK(1:1) .NE. ' ') WRITE (6,315) SROCK
315 FORMAT(' ROCK NAME',10%,A80)
    WRITE(5,121)
121 FORMAT(' ROCK UNIT?')
    READ(5,201) SUNIT
    IF (SUNIT(1:1) .NE. ' ') WRITE (6,316) SUNIT
316 FORMAT(' ROCK UNIT',10%,A80)
    WRITE(5,122)
122 FORMAT(' AGE?')
    READ(5,201) SAGE
    IF (SAGE(1:1) .NE. ' ') WRITE (6,317) SAGE
317 FORMAT(' AGE',10%,A80)
    WRITE(5,123)
123 FORMAT(' COLOUR (0-9)?')
    READ(5,201) SCOLOUR
    IF (SCOLOUR(1:1) .NE. ' ') WRITE (6,318) SCOLOUR
318 FORMAT(' COLOUR',10%,A80)
    WRITE(5,124)
124 FORMAT(' GENERIC ENVIRONMENT (0-D)?')
    READ(5,201) SGENERIC
    IF (SGENERIC(1:1) .NE. ' ') WRITE (6,319) SGENERIC
319 FORMAT(' GENERIC ENVIRONMENT',10%,A80)
    WRITE(5,125)
125 FORMAT(' EXTRACTABILITY (0-3)?')
    READ(5,201) SEXTRACT
    IF (SEXTRACT(1:1) .NE. ' ') WRITE (6,320) SEXTRACT
320 FORMAT(' EXTRACTABILITY',10%,A80)
    WRITE(5,126)
126 FORMAT(' COLLECTOR?')
    READ(5,201) SCOLLECT
    IF (SCOLLECT(1:1) .NE. ' ') WRITE (6,321) SCOLLECT
321 FORMAT(' COLLECTOR',10%,A80)
    WRITE(5,127)
127 FORMAT(' RANGE OF YEARS FOR FIELD DATA COLLECTION' /
. ' ENTER START OF RANGE')
    READ(5,204) SYEAR
    IF (SYEAR .NE. ' ') THEN
        WRITE(5,128)
128 FORMAT(' ENTER END OF RANGE')
        READ(5,204) FYEAR
        WRITE(6,322) SYEAR,FYEAR
322 FORMAT(' LOOKING FOR FIELD DATA COLLECTED BETWEEN ',A4,' AND ',
. A4)
        BYEAR=CTOI(SYEAR,K)
        EYEAR=CTOI(FYEAR,K)
        ENDIF
        ENDIF
C END OF READING FIELD DATA IF REQUIRED
C
C
    WRITE(5,129)
129 FORMAT(' TO SEARCH ON TEST DATA TYPE Y HERE')
    READ(5,202) STEST

```

```

      IF (STEST .NE. ' ') THEN
C SKIP ROUND IF TEST DATA NOT TO BE SEARCHED ON
      WRITE(5,130)
130  FORMAT(' GEOPHYSICS (0-4)?')
      READ(5,201) SGEOPHYS
      IF(SGEOPHYS(1:1) .NE. ' ') WRITE(6,323) SGEOPHYS
323  FORMAT(' GEOPHYSICS',10%,A80)
      WRITE(5,131)
131  FORMAT(' DRILLING (0-5)?')
      READ(5,201) SDRILL
      IF(SDRILL(1:1) .NE. ' ') WRITE(6,324) SDRILL
324  FORMAT(' DRILLING',10%,A80)
      WRITE(5,132)
132  FORMAT(' TEST: GRAIN SIZE ANALYSIS')
      READ(5,202) SGRAIN
      WRITE(5,133)
133  FORMAT(' DO YOU WANT THE GRAIN SIZE ANALYSES PRINTED')
      READ(5,202) GRANAL
      IF (GRANAL .EQ. 'Y' .AND. SGRAIN .NE. 'Y') SGRAIN='Y'
      IF (SGRAIN .EQ. 'Y') WRITE(6,325)
325  FORMAT(' GRAIN SIZE ANALYSIS MUST HAVE BEEN DONE')
      IF (GRANAL .EQ. 'Y') WRITE(6,326)
326  FORMAT(' GRAIN SIZE ANALYSES TO BE PRINTED')
      WRITE(5,134)
134  FORMAT(' TEST: ATTERBERG LIMITS')
      READ(5,202) SATTBG
      IF (SATTBG .EQ. 'Y') WRITE(6,327)
327  FORMAT(' ATTERBERG LIMITS MUST HAVE BEEN DONE')
      WRITE(5,135)
135  FORMAT(' TEST: STRENGTH PROPERTIES')
      READ(5,202) SSTRONG
      IF (SSTRONG .EQ. 'Y') WRITE(6,328)
328  FORMAT(' STRENGTH PROPERTIES MUST HAVE BEEN DONE')
      WRITE(5,136)
136  FORMAT(' TEST: PETROLOGY')
      READ(5,202) SPETROL
      IF (SPETROL .EQ. 'Y') WRITE(6,329)
329  FORMAT(' PETROLOGY MUST HAVE BEEN DONE')
      WRITE(5,137)
137  FORMAT(' TEST: CHEMICAL ANALYSIS')
      READ(5,202) SCHEM
      IF (SCHEM .EQ. 'Y') WRITE(6,330)
330  FORMAT(' CHEMICAL ANALYSIS MUST HAVE BEEN DONE')
      WRITE(5,138)
138  FORMAT(' TEST: X-RAY DIFFRACTION')
      READ(5,202) SXRD
      IF (SXRD .EQ. 'Y') WRITE(6,331)
331  FORMAT(' X-RAY DIFFRACTION MUST HAVE BEEN DONE')
      WRITE(5,139)
139  FORMAT(' TEST: CERAMIC')
      READ(5,202) SCERAM
      IF (SCERAM .EQ. 'Y') WRITE(6,332)
332  FORMAT(' CERAMIC TESTING MUST HAVE BEEN DONE')
      WRITE(5,140)
140  FORMAT(' TEST: OTHER')
      READ(5,202) SOTHERTEST
      IF (SOTHERTEST .EQ. 'Y') WRITE(6,333)
333  FORMAT(' OTHER TESTS MUST HAVE BEEN DONE')
      WRITE(5,141)
141  FORMAT(' LABORATORY (0-3)?')

```

```

      READ(5,201) SLAB
      IF(SLAB(1:1) .NE. ' ') WRITE(6,334) SLAB
334  FORMAT(' LABORATORY',10X,A80)
      ENDIF
C END OF INPUTTING OPTIONS FOR SEARCHING TESTING
C
C
C
      WRITE(5,142)
142  FORMAT(' UNIFIED SOIL CLASSIFICATION?')
      READ(5,201) SCLASS
      IF (SCLASS(1:1) .NE. ' ') WRITE(6,335) SCLASS
335  FORMAT(' UNIFIED SOIL CLASSIFICATION',5X,A80)
      WRITE(5,143)
143  FORMAT(' USE (A-Z)?')
      READ(5,201) SUSE
      IF(SUSE(1:1) .NE. ' ') WRITE(6,336) SUSE
336  FORMAT(' USE',10X,A80)
      WRITE(5,144)
144  FORMAT(' QUALITY (0-2)?')
      READ(5,201) SQUALITY
      IF(SQUALITY(1:1) .NE. ' ') WRITE(6,337) SQUALITY
337  FORMAT(' QUALITY',10X,A80)
      WRITE(5,145)
145  FORMAT(' STANDARD (0-4)?')
      READ(5,201) SSTANDARD
      IF(SSTANDARD(1:1) .NE. ' ') WRITE(6,338) SSTANDARD
338  FORMAT(' STANDARD',10X,A80)
C END OF INPUTTING SEARCH OPTIONS
C
C
C
C NOW TO INPUT THE DISPLAY OPTIONS
      18 WRITE(5,146)
146  FORMAT(///// ' DISPLAY OPTIONS ARE :'/
.      ' 1      FULL LISTING TO PRINTER ONLY'/
.      ' 2      FULL LISTING TO SCREEN WITH OPTION OF PRINTING'/
.      ' 3      ABBREVIATED LISTING TO PRINTER ONLY'/
.      ' /// GRAIN SIZE ANALYSIS RESULTS ONLY APPEAR ON THE PRINTER'/
.      ' /// ENTER OPTION NUMBER')
      READ(5,*) IDISPLAY
      IF (IDISPLAY .LT. 1 .OR. IDISPLAY .GT. 3) GOTO 18
C END OF DISPLAY OPTIONS
C
C
C *****
C NOW FOR THE SEARCH
C
      FCOUNT=0
C COUNTER FOR NUMBER OF FOUND ENTRIES
      IANAL=0
C COUNTER FOR NUMBER OF REFNOs TO CHECK THE GRAIN SIZE ANALYSES OF
      ASRCH='Y'
C INDICATE THAT WANT TO CONTINUE SEARCHING
C
      20 READ(4,END=40) BUFF
C READ ONE ENTRY
      IF (SQUAD(1:1) .NE. ' ' .AND. INDEX (SQUAD,REFNO(1:2)) .EQ. 0)
.      GOTO 20
C NOT RIGHT QUADRANGLE

```

```

      IF (NOTIN(SMAP,SHEET)) GOTO 20
C NOT THE RIGHT SHEET
      IF (NCOORD .NE. 0) THEN
      IF (EAST .LT. IXMIN .OR. EAST .GT. IXMAX) GOTO 20
      IF (NORTH .LT. IYMIN .OR. NORTH .GT. IYMAX) GOTO 20
C CANT POSSIBLY BE IN AREA
      IF (NCOORD .GT. 2) THEN
      XTMP=EAST*0.1
      YTMP=NORTH*0.1
C CONVERT TO KM
      IF (.NOT. INOUT(XTMP,YTMP,X,Y,YINTVL,INTVLS,SWATH,RSLOPE))
      . GOTO 20
C NOT IN THE SPECIFIED AREA
      ENDIF
C FOR THE SIMPLE RECTANGLE DONT NEED THE POLYGON SEARCH
      ENDIF
      IF(NOTIN(SOCCUPY,OCCUPY)) GOTO 20
C NOT THE RIGHT OCCUPIER
      IF (SEMIN(SLEASE,LEASE)) GOTO 20
C NOT RIGHT LEASE
      IF(NOTIN(SLOCN,LOCAL)) GOTO 20
C NOT THE RIGHT LOCALITY
      IF (STEN(1:1) .NE. ' ' .AND. INDEX(STEN,TENURE) .EQ. 0) GOTO 20
C NOT THE RIGHT TENURE
      IF (SLANDUSE(1:1) .NE. ' ' .AND. INDEX(SLANDUSE,LANDUSE) .EQ. 0)
      . GOTO 20
C NOT THE RIGHT LANDUSE
C
      IF (SFIELD .NE. ' ') THEN
C SKIP ROUND SEARCHES ON FIELD DATA IF NOT NEEDED
      IF (SANNUAL .NE. ' ') THEN
      IF (ANNUAL .LT. BANNUAL .OR. ANNUAL .GT. EANNUAL) GOTO 20
C ANNUAL PRODUCTION FIGURES NOT IN RANGE
      ENDIF
      IF (STOTAL .NE. ' ') THEN
      IF (TOTAL .LT. BTOTAL .OR. TOTAL .GT. ETOTAL) GOTO 20
C TOTAL PRODUCTION FIGURES NOT IN RANGE SELECTED
      ENDIF
      IF (SRESERVE(1:1) .NE. ' ' .AND. INDEX(SRESERVE,RESERVE) .EQ. 0)
      . GOTO 20
C NOT THE RIGHT RESERVES
      IF (SSTATUS(1:1) .NE. ' ' .AND. INDEX(SSTATUS,STATUS) .EQ. 0)
      . GOTO 20
C NOT THE RIGHT STATUS
      IF (NOTIN(SROCK,ROCK)) GOTO 20
C NOT THE RIGHT ROCK NAME
      IF(NOTIN(SUNIT,UNIT)) GOTO 20
C NOT THE RIGHT UNIT
      IF(NOTIN(SAGE,AGE)) GOTO 20
C NOT THE RIGHT AGE
      IF(NOTIN(SCOLOUR,COLOUR)) GOTO 20
C NOT THE RIGHT COLOUR
      IF(NOTIN(SGENERIC,GENERIC)) GOTO 20
C NOT THE RIGHT GENERIC ENVIRONMENT
      IF (SEXTRACT(1:1) .NE. ' ' .AND. INDEX(SEXTRACT,EXTRACT) .EQ. 0)
      . GOTO 20
C NOT THE RIGHT EXTRACTIBILITY
      IF(NOTIN(SCOLLECT,COLLECT)) GOTO 20
C NOT THE RIGHT COLLECTOR
      IF (SYEAR .NE. ' ') THEN

```

```

      IF (IYEAR .LT. BYEAR .OR. IYEAR .GT. EYEAR) GOTO 20
C YEAR NOT IN THE RANGE SELECTED
      ENDIF
      ENDIF
C
C END OF SEARCHING FIELD DATA
C
C
      IF (STEST .NE. ' ') THEN
C ONLY SEARCH ON TESTS IF NEEDED
      IF (NOTIN(SGEOPHYS, GEOPHYS)) GOTO 20
C NOT THE RIGHT GEOPHYSICAL TESTING
      IF (NOTIN(SDRILL, DRILL)) GOTO 20
C NOT THE RIGHT DRILL TYPE
      IF (SGRAIN .EQ. 'Y' .AND. GRAIN .NE. '1') GOTO 20
C NO GRAIN SIZE ANALYSIS DONE
      IF (SATTBG .EQ. 'Y' .AND. ATTBG .NE. '1') GOTO 20
C NO ATTERBERG LIMITS TEST DONE
      IF (SSTRONG .EQ. 'Y' .AND. STRONG .NE. '1') GOTO 20
C NO STRENGTH TESTS DONE
      IF (SPETROL .EQ. 'Y' .AND. PETROL .NE. '1') GOTO 20
C NO PETROLOGY DONE
      IF (SCHEM .EQ. 'Y' .AND. SCHEM .NE. '1') GOTO 20
C NO GRAIN SIZE ANALYSIS DONE
      IF (SXRD .EQ. 'Y' .AND. XRD .NE. '1') GOTO 20
C NO X-RAY DIFFRACTION DONE
      IF (SCERAM .EQ. 'Y' .AND. CERAM .NE. '1') GOTO 20
C NO CERAMIC TESTS DONE
      IF (SOTHERTEST .EQ. 'Y' .AND. OTHERTEST .NE. '1') GOTO 20
C NO OTHER TESTS DONE
      IF (SLAB(1:1) .NE. ' ' .AND. INDEX(SLAB, LAB) .EQ. 0) GOTO 20
C NOT THE RIGHT LABORATORY
      ENDIF
C END OF SEARCHING FOR TESTING IF REQUIRED
C
C
C
      IF (NOTIN(SCLASS, CLASS)) GOTO 20
C NOT THE RIGHT UNIFIED SOIL CLASSIFICATION
      IF (NOTIN(SUSE, USE)) GOTO 20
C NOT THE RIGHT USE
      IF (SQUALITY(1:1) .NE. ' ' .AND. INDEX(SQUALITY, QUALITY) .EQ. 0)
      . GOTO 20
C NOT THE RIGHT QUALITY
      IF (SSTANDARD(1:1) .NE. ' ' .AND. INDEX(SSTANDARD, STANDARD) .EQ. 0)
      . GOTO 20
C NOT THE RIGHT STANDARD
C
C IF FINALLY GET HERE HAVE FOUND AN ENTRY THAT MATCHES THE SEARCH OPTIONS
C
C EXPAND THE MNEMONICS COMMON TO ALL THE OUTPUT OPTIONS
      CALL MNABREV(NTEN, TENURE, MNTEN)
      IF (LANDUSE .NE. ' ') LANDUSE=CHAR(ICHAR(LANDUSE)-1)
C LANDUSE HAS VALUES 1-3 AND MNABREV ASSUMES 0-2
      CALL MNABREV(NLUSE, LANDUSE, MNLUSE)
      CALL MNABREV(NRES, RESERVE, MNRES)
      CALL MNABREV(NSTAT, STATUS, MNSTAT)
      CALL MNABREV(NCOL1, COLOUR(1:1), MNCOL)
      CALL MNABREV(NCOL2, COLOUR(2:2), MNCOL)
      CALL MNABREV(NEXTRACT, EXTRACT, MNEXTRACT)

```

```

DO 25 I=1,6
IF (USE(I:I) .EQ. ' ') THEN
AUSE=' '
ELSE
AUSE=CHAR(ICHAR(USE(I:I))-17)
ENDIF
C USE IS FORM A-Z AND NEED 0-
CALL MNABREV(NUSE(I),AUSE,MNUSE)
25 CONTINUE
CALL MNABREV(NQUAL,QUALITY,MNQUAL)
C NOW EXPANDED MNEMONICS COMMON TO ALL THREE OUTPUT OPTIONS
C
C
IF (IDISPLAY .EQ. 3) THEN
C THE ABBREVIATED LISTING TO THE PRINTER
IF (MOD(FCOUNT,53) .EQ. 0) CALL HEAD3
C HEAD UP THE PAGE AS NEEDED
FCOUNT=FCOUNT+1
C INCREMENT FOUND ENTRY COUNTER
C WANT A SIMPLE YES/NO INDICATION OF GEOPHYSICAL, DRILLING AND
C OTHER TESTING
IF (GEOFYS .NE. ' ') THEN
NG='Y'
ELSE
NG='N'
ENDIF
IF (DRILL .NE. ' ') THEN
ND='Y'
ELSE
ND='N'
ENDIF
IF (GRAIN .NE. ' ' .OR. ATTBG .NE. ' ' .OR. STRONG .NE. ' '
. OR. PETROL .NE. ' ' .OR. CHEM .NE. ' ' .OR. XRD .NE. ' '
. OR. CERAM .NE. ' ' .OR. OTHERTEST .NE. ' ') THEN
NT='Y'
ELSE
NT='N'
ENDIF
C CHECKED FOR TESTS ETC
C
WRITE(6,400) REFNO,EAST,NORTH,LOCAL,OCCUPY,LEASE,NTEN,NLUSE,
. NRES,NSTAT,NCOL1,NCOL2,NEXTRACT,CLASS,NUSE,NQUAL,
. NG,ND,NT
400 FORMAT(1X,A5,' ',I4,I5,' ',A12,' ',A20,' ',A7,' ',2(A2,' '),
. 2(A3,' '),A2,' ',A2,' ',A5,' ',5(A2,' '),A2,' ',
. 4(1X,A1,' '))
C PRINT ONE LINE
GOTO 20
C BACK ROUND TO READ ANOTHER RECORD
ENDIF
C END OF ABBREVIATED PRINTING
C
C
C
C NOW TO EXPAND THE OTHER ABBREVIATIONS
IF (GENERIC(1:1) .GT. '9') GENERIC(1:1)=CHAR(ICHAR(GENERIC(1:1))-7)
IF (GENERIC(2:2) .GT. '9') GENERIC(2:2)=CHAR(ICHAR(GENERIC(2:2))-7)
C GENERIC ENVIRONMENT HAS VALUES 0-9,A-D
CALL MNABREV(NGEN1,GENERIC(1:1),MNGEN)
CALL MNABREV(NGEN2,GENERIC(2:2),MNGEN)

```

```

CALL MNABREV(NGP1,GEOPHYS(1:1),MNGP)
CALL MNABREV(NGP2,GEOPHYS(2:2),MNGP)
CALL MNABREV(NDRILL1,DRILL(1:1),MNDRILL)
CALL MNABREV(NDRILL2,DRILL(2:2),MNDRILL)
CALL MNABREV(NLAB,LAB,MNLAB)
CALL MNABREV(NSTD,STANDARD,MNSTD)
C NOW FOR THE TESTS WHICH WILL BE PUT INTO AN ARRAY AFTER EXPANSION
IF (GRAIN .EQ. '1') THEN
  NTEST(1)='GS'
ELSE
  NTEST(1)=' '
ENDIF
IF (ATTBG .EQ. '1') THEN
  NTEST(2)='AL'
ELSE
  NTEST(2)=' '
ENDIF
IF (STRONG .EQ. '1') THEN
  NTEST(3)='SP'
ELSE
  NTEST(3)=' '
ENDIF
IF (PETROL .EQ. '1') THEN
  NTEST(4)='PE'
ELSE
  NTEST(4)=' '
ENDIF
IF (CHEM .EQ. '1') THEN
  NTEST(5)='CA'
ELSE
  NTEST(5)=' '
ENDIF
IF (XRD .EQ. '1') THEN
  NTEST(6)='XR'
ELSE
  NTEST(6)=' '
ENDIF
IF (CERAM .EQ. '1') THEN
  NTEST(7)='CR'
ELSE
  NTEST(7)=' '
ENDIF
IF (OTHERTEST .EQ. '1') THEN
  NTEST(8)='OT'
ELSE
  NTEST(8)=' '
ENDIF
C END OF EXPANDING ABBREVIATIONS
C
  IF (IDISPLAY .EQ. 2) THEN
C LIST TO VDU WITH OPTION OF SENDING TO THE PRINTER
  WRITE(5,401) REFNO,SHEET,EAST,NORTH,OCCUPY,LEASE,NTEN,
  . NLUSE,REPORT,ANNUAL,TOTAL,NRES,NSTAT,LOCAL,ROCK,
  . UNIT,AGE,NCOL1,NCOL2,NGEN1,NGEN2,NEXTRACT,COLLECT,
  . IYEAR,NGP1,NGP2,NDRILL1,NDRILL2,NTEST,NLAB,CLASS,
  . NUSE,NQUAL,NSTD
401 FORMAT(///' REF:',A5,' MAP:',A5,' COORDS:',I4,I5,
  . ' OCCUPIER:',A20/12X,' LEASE:',A7,' LAND TENURE:',A2,
  . ' USE:',A2,' REPORT:',A12/12X,11'HANN PROD'N:,I4,
  . 15H TOTAL PROD'N:,I4,' RESERVES:',A3,' OP STATUS:',

```

```

. A3/12X,'LOCAL:',A12,' ROCK NAME:',A10,' ROCK UNIT:',A8,
. ' AGE:',A3/12X,'COL:',A2,' ',A2,' GENERIC TYPE:',
. A2,' ',A2,' EXTRACTN:',A2,' COLLECTOR:',A3,' YEAR:',
. I4/12X,'GEOPHYS:',A2,' ',A2,' DRILL:',A2,' ',A2,
. ' TEST:',7(A2,' '),A2,' LAB:',A3/12X,'SOIL CLASS:',
. A5,' USES:',5(A2,' '),A2,' QUALITY:',A1,' STANDARD:',
. A2//////////)
WRITE(5,147)
147 FORMAT(// ' TO PRINT THIS ENTRY TYPE Y NOW')
READ(5,202) APRINT
WRITE(5,148)
148 FORMAT(' TO STOP THE SEARCH THROUGH MORE ENTRIES TYPE N NOW')
READ(5,202) ASRCH
WRITE(5,149)
149 FORMAT(' TO SEND ENTRIES TO PRINTER ONLY TYPE Y NOW')
READ(5,202) ITYPE
IF (ITYPE .EQ. 'Y') IDISPLAY=1
IF (ASRCH .EQ. 'N' .AND. APRINT .NE. 'Y') GOTO 40
C WANT NO FURTHER SEARCHING AND DONT WANT TO PRINT THIS ENTRY SO
C GO TO THE END
IF (APRINT .NE. 'Y') GOTO 20
C DONT WANT TO PRINT
ENDIF
C FINISHED WITH THIS ENTRY ON SCREEN
C
C
C NOW FOR THE PRINTER
IF (MOD(FCOUNT,14) .EQ. 0) CALL HEAD12
C HEAD THE PAGE TO LEAVE A GAP
FCOUNT=FCOUNT+1
C INCREMENT THE COUNTER FOR THE NUMBER OF FOUND ENTRIES
WRITE(6,402) REFNO,SHEET,EAST,NORTH,OCCUPY,LEASE,LOCAL,
. NTEN,NLUSE,REPORT,ANNUAL,TOTAL,NRES,NSTAT,ROCK,UNIT,
. AGE,NCOL1,NCOL2,NGEN1,NGEN2,NEXTRACT,COLLECT,IYEAR,
. NGP1,NGP2,NDRILL1,NDRILL2,NTEST,NLAB,CLASS,NUSE,
. NQUAL,NSTD
402 FORMAT(' REF: ',A5,' MAP: ',A5,' COORDS: ',I4,I5,
. ' OCCUPIER: ',A20,' LEASE: ',A7,' LOCAL: ',A12,
. ' TEN: ',A2,' USE: ',A2/13X,'REPORT: ',A12,
. 14H ANN PROD'N: ',I4,' TOT: ',I4,' RES: ',A3,
. ' STAT: ',A3,' ROCKNAME: ',A10,' UNIT: ',A8,
. ' AGE: ',A3/13X,'COLOUR: ',A2,' ',A2,' GEN TYPE: ',
. A2,' ',A2,13H EXTRACT'N: ',A2,' COLLECTOR: ',A3,
. ' YEAR: ',I4,' GEOPHYS: ',A2,' ',A2,' DRILL: ',
. A2,' ',A2/13X,'TEST: ',7(A2,' '),A2,' LAB: ',A3,
. ' SOIL CLASS: ',A5,' USES: ',5(A2,' '),A2,
. ' QUALITY: ',A1,' STANDARD: ',A2)
IF (GRANAL .EQ. 'Y') THEN
C WANT ANY GRAINSIZE ANALYSIS PRINTED ALSO
IANAL=IANAL+1
GSRCH(IANAL)=REFNO
C STORE THE REF NO FOR USE IN SEARCHING THE GRAIN SIZE ANALYSIS
C DATA BASE
ENDIF
C END OF PRINTING ENTRY AND NOTING THAT ANY GRAIN SIZE ANALYSIS SHOULD BE
C PRINTED
C
C
IF (ASRCH .NE. 'N') GOTO 20
C BACK ROUND FOR THE NEXT ONE

```

```

C
C
C NOW APPROACHING THE END OF THE RUN WITH THE FINAL QUESTIONS RE THE PRINTOUT
C AND PRINTING OF THE ANALYSES IF REQUIRED
  40 CLOSE(UNIT=4,STATUS='KEEP')
    WRITE(5,150) FCOUNT
  150 FORMAT(I7,' RECORDS WERE SENT TO THE PRINTER'/
. ' TO PRINT THESE TYPE Y NOW')
    READ(5,202) APRINT
    IF (APRINT .NE. 'Y' .OR. FCOUNT .EQ. 0) THEN
      CLOSE(UNIT=6,STATUS='DELETE')
      STOP
    ENDIF
C IF NO ENTRIES OR PRINT NOT REQUIRED DELETE PRINT FILE AND STOP
C
    IF (IANAL .GT. 0 .AND. IDISPLAY .NE. 3) CALL PRGRAIN(IANAL,GSRCH)
C PRINT ANY GRAIN SIZE ANALYSES
C
C NOW PRINT THE FILE OF NMONICS
  OPEN (UNIT=4,FILE='COMMON.TXT',SHARE='ERO')
  WRITE(6,403) FFEED
  403 FORMAT(1A1)
  45 READ(4,201,END=46) SQUAD
  WRITE(6,404) SQUAD
  404 FORMAT(1X,A80)
  GOTO 45
C COPY NMENQIC FILE
  46 CONTINUE
  CLOSE(UNIT=4,STATUS='KEEP')
  CLOSE(UNIT=6,STATUS='KEEP')
  STOP
  END
  LOGICAL FUNCTION NOTIN(SSTRNG,RSTRNG)
C SSTRNG CONTAINS A SERIES OF STRINGS TERMINATED BY /
C E.G. FRED/BILL/TOM/
C AND RSTRNG IS SEARCHED FOR THE OCCURENCE OF ONE OF THESE STRINGS
C IF ONE IS FOUND TO MATCH NOTIN IS .FALSE.
C IF STRNG IS EMPTY NOTIN IS .FALSE.
  CHARACTER*80 SSTRNG
  CHARACTER* (*) RSTRNG
  NOTIN=.FALSE.
  IF (SSTRNG(1:2) .EQ. ' ') RETURN
C NO NEED TO LOOK
  ILAST=1
C COUNTER FOR POSITION IN SSTRNG
  20 ICHAR=INDEX(SSTRNG(ILAST:80),'/')
C LOOK FOR / AS TERMINATOR OF STRING
  IF (ICHR .EQ. 0) GOTO 25
C HAVENT FOUND A MATCH BY THE END OF THE LINE
  IF (INDEX(RSTRNG,SSTRNG(ILAST:ILAST+ICHR-2)) .NE. 0) RETURN
C LOOK BETWEEN /S IN SSTRNG AND IF FIND A MATCH RETURN
  ILAST=ILAST+ICHR
C POSITION AFTER THE /
  IF (ILAST .LE. 79) GOTO 20
C BACK ROUND IF NOT AT END OF LINE
C
C ELSE END
  25 CONTINUE
  NOTIN=.TRUE.
C NO MATCH

```

RETURN
END

SUBROUTINE HEAD12
C HEAD UP PAGES FROM SEARCH
INTEGER*2 FFEED
DATA FFEED/3072/
C USED TO PUT FORM FEEDS IN OUTPUT FILE
WRITE(6,100) FFEED
100 FORMAT(1A1/20X,'TASMANIAN CONSTRUCTION MATERIALS REGISTER')
RETURN
END

SUBROUTINE HEAD3
C HEAD UP PAGES FOR ABBREVIATED SUMMARY
CALL HEAD12
WRITE(6,100)
100 FORMAT(6X,'1',9X,'1',12X,'1',20X,'1',7X,'1 LAND: | |',
. 5X,'1',5X,'1',17X,'1 | TESTS 1'/
. 1X,'REFNO: CO-ORDS | LOCALITY 1',6X,'OCCUPIER',6X,
. 'IM LEASEITE|US|RES|OPS| COL |EX| USCS|',6X,'USES',7X,
. 'IQU|GP|DR|LA|'/1X,117(' '))
RETURN
END

LOGICAL FUNCTION SEMIN(SSTRNG,RSTRNG)
C SSTRNG CONTAINS A SERIES OF STRINGS TERMINATED BY ;
C E.G. FRED;BILL;TOM;
C AND RSTRNG IS SEARCHED FOR THE OCCURENCE OF ONE OF THESE STRINGS
C IF ONE IS FOUND TO MATCH SEMIN IS .FALSE.
C IF STRNG IS EMPTY SEMIN IS .FALSE.
CHARACTER*80 SSTRNG
CHARACTER* (*) RSTRNG
SEMIN=.FALSE.
IF (SSTRNG(1:2) .EQ. ' ') RETURN
C NO NEED TO LOOK
ILAST=1
C COUNTER FOR POSITION IN SSTRNG
20 ICHAR=INDEX(SSTRNG(ILAST:80),';')
C LOOK FOR ; AS TERMINATOR OF STRING
IF (ICHR .EQ. 0) GOTO 25
C HAVENT FOUND A MATCH BY THE END OF THE LINE
IF (INDEX(RSTRNG,SSTRNG(ILAST:ILAST+ICHR-2)) .NE. 0) RETURN
C LOOK BETWEEN ;S IN SSTRNG AND IF FIND A MATCH RETURN
ILAST=ILAST+ICHR
C POSITION AFTER THE ;
IF (ILAST .LE. 79) GOTO 20
C BACK ROUND IF NOT AT END OF LINE
C
C ELSE END
25 CONTINUE
SEMIN=.TRUE.
C NO MATCH
RETURN
END

SUBROUTINE MNABREV(NVAR,CVAR,CONST)
CHARACTER * (*) NVAR,CVAR,CONST(2)
IF (CVAR .EQ. ' ') THEN
NVAR=' '

```

ELSE
NVAR=CONST(CTOI(CVAR,K)+1)
ENDIF
RETURN
END

```

```

SUBROUTINE PRGRAIN(IANAL,GRSRCH)
INTEGER*4 IANAL
CHARACTER*5 GRSRCH(2)

```

```

C USED TO SEARCH THE GRAIN SIZE ANALYSIS DATA BASE
C IANAL IS THE NUMBER OF REF NOS TO BE LOOKED FOR
C AND GRSRCH CONTAINS THE REF NOS
INTEGER*2 IQUAD(98)
C THE ARRAY TO STORE THE STARTING RECORDS FOR EACH QUADRANGLE
REAL PHI(30),PCENT(30),MEAN, SORT, SKEW, KURT, LL, PI, LS, DR
INTEGER*4 N
CHARACTER*5 SEDSID
CHARACTER*1 IGNO, CL1, CL2, DL1, DL2
CHARACTER*1 BIN(300)
EQUIVALENCE (BIN(1),SEDSID), (BIN(6),PHI), (BIN(126),PCENT)
- , (BIN(246),MEAN), (BIN(250),SORT), (BIN(254),SKEW),
- (BIN(258),KURT), (BIN(262),LL), (BIN(266),PI), (BIN(270),LS)
- , (BIN(274),DR), (BIN(278),N), (BIN(282),IGNO), (BIN(283),CL1)
- , (BIN(284),CL2), (BIN(285),DL1), (BIN(286),DL2)
C THE COMMON BLOCK FROM SEDMERGE TO ALLOW BINARY ACCESS USEING
C EQUIVALENCE
LCOUNT=90
C COUNTER FOR NUMBER OF LINES PRINTED ON THE PAGE
OPEN(UNIT=3,FILE='SEDQUAD.IND',RECL=2,FORM='BINARY',SHARE='SRO')
C THE BINARY FILE CONTAINING THE QUADRANGLE INDEX
DO 8 I=1,98
READ(3) IQUAD(I)
8 CONTINUE
CLOSE(UNIT=3,STATUS='KEEP')
C READ THE STARTING RECORD OF EACH QUADRANGLE IN THE GRAIN SIZE
C ANALYSIS FILE
C
OPEN(UNIT=3,FILE='SEDIND.DAT',RECL=300,ACCESS='DIRECT',
. FORM='BINARY',SHARE='SRO')
C OPEN THE MAIN GRAIN SIZE ANALYSIS FILE
C
DO 20 I=1,IANAL
C LOOP ONCE FOR EACH REF NO AS MAY HAVE MORE THAN ONE ANALYSIS
C FOR EACH REF NO
IBASE=IQUAD(CTOI(GRSRCH(I)(1:2),J))
C THE FIRST RECORD WITH THIS QUADRANGLE NUMBER
IF (IBASE .EQ. 0) GOTO 20
C NO ENTRIES FOR THIS QUADRANGLE
C
IF (IBASE .NE. 1) THEN
C NOT THE FIRST RECORD
READ(3,REC=IBASE-1) BIN
C POSITION TO THE RECORD BEFORE THE FIRST OF THE QUAD
ELSE
REWIND 3
C IF IBASE IS THE FIRST RECORD JUST REWIND THE FILE
ENDIF
C
C NOW SCAN THE FILE LOOKING FOR MATCHING REF NOS
12 READ(3,END=20) BIN

```

```

C IF HIT END LOOK FOR ANOTHER QUAD NO
  IF (SEDSID .GT. GRSRCH(I)) GOTO 20
C THE ANALYSIS FILE IS ORDERED IN ASCENDING REF NO ORDER
C SO IF THE REFNO IN THE FILE IS BIGGER THAN THAT BEING SOUGHT
C DONT HAVE A MATCH
  IF (SEDSID .LT. GRSRCH(I)) GOTO 12
C STILL TOO FAR DOWN THE ANALYSIS FILE
C
C AT THIS STAGE HAVE FOUND A MATCH
  CALL HEADSED(LCOUNT)
C HEADSED CHECK LINE COUNT AND HEADS PAGE IF NEEDED
C
C WAS IT INCLUDED FRACTION OR EXCLUDED FRACTION
  IF (IGNO .EQ. 'I') THEN
    WRITE(6,101) SEDSID,PHI(1),PCENT(1)
101 FORMAT(3X,A5,' PHI=',F10.3,' PERCENT=',F10.3,
. 6X,'CALCULATIONS ARE FOR INCLUDED FRACTION')
  ELSE
    WRITE(6,102) SEDSID,PHI(1),PCENT(1)
102 FORMAT(3X,A5,' PHI=',F10.3,' PERCENT=',F10.3,
. 6X,'CALCULATIONS ARE FOR EXCLUDED FRACTION')
  ENDIF
  CALL HEADSED(LCOUNT)
C THE FIRST LINE HAS THE REF NO ETC
  DO 14 J=2,N
C ALREADY PRINTED (1)
  WRITE(6,103) PHI(J),PCENT(J)
103 FORMAT(10X,'PHI=',F10.3,' PERCENT=',F10.3)
  CALL HEADSED(LCOUNT)
  14 CONTINUE
C END PRINT OUT THE PHIS AND %S
C
C NOW FOR THE CALCULATIONS BASED ON THE ABOVE
  IF (CL1 .EQ. 'M') THEN
C ONLY THE MEAN CALCULATED
  WRITE(6,104) MEAN
104 FORMAT(10X,'MEAN=',F9.3/10X,'NO SORTING, SKEWNESS OR ',
. 'KURTOSIS CALCULATED')
  CALL HEADSED(LCOUNT)
  CALL HEADSED(LCOUNT)
  ELSE
  IF (CL1 .EQ. 'A') THEN
C MEAN, SORTING, SKEWNESS AND KURTOSIS CALCLUATED
  WRITE(6,105) MEAN, SORT, SKEW, KURT
105 FORMAT(10X,'MEAN=',F9.3,' SORTING=',F9.3,' SKEWNESS=',F9.3,
. ' KURTOSIS=',F9.3)
  CALL HEADSED(LCOUNT)
  ELSE
C NONE OF MEAN, SORTING, SKEW OR KURT CALCULATED
  WRITE(6,106)
106 FORMAT(10X,'NO MEAN, SORTING, SKEWNESS OR KURTOSIS CALCUATED')
  CALL HEADSED(LCOUNT)
  ENDIF
  ENDIF
C
C NOW FOR THE PLASTICITY ETC
  IF (DL1 .EQ. 'X') THEN
C THE MATERIAL HAS NO PLASTICITY
  WRITE(6,107)
107 FORMAT(10X,'THIS MATERIAL HAS NO PLASTICITY')

```

```

CALL HEADSED(LCOUNT)
ELSE
  IF (DL1 .EQ. 'A') THEN
C L.L.,P.I.,L.S. SUPPLIED
  WRITE(6,108) LL,PI,LS
  108 FORMAT(10X,'L.L.=',F9.3,' P.I.=',F9.3,' L.S.=',F9.3)
  CALL HEADSED(LCOUNT)
  ELSE
  WRITE(6,109)
  109 FORMAT(10X,'NO VALUES FOR L.L., P.I. OR L.S. SUPPLIED')
  CALL HEADSED(LCOUNT)
  ENDIF
  ENDIF
C
C NOW FOR THE DUST RATIO
  IF (DL2 .EQ. 'D') THEN
C DUST RATIO CALCULATED
  WRITE(6,110) DR
  110 FORMAT(10X,'DUST RATIO=',F9.3)
  CALL HEADSED(LCOUNT)
  ELSE
  WRITE(6,111)
  111 FORMAT(10X,'DUST RATIO NOT CALCULATED')
  ENDIF
C
C NOW GO ROUND TO READ THE NEXT IN THE ANALYSIS FILE AS IT MAY HAVE THE
C SAME REF NO
  GOTO 12
C
  20 CONTINUE
C END OF LOOP FOR STEPPING THROUGH REF NOS
C
C NOW HAVE ALL DONE
  CLOSE(UNIT=3,STATUS='KEEP')
  RETURN
  END

  SUBROUTINE HEADSED(LCOUNT)
C TO INCREMENT LCOUNT AND HEAD PAGE IF NEEDED
  INTEGER*2 FFEED
  DATA FFEED/3072/
  LCOUNT=LCOUNT+1
  IF (LCOUNT .LT. 60) RETURN
C ENOUGH LEFT ON PAGE
  WRITE(6,100) FFEED
  100 FORMAT(A1,10X,'GRAIN SIZE ANALYSES'/' REF NO')
  LCOUNT=0
  RETURN
  END

$INCLUDE FSTJDN.FTN, -
$TITL FSTJDN.FTN - POINT IN POLYGON
C PROGRAM COLLECTION FASTJORDAN
C SALOMON,K.B., 1978. AN EFFICIENT POINT-IN-POLYGON ALGORITHM
C COMPUTERS AND GEOSCIENCES, V4, NO. 2, P. 173-178
C
C USE BY READING VERTICES OF POLYGON IN ORDER (BUT NOT CLOSING IT)
C AND CALLING PREPLY ONCE BEFORE THE SEARCH IS BEGUN. THE ACTUAL
C SEARCHING IS DONE BY MEANS OF THE LOGICAL FUNCTION INOUT.
C

```

SUBROUTINE PREPLY(X,Y,NUVERT,YINTVL,INTVLS,SWATH,RSLOPE)

```

C
C*****
C THIS ROUTINE PREPARES THE POLYGON CONSISTING OF THE NUVERT VERTICES
C (X(I),Y(I)) BY FIRST SORTING THE SEGMENT Y-END POINTS INTO
C DECREASING ORDER AND FORMING AN INTERVAL FOR EACH CONSECUTIVE PAIR:
C (YINTVL(I),YINTVL(I+1)), I=1,INTVLS. THIS IS PERFORMED BY CALLING
C SORT.
C THE CODE CONSISTING OF THE DO 100 AND DO 200 LOOPS CONSTRUCTS,
C FOR EACH INTERVAL I, THE LIST OF SEGMENTS TO BE TESTED BY INOUT.
C THIS LIST IS PLACED IN THE I-TH ROW OF SWATH. THE FIRST ENTRY,
C SWATH(I,1), WILL BE SET TO THE NUMBER OF SEGMENTS IN THE ROW. NOTE
C THAT AS YINTVL CONTAINS NO REDUNDANCIES, I.E. YINTVL(I) IS STRICTLY
C GREATER THAN YINTVL(I+1), NO HORIZONTAL SEGMENTS WILL BE PLACED IN
C THE LIST.
C THE CODE CONSISTING OF THE DO 300 LOOP ESTABLISHES THE
C RECIPROCAL SLOPE FOR EACH NON-HORIZONTAL SEGMENT. THIS IS TO BE
C USED BY INOUT. FINALLY, THE SEGMENTS WITHIN A ROW OF SWATH ARE
C ORDERED FROM LEFT-TO-RIGHT.
C
C*****
C
      INTEGER*2 SWATH(100,25)
      REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
      CALL SORT(Y,NUVERT,YINTVL,INTVLS)
      IF (INTVLS .LE. 0) GOTO 400
      X(NUVERT+1)=X(1)
      Y(NUVERT+1)=Y(1)
      DO 100 I=1,INTVLS
100  SWATH(I,1)=0
      DO 200 I=1,INTVLS
          DO 200 J=1,NUVERT
              IF (Y(J).GE.YINTVL(I) .AND. YINTVL(I+1).GE.Y(J+1) .OR.
*           Y(J+1).GE.YINTVL(I) .AND. YINTVL(I+1).GE.Y(J))
*                   CALL INCLUD(SWATH,I,J)
200  CONTINUE
      DO 300 I=1,NUVERT
          IF (Y(I).EQ.Y(I+1)) GOTO 300
          RSLOPE(I)=(X(I+1)-X(I))/(Y(I+1)-Y(I))
300  CONTINUE
      CALL ORDER(X,Y,YINTVL,INTVLS,SWATH,RSLOPE)
      RETURN
400  WRITE(7,401)
401  FORMAT(' ***** PREP OF POLYGON ABORTED SINCE NO INTERVALS',
* ' CONSTRUCTED')
      STOP
      END

```

SUBROUTINE SORT(Y,NUVERT,YINTVL,INTVLS)

```

C
C*****
C ROUTINE ESTABLISHES THE INTERVALS OF THE Y-AXIS DEFINED BY THE
C ENDPPOINTS OF THE POLYGON'S SEGMENTS. THE DO 100 LOOP INITIALLISES
C YSORT FROM THE SEGMENT Y-END POINTS. THE DO 200 LOOPS SORT YSORT
C INTO DESCENDING ORDER. THE DO 300 LOOP ELIMINATES REDUNDANCIES IN
C YSORT AND PLACES IRREDUNDANT SORTED Y'S INTO YINTVL. IT ALSO SETS
C INTVLS TO THE TRUE NUMBER OF Y INTERVALS. JUST PRIOR TO RETURNING
C A FINAL INTERVAL EXTENDING TO '-INFINITY' IS ESTABLISHED.
C

```

2/5A

```

C*****
C
  REAL Y(100),YINTVL(100),YSORT(100)
  INTEGER*2 UPPER
  DO 100 I=1,NUVERT
100  YSORT(I)=Y(I)
      UPPER=NUVERT-1
      DO 200 I=1,UPPER
          IPLS1=I+1
          DO 200 J=IPLS1,NUVERT
              IF (YSORT(I).GE.YSORT(J)) GOTO 200
                  TEMP=YSORT(I)
                  YSORT(I)=YSORT(J)
                  YSORT(J)=TEMP
200  CONTINUE
      YINTVL(1)=YSORT(1)
      INTVLS=0
      DO 300 I=1,UPPER
          IF (YSORT(I).EQ.YSORT(I+1)) GOTO 300
              INTVLS=INTVLS+1
              YINTVL(INTVLS+1)=YSORT(I+1)
300  CONTINUE
      YINTVL(INTVLS+2)=-1.0E75
      RETURN
      END

```

SUBROUTINE INCLUD(SWATH,I,J)

```

C
C*****
C ROUTINE PLACES THE J-TH POLYGON SEGMENT INTO THE NEXT AVAILABLE
C LOCATION IN ROW I OF SWATH.
C
C*****
C
  INTEGER*2 SWATH(100,25),POINTR
  SWATH(I,1)=SWATH(I,1)+1
  POINTR=SWATH(I,1)
  SWATH(I,POINTR+1)=J
  RETURN
  END

```

SUBROUTINE ORDER(X,Y,YINTVL,INTVLS,SWATH,RSLOPE)

```

C
C*****
C FOR EACH INTERVAL, A HORIZONTAL LINE IS PASSED THROUGH THE MIDDLE
C (YMID) OF THE INTERVAL. THE DO 100 LOOP PLACES THE X-INTERSECTION
C OF EACH SEGMENT IN THIS SWATH SO THAT THESE INTERSECTIONS OCCUR
C FROM LEFT-TO-RIGHT.
C
C*****
C
  REAL X(100),Y(100),YINTVL(100),RSLOPE(100),XINTSC(25)
  INTEGER*2 SWATH(100,25),POINTR,SEGNO,UPPER
  LOGICAL VERTSG
  DO 200 INTVAL=1,INTVLS
      NMBSEG=SWATH(INTVAL,1)
      YMID=(YINTVL(INTVAL)+YINTVL(INTVAL+1))/2.0
      DO 100 POINTR=1,NMBSEG
          SEGNO=SWATH(INTVAL,POINTR+1)

```

```

      VERTSG=ABS(X(SEGNO+1)-X(SEGNO)) .LT. 1.0E-5
      IF (VERTSG) XINTSC(POINTR)=X(SEGNO)
      IF (.NOT. VERTSG) XINTSC(POINTR)=X(SEGNO)+
*
*          RSLOPE(SEGNO)*(Y(MID)-Y(SEGNO))
100  CONTINUE
      IF (NMBSEG.LT.2 .OR. MOD(NMBSEG,2).NE.0) GOTO 300
      UPPER=NMBSEG-1
      DO 200 I=1,UPPER
        IPLS1=I+1
        DO 200 J=IPLS1,NMBSEG
          IF (XINTSC(I).LE.XINTSC(J)) GOTO 200
          TEMP=XINTSC(I)
          XINTSC(I)=XINTSC(J)
          XINTSC(J)=TEMP
          ITEMP=SWATH(INTVAL,I+1)
          SWATH(INTVAL,I+1)=SWATH(INTVAL,J+1)
          SWATH(INTVAL,J+1)=ITEMP
200  CONTINUE
      RETURN
300  WRITE(7,301) INTVAL
301  FORMAT(' ** PREP OF POLYGON ABORTED. INTERVAL ',I5/
* ' HAS EITHER LESS THAN TWO SEGMENTS OR AN ODD NUMBER OF THEM?')
      STOP
      END

```

LOGICAL FUNCTION INOUT(XP,YP,X,Y,YINTVL,INTVLS,SWATH,RSLOPE)

```

C
C*****
C
C THE FOUR LINES ENCLOSED IN DASHES DETERMINE THE INTERVAL CONTAINING
C YP. THE DO 400 LOOP CONTINUES UNTIL THE FIRST SEGMENT WITHIN THE
C INTERVAL FALL TO THE LEFT OF (XP,YP). IN THIS EVENT, INOUT IS SET
C .TRUE. IFF AN EVEN NUMBER OF SEGMENTS HAS BEEN TESTED.
C
C*****
C
      REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
      INTEGER*2 SWATH(100,25),SEGNO
      INOUT=.FALSE.
C-----
      INTVAL=0
100  INTVAL=INTVAL+1
      IF (YINTVL(INTVAL) .GT. YP) GOTO 100
      INTVAL=INTVAL-1
C-----
300  IF (INTVAL.LT.1 .OR. INTVAL.GT.INTVLS) RETURN
      NMBSEG=SWATH(INTVAL,1)+1
      DO 400 I=2,NMBSEG
        SEGNO=SWATH(INTVAL,I)
        IF (XP-X(SEGNO).LE.(YP-Y(SEGNO))*RSLOPE(SEGNO)) GOTO 500
400  CONTINUE
      RETURN
500  INOUT=MOD(I,2) .EQ. 1
      RETURN
      END

```