

UR1987-66

1987/66. CARS - A computer-assisted records system (Revision 5)

R. G. Richardson

Abstract

The program suite described is used for adding entries to a data-base of Engineering Geology correspondence, sorting the data-base, and searching it. The data are entered in a simple fill-in-the spaces manner, and part or all of the details entered may be searched. The programs have been revised to incorporate the date correspondence is received, and the Records Section file number.

USING THE PROGRAMS

The programs are run on the Geological Survey Perkin-Elmer mini-computer, and it is assumed that the user is familiar with the standard data editing facilities.

Data-base maintenance

Data are put into a standard format (Appendix 1) before entry. Input is commenced by typing RECADD and continues until END is typed in response to the name prompt. Data are entered left justified in response to prompts, with the category and geology number being entered as either one or two digits on the same line.

At the end of input, a proof-sheet is output and the data saved in file RECTEMP.TMP. Any corrections should be made to this file using the standard editing facilities, and a new proof sheet then printed and checked.

The new data in RECTEMP.TMP must be added to the end of the existing data-base by typing RECMERGE. To ensure that the file remains in records reference number order, it should be sorted periodically using the RECSORT command. As sorting is a slow process it should not be carried out more often than necessary.

Data-base searching

The search phase is entered by typing RECSRCH. An entry will be retrieved only if one value in each search option specified is found.

The program requests the following data:

- (i) Name - one or more names on a single line, each name terminated by /.
If a search by name is not required leave the line blank.

e.g. BROWN/JONES/SMITH/

- (ii) Job location - details as for name.

- (iii) Agency name - details as for name.

(iv) Agency type - one or more agency numbers on a single line, each terminated by /. If a search by agency type is not required leave line blank.

e.g. 0/ find agency type 0
0/2 find agency types 0 or 2

(v) Year - one or more years on a single line, each terminated by a /. Leave blank if not required.

e.g. 1982/ only year 1982
1975/1976/1977/1978/ years 1975 to 1978 inclusive.

(vi) Geologist - details as for name. e.g. PRW/WCC/DJJ/

(vii) Search also non-specified area/subject material - leave blank if this material is not to be included in a search by area.

- Y for search material that may be of a general or non-area specific nature when searching by area. The map reference must be 0 0.

e.g. if this is the only search option specified a list of general reports is produced.

e.g. a search for work done by geologist CJK on landslides in north-east Tasmania (search by area) may have this option specified to detect any general work done by CJK on landslides as well.

(viii) Search by area - leave blank for no search by area.

- Y for finding entries inside a specified area. Entries on the boundary of the area will not be found. The program prompts for the number of vertices. If 2 is entered a simple rectangle parallel to the grid may be entered by specifying the co-ordinates of any two diagonally opposite corners. Otherwise the program prompts for the vertex co-ordinates. Co-ordinates should be in the same form as used on the input sheets.

(ix) Category - one or more category numbers on a single line, each group terminated by /. Leave blank if not required.

e.g. 0/2/ groundwater or expansive soils
12/4 slope stability and expansive soils or miscellaneous.

(x) Geology- one or more geology numbers on a single line, each group terminated by /. Leave blank if not required.

e.g. 0/9 Quaternary or granite
17/ Tertiary sediments and Tertiary basalt.

(xi) Screen listing required - Y if required, N otherwise. At the end of each screen a choice is made as to whether to list any more data on the screen or not.

- (xii) Printout required - Y if the number of entries found can be realistically printed.
- N if the number of entries found is too great to want them printed.

THE PROGRAMS

RECADD (Appendix 2)

This program accepts data from the keyboard and copies it to a file in a format suitable for editing. Prompts are used to guide the user. The file created (RECTEMP.TMP) is then edited using the standard edit facilities.

RECMERGE (Appendix 3)

The data from RECTEMP.TMP are converted to the format of the data-base. The data-base is copied to a temporary work file and the new data are added to the end of this. The combined file is then copied back to the original data-base file.

RECSORT (Appendix 4)

The data are sorted into ascending records reference number order and written to a temporary file in the new order. The temporary file is then copied back to the original data-base file.

RECSRCH (Appendix 5)

The data-base is searched for the occurrence of specified strings and a point-in-polygon algorithm is used to locate data from within a specified area.

[22 December 1987]

APPENDIX 1

Input Sheet

CARS (COMPUTER ASSISTED RECORDS SYSTEM)

NAME: _____ (24)

JOB LOCATION: _____ (36)

AGENCY: _____ (24)

0 GOVERNMENT 1 PROFESSIONAL 2 INDIVIDUAL

FILE NUMBER: _____ (9)

DATE RECEIVED: ___ / ___ / 19 ___ (10)

GEOLOGIST: _____ (3)

ANG MAP REFERENCE: _____ 5 _____ (9)

CATEGORY*: # Cross two (2) maximum

0 GROUNDWATER 1 SLOPE STABILITY 2 EXPANSIVE SOILS 3 FOUNDATIONS 4 MISCELLANEOUS

GEOLOGY*: # Cross two (2) maximum

0 Quaternary 1 Tertiary Sediments 2 Triassic 3 Permian 4 Lower-Palaeozoic

5 Cambrian 6 Pre-Cambrian 7 Tertiary Basalt 8 Jurassic Dolerite 9 Granite

DATADASE PRDGRESS: Y ENTERED Y EDITED Y COMPLETED

APPENDIX 2

Program RECADD

```

*RECADD.CSS
*FOR RUNNING RECADD AND PRINTING A PROOF SHEET
$IFX RECTEMP.TMP; $WRITE ** CHECK LAST MERGE; $EXIT; $ENDC
PRE ETM; AL RECTEMP.TMP,IN,132
* SET UP THE OUTPUT FILE
L RECADD,3; AS 6,RECTEMP.TMP; * LOAD PROG AND SET LU 6
TEMPFILE 3,IN,80; ST
ENA ETM; PRI RECTEMP.TMP,DEV=EPR:
$EXIT

$TITL RECADD.FTN - ADD LETTERS TO THE RECORDS FILE
C TAKES KEYBOARD INPUT AND PREPARES A PROOF SHEET
  CHARACTER*1 AGENCY
  CHARACTER*9 MR,FILENUM
  INTEGER*4 MAPREF
  CHARACTER*24 NAME,BUFF
  CHARACTER*36 LOCATN
  CHARACTER*24 AGNAME
  INTEGER*2 AGNO,RECDAY,RECMTH,RECYR
  CHARACTER*3 GEOLST
  CHARACTER*2 CATG,GEOL
C INPUT IS NAME, LOCATION, AGENCY NAME, AGENCY TYPE(AGNO),
C     RECORDS FILE NO (RECNO/RECYR), GEOLOGIST,
C     CATEGORY(UP TO 2), GEOLOGY (UP TO 2)
C
  OPEN(UNIT=5, FILE='CON:')
C SET THE CONSOLE UP AS LU 5 FOR INPUT
C THE OUTPUT IS TO LU 6
  10 CALL ALPHA24(NAME, 'NAME OR END')
  IF (INDEX(NAME, 'END ') .NE. 0) GOTO 20
C RECOGNISE END BY HAVING END ON ITS OWN AND PRINT PROOF SHEET
  CALL ALPHA36(LOCATN, 'LOCATION')
  CALL ALPHA24(AGNAME, 'AGENCY')
  CALL NUMB1(AGENCY, 'AGENCY NO', '0', '2')
  AGNO=CTOI(AGENCY, K)
  CALL ALPHA9(FILENUM, 'RECORDS FILE NO')
  11 CALL ALPHA24(BUFF, 'DATE RECEIVED')
  DO 12 I=1,24
  IF (BUFF(I:I) .EQ. '/') BUFF(I:I)=' '
  12 CONTINUE
C CHANGE / TO , TO COPE WITH FREE FORMAT READ
  REWIND 3
  WRITE(3,109) BUFF
  109 FORMAT(A24)
  REWIND 3
  READ(3,*,END=11,ERR=11) RECDAY,RECMTH,RECYR
  IF (RECYR .LT. 100) RECYR=RECYR+1900
C GET THE RIGHT CENTURY
  CALL ALPHA3(GEOLST, 'GEOLOGIST')
  CALL ALPHA9(MR, 'MAP REF')
  MAPREF=CTOI(MR, K)
  CALL NUMB2(CATG, 'CATEGORY', '0', '4')

```

```

      CALL NUMB2(GEOL,'GEOLOGY','0','9')
C READ ONE COMPLETE DATA SHEET
C
C SO WRITE TO OUTPUT FILE
      WRITE(6,300) NAME,LOCATN,AGNAME,AGNO,FILENUM,RECDAY,RECMTH,RECYR,
      .
      GEOLST,MAPREF,CATG,GEOL
      300 FORMAT('@',A24,'@',A36,'@',A24,'@',I1,'@',A9,'@',2(I2,':'),I4,
      .
      '@',A3,'@',I9,2('@',A2),'@')
C WRITE WITH DELIMITERS AFTER EACH FIELD
      GOTO 10
C BACK AROUND
C
C OTHERWISE CLOSE UP AND STOP
      20 CONTINUE
      CLOSE(UNIT=6,STATUS='KEEP')
      END

```

```

$INCLUDE ALPHA3.FTN
      SUBROUTINE ALPHA3(SVAR,PROMPT)
      CHARACTER * (*) PROMPT
      CHARACTER *3 SVAR
      LOGICAL UNPRINT
      INTEGER*2 IBELL
      DATA IBELL/1792/
      WRITE(5,100) PROMPT
      100 FORMAT(1X,C20)
      10 READ(5,101) SVAR
      101 FORMAT(A3)
      IF (.NOT. UNPRINT(SVAR,3)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
      WRITE(5,102) IBELL,PROMPT
      102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
      GOTO 10
      END

```

```

$INCLUDE ALPHA9.FTN
      SUBROUTINE ALPHA9(SVAR,PROMPT)
      CHARACTER * (*) PROMPT
      CHARACTER *9 SVAR
      LOGICAL UNPRINT
      INTEGER*2 IBELL
      DATA IBELL/1792/
      WRITE(5,100) PROMPT
      100 FORMAT(1X,C20)
      10 READ(5,101) SVAR
      101 FORMAT(A9)
      IF (.NOT. UNPRINT(SVAR,9)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
      WRITE(5,102) IBELL,PROMPT
      102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
      GOTO 10
      END

```

```

$INCLUDE ALPHA24.FTN
      SUBROUTINE ALPHA24(SVAR,PROMPT)
      CHARACTER * (*) PROMPT
      HARACTER *24 SVAR
      LOGICAL UNPRINT

```

```

    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A24)
    IF (.NOT. UNPRINT(SVAR,24)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
    END

```

```

$INCLUDE ALPHA36.FTN
    SUBROUTINE ALPHA36(SVAR,PROMPT)
    CHARACTER * (*) PROMPT
    CHARACTER *36 SVAR
    LOGICAL UNPRINT
    INTEGER*2 IBELL
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A36)
    IF (.NOT. UNPRINT(SVAR,36)) RETURN
C LOOK FOR NON-PRINTING CHARCATERS AND IF NONE RETURN
    WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' ERROR IN KEYING - PLEASE RE ENTER ',C20)
    GOTO 10
    END

```

```

$INCLUDE NUMB1.FTN
    SUBROUTINE NUMB1(SVAR,PROMPT,LOW,UP)
    CHARACTER *(*) PROMPT
    CHARACTER*1 SVAR
    CHARACTER*1 UP,LOW
    INTEGER*2 IBELL
    LOGICAL UNPRINT
    DATA IBELL/1792/
    WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
    10 READ(5,101) SVAR
101 FORMAT(A1)
    IF (UNPRINT(SVAR,1)) THEN
        WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
        GOTO 10
    ENDIF
    IF (SVAR .EQ. ' ' .OR.
        (SVAR .GE. LOW .AND. SVAR .LE. UP)) GOTO 11
C VALID CHARACTER
    WRITE(5,102) IBELL,PROMPT
    GOTO 10
11 CONTINUE
    RETURN
    END

```

```

$INCLUDE NUMB2.FTN

```

```

SUBROUTINE NUMB2(SVAR,PROMPT,LOW,UP)
CHARACTER *(*) PROMPT
CHARACTER*2 SVAR
CHARACTER*1 UP,LOW
INTEGER*2 IBELL
LOGICAL UNPRINT
DATA IBELL/1792/
WRITE(5,100) PROMPT
100 FORMAT(1X,C20)
10 READ(5,101) SVAR
101 FORMAT(A2)
IF (UNPRINT(SVAR,2)) THEN
WRITE(5,102) IBELL,PROMPT
102 FORMAT(1X,A1,' KEYING ERROR - REENTER ',C20)
GOTO 10
ENDIF
DO 11 I=1,2
IF (SVAR(I:I) .EQ. ' ' .OR.
(SVAR(I:I) .GE. LOW .AND. SVAR(I:I) .LE. UP)) GOTO 11
C VALID CHARACTER
WRITE(5,102) IBELL,PROMPT
GOTO 10
11 CONTINUE
RETURN
END

```

```

$INCLUDE UNPRINT.FTN
LOGICAL FUNCTION UNPRINT(SVAR,NCHAR)
CHARACTER* (*) SVAR
O 10 I=1,NCHAR
IF (SVAR(I:I) .LT. ' ') THEN
UNPRINT=.TRUE.
RETURN
ENDIF
10 CONTINUE
UNPRINT=.FALSE.
RETURN
END

```

APPENDIX 3

Program RECMERGE

```

*RECMERGE.CSS
* FOR MERGING CORRECTED FILE WITH MAIN FILE
$IFNX RECTEMP.TMP;$WRITE NO FILE TO MERGE°°;$CLEAR;$ENDC
$IFX REC.UPD;$WRITE FILE BEING UPDATED;$CLEAR;$ENDC
PRE ETM; XDE RCMRGTMP.TMP; *DELETE SCRATCH FILE
$JOB
L RECMERGE,10;AS 4,JOBREC.DAT,ERO
$TERMJOB
$IFNE 0;CA;ENA ETM;$WRITE FILE BEING SEARCHED;$CLEAR;$ENDC
AL REC.UPD,IN,4; * USED TO INDICATE UPDATE IN PROGRESS
CL 4
AL RCMRGTMP.TMP,IN,114; * AL SCRATCH FILE AND LOAD PROG
REP RECTEMP.TMP,FF00; AS 6,RECTEMP.TMP,ERO; AS 4,RCMRGTMP.TMP; ST
$IFNE 0; $WRITE TRANSLATE ERROR; ENA ETM; $EXIT; $ENDC
REP RCMRGTMP.TMP,FF00
$BUILD RECCOPY.CMD
IN JOBREC.DAT
AL SYSF:RCTEMP.DAT,IN,114/6/5
OUT SYSF:RCTEMP.DAT
COPY *,*
IN RCMRGTMP.TMP
COPY *,*
END
$ENDB
L COPY32,50; ST ,COM=RECCOPY.CMD,LI=NULL:,LO=NULL:
$IFNE 0; $WRITE COPY-MERGE ERROR; ENA ETM; $EXIT; $ENDC
REP JOBREC.DAT,0; REP SYSF:RCTEMP.DAT,FF00
DE RECCOPY.CMD,JOBREC.DAT
$BUILD RECCOPY.CMD
IN SYSF:RCTEMP.DAT
AL JOBREC.DAT,IN,114/10/3
OUT JOBREC.DAT
COPY *,*
REW I
REW O
VERIFY *,*
END
$ENDB
L COPY32,50; ST ,COM=RECCOPY.CMD,LI=NULL:,LO=NULL:
$IFNE 0; $WRITE COPY BACK FAILED; ENA ETM; $EXIT; $ENDC
REP JOBREC.DAT,FF00; REP SYSF:RCTEMP.DAT,0; REP RECTEMP.TMP,0
REP RCMRGTMP.TMP,0
DE RECCOPY.CMD,RCMRGTMP.TMP,RECTEMP.TMP,SYSF:RCTEMP.DAT,REC.UPD
ENA ETM
$EXIT

```

10/22

```

$TITL  RECMERGE.FTN - CONVERT PROOF FILE TO MASTER FILE FORMAT
C
      INTEGER*4 NORTH
      INTEGER*2 EAST
C SPLIT MAPREF INTO THE RELEVANT PARTS NOW
      CHARACTER*24 NAME
      CHARACTER*36 LOCATN
      CHARACTER*24 AGNAME
      INTEGER*2 RECDAY,RECMTH,RECYR
      CHARACTER*9 FILENUM
      CHARACTER*3 GEOLST
      CHARACTER*2 CATG,GEOL
      CHARACTER*1 AGNO,BUFF(114)
C AS FOR RECADD.FTN
C
C NOW SET UP EQUIVALENCE
      EQUIVALENCE (BUFF(1),NAME),(BUFF(25),LOCATN),(BUFF(61),AGNAME),
      . (BUFF(85),FILENUM),(BUFF(95),RECDAY),(BUFF(97),RECMTH),
      . (BUFF(99),RECYR),(BUFF(101),GEOLST),
      . (BUFF(104),AGNO),(BUFF(105),CATG),(BUFF(107),GEOL),
      . (BUFF(109),EAST),(BUFF(111),NORTH)
C THIS IS USED TO ALLOW BINARY OUTPUT FOR FASTER ACCESS
C
      OPEN(UNIT=4,FORM='BINARY',RECL=114)
C OPEN THE OUTPUT FILE FOR BINARY OUTPUT
      10 READ(6,300,END=20) NAME,LOCATN,AGNAME,AGNO,FILENUM,RECDAY,RECMTH,
      . RECYR,GEOLST,EAST,NORTH,CATG,GEOL
      300 FORMAT(1X,A24,1X,A36,1X,A24,1X,A1,1X,A9,1X,2(I2,1X),I4,1X,A3,
      . 1X,I4,I5,2(1X,A2))
      WRITE(4) BUFF
C BINARY WRITE TO OUTPUT FILE
      GOTO 10
C BACK ROUND
C
C AT END
      20 CONTINUE
      CLOSE(UNIT=4,STATUS='KEEP')
      CLOSE(UNIT=6,STATUS='KEEP')
      END

```

APPENDIX 4

Program RECSORT

```

*RECSORT.CSS
* FOR SORTING JOB FILE INTO CHRONOLOGICAL ORDER
$IFX REC.UPD;$WRITE FILE BEING UPDATED;$CLEAR;$ENDC
PRE ETM
$JOB
L RECSORT,10;AS 4,JOBREC.DAT,ERO
$TERMJOB
$IFNE 0;CA;ENA ETM;$WRITE FILE BEING SEARCHED;$CLEAR;$ENDC
AL REC.UPD,IN,4; * USED TO INDICATE UPDATE IN PROGRESS
XAL SYSF:RCTEMP.DAT,IN,114/5/2
AS 6,SYSF:RCTEMP.DAT; ST
$IFNE 0; $WRITE SORT ERROR; ENA ETM; $EXIT; $ENDC
$BUILD RECCOPY.CMD
IN SYSF:RCTEMP.DAT
AL JOBREC.DAT,IN,114/10/5
OUT JOBREC.DAT
COPY *,*
REW I
REW O
VERIFY *,*
END
$ENDB
REP SYSF:RCTEMP.DAT,FF00; REP JOBREC.DAT,0; DE JOBREC.DAT
L COPY32,50; ST ,COM=RECCOPY.CMD,LI=NULL:,LO=NULL:
$IFNE 0; $WRITE SORT-COPY ERROR; ENA ETM; $EXIT; $ENDC
REP JOBREC.DAT,FF00; REP SYSF:RCTEMP.DAT,0; DE SYSF:RCTEMP.DAT,RECCOPY.CMD
DEL REC.UPD
ENA ETM; $EXIT

```

\$TITL RECSORT.FTN - SORT THE JOB FILE INTO CALENDAR ORDER
C

```

INTEGER*4 NORTH
INTEGER*2 EAST
C SPLIT MAPREF INTO THE RELEVANT PARTS NOW
CHARACTER*24 NAME
CHARACTER*36 LOCATN
CHARACTER*24 AGNAME
INTEGER*2 RECDAY,RECMTH,RECYR
CHARACTER*9 FILENUM
CHARACTER*3 GEOLST
CHARACTER*2 CATG,GEOL
CHARACTER*1 AGNO,BUFF(114)

```

C AS FOR RECADD.FTN

C

C FOLLOWING ARE FOR THE SORT

```

INTEGER*2 INDEX(8000)
INTEGER*4 IA(8000)

```

C ALLOW FOR 8000 ENTRIES

C

C NOW SET UP EQUIVALENCE

```

EQUIVALENCE (BUFF(1),NAME), (BUFF(25),LOCATN), (BUFF(61),AGNAME),
. (BUFF(85),FILENUM), (BUFF(95),RECDAY), (BUFF(97),RECMTH),

```

```

      . (BUFF(99),RECYR),(BUFF(101),GEOLST),
      . (BUFF(104),AGNO),(BUFF(105),CATG),(BUFF(107),GEOL),
      . (BUFF(109),EAST),(BUFF(111),NORTH)
C THIS IS USED TO ALLOW BINARY OUTPUT FOR FASTER ACCESS
C
      OPEN(UNIT=4,FORM='BINARY',ACCESS='DIRECT',RECL=114)
C OPEN THE INPUT FILE FOR RANDOM AND SEQUENTIAL ACCESS
      REWIND 4
      IREC=0
C COUNTER FOR NUMBER OF RECORDS
      10 READ(4,END=20) BUFF
      IREC=IREC+1
      IF (IREC .GT. 8000) STOP 'MORE THAN 8000 ENTRIES'
      INDEX(IREC)=IREC
C FILL SORT INDEX
      IA(IREC)=RECDAY+((RECMTH+(RECYR*100))*100)
C COMBINE RECDAY,RECMTH AND RECYR TO GET CHRONOLOGICAL NUMER
      GOTO 10
C BACK AROUND
C
C NOW FOR THE WORK
      20 CONTINUE
      IF (IREC .EQ. 0) STOP 'NO RECORDS'
      CALL BUBSTI(INDEX,IA,1,IREC)
C SORT INTO ASCENDING NUMBER - I.E. CHRON ORDER
      OPEN(UNIT=6,FORM='BINARY',RECL=114)
C OPEN OUTPUT FILE
      DO 30 I=1,IREC
      READ(4,REC=INDEX(I)) BUFF
      WRITE(6) BUFF
C COPY TO NEW ORDER
      30 CONTINUE
      CLOSE(UNIT=6,STATUS='KEEP')
      CLOSE(UNIT=4,STATUS='KEEP')
      END
      SUBROUTINE BUBSTI(IR,IA,IBASE,N)
      INTEGER*4 IA(N)
      INTEGER*2 IR(N)
      LOGICAL NSWAP
      IF (N .LE. 1) RETURN
C NOTHING TO SORT
      NM1=N-1
      DO 30 J=IBASE,NM1
      NSWAP=.TRUE.
      IRI=IR(1)
      DO 40 I=IBASE,NM1
      IP1=I+1
      IRIP1=IR(IP1)
      IF (IA(IRI) .LE. IA(IRIP1)) GOTO 40
      NSWAP=.FALSE.
      IR(I)=IRIP1
      IR(IP1)=IRI
      IRIP1=IRI
      40 IRI=IRIP1
      IF (NSWAP) RETURN
      30 CONTINUE
      RETURN
      END

```

APPENDIX 5

Program RECSRCH

```
*RECSRCH.CSS - SEARCH THE JOB FILE
$IFX SYSF:ENGJOBS.TMP; $WRITE STILL PRINTING; $CLEAR;$ENDC
$IFX REC.UPD;$WRITE FILE BEING UPDATED;$CLEAR;$ENDC
L RECSRCH,10; AS 4,JOBREC.DAT,ERO; XAL SYSF:ENGJOBS.TMP,IN,132/3/2
AS 6,SYSF:ENGJOBS.TMP; REW 6; AS 5,CON:; TEMPFILE 3,IN,80; ST
$IFX SYSF:ENGJOBS.TMP; PRI SYSF:ENGJOBS.TMP,DEL,DEV=EPR:; $ENDC; $EXIT
```

\$TITL RECSRCH.FTN - SEARCH JOB FILE

```
C
      INTEGER*4 NORTH
      INTEGER*2 EAST
C SPLIT MAPREF INTO THE RELEVANT PARTS NOW
      CHARACTER*24 NAME
      CHARACTER*36 LOCATN
      CHARACTER*24 AGNAME
      INTEGER*2 RECDAY,RECMTH,RECYR
      CHARACTER*9 FILENUM
      CHARACTER*3 GEOLST
      CHARACTER*2 CATG,GEOL
      CHARACTER*1 AGNO,BUFF(114)
C AS FOR RECADD.FTN
C
C NOW SET UP EQUIVALENCE
      EQUIVALENCE (BUFF(1),NAME),(BUFF(25),LOCATN),(BUFF(61),AGNAME),
      . (BUFF(85),FILENUM),(BUFF(95),RECDAY),(BUFF(97),RECMTH),
      . (BUFF(99),RECYR),(BUFF(101),GEOLST),
      . (BUFF(104),AGNO),(BUFF(105),CATG),(BUFF(107),GEOL),
      . (BUFF(109),EAST),(BUFF(111),NORTH)
C THIS IS USED TO ALLOW BINARY OUTPUT FOR FASTER ACCESS
C
      CHARACTER*80 SNAME,SLOCN,SAGNAM,SAGNO,SYEAR,SGEOLT,SCAT,SGEOL
      INTEGER*2 IYR(30),RNOSTA,YRSTA,RNOSTO,YRSTO,STYPE,SCOUNT
      INTEGER*4 FCOUNT
      CHARACTER*1 AREGN
      REAL*4 ALINE(124)
      INTEGER*2 FFEED
C USED TO PUT FORM FEEDS INTO OUTPUT FILE
      REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
      INTEGER*2 SWATH(100,25)
C ABOVE 2 LINES USED FOR FSTJDN POINT IN POLYGON SEARCH
      LOGICAL NOTIN,INOUT
      DATA FFEED/3072/
C THE FORM FEED CHARACTER IN A1
      OPEN(UNIT=4,FORM='BINARY',RECL=114)
C OPEN THE INPUT FILE
      WRITE(5,100)
      100 FORMAT(' SEARCHING JOB RECORDS')
C
C NOW FOR A FULL SEARCH
      WRITE(6,400)
      400 FORMAT(' SEARCH OPTIONS ARE:')
```

```

WRITE(5,101)
101 FORMAT(' FOR EACH OPTION ENTER EITHER A BLANK LINE OR'/
. ' THE DESIRED VALUES FOR THE OPTION, EACH TERMINATED BY'
. , ' A //' ' E.G. FRED/BILL/TOM/SMITH/')
WRITE(5,102)
102 FORMAT(' NAME?')
READ(5,201) SNAME
201 FORMAT(A80)
IF (SNAME(1:1) .NE. ' ') WRITE(6,401) SNAME
401 FORMAT(' NAME',10X,A80)
WRITE(5,103)
103 FORMAT(' JOB LOCATION?')
READ(5,201) SLOCN
IF (SLOCN(1:1) .NE. ' ') WRITE (6,402) SLOCN
402 FORMAT(' JOB LOCATION',10X,A80)
WRITE(5,104)
104 FORMAT(' AGENCY NAME?')
READ(5,201) SAGNAM
IF (SAGNAM(1:1) .NE. ' ') WRITE(6,403) SAGNAM
403 FORMAT(' AGENCY NAME',10X,A80)
WRITE(5,105)
105 FORMAT(' AGENCY TYPE (0,1,2)?')
READ(5,201) SAGNO
IF (SAGNO(1:1) .NE. ' ') WRITE(6,404) SAGNO
404 FORMAT(' AGENCY NO.',10X,A80)
WRITE(5,106)
106 FORMAT(' YEAR?')
READ(5,201) SYEAR
NYEAR=0
C COUNTER FOR NUMBER OF YEAR OPTIONS INPUT
IF (SYEAR(1:2) .EQ. ' ') GOTO 21
C NO YEAR SEARCH DESIRED
WRITE(6,405) SYEAR
405 FORMAT(' YEAR',10X,A80)
ILAST=1
C COUNT POSITION ALONG INPUT LINE
20 ICHAR=INDEX(SYEAR(ILAST:80),'/')
C LOOK FOR / AS TERMINATOR OF A YEAR
IF (ICHRAR .EQ. 0) GOTO 21
C NO MORE /
ENCODE(BUFF,300) SYEAR(ILAST:ILAST+3)
300 FORMAT(A4)
NYEAR=NYEAR+1
DECODE(BUFF,301) IYR(NYEAR)
301 FORMAT(I4)
C CONVERTED TO AN INTEGER
ILAST=ILAST+ICHRAR
C POSITION TO AFTER THE /
IF (ILAST .NE. 79) GOTO 20
C ROUND FOR NEXT YEAR
C
C NOW GET THE NEXT SEARCH OPTION
21 CONTINUE
WRITE(5,107)
107 FORMAT(' GEOLOGIST?')
READ(5,201) SGEOLT
IF (SGEOLT(1:1) .NE. ' ') WRITE(6,406) SGEOLT
406 FORMAT(' GEOLOGIST',10X,A80)

```

```

WRITE(5,416)
416 FORMAT(' SEARCH ALSO NON-SPECIFIED AREA/SUBJECT MATERIAL (Y)')
READ(5,200) AREGN
200 FORMAT(A1)
IF (AREGN .EQ. 'Y') WRITE(6,417)
417 FORMAT(' SEARCHING ALSO NON-SPECIFIED AREA/SUBJECT MATERIAL')
WRITE(5,108)
108 FORMAT(' SEARCH FOR SITES WITHIN A SPECIFIED AREA (Y)?')
READ(5,200) STYPE
IF (STYPE .EQ. 'Y') GOTO 23
C WANT TO READ COORDS
NCOORD=0
GOTO 26
C DONT WANT TO SEARCH FOR SITES IN AN AREA
C
23 CONTINUE
C READ VERTICES
WRITE(5,109)
109 FORMAT(' NUMBER OF VERTICES OF AREA?'/
. ' ENTER 2 TO SPECIFY A RECTANGLE')
READ(5,*) NCOORD
IF (NCOORD .LT. 2) GOTO 23
C NEED AT LEAST 3 VERTICES TO DEFINE AN AREA
IF (NCOORD .EQ. 2) THEN
WRITE(5,515)
515 FORMAT(' ENTER COORDS OF TWO DIAGONALLY OPPOSITE CORNERS OF ',
. ' THE RECTANGLE'/' ONE PER LINE IN THE FORM EASTNORTH')
ELSE
WRITE(5,110)
110 FORMAT(' ENTER VERTEX COORDS IN CLOCKWISE ORDER'/
. ' ONE PER LINE IN FORM EASTNORTH')
ENDIF
IXMAX=-999999999
IXMIN=-IXMAX
IYMAX=IXMAX
IYMIN=IXMIN
C USE THESE TO STORE THE RANGE OF THE AREA
DO 24 I=1,NCOORD
READ(5,303) IX,IY
303 FORMAT(I4,I5)
C GET INTO 100'S OF METRES EAST AND NORTH
IXMAX=MAX0(IX,IXMAX)
IXMIN=MIN0(IX,IXMIN)
IYMAX=MAX0(IY,IYMAX)
IYMIN=MIN0(IY,IYMIN)
C FIND THE RANGE
X(I)=IX*0.1
Y(I)=IY*0.1
C CONVERT TO KM BEFORE STORING
24 CONTINUE
IF (NCOORD .GT. 2) THEN
IF (X(1) .NE. X(NCOORD) .OR. Y(1) .NE. Y(NCOORD)) THEN
NCOORD=NCOORD+1
X(NCOORD)=X(1)
Y(NCOORD)=Y(1)
C CLOSE AREA
ENDIF
WRITE(6,407)

```

```

407 FORMAT(' AREA COORDINATES (KM)')
WRITE(6,408) (X(I),Y(I),I=1,NCOORD)
408 FORMAT(20X,4(F14.2,F9.2))
NCOORD=NCOORD-1
C ROUTINE FOR LOCATING POINTS DOESNT REQUIRE CLOSURE
CALL PREPLY(X,Y,NCOORD,YINTVL,INTVLS,SWATH,RSLOPE)
C CUT THE SEARCH AREA UP INTO SWATHS
ELSE
WRITE(6,516) IXMIN,IXMAX,IYMIN,IYMAX
516 FORMAT(' SEARCH RECTANGLE FROM',I5,' OOME TO',I5,' OOME AND FROM',
I6,' OOMN TO',I6,' OOMN')
ENDIF
C
26 CONTINUE
WRITE(5,111)
111 FORMAT(' CATEGORY (0-5)?')
READ(5,201) SCAT
IF(SCAT(1:1) .NE. ' ') WRITE(6,409) SCAT
409 FORMAT(' CATEGORY',10X,A80)
WRITE(5,112)
112 FORMAT(' GEOLOGY (0-9)?')
READ(5,201) SGEOL
IF (SGEOL(1:1) .NE. ' ') WRITE(6,410) SGEOL
410 FORMAT(' GEOLOGY',10X,A80)
C END OF OPTION INPUT
C
C*****
C NOW FOR THE SEARCH
FCOUNT=0
C COUNTER FOR NUMBER OF FOUND ENTRIES
27 READ(4,END=40) BUFF
C READ ONE ENTRY
IF (NOTIN(SNAME,NAME)) GOTO 27
C NOT THE RIGHT NAME
IF(NOTIN(SLOCN,LOCATN)) GOTO 27
C NOT THE RIGHT LOCATION
IF(NOTIN(SAGNAM,AGNAME)) GOTO 27
C NOT THE AGENCY
IF (SAGNO(1:1) .NE. ' ' .AND. INDEX(SAGNO,AGNO) .EQ. 0) GOTO 27
C NOT THE DESIRED AGENCY NUMBER
IF (NYEAR .NE. 0) THEN
DO 28 I=1,NYEAR
IF (IYR(I) .EQ. RECYR) GOTO 29
28 CONTINUE
GOTO 27
C NOT FOUND SO FALL OUT
29 CONTINUE
ENDIF
C LOOKED FOR YEAR
IF (NOTIN(SGEOLT,GEOLST)) GOTO 27
C NOT THE GEOLOGIST
IF (AREGN .EQ. 'Y') THEN
IF (EAST .EQ. 0 .AND. NORTH .EQ. 0) GOTO 41
C IF FOUND A GENERAL REPORT DONT ALSO DO A COORDINATE SEARCH
IF (NCOORD .EQ. 0) GOTO 27
C IF NOT CHECKING COORDS AS WELL AND IT WASNT A GENERAL GO BACK ROUND
ENDIF
C NOT AN AREA OR SUBJECT SPECIFIC REPORT

```

```

IF (NCOORD .NE. 0) THEN
  IF (EAST .LT. IXMIN .OR. EAST .GT. IXMAX) GOTO 27
  IF (NORTH .LT. IYMIN .OR. NORTH .GT. IYMAX) GOTO 27
C CANT POSSIBLY BE IN AREA
  IF (NCOORD .GT. 2) THEN
    XTMP=EAST*0.1
    YTMP=NORTH*0.1
C CONVERT TO KM
  IF (.NOT. INOUT(XTMP,YTMP,X,Y,YINTVL,INTVLS,SWATH,RSLOPE))
    GOTO 27
C NOT IN THE SPECIFIED AREA
  ENDIF
C FOR THE SIMPLE RECTANGLE DONT NEED THE POLYGON SEARCH
  ENDIF
  41 IF (NOTIN(SCAT,CATG)) GOTO 27
C NOT RIGHT CATEGORY
  IF (NOTIN(SGEOL,GEOL)) GOTO 27
C NOT RIGHT GEOLOGY
C IF FINALLY GET TO HERE HAVE FOUND AN ENTRY THAT MATCHES THE
C SEARCH OPTIONS
C
  IF (MOD(FCOUNT,53) .EQ. 0) CALL HEAD
C HEAD PAGE
  FCOUNT=FCOUNT+1
C INCREMENT FOUND ENTRY COUNTER
  WRITE(6,412) NAME,LOCATN,AGNAME,FILENUM,RECDAY,RECMTH,RECYR,
    GEOLST,EAST,NORTH,CATG,GEOL
  412 FORMAT(A24,' ',A36,' ',A24,' ',A9,' ',2(I2,' '),I4,
    ' ',A3,' ',I4,I5,' ',A2,1X,' ',1X,A2)
  GOTO 27
C BACK AROUND
C
C NOW AT THE END OF THE RUN
  40 CONTINUE
  WRITE(6,414) FFEED
  414 FORMAT(1A1,
    . /' AGENCY TYPE'
    . /'      0 GOVT.          1 PROF.          2 INDIV.'//
    . /' CATEGORY'
    . /'      0 GROUNDWATER    1 SLOPE          2 EXPANSIVE'
    . /'                          STABILITY        SOILS'
    . /'      3 FOUNDATION    4 MISCELLANEOUS'
    . /'      INVESTIGATION'//
    . /' GEOLOGY'
    . /'      0 QUATERNARY     1 TERTIARY        2 TRIASSIC'
    . /'                          SEDIMENTS'
    . /'      3 PERMIAN        4 LOWER          5 CAMBRIAN'
    . /'                          PALAEOZOIC'
    . /'      6 PRECAMBRIAN    7 TERTIARY        8 JURASSIC'
    . /'                          BASALT          DOLERITE'
    . /'      9 GRANITE')
C NOW DECIDE IF IT IS GOING TO BE PUT OUT ON THE SCREEN
  WRITE(5,115) FCOUNT
  115 FORMAT(I7,' RECORDS WERE FOUND'/' DO YOU WANT A',
    ' SCREEN LISTING (Y OR N)?')
  READ(5,200) STYPE
  IF (STYPE .EQ. 'N') GOTO 47
C NO SCREEN LIST WANTED

```

```

        REWIND (6)
C BACK TO THE START
        SCOUNT=0
C COUNTER FOR NUMBER OF LINES ON SCREEN
        45 READ(6,415) ALINE
        415 FORMAT(2A4,124A1)
        IF (ALINE(1) .EQ. ' AGE' .AND. ALINE(2) .EQ. 'NCY ') GOTO 47
C TEST FOR THE END OF THE ENTRIES
        WRITE(5,116) ALINE
        116 FORMAT(1X,2A4,54A1/8X,70A1)
        SCOUNT=SCOUNT+1
        IF (SCOUNT .LT. 10) GOTO 45
C ALLOW 10 ENTRIES PER SCREENFULL
        SCOUNT=0
C RESET
        WRITE(5,117)
        117 FORMAT(' LIST MORE ENTRIES ON SCREEN (Y OR N)?')
        READ(5,200) STYPE
        IF (STYPE .EQ. 'Y') GOTO 45
C ROUND AGAIN FOR ANOTHER SCREEN FULL
        47 WRITE(5,118)
        118 FORMAT(' DO YOU WANT A PRINTOUT (Y OR N)?')
        READ(5,200) STYPE
        IF (STYPE .NE. 'Y' .OR. FCOUNT .EQ. 0) THEN
            CLOSE(UNIT=6,STATUS='DELETE')
            STOP
C CLOSE FILE AND DELETE IT THEN STOP
        ENDIF
        CLOSE(UNIT=6,STATUS='KEEP')
        STOP
        END
        LOGICAL FUNCTION NOTIN(SSTRNG,RSTRNG)
C SSTRNG CONTAINS A SERIES OF STRINGS TERMINATED BY /
C E.G.   FRED/BILL/TOM/
C AND RSTRNG IS SEARCHED FOR THE OCCURENCE OF ONE OF THESE STRINGS
C IF ONE IS FOUND TO MATCH NOTIN IS .FALSE.
C IF STRNG IS EMPTY NOTIN IS .FALSE.
        CHARACTER*80 SSTRNG
        CHARACTER* (*) RSTRNG
        NOTIN=.FALSE.
        IF (SSTRNG(1:1) .EQ. ' ') RETURN
C NO NEED TO LOOK
        ILAST=1
C COUNTER FOR POSITION IN SSTRNG
        20 ICHAR=INDEX(SSTRNG(ILAST:80),'/')
C LOOK FOR / AS TERMINATOR OF STRING
        IF (ICHRAR .EQ. 0) GOTO 25
C HAVENT FOUND A MATCH BY THE END OF THE LINE
        IF (INDEX(RSTRNG,SSTRNG(ILAST:ILAST+ICHRAR-2)) .NE. 0) RETURN
C LOOK BETWEEN /S IN SSTRNG AND IF FIND A MATCH RETURN
        ILAST=ILAST+ICHRAR
C POSITION AFTER THE /
        IF (ILAST .LE. 79) GOTO 20
C BACK ROUND IF NOT AT END OF LINE
C
C ELSE END
        25 CONTINUE
        NOTIN=.TRUE.

```

C NO MATCH
RETURN
END

SUBROUTINE HEAD
C HEAD UP PAGES FROM SEARCH
INTEGER*2 FFEED
DATA FFEED/3072/
C USED TO PUT FORM FEEDS IN OUTPUT FILE
WRITE(6,100) FFEED
100 FORMAT(1A1/9X,'NAME',11X,';',11X,'JOB LOCATION',12X,';',9X,
. 'AGENCY',9X,'; RECORDS : DATE ;INI; MAPREF ;',
. 'CAT; GEOL'/24X,';',36X,';',10X,'NAME',10X,';',
. 3X,'FILE',2X,'; RECEIVED ;',3X,';',9X,';',3X,';'/
. 130('-'))
RETURN
END

\$INCLUDE FSTJDN.FTN,-(NLIST)

\$TITL FSTJDN.FTN - POINT IN POLYGON
C PROGRAM COLLECTION FASTJORDAN
C SALOMON,K.B., 1978. AN EFFICIENT POINT-IN-POLYGON ALGORITHM
C COMPUTERS AND GEOSCIENCES, V4, NO. 2, P. 173-178
C
C USE BY READING VERTICES OF POLYGON IN ORDER (BUT NOT CLOSING IT)
C AND CALLING PREPLY ONCE BEFORE THE SEARCH IS BEGUN. THE ACTUAL
C SEARCHING IS DONE BY MEANS OF THE LOGICAL FUNCTION INOUT.

C SUBROUTINE PREPLY(X,Y,NUVERT,YINTVL,INTVLS,SWATH,RSLOPE)
C
C*****
C THIS ROUTINE PREPARES THE POLYGON CONSISTING OF THE NUVERT VERTICES
C (X(I),Y(I)) BY FIRST SORTING THE SEGMENT Y-END POINTS INTO
C DECREASING ORDER AND FORMING AN INTERVAL FOR EACH CONSECUTIVE PAIR:
C (YINTVL(I),YINTVL(I+1)), I=1,INTVLS. THIS IS PERFORMED BY CALLING
C SORT.
C THE CODE CONSISTING OF THE DO 100 AND DO 200 LOOPS CONSTRUCTS,
C FOR EACH INTERVAL I, THE LIST OF SEGMENTS TO BE TESTED BY INOUT.
C THIS LIST IS PLACED IN THE I-TH ROW OF SWATH. THE FIRST ENTRY,
C SWATH(I,1), WILL BE SET TO THE NUMBER OF SEGMENTS IN THE ROW. NOTE
C THAT AS YINTVL CONTAINS NO REDUNDANCIES, I.E. YINTVL(I) IS STRICTLY
C GREATER THAN YINTVL(I+1), NO HORIZONTAL SEGMENTS WILL BE PLACED IN
C THE LIST.
C THE CODE CONSISTING OF THE DO 300 LOOP ESTABLISHES THE
C RECIPROCAL SLOPE FOR EACH NON-HORIZONTAL SEGMENT. THIS IS TO BE
C USED BY INOUT. FINALLY, THE SEGMENTS WITHIN A ROW OF SWATH ARE
C OREORDERED FROM LEFT-TO-RIGHT.
C
C*****
C

INTEGER*2 SWATH(100,25)
REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
CALL SORT(Y,NUVERT,YINTVL,INTVLS)
IF (INTVLS .LE. 0) GOTO 400
X(NUVERT+1)=X(1)
Y(NUVERT+1)=Y(1)
DO 100 I=1,INTVLS

```

100 SWATH(I,1)=0
   DO 200 I=1,INTVLS
     DO 200 J=1,NUVERT
       IF (Y(J).GE.YINTVL(I) .AND. YINTVL(I+1).GE.Y(J+1) .OR.
*       Y(J+1).GE.YINTVL(I) .AND. YINTVL(I+1).GE.Y(J))
*         CALL INCLUD(SWATH,I,J)
200 CONTINUE
   DO 300 I=1,NUVERT
     IF (Y(I).EQ.Y(I+1)) GOTO 300
     RSLOPE(I)=(X(I+1)-X(I))/(Y(I+1)-Y(I))
300 CONTINUE
   CALL ORDER(X,Y,YINTVL,INTVLS,SWATH,RSLOPE)
   RETURN
400 WRITE(7,401)
401 FORMAT(' ***** PREP OF POLYGON ABORTED SINCE NO INTERVALS',
* ' CONSTRUCTED')
   STOP
   END
   SUBROUTINE SORT(Y,NUVERT,YINTVL,INTVLS)
C
C*****
C
C ROUTINE ESTABLISHES THE INTERVALS OF THE Y-AXIS DEFINED BY THE
C ENDPOINTS OF THE POLYGON'S SEGMENTS. THE DO 100 LOOP INITIALISES
C YSORT FROM THE SEGMENT Y-END POINTS. THE DO 200 LOOPS SORT YSORT
C INTO DESCENDING ORDER. THE DO 300 LOOP ELIMINATES REDUNDANCIES IN
C YSORT AND PLACES IRREDUNDANT SORTED Y'S INTO YINTVL. IT ALSO SETS
C INTVLS TO THE TRUE NUMBER OF Y INTERVALS. JUST PRIOR TO RETURNING
C A FINAL INTERVAL EXTENDING TO '-INFINITY' IS ESTABLISHED.
C
C*****
C
   REAL Y(100),YINTVL(100),YSORT(100)
   INTEGER*2 UPPER
   DO 100 I=1,NUVERT
100 YSORT(I)=Y(I)
   UPPER=NUVERT-1
   DO 200 I=1,UPPER
     IPLS1=I+1
     DO 200 J=IPLS1,NUVERT
       IF (YSORT(I).GE.YSORT(J)) GOTO 200
       TEMP=YSORT(I)
       YSORT(I)=YSORT(J)
       YSORT(J)=TEMP
200 CONTINUE
   YINTVL(1)=YSORT(1)
   INTVLS=0
   DO 300 I=1,UPPER
     IF (YSORT(I).EQ.YSORT(I+1)) GOTO 300
     INTVLS=INTVLS+1
     YINTVL(INTVLS+1)=YSORT(I+1)
300 CONTINUE
   YINTVL(INTVLS+2)=-1.0E75
   RETURN
   END
   SUBROUTINE INCLUD(SWATH,I,J)
C
C*****

```


C THE FOUR LINES ENCLOSED IN DASHES DETERMINE THE INTERVAL CONTAINING
 C YP. THE DO 400 LOOP CONTINUES UNTIL THE FIRST SEGMENT WITHIN THE
 C INTERVAL FALL TO THE LEFT OF (XP,YP). IN THIS EVENT, INOUT IS SET
 C .TRUE. IFF AN EVEN NUMBER OF SEGMENTS HAS BEEN TESTED.

C

C*****

C

```
REAL X(100),Y(100),YINTVL(100),RSLOPE(100)
INTEGER*2 SWATH(100,25),SEGNO
INOUT=.FALSE.
```

C-----

```
INTVAL=0
100 INTVAL=INTVAL+1
    IF (YINTVL(INTVAL) .GT. YP) GOTO 100
    INTVAL=INTVAL-1
```

C-----

```
300 IF (INTVAL.LT.1 .OR. INTVAL.GT.INTVLS) RETURN
    NMBSEG=SWATH(INTVAL,1)+1
    DO 400 I=2,NMBSEG
        SEGNO=SWATH(INTVAL,I)
        IF(XP-X(SEGNO).LE.(YP-Y(SEGNO))*RSLOPE(SEGNO)) GOTO 500
400 CONTINUE
    RETURN
500 INOUT=MOD(I,2) .EQ. 1
    RETURN
    END
```