





AMOCO AUSTRALIA PETROLE
PELICAN #1
AUSTRALIA
219820
1 cm


317135
DC-277
THE DOW CHEMICAL COMPANY
FILE COPY
Midland, Michigan
Date 10-27-1967
Time 10:30 AM
Operator












































































































































































ARGO PRODUCTION COMPANY
ARGOSYS PETROLEUM
PLATFORM A
PLAT. SLOT A - X, Y: 500,2000
WATER DEPTH: 1,000 FT
DRILL RIG: SEMI-SUBMERSIBLE
ZONE
ZONE TOP
ZONE BAT
OIL
FEET
GAS
FEET
Ro:
2134.7500
2174.9000
TOTAL POSSIBLE PAY IN NOTICE INTERVAL
POSSIBLE PAY: 39.1500
ARGO PRODUCTION COMPANY
ARGOSYS PETROLEUM
PLATFORM A
PLAT. SLOT A - X, Y: 500,2000
WATER DEPTH: 1,000 FT
DRILL RIG: SEMI-SUBMERSIBLE
ZONE
ZONE TOP
ZONE BAT
OIL
FEET
GAS
FEET
Ro:
2134.7500
2174.9000
TOTAL POSSIBLE PAY IN NOTICE INTERVAL
POSSIBLE PAY: 39.1500
ARGO PRODUCTION COMPANY
ARGOSYS PETROLEUM
PLATFORM A
PLAT. SLOT A - X, Y: 500,2000
WATER DEPTH: 1,000 FT
DRILL RIG: SEMI-SUBMERSIBLE
ZONE
ZONE TOP
ZONE BAT
OIL
FEET
GAS
FEET
Ro:
2134.7500
2174.9000
TOTAL POSSIBLE PAY IN NOTICE INTERVAL
POSSIBLE PAY: 39.1500
ARGO PRODUCTION COMPANY
ARGOSYS PETROLEUM
PLATFORM A
PLAT. SLOT A - X, Y: 500,2000
WATER DEPTH: 1,000 FT
DRILL RIG: SEMI-SUBMERSIBLE
ZONE
ZONE TOP
ZONE BAT
OIL
FEET
GAS
FEET
Ro:
2134.7500
2174.9000
TOTAL POSSIBLE PAY IN NOTICE INTERVAL
POSSIBLE PAY: 39.1500
ARGO PRODUCTION COMPANY
ARGOSYS PETROLEUM
PLATFORM A
PLAT. SLOT A - X, Y: 500,2000
WATER DEPTH: 1,000 FT
DRILL RIG: SEMI-SUBMERSIBLE
ZONE
ZONE TOP
ZONE BAT
OIL
FEET
GAS
FEET
Ro:
2134.7500
2174.9000
TOTAL POSSIBLE PAY IN NOTICE INTERVAL
POSSIBLE PAY: 39.1500




ANADRILL
ANADRILL SCHLUMBERGER
ANADRILL PRODUCTION COMPANY
HERMITTE PEINDRE.FLM
PIP2PM 1
21/10/01
PIP2PM 1
21/10/01
HERMITTE PEINDRE.FLM



ARCO
In cooperation with Petroleum Corporation
BASIN
COMPUTER LOG ANALYSIS DISPLAYS
PART-2
PIPIPA-1
Ref. 387 Ref. API RP 40, Appendix F
F. Bates Enclosure 55

02.27


313761





ARCO PRODUCTION COMPANY


HEMATITE PETROLEUM PIPIPA 1 Z12520


******** RESERVOIR QUALITY PLOT **********
CUTT-SFFS: VSH =< 50%, EFFECTIVE POROSITY >= 15.0000
NET THICKNESS = 219.7638 AUNITS
AVG. EFFEC. POR = 23.8249
DATE-09/05/87





| | | | |
|---|---|---|---|
| 1500 | | | |
| 1510 | | | |
| 1520 | | | |
| 1530 | 10.7 | 32.5 | 23.4 |
| 1540 | 1.5<br>3.4 | 31.2<br>29.3 | 19.3<br>18.9 |
| 1550 | 1.5 | 27.8 | 12.6 |
| 1560 | 1.5<br>4.0 | 28.2<br>27.3 | 14.0<br>17.3 |
| 1570 | 1.5<br>1.5<br>1.5<br>3.4 | 33.0<br>32.1<br>32.1<br>36.3 | 17.5<br>20.1<br>20.1<br>26.6 |
| 1580 | 1.5 | 35.0 | 20.7 |
| 1590 | 6.4 | 31.0 | 22.5 |
| 1600 | 9.4<br>1.5<br>1.5 | 31.7<br>28.0<br>28.0 | 25.2<br>17.9<br>17.9 |
| 1610 | 1.2 | 31.5 | 15.3 |
| 1620 | 1.5<br>2.4 | 28.5<br>31.6 | 18.8<br>22.7 |
| 1630 | 17.4 | 33.7 | 28.7 |
| 1640 | 1.5<br>1.5<br>1.5 | 34.6<br>34.6<br>34.6 | 24.9<br>24.9<br>24.9 |
| 1650 | | | |
| 1660 | 8.7 | 31.2 | 23.6 |
| 1670 | 1.5 | 30.5 | 21.5 |
| 1680 | 5.8<br>1.5 | 33.0<br>35.4 | 27.0<br>24.8 |
| 1690 | 15.2 | 33.8 | 27.7 |
| 1700 | | | |
| 1710 | 10.1 | 32.4 | 24.8 |
| 1720 | | | |
| 1730 | 1.5<br>1.8 | 30.3<br>28.0 | 17.2<br>16.9 |
| 1740 | | | |
| 1750 | | | |
| 1760 | 1.5<br>1.8 | 33.6<br>29.8 | 15.4<br>19.2 |
| 1770 | 6.8 | 30.9 | 24.2 |
| 1780 | | | |
| 1790 | 2.4<br>1.5<br>6.7 | 28.7<br>30.4<br>28.1 | 18.2<br>18.8<br>20.2 |
| 1800 | 10.1 | 31.6 | 23.8 |
| 1810 | 1.5<br>5.2 | 32.8<br>29.2 | 19.9<br>22.1 |
| 1820 | 1.5<br>6.1 | 33.5<br>33.4 | 19.8<br>26.3 |
| 1830 | | | |
| 1840 | 8.5<br>2.4 | 34.7<br>30.8 | 27.1<br>21.1 |
| 1850 | 2.1 | 34.2 | 23.9 |
| 1860 | 4.8<br>2.1 | 35.1<br>30.8 | 14.8<br>21.5 |
| 1870 | 3.0<br>1.5 | 31.6<br>30.8 | 21.5<br>17.2 |
| 1880 | 1.8 | 28.7 | 19.6 |
| 1890 | 3.0<br>1.5<br>3.4 | 31.2<br>34.3<br>35.3 | 24.7<br>22.2<br>25.3 |
| 1900 | 9.4 | 31.2 | 24.4 |
| 1910 | | | |
| 1920 | | | |
| 1930 | 1.5<br>1.5 | 31.2<br>30.4 | 18.1<br>20.5 |
| 1940 | | | |
| 1950 | 5.8 | 28.4 | 22.5 |
| 1960 | | | |
| 1970 | 4.5 | 27.3 | 15.5 |
| 1980 | | | |
| 1990 | 2.4 | 31.7 | 19.5 |
| 2000 | | | |
| 2010 | 6.8 | 30.2 | 22.1 |
| 2020 | | | |
| 2030 | 1.5<br>1.5 | 31.7<br>31.7 | 18.2<br>18.2 |
| 2040 | | | |
| 2050 | 1.5<br>6.4 | 22.8<br>30.1 | 9.6<br>23.3 |
| 2060 | | | |
| 2070 | 1.5 | 35.5 | 10.2 |
| 2080 | | | |
| 2090 | | | |
| 2100 | | | |
| 2110 | | | |
| 2120 | | | |
| 2130 | | | |
| 2140 | | | |
| 2150 | | | |
| 2160 | | | |
| 2170 | | | |
| 2180 | | | |
| 2190 | | | |
| 2200 | | | |



Weatherford International Limited
Houston, Texas
Weatherford Directional Services
Weatherford Directional Drilling
Survey Report
Company: Chesapeake Operating, Inc.
Field: Bradford County (NAD 83)
Well: Bradford County
Location: Bradford County, PA
Rig: Nabors M-27
Job Number: 0000
Survey Name: Survey #1
Survey Date: 3/31/2013
















ESSO P00NBOON 1 Z11120
BUTLER PLOT - ZONE ALL
X1TOP= 6000.00 X1BOT=10885.00 HOLGATE=NO DATE=08/29/87
STMOD= 3 COMPUTATION STARTED AT 0
JOB NAME=P00NODCC. PLOT TAPE VOL. SER.=TD8713




ESSO P00NBOON 1 Z11120
PICKETT PLOT - ZONE ALL
X1TOP= 6000.00 X1BOT=10885.00 HOLGATE=NO DATE=08/29/87
STMOD= 3 COMPUTATION STARTED AT 0
JOB NAME=P00NODCC. PLOT TAPE VOL. SER.=TD8713 2.25 AVERAGE PHIE = 18.75

