

MARGIEADDITIONAL EQUIPMENT

I. VESSEL MOORING SYSTEM

- A. Two (2) spare 33,000 lbs. LWT anchors.
- B. Pendant wires and sockets as required.
- C. Two (2) spare pendant buoys.

II. DRILL STRING HANDLING TOOLS

A. Slips:-

- 1. Two (2) Varco type "DCS-S" drill collar slips, P/N 2573, for 4-3/4" drill collars.
- 2. Two (2) Varco type "SCX-L" rotary slips, P/N 15515, for 3-1/2" drill pipe.
- 3. One (1) Varco type "SDS" tubing slips, P/N 19326 for 2-7/8" to 3-1/2" drill pipe.

B. Elevators:-

- 1. Two (2) Webb Wilson type T-150 center latch elevators, P/N 8536-5182 for 3-1/2" O.D. 18-1/2" taper drill pipe.
- 2. One (1) B.J. type "YT" center latch elevators, P/N 23105 C/W.
One (1) 3-1/2" slip assembly, P/N 23108-5, and
One (1) 2-7/8" slip assembly, P/N 23108-4 for
3-1/2" and 2-7/8" tubing.

III. DRILL STRING

A. Drill Pipe:-

- 1. 3,000' - 3-1/2" O.D., Grade E, drill pipe; with 4-3/4" O.D. tool joints with 3-1/2" I.F. box and pin connections.

B. Drill Collars:-

- 1. Twenty-five (25) 4-3/4" x 2-1/4" I.D. x 31' long drill collars w/3-1/2" I.F. connections with zip groove slip and elevator recess.