

TELEX MESSAGE

TELEX MESSAGE

1100 - 1330: CIRC., CMT. WITH 225 SX CMT PLUS 10 PER CENT GEL,
 FOLLOW WITH 700 SX NEAT CL. 'G' CMT. BUMP PLUG
 WITH 2000 PSI. FLOAT HELD.
 1330 - 1600: PULL RT, RIH WITH JET TOOL; WASH WH; RU AND SET
 SEAL ASSEMBLY.
 1600 - 1930: TEST BOP AND RUN WB
 1930 - 2330: CHG. BHA AND RIH
 2330 - 2400: SLIP AND CUT DRILL LINE

271228

WEATHER: MAX WIND 35-40 KTS E; MAX SEA 6 FT E.
 HEAVE 3 FT; PITCH 1; ROLL 1.1/2 DEG

MUD DETAILS:

TYPE: FRESHWATER GEL	WEIGHT: 9.5 PPG	F.VIS: 46	W.L.: 12/8
PH: 10.5	MUD CAKE: 3/32	YP: 16	PV: 15
CHL: 16,500	CA: 120	NITR: -	
CONT./ 2			

*
TASROK AA58276

PAGE: 2 A0480027

GEOLOGICAL REPORT: NOT APPLICABLE

REGARDS, BRIDGE OIL SYDNEY
G.G.FENTON/K.SKIPPER,

REPLY TO:

*
 TASROK AA58276
 BRIOIL AA26518*
 TASROK AA58276