CWLS LOG

CWLS Log

COMPANY: ANYCOMP OIL LTD.
WELL: DEVIL 33
FIELD: WILDCAT
LOCATION: 1234 FSL 5678 FEL
SECTION: 33 TOWNSHIP: 4 N RANGE: 5 W
COUNTY: ANYCOUNTY STATE: ALBERTA

LOCATION: 1234 FSL 5678 FEL
SECTION: 33 TOWNSHIP: 4 N RANGE: 5 W

PERMANENT DATUM: ELEVATIONS:
LOG MEASURED FROM: 7.5 m KB KB: 1234.5 m
7.5 m ABOVE PERM. DATUM DF: 1233.0 m
CWLS Reference Point: GL: 1226.0 m

DATE:
RUN NO.: AT TOP RUN

DEPTH DRILLER: 1275.0 m
DEPTH LOGGER: 1274.5 m
BTM. LOG INTERVAL: 1270.0 m
TOP LOG INTERVAL: 1000.0 m

CASING DRILLER: 339.0 m @ 244.5 mm
CASING LOGGER: 339.0 m @ 244.5 mm
BIT SIZE: 311.1 mm @ 339.0 m TO 1275.0 m
TYPE FLUID IN HOLE: LIGNOSULFONATE/GELPOLY
DENSITY: 1.18 g/cm³
VISCOSITY: 48 s
PH: 10.5
FLUID LOSS: 12.0 cm³/30 min
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.180 ohmm @ 21.0 degC
RMF @ MEAS. TEMP: 0.150 ohmm @ 21.0 degC
RMC @ MEAS. TEMP: 0.220 ohmm @ 21.0 degC
RM @ BHT: 0.095 ohmm @ 68.0 degC
TIME CIRCULATED: 12.0 h
TIME LOGGER ON BTM.: 2015-06-14 01:30
MAX. REC. TEMP.: 68.0 degC
EQUIPMENT NUMBER:
LOCATION:
RECORDED BY: ENGINEER, J. SMITH
WITNESSED BY: SUPERVISOR, A. N. OPERATOR

REMARKS:
RUN 1 - 339.0 m TO 1275.0 m

EQUIPMENT NUMBERS

DLL-MSFL	1234	TCC-B	5678
BHC-AC-GR	1235	SDL-DSN	5679

DLL-MSFL: DUAL LATEROLOG-MICRO SFL; BHC-AC-GR: BOREHOLE COMPENSATED SONIC-GAMMA RAY; TCC-B: TRIPLE COMBO CABLE; SDL-DSN: SPECTRAL DENSITY-DUAL SPACED NEUTRON. ALL TOOLS RUN IN COMBINATION. LOGGED UP AT 1800 M/H. CALIPER CHECKED IN CASING AT 339.0 M. REPEAT SECTION 1000.0 M TO 1050.0 M. MAIN PASS 1270.0 M TO 1000.0 M. NO DIFFICULTIES ENCOUNTERED. TOOLS DECENTRALIZED IN OPEN HOLE. GOOD REPEATABILITY OBSERVED.

CHANNEL PARAMETERS

NAME	VALUE	UNIT	DEPTH 1 m	NAME	VALUE	UNIT	DEPTH 1 m
GR	0.000	GAPI	1000.0	GR	0.000	GAPI	1000.0
GR	150.000	GAPI	1270.0	GR	150.000	GAPI	1270.0
RT	0.200	OHMM	1000.0	RT	0.200	OHMM	1000.0
RT	2000.000	OHMM	1270.0	RT	2000.000	OHMM	1270.0