OR-0282

ENCLOSURE 15.

Schlumberger

DIL-MSFL-LSS-GR 1/200 DATA TRANS.

CSU Field Log

COMPANY: BRIDGE OIL LTD

WELL: SEAL #1

FIELD: WILDCAT
RIG : MARGIE
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: BASS STRAIT E.P. T-19-P.

LATITUDE: 039 21 49.2 S
LONGITUDE: 144 52 51.5 E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM: 0.0 M
LOG MEASURED FROM: KB
25.3 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 25.3 M
DF: 25.0 M
GL: -64.6 M

DATE: 20 FEB 86
RUN NO: 2

OTHER SERVICES-
LDL-CNL-GR
CST-GR

PROGRAM
TAPE NO:
28.4
SERVICE
ORDER NO:
MGE86-04

DEPTH-DRILLER:	1670.0 M		
DEPTH-LOGGER:	1670.0 M		
BTM. LOG INTERVAL:	1668.5 M		
TOP LOG INTERVAL:	644.0 M		
CASING-DRILLER:	232.0 M	642.0 M	
CASING-LOGGER:	232.0 M	644.0 M	
CASING:	20 "	13 3/8 "	
WEIGHT:	94.0000 LB/F	68.0000 LB/F	
BIT SIZE:	26 "	17 1/2 "	12 1/4 "
DEPTH:	261.0 M	656.0 M	1670.0 M

TYPE FLUID IN HOLE: LIGNOSULFONATE/DEXTRID
DENSITY: 9.80 LB/G
VISCOSITY: 44.0 S
PH: 9.5
FLUID LOSS: 5.0 C3
SOURCE OF SAMPLE: MUDPIT
RM: .492 OHMM AT 16.0 DEGC
RMF: .395 OHMM AT 15.0 DEGC
RMC: .628 OHMM AT 13.0 DEGC
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .206 OHMM AT 68.3 DEGC
RMF AT BHT: .161 OHMM AT 68.3 DEGC
RMC AT BHT: .242 OHMM AT 68.3 DEGC

TIME CIRC. STOPPED: 23:50 (19/2)
TIME LOGGER ON BTM.: 05:30 (20/2)

MAX. REC. TEMP: 68.3 DEGC

LOGGING UNIT NO: 390
LOGGING UNIT LOC: VEA
RECORDED BY: I. CHANDRA / T. BROPHY
WITNESSED BY: M. HANZALIK / D. BROOKMAN

REMARKS:

5 cm

TOOL STRING RUN ECCENTRALIZED
1 1/2" STAND OFF USED ON DITD
SONIC SKIPPING IS DUE TO ROUGH HOLE CONDITIONS.
THERMOMETER READINGS : 155 DEGF AND 155 DEGF.

EQUIPMENT NUMBERS-

SGC-JC 3374	SLC-KB 1908	SLS-SC 203	SLM-DA 835
DIC-DA 1435	DIS-EC 1471	IEM-BE 1759	NSM-A 2794
SRE-CB 1715	DRS-C 3714		

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 28.4 FILE 102 21- -14 00:17
DATA ACQUIRED 20-FEB-86 07:21

EVENT MARK SUMMARY:

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	.100000 M3	LEFT EDGE
ITT	.00100000 S	RIGHT EDGE

BS (IN) 10.000 20.000
CALI(IN) 10.000 20.000
GR (GAPI) 0.0 200.00
SP (MV) -80.00 20.000

ILD (OHMM) 200.00 20000.
SFLU(OHMM) 200.00 20000.
MSFL(OHMM) 200.00 20000.
ILD (OHMM) .20000 200.00
MSFL(OHMM) .20000 200.00
SFLU(OHMM) .20000 200.00

DT (US/F) 140.00 40.000
DTL (US/F) 140.00 40.000

CP 28.4 FILE 102 21- -14 00:17
DATA ACQUIRED 20-FEB-86 07:21