ENCLOSURE 19.

Schlumberger

LDL-CNL-GR-CAL 1:200 SUITE#2 RUN#1

[illegible]

CSU Field Log

COMPANY: BRIDGE OIL LTD

WELL: SEAL #1

FIELD: WILDCAT
RIG : MARGIE
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: BASS STRAIT E.P. T-19-P

LATITUDE: 039 21 49.2 S
LONGITUDE: 144 52 51.5 E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM: 0.0 M
LOG MEASURED FROM: KB
25.3 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 25.3 M
DF: 25.0 M
GL: -64.6 M

DATE: 20 FEB 86
RUN NO: 1

OTHER SERVICES-
DIL-LSS-MSFL
CST-GR

PROGRAM TAPE NO:
28.2
SERVICE ORDER NO:
MGE86-04

DEPTH-DRILLER: 1670.0 M
DEPTH-LOGGER: 1670.0 M
BTM. LOG INTERVAL: 1669.0 M
TOP LOG INTERVAL: 644.0 M

CASING-DRILLER:	232.0 M	642.0 M	
CASING-LOGGER:	232.0 M	644.0 M	
CASING:	20 "	13 3/8 "	
WEIGHT:	94.0000 LB/F	64.0000 LB/F	
BIT SIZE:	26 "	17 1/2 "	12 1/4 "
DEPTH:	261.0 M	656.0 M	1670.0 M

TYPE FLUID IN HOLE: LIGNOSULFONATE/DEXTRID
DENSITY: 9.80 LB/G
VISCOSITY: 44.0 S
PH: 9.5
FLUID LOSS: 5.0 C3
SOURCE OF SAMPLE: MUDPIT
RM: .492 OHMM AT 16.0 DEGC
RMF: .395 OHMM AT 15.0 DEGC
RMC: .628 OHMM AT 13.0 DEGC
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .193 OHMM AT 74.4 DEGC
RMF AT BHT: .151 OHMM AT 74.4 DEGC
RMC AT BHT: .227 OHMM AT 74.4 DEGC

TIME CIRC. STOPPED: 23:50 (19/2)
TIME LOGGER ON BTM.: 09:35 (20/2)

MAX. REC. TEMP: 74.4 DEGC

LOGGING UNIT NO: 390
LOGGING UNIT LOC: VEA
RECORDED BY: I. CHANDRA / T. BROPHY
WITNESSED BY: M. HANZALIK / D. BROOKMAN

REMARKS:

LDT-LOG RECORDED IN SANDSTONE MATRIX
BARITE CONTAINED IN MUD : 2.72 %

5 cm

EQUIPMENT NUMBERS-

SGC-JC 3374	NSC-C 736	PGD-G 1877	DRS-B 3871
CNC-A 2173	NSM-A 2794	GSR-J 6923	CNB-AB 578

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 28.2 FILE 0 20-FEB-86 15:52

AFTER SURVEY TOOL CHECK SUMMARY

PERFORMED: 20-FEB-86 12:24
PROGRAM FILE: MEGISN (VERSION 28.4 85/11/11)

LDTA TOOL CHECK

DRS SONDE NUMBER : 3871
NUCLEAR SERVICE CARTRIDGE NUMBER : 736
POWERED DETECTOR HOUSING NUMBER : 1944
POWERED GAMMA-GAMMA DETECTOR NUMBER : 1877
LDT LOGGING SOURCE NUMBER : 6923
LDT CALIBRATION MODE : WATE
MUD DENSITY : 9.80000 LB/G

BACKGROUND MEASURED

	BEFORE	AFTER	UNITS
LL	17.89	17.95	CPS
LU1	35.12	34.90	CPS
LU2	34.43	35.00	CPS
LU	69.56	69.87	CPS
LS	52.68	52.90	CPS
LITH	5.265	5.20	CPS
SS1	14.57	14.60	CPS
SS2	9.835	9.84	CPS

CNTA TOOL CHECK

	JIG	
	BEFORE	AFTER
NRAT	2.183	2.182

POROSITY CHANGE (LIME): .000

CP 28.4 FILE 5 20-FEB-86 12:23

EVENT MARK SUMMARY:

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	.100000 M3	LEFT EDGE

CHANGED PARAMETERS

NAME	VALUE	UNIT	DEPTH (M)	NAME	VALUE	UNIT	DEPTH (M)
DO	-1.50000	M	1000.0				
DO	-1.50000	M	1605.8	DO	-1.70000	M	1355.9

CP 28.4 FILE 102 20-FEB-86 12:08
DATA ACQUIRED 20-FEB-86 11:19