CSU

WELL: 1-15-HP SURF: 2195 FSL 2270 FWL
FIELD: WILDCAT
COUNTY: GRAND
STATE: UTAH
API NUMBER: 43-019-31511
LOCATION: SEC 15 T21S R24E
PERMANENT DATUM: GL ELEVATION: 4787.0 FT
LOG MEASURED FROM: KB 16.0 FT ABOVE PERM. DATUM
DRL. MEASURED FROM: KB

DATE: 27-FEB-96
RUN NO.: ONE

DEPTH-DRILLER: 8350.0 M
DEPTH-LOGGER: 8350.0 M
BOT. LOG INTERVAL: 8350.0 M
TOP LOG INTERVAL: 2000.0 M
CASING-DRILLER: 406.0 M @ 406.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
SOURCE RMF/RMC: CALCULATED
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

REMARKS:
RUN 1 WAS RUN TOGETHER WITH
RUN 2 FOR THE PURPOSE OF OBTAINING
THE REQUIRED OVERLAP. THE DEPTH
CONTROL USED WAS THE SCHLUMBERGER
CORRELATION LOG DATED 27-FEB-96.
ALL LOGS WERE RUN WITH A 2.5 INCH
STANDOFF ON THE TOOL. THE HOLE
WAS IN GOOD CONDITION AT TOTAL
DEPTH. THANK YOU FOR USING
SCHLUMBERGER.

RUN NUMBER	ONE	TWO
TOP LOG INTERVAL	2000.0 M	8200.0 M
BOTTOM LOG INTERVAL	8350.0 M	8350.0 M
CASING-LOGGER	406.0 M @ 406.0 M	406.0 M @ 406.0 M
BIT SIZE	311.1 MM @ 406.0 M	311.1 MM @ 406.0 M
TYPE FLUID IN HOLE	LIGNOSULFONATE FRESHWATER	LIGNOSULFONATE FRESHWATER
DENSITY	9.6 LB/G	9.6 LB/G
VISCOSITY	40.0 S	40.0 S
PH	10.0	10.0
FLUID LOSS	6.0 C3	6.0 C3
RM @ MEAS. TEMP.	0.060 @ 68 DEG F	0.060 @ 68 DEG F
RMF @ MEAS. TEMP.	0.050 @ 68 DEG F	0.050 @ 68 DEG F
RMC @ MEAS. TEMP.	0.080 @ 68 DEG F	0.080 @ 68 DEG F
RM @ BHT	0.030 @ 200 DEG F	0.030 @ 200 DEG F
TIME SINCE CIRC.	24.0 HOURS	12.0 HOURS
MAX. REC. TEMP.	200 DEG F	200 DEG F
EQUIPMENT NO.	SUN 3	SUN 3
LOCATION	VERNAL, UTAH	VERNAL, UTAH
RECORDED BY	JOHN DOE	JOHN DOE
WITNESSED BY	MR. COMPANY REPRESENTATIVE	MR. COMPANY REPRESENTATIVE

REMARKS:
RUN 1 WAS RUN TOGETHER WITH RUN 2 FOR THE PURPOSE OF OBTAINING THE REQUIRED OVERLAP. THE DEPTH CONTROL USED WAS THE SCHLUMBERGER CORRELATION LOG DATED 27-FEB-96. ALL LOGS WERE RUN WITH A 2.5 INCH STANDOFF ON THE TOOL. THE HOLE WAS IN GOOD CONDITION AT TOTAL DEPTH. THANK YOU FOR USING SCHLUMBERGER.

THIS DATA IS PROVIDED AS A SERVICE. NEITHER SCHLUMBERGER NOR ANY OF ITS AFFILIATES MAKES ANY WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OR SUITABILITY OF THIS DATA FOR ANY PURPOSE. ANY USE OF THIS DATA IS AT THE SOLE RISK OF THE USER. SCHLUMBERGER SHALL NOT BE LIABLE FOR ANY LOSS, DAMAGE, OR EXPENSE ARISING FROM THE USE OF THIS DATA. THE USER AGREES TO INDEMNIFY SCHLUMBERGER AGAINST ANY CLAIM ARISING FROM THE USE OF THIS DATA.

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: 0.030 @ 200 DEG F
TIME SINCE CIRC.: 24.0 HOURS
MAX. REC. TEMP.: 200 DEG F
EQUIPMENT NO.: SUN 3
LOCATION: VERNAL, UTAH
RECORDED BY: JOHN DOE
WITNESSED BY: MR. COMPANY REPRESENTATIVE

RUN 1 AT 2000.0 TO 8350.0 M
RUN 2 AT 8200.0 TO 8350.0 M
CASING-LOGGER: 406.0 M @ 406.0 M
BIT SIZE: 311.1 MM @ 406.0 M
TYPE FLUID IN HOLE: LIGNOSULFONATE FRESHWATER
DENSITY: 9.6 LB/G
VISCOSITY: 40.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.060 @ 68 DEG F
RMF @ MEAS. TEMP: 0.050 @ 68 DEG F
RMC @ MEAS. TEMP: 0.080 @ 68 DEG F
RM @ BHT: