

- P. Pipe Handling System: B.J. Hughes Telescopic Racker Arm.
- Q. Spinning Wrench: Varco Model 10, with rollers for 5" O.D. and 3-1/2" O.D.
- R. Kelly Spinner: International.
- S. "Ezy Torq": Drilco unit with 10 HP motor.
- T. Recorder: One (1) Totco drilling recorder. Six (6) pens for penetration, weight, pump pressure, torque (electricity) rotary rpm and pump rated for two (2) pumps alternately.
- U. Control Valves:-
1. Inside BOP: Flocon, with 6-1/2" O.D. and 4-1/2" I.F. connections, P/N 700053-H trimmed for hydrogen sulphide.
 2. Lower Kelly Valves: Two (2) Hydril P/N 10088.80-1, 7" O.D. x 3-1/4" bore - 7,500 psi test, 5,000 psi working pressure w/4-1/2" I.F. connections Box X pin trimmed for hydrogen sulphide service.
 3. Upper Kelly Valves: Two (2) each Omsco 15,000 psi test, 10,000 psi working pressure.
 4. Drop-in Back Pressure Valve: One (1) Hydril 3-1/4" I.D. x 6-1/2" O.D. sub with 4-1/2" I.F. tool joints and No. 13 plug.
- V. Circulating Head:-
1. One (1) Model 4-SC King Super "C" with 4" P.T. up and 4-1/2" I.F. pin down.
- W. Wireline Stripper:-
1. One (1) Model 4-AR King for 9/16" wire.