

2. One (1) replacement slip joint with kill and choke lines certified for hydrogen sulphide service.

J. Choke and Kill Hoses Certified for Hydrogen Sulphide Service:-

1. Three (3) each 2-1/2" I.D. x 45' long, 15,000 psi test pressure, 10,000 psi WP, rotary hose. Two (2) hoses installed and one (1) hose will be maintained in inventory as spare equipment.

K. Marine Riser Tensioning System:-

1. Six (6) Rucker Model XL tensioner units, each 60,000 lbs. line load capacity, 30' line travel.
2. Six (6) 42" diameter sheaves for 1-1/2" wire line.
3. Nine (9) 275 gallon air receivers and one (1) 140 gallon air receiver (for supply also to guideline tensioners).
4. Control Panel.
5. Wire line, size 1.1/2".

L. Guideline Tensioning System:-

1. Six (6) Rucker Model RED-6-7.5-A/B-.75 tensioner unit, each 14,000 lbs. line load capacity, 30' line travel.
2. Six (6) 24" diameter sheaves for 3/4" wire line.
3. Compressed air system incorporated in riser tensioning system.
4. Control Panel.
5. Wire line, size 3/4".

M. BOP Control Pod Tensioning System:-

1. Two (2) Rucker - 14,000 lbs. tensioner units.
2. Two (2) 24" diameter sheaves for 3/4" wire lines.