

2. One (1) Bowen Junk sub, with 4-1/2" regular connections for 8-1/2" hole, 6-5/8" O.D. x 5-15/16" I.D. cup, 2-1/4" bore.

E. Safety Joints:-

1. One (1) safety joint, Bowen 6-1/8" O.D., 4-1/2" I.F. connections.
2. One (1) safety joint, Bowen 7-3/4" O.D. with 6-5/8" API regular connections.

F. Taper Taps:-

1. One (1) #19494 Bowen 6-1/8" O.D. rotary taper tap. Tapered from 2-1/2" O.D. to 4-3/4" O.D.F. w/4-1/2" I.F. box up.
2. One (1) #4864 Bowen 7-7/8" O.D. removable skirt for above.
3. One (1) #4668 Bowen 10-3/4" O.D. oversize lip guide for above.
4. One (1) #57020 Bowen 11" O.D. removable skirt for above.

G. Fishing Magnets:-

1. One (1) #32370 11" O.D. Bowen K. & G. Magnet complete with flush guide for operation in 12-1/4" hole, w/6-5/8" API regular pin up.
2. One (1) each #32310 8" O.D. Bowen K. & G. Magnet complete with flush guide for operation in 8-1/2" hole w/4-1/2" API regular pin up.

H. Junk Mills:-

1. One (1) each 12" O.D. Bowen with 6-5/8" API regular pin connections dressed with Itcoloy crushed sintered tungsten carbide for use in 12-1/4" hole.
2. One (1) each 8-1/4" O.D. Bowen with 4-1/2" API regular pin connections dressed as above for use in 8-1/2" hole.

I. Spears:-

1. One (1) Bowen releasing spear, Itco type, P/N 17246, complete with packoff #9625 for 9-5/8" casing and grapple assembly #17248 for 13-3/8" casing.
2. One (1) Bowen releasing spear, Itco type, complete for 7" casing, P/N 9266.