

XXIII. ADDITIONAL EQUIPMENT

- A. Choke Manifold (see schematic "Standard Choke Manifold" inserted as "Figure 2" on page C-24).

1. 3-1/16", 10,000 psi WP choke manifold trimmed for hydrogen sulphide service includes two (2) Cameron adjustable chokes, one (1) Cameron positive choke and one (1) remote manual Cameron drilling choke.

Choke and Kill line piping from moon pool area to manifold, designed to 10,000 psi WP.

All downstream manifolding from choke manifold will be minimum 5,000 psi WP, 3-1/3" Cameron type F.

Permanent piping from manifold to test equipment to be 5,000 psi WP.

2. Bow and stern flare lines, 2,500 psi WP.

- B. Totco drift indicator, 0-8 degrees and 0-16 degrees.

- C. Cementing Unit:-

Halliburton SKD-4 skid unit with recirculating mixer 10,000 psi and 20 BPM.

If service company other than Halliburton is used, equipment rental and maintenance shall be reimbursable by the Company.

- D. Fire Fighting and Safety Equipment:-

1. CO₂ System for engine room, mud pits and paint locker.
2. Fire hydrant system.
3. Portable CO₂ fire extinguisher.
4. Portable dry chemical extinguishers.
5. Foam system for helicopter refueling area.