

C. Subs and Bit Subs:-

1. Two (2) Drilco Bit Subs, 4-3/4" O.D. x 48" long, 3-1/2" I.F. box up x 3-1/2" API reg. box down for 2F3R drill pipe.
2. Two (2) Crossover subs, 36" long, 6-3/8" O.D. top section with 4-1/2" I.F. box connection x 4-3/4" O.D. bottom section with 3-1/2" I.F. pin connection.
3. Two (2) Crossover sub from 4-3/4" drill collar to 6-1/2" drill collar 6-1/2" O.D. x 2-13/16" I.D. x 36" long, 3-1/2" I.F. box up x 4-1/2" I.F. pin down, 4-3/4" O.D. x 18" long fishneck box end.

D. Stabilizers:-

1. Two (2) 25-1/2" O.D. welded blade stabilizer with 7-5/8" reg. connections, pin x box.
2. One (1) 17-1/4" O.D. welded blade stabilizer with 7-5/8" reg. connections, pin x box.
3. Two (2) 8-1/4" O.D. sleeve stabilizers, near bit type with 6-5/8" reg. connections, box x box.
4. Seven (7) 8-1/4" O.D. sleeve stabilizers string type with 6-5/8" reg. connections.
5. Two (2) 6-1/2" O.D. sleeve stabilizers, near bit type with 4-1/2" I.F. connections.
6. Five (5) 6-1/2" O.D. sleeve stabilizers, string type with 4-1/2" I.F. connections.
7. One (1) 17-1/4" O.D. welded blade stabilizer with 6-5/8" API reg. box and pin connections, 8-1/4" O.D. body x 2-3/4" I.D.

E. Holes Openers and Reamers:-

1. One (1) 12-1/4" Drilco roller reamer P/N 201393 with 6-5/8" reg. connections pin x box, 8" O.D. x 2-7/8" I.D.
2. One (1) 8-1/4" Drilco roller reamer P/N 23895 with 4-1/2" I.F. connection pin x box, 6-1/4" O.D. x 2-7/8" I.D.
3. One (1) 36" Smith hole opener - GTA36, 9-1/2" O.D. with 7-5/8" reg. pin up x 7-5/8" reg. box down.
4. One (1) 17-1/2" Security hole opener, 9-1/2" O.D. with 6-5/8" reg. pin up x 6-5/8" reg. box down.