

TERRALOG - MAY 86 - 5  
 WELL NAME: CHAT #1  
 LOCATION: T-15P BASS BASIN  
 DATE: RIG RELEASE 6/2/86

DEPTH	CALRES	GR-RES	GR-RES BHC	VSH-GR BHC	ILDBHC	N-DPOR	PORSON SC	SW-IND
2916.500	13.31	41.81	50.45	.27	2.46	.22	.25	.87
2918.500	13.23	40.32	48.45	.25	2.52	.24	.25	.79
2918.750	13.20	39.03	46.83	.24	2.54	.24	.26	.80
2919.000	12.99	40.53	48.05	.25	2.59	.23	.27	.81
2919.250	13.00	37.07	43.98	.21	2.66	.22	.22	.85
2919.500	13.02	32.89	39.06	.17	2.96	.18	.14	1.00
2919.750	12.97	34.03	40.30	.18	3.10	.13	.15	1.00
2920.000	12.78	36.00	42.17	.20	2.69	.16	.17	1.00
2920.250	12.41	35.91	41.20	.19	1.61	.22	.24	1.00
2920.500	12.35	35.94	41.09	.19	1.59	.26	.26	.96
2920.750	12.35	37.85	43.28	.21	1.59	.25	.26	.97
2921.000	12.35	37.68	43.09	.21	1.59	.25	.25	.98
2921.250	12.35	38.35	43.86	.21	1.58	.25	.26	.98
2921.500	12.35	39.83	45.54	.23	1.58	.25	.27	.96
2921.750	12.51	41.43	47.79	.25	1.72	.24	.27	.95
2922.000	12.81	44.86	52.64	.29	1.80	.21	.24	1.00
2923.750	12.82	44.69	52.48	.29	6.12	.19	.21	.91
2924.250	12.63	44.07	51.20	.28	6.07	.19	.20	.92
2924.500	12.64	37.81	43.94	.21	6.02	.22	.22	.86
2924.750	12.61	39.45	45.76	.23	6.06	.23	.23	.83
2925.000	12.57	42.54	49.26	.26	6.07	.23	.23	.81
2925.250	12.56	39.30	45.47	.23	6.01	.24	.23	.80
2925.500	12.60	36.74	42.60	.20	6.08	.24	.25	.80
2925.750	12.61	37.38	43.38	.21	6.67	.23	.24	.80
2926.000	12.76	35.18	41.16	.19	6.96	.20	.20	.90
2926.250	12.96	33.37	39.49	.17	7.43	.14	.16	.80
2926.500	13.10	35.86	42.77	.20	10.31	.09	.06	.95
2926.750	13.49	36.09	44.01	.21	10.40	.06	.04	1.00
2927.000	13.62	37.41	45.96	.23	10.55	.06	.06	1.00
2927.250	13.54	37.11	45.37	.23	8.30	.09	.10	1.00
2927.500	13.34	38.70	46.77	.24	6.59	.12	.12	.89
2927.750	13.24	42.91	51.58	.28	6.23	.11	.13	.92
2928.250	13.30	40.50	48.86	.26	4.89	.14	.14	.89
2928.500	13.23	37.02	44.49	.22	4.38	.15	.14	.92
2928.750	13.24	37.88	45.55	.23	3.91	.17	.17	.89
2929.000	13.23	39.56	47.54	.25	3.42	.21	.22	.78
2929.250	13.24	38.87	46.73	.24	3.15	.23	.24	.74
2929.500	13.26	41.32	49.74	.27	3.19	.22	.20	.76
2929.750	13.27	41.61	50.12	.27	3.28	.19	.21	.86
2961.500	13.01	40.54	48.11	.25	8.09	.06	.05	1.00
2963.500	12.83	43.94	51.61	.28	3.47	.18	.21	.83
2964.250	12.80	44.58	52.29	.28	3.27	.20	.22	.80
2964.500	12.82	42.83	50.28	.27	3.71	.21	.21	.73
2964.750	12.88	37.50	44.18	.21	4.01	.18	.20	.82
2965.000	13.12	35.66	42.57	.20	4.18	.13	.17	1.00
2965.250	13.21	38.02	45.65	.23	4.35	.12	.18	1.00
2981.250	14.29	40.00	51.01	.28	5.51	.15	.08	.80
2993.000	14.27	40.36	51.41	.28	2.29	.28	.26	1.00
2993.250	14.49	36.28	46.78	.24	2.51	.29	.27	.95
2993.500	14.36	39.66	50.78	.28	2.65	.27	.26	.99
2994.750	15.30	36.82	49.69	.27	2.85	.31	.27	.85
2995.000	14.52	37.33	48.23	.25	2.82	.29	.27	.89

display limited to Vsh < 30% for 2900 - 3000m  
 used Rw = 0.15 ohm @ 104.8 deg C  
 used N-D shale corr. porosity  
 used Vsh from GR-RESEBHC, Rsh = 11.0 ohm

274149