

<u>S1 (mg/g or kg/tonne)</u>	<u>Classification</u>
0.00 - 0.20	Poor
0.20 - 0.40	Fair
0.40 - 0.80	Good
0.80 - 1.60	Very Good
> 1.60	Excellent

- (ii) S1+S2 - referred to as the genetic potential this parameter is used for source rock classification according to the following criteria:

<u>S1+S2 (mg/g or kg/tonne)</u>	<u>Classification</u>
0.00 - 1.00	Poor
1.00 - 2.00	Marginal
2.00 - 6.00	Moderate
6.00 - 10.00	Good
10.00 - 20.00	Very Good
> 20.00	Excellent

- (iii) S1/(S1+S2)- this parameter is the production index (PI) which is a measure of the level of maturity of the sample. For oil prone sediments, values less than 0.1 are indicative of immaturity, the values increase from 0.1 to 0.4 over the oil window and values greater than 0.4 represent over maturity. For gas prone sediments, the PI data shows a relatively smaller change with increasing maturity.

- (iv) Tmax - the temperature corresponding to the S2 maxima. This temperature increases with increasingly mature sediments. Values less than 430 Deg. C are indicative of immaturity while values from 430/435 to 460 Deg. C represent the maturity range of the oil window. Tmax values greater than 460 Deg. C are indicative of over maturity.

- (v) HI, OI - the hydrogen ((S2 x 100)/TOC) and oxygen ((S3 x 100)/TOC) indices when plotted against one another provide information about the type of kerogen contained in the sample and the maturity of the sample. Both parameters decrease in value with increasing maturity. Samples with large HI and low OI are dominantly oil prone and conversely samples with low HI and large OI are at best gas prone.

## 5. EXTRACTION OF SEDIMENT SAMPLES

Crushed sediment (maximum of 250g) and 300mls of purified dichloromethane are placed in a 500ml conical flask and are then blended for ten minutes with a Janke and Kunkel Ultra-Turrax T45/2G high efficiency disperser. After a ten minute settling period the solvent is separated from the sediment using a large Buchner filtration system. The extract is recovered by careful evaporation of the solvent on a steam bath and weighed. The weight of extract is used to calculate % EOM and ppm EOM using the following formulae: