Schlumberger

LDL-CNL-GR-CAL 1:200 SUITE#2 RUN#1

CSU Field Log

5 cm

ENCLOSURE 12.

CR- 0284

272040

COMPANY: BRIDGE OIL LTD

WELL: CHAT #1

FIELD: WILDCAT
RIG : MARGIE
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: BASS STRAIT E.P. T/15P

LATITUDE: 040 10 53.2 S
LONGITUDE: 146 41 54.9 E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM: 0.0 M
LOG MEASURED FROM: KB
25.3 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 25.3 M
DF: 25.0 M
GL: -81.4 M

DATE: 2 FEB 86
RUN NO: 1

OTHER SERVICES-
DIL-LSS-MSFL

PROGRAM
TAPE NO:
28.4
SERVICE
ORDER NO:
MGE86-02

DEPTH-DRILLER:	3104.0 M	
DEPTH-LOGGER:	3107.0 M	
BTM. LOG INTERVAL:	3106.0 M	
TOP LOG INTERVAL:	913.5 M	
CASING-DRILLER:	256.0 M	917.0 M
CASING-LOGGER:	256.0 M	913.5 M
CASING:	20 "	13 3/8 "
WEIGHT:	94.0000 LB/F	72.0000 LB/F
BIT SIZE:	26 "	12 1/4 "
DEPTH:	256.0 M	3104.0 M

TYPE FLUID IN HOLE: LIGNITE/LIGNOSULFONITE SOLTEX
DENSITY: 10.30 LB/G
VISCOSITY: 53.0 S
PH: 9.5
FLUID LOSS: 4.5 C3
SOURCE OF SAMPLE: MUDPIT
RM: .515 OHMM AT 19.0 DEGC
RMF: .360 OHMM AT 18.0 DEGC
RMC: .455 OHMM AT 19.0 DEGC
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .166 OHMM AT 104. DEGC
RMF AT BHT: .113 OHMM AT 104. DEGC
RMC AT BHT: .147 OHMM AT 104. DEGC

TIME CIRC. STOPPED: 21:30(1/2)
TIME LOGGER ON BTM.: 13:45(2/2)

MAX. REC. TEMP: 104.4 DEGC

LOGGING UNIT NO: 390
LOGGING UNIT LOC: VEA
RECORDED BY: I CHANDRA
WITNESSED BY: B. C. FURR

REMARKS:

LOG IS RECORDED IN SANDSTONE MATRIX.
BARITE CONTAIN IN MUD : 4 % (52 LBS/BBL).
BOTTOM HOLE TEMPERATURES : 220 DEGF AND 220 DEGF.
LOG IS PLAYED BACK WITH RHOB SCALE : 1.9 - 2.9 G/C3.

EQUIPMENT NUMBERS-

SGC-JC 3374	NSC-C 736	PGD-G 1877	DRS-B 3871
CNC-A 2173	NSM-A 2794	GSR-J 6923	CNB-AB 578

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

```
   CP 28.4              FILE     0       03-FEB-86 20:51
                        DATA ACQUIRED   00-    -00 00:00


                 AFTER SURVEY TOOL CHECK SUMMARY


  PERFORMED:     03-FEB-86 20:46
  PROGRAM FILE: MEGISN (VERSION    28.4    85/11/11)

 LDTA                        TOOL   CHECK

         DRS SONDE NUMBER                          :   3871
         NUCLEAR SERVICE CARTRIDGE NUMBER          :   736
         POWERED DETECTOR HOUSING NUMBER           :   1944
         POWERED GAMMA-GAMMA DETECTOR NUMBER       :   1877
         LDT LOGGING SOURCE NUMBER                 :   6923
         LDT CALIBRATION MODE                      :   WATE
         MUD DENSITY                               :   10.3000    LB/G

             BACKGROUND MEASURED
             BEFORE         AFTER         UNITS
     LL      17.87          18.01          CPS
    LU1      35.75          34.75          CPS
    LU2      34.62          35.40          CPS
     LU      70.37          70.12          CPS
     LS      53.06          53.09          CPS
   LITH       5.152          5.30          CPS
    SS1      14.71          14.60          CPS
    SS2       9.890          9.86          CPS

 CNTA                        TOOL   CHECK

                          JIG
                 BEFORE        AFTER
   NRAT          2.161         2.154

   POROSITY CHANGE  (LIME):  -.001

   CP 28.4              FILE     0       03-FEB-86 20:46
```

EVENT MARK SUMMARY:

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	.100000 M3	LEFT EDGE

BS (IN)	10.000	20.000	
CALI(IN)	10.000	20.000	
GR (GAPI)	0.0	200.00	
DRHO(G/C3)	-.2500	.25000	
PEF	0.0	10.000	
NPHI	.45000	-.1500	
RHOB(G/C3)	1.9000	2.9000	

CP 28.4 FILE 101 03-FEB-86 20:39
DATA ACQUIRED 02-FEB-86 17:05