CSU Log

Run ... of ...

COMPANY: BEYOND OIL LTD	
WELL: CHAT 01	
FIELD: CHATTERTON	
COUNTY: [redacted]	
STATE: [redacted]	
API NUMBER: 42-[redacted]-01-01	
LOCATION: 1100 FT FSL & 1100 FT FWL OF SEC 1 BLOCK 1	
PERMANENT DATUM: MSL Elevation: 0 ft	
LOG MEASURED FROM: RT 25.0 ft above PERM. DATUM	
DRILL MEASURED FROM: RT	
Date: 27-FEB-95	
Run No.: ONE	
DEPTH DRILLER: 8500.0 ft	
DEPTH LOGGER: 8500.0 ft	
BTM LOG INTERVAL: 8500.0 ft	
TOP LOG INTERVAL: 8000.0 ft	
CASING DRILLER: 9 5/8 in @ 8000.0 ft	
CASING LOGGER: 9 5/8 in @ 8000.0 ft	
BIT SIZE: 8.5 in	
TYPE FLUID IN HOLE: KCl/POLYMER	
DENSITY: 10.0 lb/gal	
VISCOSITY: 45.0 s	
PH: 9.5	
FLUID LOSS: 4.0 cc	
SOURCE OF SAMPLE: FLOWLINE	
RM @ MEAS TEMP: 0.150 @ 65.0 DEGF	
RMF @ MEAS TEMP: 0.120 @ 65.0 DEGF	
RMC @ MEAS TEMP: 0.200 @ 65.0 DEGF	
RM @ BHT: 0.080 @ 180.0 DEGF	
TIME CIRC ENDED: 03:00 27-FEB	
TIME LOGGER ON BTM: 06:00 27-FEB	
MAX. REC. TEMP.: 180.0 DEGF	
EQUIPMENT NO.: [redacted]	
LOCATION: [redacted]	
RECORDED BY: [redacted]	
WITNESSED BY: [redacted]	

REMARKS:

RUN 1 LOGGED WITH SCHLUMBERGER CSU TOOLS AS FOLLOWS: DSI-GR-SP-CAL-BHC-AMS-LDT-CNL-NGT. DSI RAN IN COMBINED MONOPOLE AND DIPOLE MODE. LDT RAN WITH 8 LB/GAL SOURCE. CNL RAN IN LIMESTONE MATRIX. NGT RAN WITH 3 MINUTE STATION AT EACH STOP.

EQUIPMENT NUMBERS

DSI-GR	1234	LDT-CNL-GR	5678
SP-CAL	1234	NGT	5678
BHC-AMS	1234		

THE INFORMATION CONTAINED HEREIN IS CONSIDERED CONFIDENTIAL AND PROPRIETARY TO SCHLUMBERGER AND IS FURNISHED TO THE CUSTOMER FOR THE EXCLUSIVE USE OF THE CUSTOMER AND ITS AFFILIATES. IT IS NOT TO BE REPRODUCED, USED OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF SCHLUMBERGER. THE INFORMATION IS PROVIDED "AS IS" AND SCHLUMBERGER MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, AS TO ITS ACCURACY OR COMPLETENESS OR AS TO THE RESULTS OBTAINED FROM ITS USE. ALL RISK IN CONNECTION WITH THE USE OF THE INFORMATION IS ASSUMED BY THE CUSTOMER. SCHLUMBERGER SHALL NOT BE LIABLE FOR ANY LOSS, COST, DAMAGE OR EXPENSE INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY USE OF THE INFORMATION.

SP 25.0

RUN 1 DSI-GR

DEPTH DRILLER:	8500.0 ft		
DEPTH LOGGER:	8500.0 ft		
BTM LOG INTERVAL:	8500.0 ft		
TOP LOG INTERVAL:	8000.0 ft		
CASING DRILLER:	9 5/8 in @ 8000.0 ft		
CASING LOGGER:	9 5/8 in @ 8000.0 ft		
BIT SIZE:	8.5 in		
TYPE FLUID IN HOLE:	KCl/POLYMER		
DENSITY:	10.0 lb/gal		
VISCOSITY:	45.0 s		
PH:	9.5		
FLUID LOSS:	4.0 cc		
SOURCE OF SAMPLE:	FLOWLINE		
RM @ MEAS TEMP:	0.150 @ 65.0 DEGF		
RMF @ MEAS TEMP:	0.120 @ 65.0 DEGF		
RMC @ MEAS TEMP:	0.200 @ 65.0 DEGF		
RM @ BHT:	0.080 @ 180.0 DEGF		
TIME CIRC ENDED:	03:00 27-FEB		
TIME LOGGER ON BTM:	06:00 27-FEB		
MAX. REC. TEMP.:	180.0 DEGF		
EQUIPMENT NO.:	[redacted]		
LOCATION:	[redacted]		
RECORDED BY:	[redacted]		
WITNESSED BY:	[redacted]		

REMARKS:

RUN 1 LOGGED WITH SCHLUMBERGER CSU TOOLS AS FOLLOWS: DSI-GR-SP-CAL-BHC-AMS-LDT-CNL-NGT. DSI RAN IN COMBINED MONOPOLE AND DIPOLE MODE. LDT RAN WITH 8 LB/GAL SOURCE. CNL RAN IN LIMESTONE MATRIX. NGT RAN WITH 3 MINUTE STATION AT EACH STOP.

EQUIPMENT NUMBERS

DSI-GR	1234	LDT-CNL-GR	5678
SP-CAL	1234	NGT	5678
BHC-AMS	1234		

THE INFORMATION CONTAINED HEREIN IS CONSIDERED CONFIDENTIAL AND PROPRIETARY TO SCHLUMBERGER AND IS FURNISHED TO THE CUSTOMER FOR THE EXCLUSIVE USE OF THE CUSTOMER AND ITS AFFILIATES. IT IS NOT TO BE REPRODUCED, USED OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN PERMISSION OF SCHLUMBERGER. THE INFORMATION IS PROVIDED "AS IS" AND SCHLUMBERGER MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, AS TO ITS ACCURACY OR COMPLETENESS OR AS TO THE RESULTS OBTAINED FROM ITS USE. ALL RISK IN CONNECTION WITH THE USE OF THE INFORMATION IS ASSUMED BY THE CUSTOMER. SCHLUMBERGER SHALL NOT BE LIABLE FOR ANY LOSS, COST, DAMAGE OR EXPENSE INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY USE OF THE INFORMATION.

SP 25.0

RUN 1 DSI-GR

DEPTH DRILLER:	8500.0 ft		
DEPTH LOGGER:	8500.0 ft		
BTM LOG INTERVAL:	8500.0 ft		
TOP LOG INTERVAL:	8000.0 ft		
CASING DRILLER:	9 5/8 in @ 8000.0 ft		
CASING LOGGER:	9 5/8 in @ 8000.0 ft		
BIT SIZE:	8.5 in		
TYPE FLUID IN HOLE:	KCl/POLYMER		
DENSITY:	10.0 lb/gal		
VISCOSITY:	45.0 s		
PH:	9.5		
FLUID LOSS:	4.0 cc		
SOURCE OF SAMPLE:	FLOWLINE		
RM @ MEAS TEMP:	0.150 @ 65.0 DEGF		
RMF @ MEAS TEMP:	0.120 @ 65.0 DEGF		
RMC @ MEAS TEMP:	0.200 @ 65.0 DEGF		
RM @ BHT:	0.080 @ 180.0 DEGF		
TIME CIRC ENDED:	03:00 27-FEB		
TIME LOGGER ON BTM:	06:00 27-FEB		
MAX. REC. TEMP.:	180.0 DEGF		
EQUIPMENT NO.:	[redacted]		
LOCATION:	[redacted]		
RECORDED BY:	[redacted]		
WITNESSED BY:	[redacted]		

SP 25.0

RUN 1 DSI-GR

DEPTH DRILLER:	8500.0 ft		
DEPTH LOGGER:	8500.0 ft		
BTM LOG INTERVAL:	8500.0 ft		
TOP LOG INTERVAL:	8000.0 ft		
CASING DRILLER:	9 5/8 in @ 8000.0 ft		
CASING LOGGER:	9 5/8 in @ 8000.0 ft		
BIT SIZE:	8.5 in		
TYPE FLUID IN HOLE:	KCl/POLYMER		
DENSITY:	10.0 lb/gal		
VISCOSITY:	45.0 s		
PH:	9.5		
FLUID LOSS:	4.0 cc		
SOURCE OF SAMPLE:	FLOWLINE		
RM @ MEAS TEMP:	0.150 @ 65.0 DEGF		
RMF @ MEAS TEMP:	0.120 @ 65.0 DEGF		
RMC @ MEAS TEMP:	0.200 @ 65.0 DEGF		
RM @ BHT:	0.080 @ 180.0 DEGF		
TIME CIRC ENDED:	03:00 27-FEB		
TIME LOGGER ON BTM:	06:00 27-FEB		
MAX. REC. TEMP.:	180.0 DEGF		
EQUIPMENT NO.:	[redacted]		
LOCATION:	[redacted]		
RECORDED BY:	[redacted]		
WITNESSED BY:	[redacted]		