

TABLE 1: SUMMARY OF VITRINITE REFLECTANCE MEASUREMENTS, KOORKAH-1

Depth (m)	Mean Maximum Reflectance (%)	Standard Deviation	Range	Number of Determinations
1520-1530	0.39	0.08	0.32-0.52	28
1590-1600	0.41	0.03	0.36-0.44	7
1708-1717	0.42	0.03	0.38-0.46	15
1807-1816	0.43	0.08	0.37-0.54	19
1906-1915	0.43	0.05	0.36-0.49	7
1996-2005	0.51	0.04	0.47-0.59	15
2086-2095	-	-	-	-
2203-2212	0.58	0.05	0.50-0.71	16
2302-2311	0.53	0.04	0.46-0.66	27
2401-2410	0.49	0.03	0.42-0.54	18
2465.5 ⁺	0.55* (0.51)	0.06	0.44-0.65	23
2500-2509	-	-	-	-
2555 ⁺	-	-	-	-
2608-2617	0.59	0.03	0.53-0.63	8
2707-2716	0.56	0.03	0.52-0.62	8
2806-2815	0.65	0.04	0.55-0.75	24
2905-2914	0.64	0.01	0.63-0.65	2
3004-3013	0.69	0.07	0.53-0.76	10
3062 ⁺	0.85	0.06	0.74-0.98	36
3103-3112	0.87	0.07	0.77-1.00	21
3126 ⁺	0.85	0.06	0.69-0.85	31

*influenced by reworked vitrinite.

() preferred value.

⁺SWC