OR 0386

Enclosure 10
Schlumberger

ISF-BHC-GR-SP-CAL SUITE #1 1/500

CSU Field Log

COMPANY: AMOCO AUSTRALIA PETROLEUM CO.
WELL: KOORKAH #1
FIELD: WILDCAT
STATE: TASMANIA
RIG: D.M.EPOCH
NATION: AUSTRALIA
LOCATION: SHOT POINT 290, LINE TP85-7
LATITUDE: 39 37'57.24"S
LONGITUDE: 145 09'05.13"E

OTHER SERVICES-

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM: 0.0 M
LOG MEASURED FROM: KB 22.3 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS- KB: 22.3 M DF: 22.0 M GL: -62.6 M

PROGRAM
TAPE NO: 28.2
SERVICE ORDER NO: DME 851201

DATE: 6 DEC 85
RUN NO: 1

DEPTH-DRILLER: 1599.0 M
DEPTH-LOGGER: 1602.0 M
BTM. LOG INTERVAL: [illegible] M
TOP LOG INTERVAL: 25.9 M

CASING-DRILLER: 402.0 M @ 0.0 M
CASING-LOGGER: 403.0 M @ 0.0 M
CASING WEIGHT: 94.000 LB/F 0.0 LB/F 0.0 LB/F
BIT SIZE: 26 IN. 17 1/2 IN.
DEPTH: 415.5 M 1599.0 M 0.0 M

TYPE FLUID IN HOLE: FRESH WATER GEL
DENSITY: 9.80 LB/G
VISCOSITY: 48.0 S
PH: 10.5
FLUID LOSS: 6.2 C3
SOURCE OF SAMPLE: FLOWLINE
RM: .597 OHMM AT 65.3 DEGF
RMF: .466 OHMM AT 59.9 DEGF
RMC: .887 OHMM AT 58.3 DEGF
SOURCE RMF/RMC: PRESS/PRESS
RM AT BHT: .298 OHMM AT 138. DEGF
RMF AT BHT: .215 OHMM AT 138. DEGF
RMC AT BHT: .399 OHMM AT 138. DEGF

TIME CIRC. STOPPED: 1530/6
TIME LOGGER ON BTM.: 1925/6

MAX. REC. TEMP: 138.0 DEGF

LOGGING UNIT NO: 822
LOGGING UNIT LOC: VEA
RECORDED BY: WINSLOE
WITNESSED BY: B.WHEELER/W.CROMER/K.MORRISON

REMARKS:

INDUCTION LOGGED WITH 2 1/2" STAND-OFF
GAMMA RAY LOGGED TO SEABED.
BOTTOM HOLE TEMPERATURE RECORDED =138 DEGF

5 cm

EQUIPMENT NUMBERS-

IRS-VA 1738	IRC-QB 1725	SLS-RD 2186	SLC-KB 741
SRE-CB 795	DRS-B 858	SRA-A 885	SGC-JC 3562
SLM-DA 755	NSM-A 2866	IEM-BD 805	MRM-AB2876

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

EVENT MARK SUMMARY:

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	3.53147 F3	LEFT EDGE
ITT	.00100000 S	RIGHT EDGE

BS (IN) 15.000 – 25.000	ILD (OHMM) .20000 – 200.00	
CALI(IN) 15.000 – 25.000		
GR (GAPI) 0.0 – 150.00		
SP (MV) -80.00 – 20.000	SFLU(OHMM) .20000 – 200.00	DT (US/F) 140.00 – 40.000

CP 28.2 FILE 101 06-DEC-85 22:50
DATA ACQUIRED 06-DEC-85 21:07

CP 28.2 FILE 101 06-DEC-85 22:37
DATA ACQUIRED 06-DEC-85 19:25

5 cm

BS (IN) 15.000 – 25.000	ILD (OHMM) .20000 – 200.00	
CALI(IN) 15.000 – 25.000		
GR (GAPI) 0.0 – 150.00		
SP (MV) -80.00 – 20.000	SFLU(OHMM) .20000 – 200.00	DT (US/F) 140.00 – 40.000

SENSOR MEASURE POINT TO TOOL ZERO

SRAT	9.52 METER	AMPL	10.29 METER
TT1	9.98 METER	CBL	10.29 METER
TT3	9.14 METER	TT2	10.29 METER
T0	10.29 METER	TT4	8.84 METER
SLTT	10.29 METER	TT	10.29 METER
GR	16.84 METER	SCBL	10.29 METER
ILD	2.08 METER	CALI	18.01 METER
SP	.10 METER	SFL	1.93 METER
TENS	.10 METER	SPAR	.10 METER
CMSF	17.91 METER	I1	17.98 METER
MDIS	.10 METER		

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
CDTS	100.000		SPFS	R-H	
DTF	189.000	US/F	DTM	56.0000	US/F
DSIM	5	US	DDEL	200	US
WMUD	8.00000	LB/G	DWCO	512	
SBR	1.00000	OHMM	DSEC	5.00000	MMHO
BHS	OPEN		SPI	STOH	
DO	0.0	M	BS	17.5000	IN
PP	NORM				