

ENCLOSURE 12
Schlumberger

SIDEWALL CORES SUITE #2 1/200

CSU Field Log

COMPANY: AMOCO AUSTRALIA PETROLEUM CO.
WELL: KODRKAH #1
FIELD: MILDCAI
STATE: TASMANIA
RIG: D.N.EPOCH
NATION: AUSTRALIA
LOCATION: SHOT POINT 290,
LINE TP05-7
LATITUDE: 39 37'57.24"S
LONGITUDE: 145 09'05.13"E
PERMANENT DATUM: MSL
ELEVATIONS:-
ELEV. OF PERM. DATUM: 0.0 M
LOG MEASURED FROM: KB
DRG. MEASURED FROM: KB
DATE: 22 DEC 85
RUN NO: 1
DEPTH-DRILLER: 3149.0 M
DEPTH-LOGGER: 3154.0 M
BTM. LOG INTERVAL: 3140.0 M
TOP LOG INTERVAL: 1605.0 M
CASING-DRILLER: 402.0 M
CASING-LOGGER: 403.0 M
CASING: 80 IN.
WEIGHT: 94,000 LB/F
BIT SIZE: 26 IN.
DEPTH: 415.5 M
1587.5 M
1589.0 M
13 3/8 IN.
68,000 LB/F
17 1/2 IN.
1599.0 M
0.0 M
0.0 M
0.0 M
0.0 M
3149.0 M

OTHER SERVICES-
ISF-BHC-MSFL
LDL-CNL-GR
MST
HDT

PROGRAM
TAPE NO:
27.61F
SERVICE
DRDER NO:
DME 851202

TYPE FLUID IN HOLE: FRESH WATER GEL
DENSITY: 9.30 LB/G
VISCOSITY: 56.0 S
PH: 11.1
FLUID LOSS: 7.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM: .887 DHMM AT 84.2 DEGF
RMF: .851 DHMM AT 60.8 DEGF
RMC: 1.480 DHMM AT 59.9 DEGF
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .297 DHMM AT 265. DEGF
RMF AT BHT: .212 DHMM AT 265. DEGF
RMC AT BHT: .364 DHMM AT 265. DEGF
TIME CIRC. STOPPED: 1425/21
TIME LOGGER ON BTM.: 1900/22
MAX. REC. TEMP: 265.0 DEGF
LOGGING UNIT NO: 822
LOGGING UNIT LOC: VEA
RECORDED BY: WINSLOE/BONNEMOY
WITNESSED BY: B.WHEELER

REMARKS:
4 LB/B GILSONITE ADDED TO MUD WHILE DRILLING.



EQUIPMENT NUMBERS-
GPC-A 619 SHM-AA 1778 STC-B CST-Z 799
CST-C 3742

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 27.61F FILE 5 22-DEC-85 21:05
CP 27.61F FILE 5 22-DEC-85 20:57

SHOT SUMMARY LISTING PERFORMED 22-DEC-85 20:57

SHOT	STATUS	DEPTH	TENSION
1	FIRED	3140.07	576.0
2	FIRED	3125.88	395.5
3	FIRED	3109.44	337.0
4	FIRED	3094.97	309.2
5	FIRED	3081.51	409.2
6	FIRED	3061.93	1641.
7	FIRED	3029.99	467.7
8	FIRED	3018.82	810.5
9	FIRED	3000.76	423.7
10	FIRED	2959.38	581.5
11	FIRED	2955.03	197.8
12	FIRED	2928.87	302.0
13	FIRED	2884.01	204.1
14	FIRED	2858.03	1804.
15	FIRED	2817.99	741.0
16	FIRED	2794.41	562.5
17	FIRED	2763.54	192.3
18	FIRED	2756.97	120.6
19	FIRED	2727.94	94.75
20	FIRED	2676.35	44.56
21	FIRED	2621.01	268.7
22	FIRED	2610.41	566.5
23	FIRED	2603.47	158.5
24	FIRED	2555.00	110.7
25	FIRED	2467.84	491.5
26	FIRED	2439.96	584.5
27	FIRED	2348.93	424.5
28	FIRED	2305.54	1617.
29	FIRED	2297.50	669.0
30	FIRED	2266.40	210.5
31	FIRED	2241.03	155.3
32	FIRED	2213.04	1488.
33	FIRED	2200.00	218.6
34	FIRED	2196.51	202.8
35	FIRED	2181.07	668.0
36	FIRED	2160.08	1449.
37	FIRED	2146.04	619.5
38	FIRED	2135.06	689.0
39	FIRED	2127.60	315.0
40	FIRED	2083.02	1823.
41	FIRED	2069.99	2198.
42	FIRED	2037.02	1796.
43	FIRED	2031.06	1031.
44	FIRED	1972.37	1982.
45	FIRED	1909.93	272.2
46	FIRED	1904.85	1249.
47	FIRED	1850.39	190.6
48	FIRED	1801.03	177.0
49	FIRED	1779.06	242.6
50	FIRED	1748.39	554.0
51	FIRED	1702.04	759.0
52	FIRED	1655.08	890.0
53	FIRED	1636.13	1453.
54	FIRED	1615.45	1839.
55	FIRED	1605.01	1482.

DEPTH UNITS : METE BIT SIZE : 12.250 IN
RING TYPE : NONE BULLET TYPE : COMB
POWDER LOAD : 12.00 G POWDER TYPE : AHT

