

DESCRIPTION	SPECIFICATION
<b>Telescopic Slip Joint</b>	
Manufacturer	Cameron
Stroke length	55 ft
Tensioner ring type	Fixed
No of attachments	Six (6)
<b><u>Riser Tensioner System</u></b>	
Manufacturer	Western Gear
Type of tensioner unit and nos	Pipemaster Type B307026-Six (6)
Unit rating	80,000 lbs each
<b><u>Surface BOP Equipment and Controls</u></b>	
<b>Diverter</b>	
Manufacturer and type	Regan KDFH
Nominal size	20
Max rotary size passed	37½"
Outlet size	12"
Control panels	Koomey
<b>Choke Manifold</b>	
Pressure rating	10,000 psi WP, H <sub>2</sub> S Trim
Adjustable chokes	Two (2) Thornhill-Craver 2"
Hydraulic operated chokes	One (1) Swaco Super Choke
<b>Drilling Choke Control Console</b>	
Manufacture	Swaco
Type	Super Choke
<b>Hydraulic Accumulator and Control Manifold</b>	
Manufacturer	Koomey
Air powered pump	2 each, 60:1, Model 88660
<b>Subsea TV System</b>	
Manufacturer	Subsea Systems
Type	PAN and TILT
Monitor(s)	One (1) plus one spare
Camera(s)	One (1) plus one spare
Light(s)	One (1) plus one spare
<b><u>Section E:</u></b>	
<b>Drill String and Accessories</b>	
<b>Float Valve</b>	
Make, type and size	Baker Type "G" or similar For 9", 8", 6½" and 5" DC
<b><u>Surface Safety Valve</u></b>	
<b>For 5" Drill String</b>	
Make, type and size	Lynn or equal, Inside BOP
Connection	4½" IF