

DESCRIPTION	SPECIFICATION
<b>Anchor Tension Instrumentation</b>	
Recording devices	
Manufacturer	Oilfield Instruments
Type	Sensing/Indicating
Location	At Anchor Winches
<b><u>Section D:</u></b>	
Storage Capacities	
<b>Tubular Goods</b>	
Casing/tubing	950 s tons
Drill pipe	
Drill collars	
<b>Sack Material Area</b>	
Capacity (pallets)	4' x 4' pallets 5100 sacks total
<b>Bulk Mud</b>	
Barite	Three (3) 1250 cu ft each
Bentonite	One (1) 1250 cu ft each
<b>Liquid Mud</b>	
Active capacity (usable)	840 bbls
Reserve capacity (usable)	708 bbls
Total	1548 bbls
<b>Bulk Cement</b>	Four (4) 1250 cu ft each
<b>Potable Water</b>	755 bbls
<b>Drill Water</b>	15,842 bbls
<b>Brine/Ballast</b>	8,472 bbls
<b>Fuel Oil</b>	6,412 bbls
<b>Lube Oil</b>	10 bbls
<b><u>Section E:</u></b>	
Helicopter Facilities	
<b>Helideck Dimensions</b>	83 ft x 83 ft
<b>Helideck Surface</b>	Steel painted non-skid surface w/net designed for Sikorsky S-6IN or equivalent
<b>Refuelling System</b>	1200 gallons at 36 gal/min
<b>Dedicated ND Beacon</b>	
Frequency details etc	250 KHZ to 340 KHZ
Type	Southern Avionics Model SS800A, 100 watt
<b>Heli Deck Fire Fighting Facilities</b>	USCG approved fixed foam system and 1500 lb dry chemical system