

DESCRIPTION	SPECIFICATION
<b><u>Section F:</u></b>	
<b>Material Handling Equipment</b>	
<b>Crane (x2)</b>	
Type/model	ABS 238
Manufacturer	FMC Linkbelt
Boom Length	120 ft
Typical lift capacity at specified radii	
a) Main hoist	41,800 lbs/60 ft
b) Whip line	10,000 lbs/120 ft
Max rated load capacity	99,200 lbs/30 ft
<b>Forklift Truck</b>	
Handling Capabilities	4,800 lbs
<b>Bulk Transfer Hoses</b>	
Number	Four (4)
Size/rating	4"/150 psi
Connection type(s)	Quick Lock
Length	50 ft
<b>Personnel Transfer Basket</b>	
Number	Two (2)
Type	Bill Pugh
<b><u>Section G:</u></b>	
<b>Power Equipment</b>	
<b>Diesel Engines</b>	
Number	Three (3)
Manufacturer	EMD
Type	Two (2) 16E-9/One (1) 16 E-8
Output (HP)	E-9 3070 HP/E-8 2200 HP
<b>Generators</b>	
Number	Three (3)
Manufacturer	EMD
Type	Two (2) A2ON6/One (1) A20T6
Output (KW)	N6-2000 KW/T6-1500 KW
<b>Independent Emergency Generator</b>	
Type/Manufacturer	Diesel/Detroit Diesel 8V-71N
Output	600 VAC/250 KW
Units supplied/services powered	Emergency lights, fire pump, radios, ballast pumps
<b><u>Section H:</u></b>	
<b>Compressed Air System</b>	
<b>Main Air Compressors</b>	
Manufacturer	Two (2) Quincy
Type	Screw type
Volume and Output press	490 CFM at 125 psi each