

DESCRIPTION	SPECIFICATION
Emergency Air Supply	
Manufacturer	Quincy
Type	Model S120, Detroit Diesel 271 length
Output Press & Volume	123 CFM at 100 psi, 1750 RPM
Main Air Receivers, Capacity	
Auxiliary air receivers, capacity	Two (2) Horizontal 100 cu ft ea
Separate Bulk-Chemical Transfer Compressor	
	Quincy D50AS, 307
High Pressure Air Compressors	
Manufacturer	Ingersoll-Rand
Type	15T4 x 20, Type 30
<u>Section I:</u>	
Water Distillation System	
Desalinator	
Manufacturer	Alpha-Laval
Output	10,000 GPD
Number of Units	One (1)
<u>Section J:</u>	
Accommodation	
Number of Personnel Accommodated	
(Breakdown into single, double, 4 man rooms, etc)	19 - four (4) man rooms 5 - two (2) man rooms 2 - one (1) man rooms
Max number permitted on board overnight	88 men
<u>Section K:</u>	
Fire and Safety Equipment	
Lifeboats	
Size and capacity (no of men)	Two (2) 64 man each
Manufacturer	MASECO
Engine type	Diesel
Max speed and range	6 knots, 20 hour
Davits/launch system	Harkrader type S30-22
Release mechanism	MASECO Type 550
Inflatable Life Rafts	
Capacity	25 man each
Manufacturer	Viking DKF
Release mechanism	Davit Launch
Life Jackets	Per USCG requirements
Working Life Jackets	Per USCG requirements
Lifebuoys	Per USCG requirements
Rope Ladders/Escape Ropes	Per USCG requirements