

	DESCRIPTION	SPECIFICATION
5.13.2	<u>Drilling and Associated Equipment</u>	

	DESCRIPTION	SPECIFICATION
--	-------------	---------------

Section A:**Hoisting Equipment**

Make and Type	Oilwell E-3000
Rated capacity w/5" DP	25,000 ft
Drive	Two (2) GE 752 DC motors
Auxiliary brake	Baylor Model 7838
Maximum input HP	3000 HP (3000 HPW/add motor)
Catheads	Two (2) Kelco Model 16

Derrick

Make and Type	Skytop Brewster
Dimensions	40' x 40' x 185'
Gross nominal capacity	1,333,000 lb
Static	1,000,000 lb
Crown block - type	Oilwell Type 760
No + size of sheaves	Seven (7) 60" sheaves
Rating	760 ton
Racking capacity	25,000' of 5" DP 15 stands of 8" DC

Travelling Assembly

Block, type and rating	Oilwell 650-650 ton
Hook, type and rating	BJ 5500 Dynaplex-500 ton
Elevator lins, size and rating	3½" x 132", 500 ton OR 2¾" x 144", 350 ton

Wirelines

Drilling Line : size and length	1½" x 7500 ft
Sandline : size and length	9/16" x 7500 ft

Heave Compensator

Make and type	Vetco Model 400-20D
Working capacity	400,000 lb
Static capacity	1,300,000 lb

Racking Arm

Make and type	Victoria Machine Works
---------------	------------------------

Section B:**Rotary Equipment****Rotary Table**

Make and Type	Oilwell
Drive	One (1) GE752 DC motor
Opening	37½"
Max input HP at 125 rpm	600 HP
Master bushings - split - dimensions	Varco MPCH
Static load rating	800 tons