

| DESCRIPTION | SPECIFICATION |
|--|--|
| Telescopic Slip Joint | |
| Manufacturer | Cameron |
| Stroke length | 55 ft |
| Tensioner ring type | Fixed |
| No of attachments | Six (6) |
| <u>Riser Tensioner System</u> | |
| Manufacturer | Western Gear |
| Type of tensioner unit and nos | Pipemaster Type B307026-Six (6) |
| Unit rating | 80,000 lbs each |
| <u>Surface BOP Equipment & Controls</u> | |
| Diverter | |
| Manufacturer and type | Regan KDFH |
| Nominal size | 20 |
| Max rotary size passed | 37½" |
| Outlet size | 12" |
| Control panels | Koomey |
| Choke Manifold | |
| Pressure rating | 10,000 psi WP, H ₂ S Trim |
| Adjustable chokes | Two (2) Thornhill-Craver 2" |
| Hydraulic operated chokes | One (1) Swaco Super Choke |
| Drilling Choke Control Console | |
| Manufacture | Swaco |
| Type | Super Choke |
| Hydraulic Accumulator and Control Manifold | |
| Manufacturer | Koomey |
| Air powered pump | 2 each, 60:1, Model 88660 |
| Subsea TV System | |
| Manufacturer | Subsea Systems |
| Type | PAN and TILT |
| Monitor(s) | One (1) plus one spare |
| Camera(s) | One (1) plus one spare |
| Light(s) | One (1) plus one spare |
| <u>Section E:</u> | |
| Drill String and Accessories | |
| Float Valve | |
| Make, type and size | Baker Type "G" or similar For 9", 8", 6½" and 5" DC |
| <u>Surface Safety Valve</u> | |
| For 5" Drill String | |
| Make, type and size | Lynn or equal, Inside BOP |
| Connection | 4½" IF |