

304292

BIT RECORD

COMPANY AMOCO AUSTRALIA PETROLEUM COMPANY		CONTRACTOR GLOBAL MARINE			COUNTY AUSTRALIA			STATE TASMANIA			
LEASE T/14-P		WELL NO YOLLA # 1		SEC		TOWNSHIP		RANGE BASS STRAIT		BLOCK	FIELD

TOOL PUSHER WILLIAMS/WILSON/GOSS/LAWSON				DRILL PIPE 5" 19.50				DRAW WORKS NATIONAL 1625 U.E.				
DAY DRILLER DODD/BRONDEL/WACHTER/TRAUTH				FOOT JOINT MAKE SIZE TYPE		4-1/2" IF		POWER 3000		H P		UNDER SURF
EVENING DRILLER				DRILL COLLAR NO O D I D LENGTH		6.5 2 13/16		PUMP NO 1 MAKE MODEL STROKE		NATIONAL 12P-160 12		INT DATE
MORNING DRILLER				DRILL COLLAR NO O D I D LENGTH		8 2 13/16		PUMP NO 2 MAKE MODEL STROKE		" " " "		T D DATE

BIT NO	BIT SIZE	BIT MFR	BIT TYPE	SERIAL NO OF BIT	JET SIZE			DEPTH OUT	FTGE	HOURS RUN	ACC HOURS	FT/HR	WEIGHT 1000 LBS	ROTARY R P M	VERT DEV.	PUMP PRESS	PUMPS			MUD		DULL CODE			REMARKS FORMATION, CIRC. FLUID, ETC.	DATE	
					1	2	3										No	Liner	SPM	Wt	Vis	T	B	G			
1	26	S	DSJ	XR 6740	18	18	18	645	348	5 1/2	5.5	63.3	0-10	100	3/4	1200	2	7	100	9	100	2	2	I	26/36 H.O. ASSEM.	9/6	
2	17-1/2	S	DSJ	XO 5484	18	18	18	1350	705	6 1/2	12	108.5	5-8	140	3/4	2900	2	7	180	9	100	1	1	I	PILOT HOLE	18/6	
RR1 3	26	S	DSJ	XR 6740	20	20	20	1350	(705)	8	20	94	5-8	120	1 1/2	2300	2	7	198	9	100	2	2	I	OPEN PILOT HOLE	20/6	
4	17 1/2	S	SDSC	XE 0162	16	16	16	2364	1014	13	33	78	5-10	60-120	1/2	2620	2	7	160	9.2	69	1	1	I	HUNG OFF WOW	24/6	
RR4 5	17-1/2	S	SDSC	XE 0162	16	16	16	4101	2751	TOT 53	73	51.9	15-20	120-125	1	3000	2	7	164	9.2	65	3	6	I	SEAL EFFECTIVE	26/6	
6	17-1/2	S	SDT-C	ER 4031	15	15	15	4763	663	43	116	15.4	25-30	120	1	2750	2	7	154	9.0	48	6	4	I	HEEL ROW SEVERELY WORN	30/6	
7	17-1/2	S	SDGHC	XD 9464	15	15	15	5220	578	44-1/2	160.5	13	25-40	120	1/2	2800	2	7	140	9.2	43	7	5	I	SEAL EFFECTIVE	7/7	
8	17-1/2	S	SDGH	XO 9378	16	16	18	5769	427	27	187.5	15.8	35	90	1/2	2850	2	7	142	9.2	45	3	3	I	PIN GALLED	9/7	
9	17-1/2	S	SDTC	RR-6																					CLEAN-UP TRIP	10/7	
10	12-1/4	S	SDGH	ER 8788	14	14	13	6030	261	6 1/2	194	40	25	80		2750	2	7	114	8.9	48	6	2	I	1/15		
11	8-1/2	DB	CB-303	1173				6063	33	1 1/2	195.5	22	8-18	80-110		2800	2	7	116	8.9	45					WEAR ON DIAMONDS NEGLIB	14/7
12	12-1/4	S	F-2	EV 9877	14	14	13	6503	439	12	207.5	36.1	25	70		2800	2	7	114	8.9	49	1	2	I	POH TO LOG	19/7	
13	12-1/4	S	F-2	EW 1050	14	14	13	7726	1222	35-1/2	243	34.4	35-45	80-100	1-1/2	2900	2	7	106	9.2	49	1	4	I	1/15	27/7	
14	12-1/4	S	F-2	EX 0219	14	14	13	8902	1126	66-1/2	309.5	16.9	50-55	95	1/2	3000	2	7	100	9.1	53	2	6	I	1/15	4/8	
15	12-1/4	S	F-2	EV 9360	14	14	13	9515	613	34-1/2	334	17.8	40-55	95	1	3000	2	7	100	9.6	55	3	8		BEARINGS FAILED, CONES LOCKED	8/8	
16	12-1/4	S	F-2	EV 9500	14	14	13	10097	582	49.5	383.5	11.8	45-50	100	1/2	3000	2	7	102	9.7	45	8	8	1		8/11	
17	12-1/4	S	F-3	XE 2971	14	14	14	10412	315	27	410.5	11.7	45	75	1	3000	2	7	101	9.6	44	1	5	1		8/13	
18	12-1/4	S	F-3	XB 2688	14	14	14	10879	467	46	456.5	10.2	40-45	80	1	3000	2	7	104	9.6	40					8/15	
19	12-1/4	S	F-3	XA 8997	14	14	14	10974	95	8 1/2	465	11.2	25-30	70		3000	2	7	102	9.8	43	1	4	I	1/8	OUT OF GAGE	8/21
20	8-1/2	DB	CB-303	(RR-11)				10981	7	2	467	3.5	10-18	80-100		800	1	7	40	9.8	44					NO VISIBLE WEAR	8/22
31	12 1/4	S	F-3	RR-18	14	14	14	10981	-	-	467	-	-	-												CLEANOUT TRIP	

59