

COMPANY AMOCO AUSTRALIA		WELL NAME & No. YOLLA NO 1		FIELD BASS BASIN	COUNTRY TASMANIA	SPUD DATE	RIG RELEASE	DRILLING PARAMETERS				
BHA No.	BIT No.	BOTTOM HOLE ASSEMBLY					WOB	RPM	DEPTH IN	DEPTH OUT	ANGLE BELOW	ANGLE ABOVE
1	1	26"	36" FS	15-8" DC	.XO.	3-5" HWDP	0-10	100	261'	645'		3/4°
				462.13'		90.45'						
2	2	17½"	FS	9-8" DC	.XO.	9-5" HWDP	5-8	120	645'	1350'		1½°
				277.39'		272.14'						
3	3	26"	FS	9-8" DC	.XO.	9-5" HWDP	5-8	120	645'	1350'		1½°
				277.39'		272.14'						
4	4-7	17½"	FS 8" Mn1.	8" DC	10-8" DC	.XO. 6-5" HWDP 6¼" Jars, 8-5" HWDP	25-40	120	1350'	5220'		½°
				29.78'	339.70'	459.00'						
5	8-9	17½"	FS 8" Mn1.	8" DC	16-8" DC	.XO. 6-5" HWDP 6¼" Jars, 8-5" HWDP	35-40	90	5220'	5769'		½°
				29.78'	530.45'	455.96'						
6	10	12¼"	JS FS 8" Mn1	17-8" DC	.XO. 6-5" HWDP 6¼" Jars 8-5" HWDP	25-30	80	5769'	6030'			
				525.18'		455.96'						
7	11	8½"C	Core Bbl .XO.	8" Mn1 17-8" DC	.XO. 6-5" HWDP 6¼" Jars, 8-5" HWDP	8-1880-110		6030'	6063'			
				554.96'		456.13'						
8	12-13	12¼"	FS 8" Mn1	8" DC	16-8" DC	.XO. 6-5" HWDP 6¼" Jars, 8-5" HWDP	40-45	100	6063'	7726'		1½°
				560.20'		456.13'						
9	14-16	12¼"	FS 8" Mn1	SDC 8" DC	16-8" DC	.XO. 6-5" HWDP, 6¼" Jars, 8-5" HWDP	50-55	95	7726'	10097'		1-3/4°
10	17-19	12¼"	JS FS 8" Mn1	SDC 8" DC	16-8" DC	.XO. 6-5" HWDP 6¼" Jars, 8-5" HWDP	40-45	80	10097'	10974'		1°
11	20	8½"CH	Core Bbl .XO.	8" SDC 17-8" DC	.XO. 6-5" HWDP Jars, 8-5" HWDP	10-1880-100		10974'	10981'			1°