Schlumberger

HDT-GR YOLLA#1 SUITE#3 1/200

CSU Field Log

Attachment 16

OR. 0310

COMPANY: AMOCO AUSTRALIA PETROLEUM CO.

WELL: YOLLA #1

FIELD: WILDCAT
RIG .: R F BAUER
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: BASS STRAIT - OFFSHORE TAS

LATITUDE: 039 50 18.96 S
LONGITUDE: 145 48 21.2 E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM: 0.0 M
LOG MEASURED FROM: KB
11.0 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 11.0 M
DF: 10.4 M
GL: -79.6 M

DATE: 23 AUG 85
RUN NO: B

OTHER SERVICES-
ISF-BHC-MSFL
LDL-CNL-NGT-
VSP-GR
RFT-HP-GR
STL-GR

PROGRAM TAPE NO:
28.2
SERVICE ORDER NO:
RFB 850801

DEPTH-DRILLER: 3347.0 M
DEPTH-LOGGER: 3351.0 M
BTM. LOG INTERVAL: 3350.0 M
TOP LOG INTERVAL: 1755.0 M

CASING-DRILLER:	399.0 M	1752.0 M	0.0 M
CASING-LOGGER:	0.0 M	1755.0 M	0.0 M
CASING:	20	13 3/8	
WEIGHT:	129.000 LB/F	72.0000 LB/F	0.0 LB/F
BIT SIZE:	26	17 1/2	12 1/4
DEPTH:	399.0 M	1759.0 M	3347.0 M

TYPE FLUID IN HOLE: FRESH WATER/AQUAGEL/POLYME
DENSITY: 9.80 LB/G
VISCOSITY: 44.0 S
PH: 11.0
FLUID LOSS: 9.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM: 1.070 OHMM AT 23.0 DEGC
RMF: .838 OHMM AT 16.0 DEGC
RMC: 1.370 OHMM AT 16.0 DEGC
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .311 OHMM AT 132. DEGC
RMF AT BHT: .205 OHMM AT 132. DEGC
RMC AT BHT: .336 OHMM AT 132. DEGC

TIME CIRC. STOPPED: 22:30 21/08
TIME LOGGER ON BTM.: 16:30 22/08

MAX. REC. TEMP: 132.0 DEGC

LOGGING UNIT NO: 65
LOGGING UNIT LOC: SEA
RECORDED BY: D.BOUBE R.WINSLOE
WITNESSED BY: G.M. KJELLGREN

REMARKS:

5 cm

LOG PLAYED BACK FROM AQUISITION DATA TAPE
CORRECT DEVIATION SCALE ON THIS FILM
DEVIATION SCALE ON FIELD AQUISITION TAPE 2DEG NEGATIVE
DEVIATION SCALE ON CLIENT TAPE CORRECTED
THERMOMETERS READING : 132,131,132 DEGC.

EQUIPMENT NUMBERS-

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 28.2 FILE 5 00- -00 02:33
DATA ACQUIRED 23-AUG-85 07:53

EVENT MARK SUMMARY:

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	10.0000 F3	LEFT EDGE
ICV	10.0000 F3	RIGHT EDGE

CEMENT VOLUME = 4978.46 F3
HOLE VOLUME = 7617.07 F3
FROM 3350.93 TO 1755.00 METE

GR (GAPI)
0.0 150.00
DEVI(DEG)
-3.000 7.0000
RB (DEG)
-40.00 360.00
AZIM(DEG)
-40.00 360.00
DEVI
-1.000 9.0000

C2 (IN)
30.000 10.000
C1 (IN)
30.000 10.000

CP 28.2 FILE 5 00- -00 00:52
DATA ACQUIRED 23-AUG-85 07:53