CSU

Run No. 1

COMPANY: WOODSIDE PETROLEUM LTD. OTHER SERVICES: NONE

WELL: TELLA 1A

FIELD: WILDCAT

COUNTY: OFFSHORE

STATE: W.A.

LOCATION: 20°17'S,114°1' WITHDRAWN TECHNICAL

SECTION: TWP: RGE:

PERMANENT DATUM: MSL ELEVATION: 0.0 m

LOG MEASURED FROM: RT 25.0 m ABOVE PERM. DATUM

DRILL MEASURED FROM: RT 25.0 m ABOVE PERM. DATUM

DATE: 8-JUL-89

RUN NO.: ONE

DEPTH-DRILLER: 2750.0 m

DEPTH-LOGGER: 2750.0 m

BTM LOG INTERVAL: 2750.0 m

TOP LOG INTERVAL: 1400.0 m

CASING-DRILLER: 1400.0 m @ 1400.0 m

CASING-LOGGER: 1400.0 m @ 1400.0 m

BIT SIZE: 311.1mm (12.25") @ 1400.0 m - 2750.0 m

TYPE FLUID IN HOLE: SEAWATER GEL

DENSITY: 1.03 g/cc

VISCOSITY: 40.0 s

FLUID LOSS: 9.0 cc

SOURCE OF SAMPLE: FLOWLINE

RM @ MEAS TEMP: 0.610 @ 20.0 DEGC

RMF @ MEAS TEMP: 0.460 @ 20.0 DEGC

RMC @ MEAS TEMP: 0.770 @ 20.0 DEGC

RM @ BHT: 0.370 @ 80.0 DEGC

TIME CIRCULATED BTM: 07:15 8-JUL

MAX. REC. TEMP.: 79.0 DEGC

EQUIPMENT NUMBER: SMT

LOCATION: ONS

RECORDED BY: D.WHITE

WITNESSED BY: D.MCKAY

REMARKS:

RUN 1 LOGGED WHILE DRILLING 12.25" HOLE FOR 13-3/8"CSG. NO LOGS WERE RECORDED ACROSS THE CASING SHOE. ALL LOGS WERE RECORDED WITH 2000 PSI SURFACE BACK PRESSURE. ALL DEPTHS ARE REFERRED TO RT. DATUM. CALIPER DATA WAS RECORDED WITH THE 3 ARM CALIPER. GR WAS RECORDED WITH THE 3 ARM CALIPER. THE CALIPER WAS USED TO CORRECT THE NEUTRON LOG FOR BOREHOLE EFFECTS. THE CALIPER WAS ALSO USED TO CALCULATE HOLE VOLUMES FOR CEMENTING PURPOSES.

EQUIPMENT SUMMARY:

NEUTRON	SNC-CB	3906	3906	3907
GR-CAL	SGC-CB	3906	3906	3907
DIL-BHC-GR	DIT-CB	3906	3906	3907

THE DIL-BHC-GR-SP TOOL WAS RUN IN COMBINATION WITH THE SNC-GR-CAL TOOL. THE DIL-BHC-GR-SP TOOL WAS RUN WITH 2 CENTRALISERS, ONE AT EACH END OF THE TOOL. THE SNC-GR-CAL TOOL WAS RUN WITH 1 CENTRALISER AT THE TOP OF THE TOOL. THE CALIPER WAS USED TO CALCULATE HOLE VOLUMES FOR CEMENTING PURPOSES. THE CALIPER DATA WAS ALSO USED TO CORRECT THE NEUTRON LOG FOR BOREHOLE EFFECTS. GR WAS RECORDED WITH THE 3 ARM CALIPER. THE CALIPER WAS USED TO CORRECT THE NEUTRON LOG FOR BOREHOLE EFFECTS. THE CALIPER WAS ALSO USED TO CALCULATE HOLE VOLUMES FOR CEMENTING PURPOSES.

NEUTRON	SNC-CB	2750	2750	2751
GR-CAL	SGC-CB	2750	2750	2751
DIL-BHC-GR	DIT-CB	2750	2750	2751

DIT-CB-GR
FILE: 001 DIT-CB-GR 07/7/8
TOOL STRING: DIT-CB-GR

AFTER SURVEY TOOL CHECK SUMMARY:

CALIBRATIONS:
CALIBRATION TYPE: DIL-CB 08/8/89

TOOL CHECKS

DATE	RESPONSE TYPE	METRES	METRES	UNITS
DIL	0.0 mmho	0.0 mmho	0.0 mmho	mmho
0.0 mmho SPHERE CONFIGURATION =	0.0 mmho			

DATE TOOL CHECKS

	RESPONSE TYPE	METRES	METRES	UNITS
CALI	0.0	0.0	0.0	mmho
	0.0	0.0	0.0	mmho
DIL-CB	FILE: 004	08/8/89		

FIELD NAME SUMMARY:

OUTPUT INTERVAL: DEPTH TRACK

DIT	FLUSHED_ZONE	DEPTH TRACK
	DELTA_T	DEPTH TRACK

DIL-CB	08/8/89	
DIL-CB	08/8/89	
DIL-CB	08/8/89	
DIL-CB	08/8/89	

DIT-CB-GR	07/7/8	
DIT-CB-GR	07/7/8	
DIT-CB-GR	07/7/8	
DIT-CB-GR	07/7/8	

