CSU

DATA

COMPANY: AMOCO AUSTRALIA PETROLEUM CO.
WELL: TELLA #1
FIELD: WILDCAT
API #: 47-195-20
LOCATION: 1650' FSL & 1650' FEL
SECTION: 30 TWP: 4S RGE: 4W
PERMANENT DATUM: MSL ELEVATION: 0.0
LOG MEASURED FROM: KB 15.0 FT. ABOVE PERM. DATUM
DRILL. MEASURED FROM: KB

DATE: 27 FEB 89
RUN NO.: ONE

DEPTH-DRILLER: 15227.0 F
DEPTH-LOGGER: 15227.0 F
BTM. LOG INTERVAL: 15224.0 F
TOP LOG INTERVAL: 7000.0 F

CASING-DRILLER: 13 3/8 @ 7000.0 F @ 0.0 F
CASING-LOGGER: 13 3/8 @ 7000.0 F @ 0.0 F
BIT SIZE(S): 12.250 IN. TO 15227.0 F @ 0.0 F
TYPE FLUID IN HOLE: LIGNO-SULFONATE MUD
DENSITY: 10.0 LB/G VISC: 45.0 S
PH: 10.5 FLUID LOSS: 4.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS. TEMP: 0.23 @ 150.0 DEGF
RMF @ MEAS. TEMP: 0.19 @ 150.0 DEGF
RMC @ MEAS. TEMP: 0.31 @ 150.0 DEGF
SOURCE: RMF: MEASURED RMC: CALCULATED
RM @ BHT: 0.12 @ 240.0 DEGF
TIME CIRC. STOPPED: 00:00 26 FEB
TIME LOGGER ON BTM: 12:00 26 FEB
MAX. REC. TEMP.: 240.0 DEGF
EQUIPMENT NO.: 3014
LOCATION: 5 MILES EAST
RECORDED BY: M. WILLIAMS

WITNESSED BY: MR. J. MCCARTHY

REMARKS:
RUN 1 LOGGED 1 DOWNPASS FROM 15227.0 F. TO 7000.0 F. AT 1800 F/HR.
TOOL STRING WAS RUN AS FOLLOWS:
DITE-MR-SP-GR-AMS-CAL-LDT-CNL-NGT-LEH-QT.
DITE-MR WAS NOT RECORDED DUE TO POWER FAILURE.
CNL-LDT WAS RUN WITH 2.5 GM/CC SOURCE.
CALIPER CORRECTIONS: 8.5 IN. FOR LDT-CNL.

EQUIPMENT NUMBERS:
DITE-MR 3014 LDT-CNL 3014 GR-AMS 3014 CAL 3014
NGT-LEH 3014 SP 3014 LEH-QT 3014 CSU 3014

THIS INFORMATION IS NOT WARRANTED, EXPRESS OR IMPLIED, BY SCHLUMBERGER AS TO THE ACCURACY, COMPLETENESS OR RELIABILITY OF THE INFORMATION, AND IS NOT TO BE CONSTRUED AS A WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR AS TO THE MERCHANTABILITY OF ANY MATERIAL. IT IS NOT TO BE CONSTRUED AS A RECOMMENDATION TO INFRINGE ANY PATENT OR AS AN INDUCEMENT TO USE ANY METHOD, APPARATUS OR MATERIAL IN CONFLICT WITH ANY PATENT. IN NO EVENT WILL SCHLUMBERGER BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

DIP DEC.0 DIP MAG. 0.0 DIP DIR.0
DIP DIP 0.0 DIP AZ. 0.0 DIP DIR.0



DIP DEC.0 DIP MAG. 0.0 DIP DIR.0
DIP DIP 0.0 DIP AZ. 0.0 DIP DIR.0

EXPERIMENTAL COMPUTATIONS:
1000 * R_M / (RXO_f / R_M - 1 + R_M/R_t)

R_M/R_t	R_M/RXO_f		
R_t/RXO_f			
R_MUDCAKE	RMC @ MEAS. TEMP	DELTA_T_MUDCAKE	LOGS
R_t	RT @ MEAS. TEMP	DELTA_T_SHALE	DITE

DIP DEC.0 DIP MAG. 0.0 DIP DIR.0
DIP DIP 0.0 DIP AZ. 0.0 DIP DIR.0

