

EXLOG

AMOCO AUST.

Tilana No.1

329090

Data Printed at time 12:39
Data Recorded at time 19:02

Date Oct 9 '85
Date Sep 10 '85

22

F#	TIME	DEPTH m	ROP m/hr	TORQUE		RPM AVG	WOB AVG	PUMP PRES	RTRNS DEPTH	MW lb/gal		FLOW/MIN		TEMP (C)		PVT	THIS BIT			COST			EST TW	DKC	NK	NKB	ECD	EST	
				AVG	MAX					IN	OUT	IN	OUT	IN	OUT		REVS	m	hrs	INST	RUN	FM						PR	
169	1902	841.62	35.1	1.76	1.76	100	23.1	2460	827.75	8.87	8.89	835	0	20.3	21.3	409	48103	423	8.8	110	118	3.48	1.07	.95	1.02	8.46	8.70	D	
170	1902	841.88	76.1	1.78	1.78	98	23.4	2480	827.91	8.87	8.89	835	0	20.3	21.3	413	48123	424	8.8	108	118	3.48	.86	.74	1.02	8.46	8.70	D	
171	1902	842.20	43.3	1.71	1.71	98	22.4	2480	828.31	8.87	8.89	834	0	20.3	21.3	415	48163	424	8.8	112	118	3.48	1.00	.89	1.02	8.46	8.70	D	
172	1902	842.47	69.9	1.81	1.81	98	22.2	2480	828.53	8.89	8.82	834	0	20.3	21.3	416	48185	424	8.8	104	118	3.48	.87	.75	1.02	8.48	8.70	D	
173	1903	842.82	40.6	1.71	1.71	99	22.4	2460	828.96	8.89	8.82	834	0	20.3	21.3	416	48236	425	8.8	123	118	3.49	1.02	.90	1.02	8.48	8.70	D	
174	1903	843.08	40.1	1.75	1.75	98	23.4	2490	829.25	8.89	8.82	835	0	20.3	21.3	419	48270	425	8.8	118	118	3.49	1.03	.91	1.02	8.48	8.70	D	
175	1904	843.40	50.9	1.72	1.72	99	23.1	2480	829.62	8.89	8.82	835	0	20.3	21.3	421	48306	425	8.8	133	118	3.49	.97	.85	1.02	8.48	8.70	D	
176	1904	843.73	85.2	1.85	1.85	98	22.8	2480	829.76	8.89	8.82	835	0	20.3	21.3	422	48328	425	8.8	78	118	3.49	.82	.70	1.02	8.48	8.70	D	
177	1904	844.02	40.4	1.64	1.64	100	21.9	2470	830.11	8.89	8.76	835	0	20.4	21.4	422	48367	426	8.8	110	118	3.50	1.02	.90	1.02	8.48	8.70	D	
178	1905	844.30	43.0	1.65	1.65	98	21.0	2470	830.44	8.89	8.76	835	0	20.4	21.4	424	48405	426	8.8	142	118	3.50	.98	.87	1.02	8.49	8.70	D	
179	1905	844.61	62.7	1.55	1.55	98	20.4	2470	830.63	8.89	8.76	835	0	20.4	21.4	425	48433	426	8.8	81	118	3.50	.88	.77	1.02	8.49	8.70	D	
180	1905	844.93	41.5	1.56	1.56	98	17.8	2480	830.96	8.89	8.76	835	0	20.4	21.4	428	48476	427	8.8	128	118	3.50	.95	.84	1.02	8.48	8.70	D	
181	1906	845.28	43.9	1.60	1.60	98	19.0	2440	831.29	8.89	8.76	835	0	20.4	21.4	426	48515	427	8.9	104	118	3.50	.95	.84	1.02	8.49	8.70	D	
182	1914	845.61	39.1	1.02	1.02	98	22.9	2470	833.44	8.87	8.90	834	0	20.3	21.8	457	48546	427	8.9	118	118	3.51	1.03	.91	1.02	8.54	8.70	D	
183	1915	846.43	35.0	1.58	1.58	98	13.9	2450	834.39	8.89	8.92	836	0	20.1	21.7	455	48600	428	8.9	192	117	3.51	.93	.83	1.02	8.57	8.70	D	
184	1915	846.84	80.6	1.64	1.64	97	20.0	2450	834.70	8.89	8.92	835	0	20.1	21.7	456	48627	428	8.9	124	117	3.51	.80	.68	1.02	8.57	8.70	D	
185	1916	847.37	41.5	1.75	1.75	95	23.5	2460	835.16	8.89	8.92	834	0	20.1	21.7	458	48679	429	8.9	143	117	3.51	1.00	.89	1.02	8.57	8.70	D	
186	1916	847.66	60.2	1.85	1.85	97	23.1	2450	835.40	8.89	8.92	834	0	20.1	21.7	458	48701	429	8.9	70	117	3.52	.91	.79	1.02	8.57	8.70	D	
187	1917	848.01	33.5	1.81	1.81	95	24.4	2460	835.91	8.88	8.88	834	0	20.1	21.8	460	48758	430	8.9	157	117	3.52	1.07	.96	1.02	8.57	8.70	D	
188	1917	848.26	30.9	1.77	1.77	96	24.0	2450	836.24	8.88	8.88	834	0	20.1	21.8	464	48794	430	8.9	109	117	3.52	1.09	.97	1.02	8.60	8.70	D	
189	1917	848.57	49.6	1.72	1.72	98	21.6	2460	836.44	8.88	8.88	834	0	20.1	21.8	469	48821	430	8.9	97	117	3.52	.94	.83	1.02	8.60	8.70	D	
190	1918	848.92	41.9	1.72	1.72	98	21.2	2460	836.84	8.88	8.88	834	0	20.1	21.8	477	48869	431	8.9	114	117	3.53	.98	.87	1.02	8.60	8.70	D	
191	1918	849.48	39.9	1.79	1.79	98	21.6	2460	837.42	8.88	8.86	834	0	20.0	22.0	490	48939	431	8.9	174	117	3.53	1.00	.88	1.02	8.62	8.70	D	
192	1919	849.79	42.9	1.73	1.73	98	22.1	2440	837.71	8.88	8.86	834	0	20.0	22.0	491	48980	432	8.9	111	117	3.53	.98	.87	1.02	8.62	8.70	D	
193	1919	850.09	42.0	1.77	1.77	97	22.5	2450	838.01	8.88	8.86	834	0	20.0	22.0	493	49020	432	8.9	118	117	3.53	.99	.87	1.02	8.62	8.70	D	
194	1920	850.40	42.9	1.68	1.68	98	20.4	2450	838.25	8.88	8.86	833	0	20.0	22.0	492	49055	432	8.9	84	117	3.54	.96	.85	1.02	8.62	8.70	D	
195	1920	850.71	55.8	1.61	1.61	98	18.6	2450	838.52	8.91	8.83	833	0	19.9	22.3	493	49086	433	9.0	96	117	3.54	.87	.76	1.02	8.62	8.70	D	
196	1920	851.01	42.0	1.79	1.79	98	18.5	2410	838.92	8.91	8.83	833	0	19.9	22.3	494	49128	433	9.0	119	117	3.54	.94	.83	1.02	8.64	8.70	D	
197	1921	851.32	51.3	1.83	1.83	98	21.9	2460	839.24	8.91	8.83	833	0	19.9	22.3	495	49162	433	9.0	111	117	3.54	.93	.82	1.02	8.64	8.70	D	
198	1921	851.64	67.9	1.84	1.84	97	22.8	2450	839.47	8.91	8.83	833	0	19.9	22.3	494	49190	433	9.0	73	117	3.55	.86	.75	1.02	8.64	8.70	D	
199	1921	851.92	59.9	1.85	1.85	98	24.8	2450	839.71	8.91	8.83	833	0	19.9	22.3	496	49214	434	9.0	91	117	3.55	.92	.80	1.02	8.64	8.70	D	
200	1921	852.26	105	1.86	1.86	98	25.9	2460	839.90	8.85	8.82	832	0	20.0	22.4	497	49232	434	9.0	82	117	3.55	.77	.65	1.02	8.67	8.70	D	
201	1922	852.53	32.9	1.75	1.75	98	24.4	2420	840.15	8.85	8.82	833	0	20.0	22.4	496	49271	434	9.0	106	117	3.55	1.07	.96	1.02	8.67	8.70	D	
202	1922	852.84	42.1	1.70	1.70	98	21.7	2450	840.40	8.85	8.82	834	0	20.0	22.4	497	49304	435	9.0	130	117	3.55	.98	.86	1.02	8.67	8.70	D	
203	1923	853.19	50.9	1.56	1.56	98	19.6	2430	840.72	8.85	8.82	834	0	20.0	22.4	497	49343	435	9.0	83	117	3.56	.90	.79	1.02	8.67	8.70	D	
204	1923	853.75	42.1	1.94	1.94	97	22.3	2410	841.12	8.86	8.82	832	0	20.0	22.5	498	49408	436	9.0	127	117	3.56	.98	.87	1.02	8.67	8.70	D	
205	1924	854.07	44.7	1.89	1.89	97	23.7	2420	841.12	8.86	8.82	832	0	20.0	22.5	498	49448	436	9.0	106	117	3.56	.98	.86	1.02	8.70	8.70	D	
206	1924	854.39	31.0	1.93	1.93	97	24.4	2440	841.12	8.86	8.82	833	0	20.0	22.5	499	49507	436	9.0	169	117	3.56	1.08	.97	1.02	8.70	8.70	D	
207	1925	854.77	44.6	1.90	1.90	96	24.6	2420	841.12	8.86	8.82	833	0	20.0	22.5	501	49549	436	9.0	134	117	3.57	.98	.87	1.02	8.71	8.70	D	
208	1932	855.61	65.9	1.48	1.48	98	16.2	2450	842.54	8.81	8.88	839	0	20.0	22.9	525	49600	437	9.0	71	117	3.57	.79	.69	1.02	8.76	8.70	D	
209	1932	855.90	39.5	1.64	1.64	98	19.7	2440	842.89	8.81	8.88	839	0	20.0	22.9	523	49639	438	9.0	95	117	3.57	.96	.85	1.02	8.76	8.70	D	
210	1933	856.22	31.2	1.76	1.76	97	24.1	2440	843.23	8.81	8.88	839	0	20.0	22.9	523	49683	438	9.1	136	117	3.58	1.07	.95	1.02	8.76	8.70	D	
211	1933	856.81	44.8	1.71	1.71	98	23.3	2440	843.84	8.84	8.88	838	0	20.0	22.9	521	49748	439	9.1	116	117	3.58	.96	.85	1.02	8.80	8.70	D	
212	1934	857.13	52.7	1.66	1.66	98	22.5	2440	844.18	8.84	8.88	838	0	20.0	22.9	520	49777	439	9.1	74	117	3.58	.91	.80	1.02	8.80	8.70	D	
213	1934	857.40	28.9	1.65	1.65	97	20.4	2440	844.61	8.84	8.88	838	0	20.0	22.9	521	49821	439	9.1	134	117	3.58	1.04	.93	1.02	8.80	8.70	D	
214	1934	857.77	67.7	1.65	1.65	98	22.1	2440	844.87	8.84	8.88	838	0	20.0	22.9	520	49844	439	9.1	70	117	3.59	.84	.73	1.02	8.80	8.70	D	
215	1935	858.04	35.3	1.53	1.53	98	20.0	2440	845.30	8.84	8																		