

F#	TIME	DEPTH	ROP	TORQUE		RPM	JOB	PUMP	RTRNS	MW lb/gal		FLOW/MIN		TEMP (C)		PVT	---THIS BIT---			---COST---		EST	DKC	NK	NKB	ECD	EST
				AVG	MAX					IN	OUT	IN	OUT	IN	OUT		REVS	m	hrs	INST	RUN						
21	0337	2793.8	13.2	3.05	3.69	37	4.0	350	2733.6	9.30	9.34	133	133	31.1	43.2	432	2003	5.19	.4	507	4231	.02	.35	.87	3.61	9.41	8.70
22	0338	2794.1	21.1	2.94	4.06	37	3.7	350	2733.6	9.30	9.34	133	133	31.1	43.2	431	2084	5.50	.4	293	4308	.02	.76	.77	3.61	9.41	8.70
23	0340	2794.4	13.8	3.13	4.23	37	4.2	350	2733.6	9.30	9.34	133	133	31.1	43.2	429	2204	5.80	.4	463	3324	.02	.36	.87	3.61	9.41	8.70
24	0341	2794.8	16.9	2.94	4.54	37	4.0	350	2733.6	9.30	9.34	133	133	31.1	43.2	431	2305	6.10	.5	424	3648	.02	.81	.82	3.61	9.41	8.70
25	0343	2795.0	11.7	2.87	4.40	37	4.8	340	2733.6	9.30	9.34	133	133	31.1	43.2	429	2415	6.41	.5	540	3491	.02	.91	.92	3.61	9.41	8.70
26	0344	2795.3	13.8	2.73	4.08	37	4.5	350	2733.6	9.30	9.35	133	133	31.4	43.2	429	2530	6.72	.5	434	3365	.02	.37	.88	3.61	9.41	8.70
27	0346	2795.7	15.1	2.85	3.93	37	3.9	360	2733.6	9.30	9.35	134	134	31.4	43.2	428	2650	7.01	.5	340	3222	.02	.83	.84	3.61	9.41	8.70
28	0347	2795.9	17.3	2.82	4.25	37	4.9	350	2733.6	9.30	9.35	134	134	31.4	43.2	427	2731	7.33	.5	342	3104	.03	.84	.85	3.61	9.42	8.70
29	0349	2796.2	14.3	2.79	3.86	37	4.2	350	2733.6	9.30	9.35	134	134	31.4	43.2	426	2833	7.63	.6	409	2993	.03	.35	.86	3.61	9.42	8.70
30	0350	2796.6	17.0	2.74	4.65	33	5.1	370	2733.6	9.30	9.35	134	134	31.4	43.2	426	2931	7.92	.6	492	2333	.03	.35	.86	3.62	9.42	8.70
31	0352	2796.3	14.5	2.88	3.30	33	4.7	350	2733.6	9.30	9.35	134	134	31.4	43.2	425	3034	8.24	.6	400	2739	.03	.86	.83	3.62	9.42	8.70
32	0353	2797.1	15.2	2.85	3.63	37	4.8	340	2733.6	9.30	9.35	134	134	31.4	43.2	425	3137	8.55	.6	385	2702	.03	.36	.87	3.62	9.42	8.70
33	0355	2797.5	14.6	2.69	3.63	37	4.3	350	2733.6	9.30	9.35	134	134	31.7	39.6	423	3247	8.95	.6	363	2521	.03	.85	.86	3.62	9.42	8.70
34	0356	2797.8	10.1	2.73	3.47	33	6.2	350	2733.6	9.30	9.35	134	134	31.7	39.6	424	3401	9.16	.7	493	2543	.03	.99	1.00	3.62	9.43	8.70
35	0359	2798.1	7.49	2.67	3.33	33	5.6	360	2733.6	9.30	9.35	133	133	31.7	39.6	422	3614	9.46	.7	1093	2486	.03	1.32	1.04	3.62	9.43	8.70
36	0403	2798.4	4.59	2.27	2.76	39	5.9	350	2733.6	9.30	9.35	133	133	31.7	39.6	421	3958	9.77	.8	1036	2442	.04	1.13	1.14	3.62	9.43	8.70
37	0404	2798.3	2.14	2.37	2.38	30	8.1	350	2733.6	9.31	9.34	133	133	32.0	39.1	421	4050	10.2	.8	1035	2433	.04	1.37	1.39	3.62	9.43	8.70
38	0408	2799.3	7.28	2.54	3.90	33	6.6	350	2733.6	9.31	9.34	134	134	32.0	39.1	418	4400	10.7	.9	521	2274	.04	1.06	1.03	3.62	9.43	8.70
39	0410	2799.6	9.60	2.64	3.42	33	6.4	350	2733.6	9.31	9.34	134	134	32.0	39.1	418	4566	11.0	.9	512	2225	.04	1.00	1.02	3.62	9.43	8.70
40	0424	2800.0	1.10	2.23	2.35	94	9.3	400	2733.6	9.28	9.52	200	200	32.7	39.4	411	5309	11.4	1.1	5	2243	.06	1.59	1.62	3.62	9.43	8.70
41	0433	2800.2	1.20	2.21	2.61	32	10.7	420	2733.6	9.29	9.55	196	196	33.0	39.8	437	6616	11.6	1.3	1207	2276	.06	1.57	1.59	3.62	9.43	8.70
42	0452	2800.5	1.72	2.18	2.71	91	10.3	330	2733.6	9.25	9.58	132	132	33.7	40.1	400	8317	11.9	1.6	2457	2360	.08	1.50	1.51	3.62	9.42	8.70
43	0457	2800.8	4.25	2.56	5.31	39	9.1	340	2733.6	9.25	9.58	137	137	33.7	40.1	396	8772	12.2	1.7	1147	2325	.08	1.26	1.27	3.62	9.43	8.70
44	0459	2801.1	11.2	3.26	4.27	33	9.9	350	2733.6	9.25	9.53	133	133	33.7	40.1	395	8905	12.5	1.7	404	2279	.08	1.07	1.09	3.62	9.43	8.70
45	1001	2801.4	8.62	3.45	5.30	35	10.2	350	2733.6	9.22	9.62	139	139	33.8	39.7	396	9087	12.8	1.7	530	2233	.09	1.13	1.15	3.63	9.43	8.70
46	1002	2801.7	19.5	3.32	4.68	37	9.3	330	2733.6	9.22	9.62	133	133	33.8	39.7	396	9172	13.1	1.8	232	2193	.09	.94	.95	3.63	9.43	8.70
47	1003	2802.0	15.9	3.02	4.18	33	10.9	320	2733.6	9.22	9.62	177	177	33.8	39.7	395	9266	13.4	1.8	311	2150	.09	1.02	1.03	3.63	9.43	8.70
48	1018	2802.4	16.5	2.46	3.25	30	8.1	220	2733.6	9.22	9.62	138	138	33.8	39.7	397	9333	13.7	1.8	301	2117	.09	.92	.95	3.63	9.42	8.70
49	1024	2802.6	6.14	3.03	6.07	56	9.4	330	2733.6	9.20	9.62	133	133	34.0	39.2	394	9692	14.0	1.9	5	2391	.09	1.09	1.15	3.63	9.43	8.70
50	1025	2802.9	13.8	2.71	3.61	33	5.5	340	2733.6	9.20	9.62	134	134	34.0	39.2	391	9903	14.3	1.9	627	2353	.09	.90	.91	3.63	9.43	8.70
51	1026	2803.3	16.6	2.71	3.06	33	4.9	330	2733.6	9.20	9.62	134	134	34.0	39.2	389	9904	14.6	1.9	294	2019	.09	.85	.86	3.63	9.43	8.70
52	1028	2803.6	12.4	2.72	3.29	33	5.8	330	2733.6	9.20	9.62	134	134	34.0	39.2	390	10032	14.9	1.9	477	1936	.10	.94	.95	3.63	9.43	8.70
53	1029	2803.9	13.9	2.92	3.68	33	6.4	330	2733.6	9.20	9.62	134	134	34.0	39.2	390	10146	15.3	1.9	339	1952	.10	.93	.94	3.63	9.43	8.70
54	1031	2804.2	14.4	2.91	3.31	33	5.9	330	2733.6	9.20	9.62	134	134	34.0	39.2	390	10258	15.5	2.0	372	1926	.10	.91	.92	3.63	9.43	8.70
55	1032	2804.5	18.6	2.73	3.61	33	5.0	330	2733.6	9.20	9.62	134	134	34.0	39.2	389	10343	15.9	2.0	273	1339	.10	.83	.84	3.63	9.44	8.70
56	1033	2804.8	15.3	2.98	3.70	33	5.0	340	2733.6	9.20	9.64	134	134	34.1	38.6	337	10447	16.2	2.0	318	1358	.10	.87	.88	3.63	9.43	8.70
57	1034	2805.1	21.3	2.99	3.70	33	6.1	350	2733.6	9.20	9.64	133	133	34.1	38.6	335	10522	16.5	2.0	242	1331	.10	.84	.85	3.63	9.43	8.70
58	1035	2805.4	15.9	3.02	3.71	39	5.4	340	2733.6	9.20	9.64	134	134	34.1	38.6	336	10620	16.8	2.0	291	1307	.10	.87	.88	3.63	9.44	8.70
59	1036	2805.7	16.6	3.00	3.85	33	6.0	340	2733.6	9.20	9.64	133	133	34.1	38.6	386	10715	17.1	2.1	288	1776	.10	.88	.89	3.63	9.44	8.70
60	1037	2806.0	21.2	3.00	3.86	33	5.3	330	2733.6	9.20	9.64	134	134	34.1	38.6	336	10789	17.4	2.1	266	1753	.10	.82	.83	3.63	9.44	8.70
61	1038	2806.3	15.7	2.97	3.86	33	5.4	230	2733.6	9.20	9.64	175	175	34.1	38.6	387	10897	17.7	2.1	315	1723	.10	.88	.89	3.64	9.44	8.70
62	1039	2806.6	29.1	2.92	4.19	30	5.1	270	2733.6	9.20	9.64	165	165	34.1	38.6	385	10952	18.0	2.1	235	1699	.10	.75	.76	3.64	9.44	8.70
63	1041	2806.9	8.50	2.46	4.31	30	7.0	270	2733.6	9.20	9.64	164	164	34.1	38.6	333	11127	18.3	2.1	332	1677	.11	1.05	1.06	3.64	9.44	8.70
+ POOH to retrieve Core #2 at 2807.3m.																											
+ NB#15 SMITH F2 12.25" 3x14 jets. Start depth 2807.3m.																											
Ream rat-hole of Core #2 from 2733.6m.																											
Date Oct 6 '85																											
63	0142	2807.5	42.8	3.64	4.36	36	26.4	2910	2796.9	9.30	9.40	615	453	31.3	46.2	445	12041	.25	2.3	107	15005	.11	.93	.93	3.64	9.40	8.70
69	0142	2807.8	65.6	3.71	3.95	36	37.6	2900	2797.0	9.30	9.40	615	450	31.3	46.2	445	12054	.57	2.3	73	57555	.11	.91	.91	3.64	9.40	8.70
70	0143	2808.1	21.4	3.50	5.17	36	38.9	2920	2797.1	9.30	9.40	616	489	31.3	46.2	446	12137	.87	2.3	216	35813	.11	1.24	1.24	3.64	9.40	8.70