

GEMDAS LOGGING REPORT NO. 54

COMPANY Amoco Aust. WELL Tilana No.1
 DATE 4 Nov. '85 TIME 0500 Hrs
 DEPTH 3900m - 3315m. LAST REPORT DEPTH 3900m.
 RIG OPERATIONS Running 9.625" casing prior to DST's.
 REPORT BY Gary Hodge REPORT RECEIVED BY S. Maxwell. (OPERATOR)

DRILLING REPORT

Bit No.: _____ Type: _____ Size: _____ Jets: _____
 On Bit: Footage: _____ Hours: _____ ROP: _____ WOB: _____ RPM: _____
 Pump Press: _____ SPM: _____ Torque: _____ TBR: _____ CP I: \$ _____ CP B: \$ _____

HYDRAULICS REPORT

Mud Density In: _____ Mud Density Out: _____ ECD: _____ PV/YP: _____
 Gels: _____ Salinity: _____ PPM Cl Solids: _____ %
 Hole Volume: _____ Annular Volume: _____ Tubing Volume: _____ Displaced Volume: _____
 Carbide Lag—Calculated Lag: _____ Flowrate: _____
 Drillpipe Annular Vel (Max. Dia. Sec.): _____ Drillpipe Annular Vel (Open Hole): _____
 Drill Collar Annular Vel (Open Hole): _____ Critical Vel: _____
 Pressure Loss System: _____ Pressure Loss Bit: _____ % Pressure Loss: _____
 Nozzel Vel: _____ Jet Impact Force: _____ HHP: _____

PRESSURE PARAMETERS

Drilling Exponent: _____ Flowline Temperature: _____
 Shale Density: _____ Shale Factor: _____
 Background Gas: _____ Max. Formation Gas: _____ @ _____ Trip Gas: _____ @ _____
 Other Gas: _____
 Fill: _____ Tight Hole: _____
 Cavings: Est %: _____ Average Size: _____

ESTIMATED PORE AND FRACTURE PRESSURE

Kick Tolerance: _____ Min. Estimated Fracture Pressure (Open Hole): _____
 Estimated Pore Pressure: _____ Min. Estimated Pore Pressure (Open Hole): _____ @ _____
 Max. Estimated Pore Pressure (Open Hole): _____ @ _____ Estimated Fracture Pressure at TD: _____

Comments: Drill cement from 3261 - 3315m, circulate hole.
Pull out drill pipe.
Run 9.625" casing (147 lb/ft) - shoe at 3300m.