

85-09-23 1405 ST *
TASROK AA58276
STBY BCAST 176199 CLG

DEPARTMENT OF MINES
RECEIVED/SENT
23 SEP 1985
2.20 AM PM
OPERATOR *BB*

SEPTEMBER 21, 1985

DRILLING WIRE - TILANA NO. 1 - BASS BASIN, AUSTRALIA
=====

AMOCO CORPORATION - CHICAGO
ATTN: T.D. STACY MC 4502
B.G. NEWTON MC 4703
CH-AUP-179-T-933.2-CWW/SCB/CDC/GMK

TX: 020/234991785+

BUREAU OF MINERAL RESOURCES
THE DIRECTOR
ATTN: J. WHITE

TX: AA62109

TASMANIAN DEPARTMENT OF MINES
ATTN: H. MURCHIE

TX: AA58276

MISC-AUP-699-T-933.2-CWW/SCB/CDC/GMK

CC: AMOCO AUSTRALIA PETROLEUM COMPANY
- HOBART ATTN: W.C. COWAN
ABB-AUP-157-T-933.2-CWW/SCB/CDC/GMK

TX: AA58162

DATE : 21 SEPTEMBER 1985
REPORT NO. : 18
DAYS FROM SPUD : 16
TD : 1662 METERS (5452 FT).
PROGRESS : 0
MUD PROPERTIES : MW - 9.0, VIS - 54, API FL - 22
LAST CASING : 13-3/8 AT 1652 METERS (5420 FT.)
BWDUBQWV60) KTNHQBCT MQF-589, : CIRCULATING CASING AFTER CEMENT JOB.

OPERATIONS SUMMARY : P.O.H. WITH RUNNING TOOL. LAY DOWN SAME.
R.I.H. WITH NEW BIT. TAG SHOE AT 1650.8 M (5416'). DRILL OUT SHOE. CLEAN OUT TO 1652.6 M (5422'). CIRC. BOTTOMS UP. P.O.H. R.I.H. WITH CASING HANGER RUNNING TOOL. CIRC. CASING AT 100 SPM 500 PSI. P.O.H. REPLACE O-RINGS ON RUNNING TOOL - R.I.H. CIRC. CASING - 100 SPM 700 PSI. P.O.H. LAY DOWN TOOL. RIG UP SCHLUMBERGER. R.I.H. WITH 13-3/8 EZSV SET AT 1621.5 M (5320'). P.O.H. RIG DOWN SCHLUMBERGER. R.I.H. WITH STINGER ASSEMBLY. TAG EZSV AT 1619 M (5312') DRILLERS DEPTH. CIRC. CASING. TEST CMT. LINES TO 3000 PSI. MIX AND PUMP CEMENT. UNBING FROM EZSV. P.O.H. WITH 13 STANDS D.P. CIRC. RISER THRU CHOKE AND KILL LINES. CIRCULATE CASING CLEAN OF CEMENT WITH SEA WATER 120 BBLs CEMENT CIRCULATED FROM RISER.

TELEX MESSAGE TELETYPE MESSAGE TELETYPE MESSAGE TELETYPE MESSAGE

TELEX MESSAGE TELETYPE MESSAGE TELETYPE MESSAGE TELETYPE MESSAGE