

NOVEMBER 19, 1985

OR-331A

329577

DRILLING WIRE - TILANA NO. 1 - BASS BASIN, AUSTRALIA

AMOCO CORPORATION - CHICAGO
ATTN: T.D. STACY MC 4502
B.G. NEWTON MC 4703
CH-AUP-274-T-933.2-CWW/SCB/CDC/GMK

TX: 020/234991785+

BUREAU OF MINERAL RESOURCES
THE DIRECTOR
ATTN: J. WHITE

TX: AA62109

TASMANIAN DEPARTMENT OF MINES
ATTN: H. MURCHIE

TX: AA58276

MISC-AUP-1007-T-933.2-CWW/SCB/CDC/GMK

CC: AMOCO AUSTRALIA PETROLEUM COMPANY
- HOBART ATTN: C.D. CORNELL
ABB-AUP-235-T-933.2-CWW/SCB/CDC/GMK

TX: AA58162

DATE : 19, NOVEMBER 1985
 REPORT NO. : 77
 DAYS FROM SPUD : 75
 TD : PB 3176 METERS (10,420 FT).
 PROGRESS : 0
 MUD PROPERTIES : MW -9.0 , VIS -110, API FL -4.4
 LAST CASING : 9-5/8 AT 3311.7 METERS (10,865 FT)
 DAILY COST (USD) : 79,671 CUM. COST :8,879,456
 PRESENT OPERATION : RUNNING IN WITH PERFORATING GUN.
 OPERATIONS SUMMARY : BREAK DOWN AND LAY OUT HALLIBURTON TEST TOOLS, LAY OUT AND WASH THRU 6-1/2'' D.C., WHILE DRESSING TEST TOOLS. PICK UP TEST TOOLS, RIH ATTEMPT TO PRESSURE TEST, LEAK AT SLIP JOINT, CHANGE OUT SLIP JOINT, TESTED, OK, RIH WITH 1 STAND D.P. ABOVE SRO NIPPLE AND TESTED TO 5000 PSI. RIH AND DRIFT D.P., FILLED 59 STANDS D.P. WITH SEA WATER CUSHION FOR 1750 PSI UNDER BLANCE, (TOP OF SEA WATER IN D.P. AT 3913 FT) TESTED TO 5000. PICK UP LANDING STRING AND SURFACE TREE, SET PACKER AT 3001.7 M (9848 FT), RIG UP SURFACE TREE AND OTIS. OPEN LPR-N VALVE WITH 1400 PSI, RIH WITH OTIS 2.125'' GAUGE RING, OUT OF TAIL PIPE, POH, RIG DOWN. RIG UP SCHLUMBERGER, PRESSURE TEST SURFACE TREE AND SCHLUMBERGER LUBRICATOR TO 5000 PSI. RIH WITH PERFORATING GUN, STARTED C.C.L. CORRELATION, (WITH NO PROBLEM).

REGARDS
C.W. WARING
AMOCO AUSTRALIA PETROLEUM COMPANY

AAAA*
TASROK AA58276

MESSAGE TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE