OR- 331A

329592

⑥

Schlumberger

BORE HOLE PROFILE.

CSU Field Log

COMPANY: AMOCO AUSTRALIA PETROLEUM CO.

WELL: TILANA #1

FIELD: WILDCAT
RIG : DIAMOND M EPOC
SLAB: TASMANIA
NATION: AUSTRALIA
LOCATION: SHOT POINT 5199 ,
LINE 871-A-50

LATITUDE: 039 53'36.96"S
LONGITUDE: 145 58'42.2" E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM:
LOG MEASURED FROM: KB
22.3 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 22.3 M
DF: 22.0 M
GL: -79.9 M

DATE: 29 OCT 85
RUN NO: 2

OTHER SERVICES-
LDL-CNL-GR
ISF-BHC-MSFL
WST
CST-GR
SLT
RFT-HP-GR

PROGRAM
TAPE NO:
28.2
SERVICE
ORDER NO:
DME851001

DEPTH-DRILLER: 3900.3 M
DEPTH-LOGGER: 3902.0 M
BTM. LOG INTERVAL: 3900.0 M
TOP LOG INTERVAL: 2850.0 M

CASING-DRILLER:	413.0 M	1651.0 M	
CASING-LOGGER:	413.0 M	1651.5 M	
CASING:	20 IN.	13 3/8 IN.	
WEIGHT:	133.000 LB/F	68.0000 LB/F	
BIT SIZE:	26 IN.	17 1/2 IN.	12 1/4 IN.
DEPTH:	416.0 M	1661.0 M	3900.3 M

TYPE FLUID IN HOLE: F/WATER-GEL-POLYMER
DENSITY: 9.90 LB/G
VISCOSITY: 47.0 S
PH: 11.6
FLUID LOSS: 5.3 C3
SOURCE OF SAMPLE: FLOWLINE
RM: .357 OHMM AT 95.0 DEGF
RMF: .309 OHMM AT 72.0 DEGF
RMC: .760 OHMM AT 70.0 DEGF
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .147 OHMM AT 240. DEGF
RMF AT BHT: .099 OHMM AT 240. DEGF
RMC AT BHT: .237 OHMM AT 240. DEGF

TIME CIRC. STOPPED: 1615/28
TIME LOGGER ON BTM.: 0

MAX. REC. TEMP: 240.0 DEGF

LOGGING UNIT NO: 822
LOGGING UNIT LOC: VEA
RECORDED BY: R.WINSLOE
WITNESSED BY: C.E.KONEN

REMARKS:

TOOL RUN WITH 1.5 IN RUBBER FIN STANDOFFS.

EQUIPMENT NUMBERS-

HDS-F 2343	HDH-LB 856	DAM-AC 3909	HDE-F
.	.	.	.
.	.	.	.

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 28.2 FILE 0 31-OCT-85 14:20

EVENT MARK SUMMARY:

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	.100000 M3	LEFT EDGE
ICV	.100000 M3	RIGHT EDGE

5 cm

DEVI(DEG)			
-1.000 9.0000			
RB (DEG)		C1 (IN)	C2 (IN)
-40.00 360.00		20.000 10.000	10.000 20.000
AZIM(DEG)		BS (IN)	BS (IN)
-40.00 360.00		20.000 10.000	10.000 20.000

CP 28.2 FILE 2 31-OCT-85 13:57
DATA ACQUIRED 29-OCT-85 18:31

CP 28.2 FILE 2 31-OCT-85 13:49
DATA ACQUIRED 29-OCT-85 16:51

DEVI(DEG)			
-1.000 9.0000			
RB (DEG)		C1 (IN)	C2 (IN)
-40.00 360.00		20.000 10.000	10.000 20.000
AZIM(DEG)		BS (IN)	BS (IN)
-40.00 360.00		20.000 10.000	10.000 20.000

SENSOR MEASURE POINT TO TOOL ZERO

C1	0.0	METER	C2	0.0	METER
PP	0.0	METER	TEMP	0.0	METER
RC	0.0	METER	EMEX	0.0	METER
FEP2	0.0	METER	REFE	0.0	METER
DEVI	0.0	METER	FEP1	0.0	METER
AZIM	0.0	METER	RB	0.0	METER
RC1	0.0	METER	RC2	0.0	METER
SHDT	0.0	METER	TENS	0.0	METER
FC3	0.0	METER	FC4	0.0	METER
FC1	0.0	METER	FC2	0.0	METER
FC0	0.0	METER			

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
MCT	72		MDEC	0	DEG
BHS	OPEN		STYP	HDSF	
DO	0.0	M	BS	12.2500	IN
PP	NORM				

TAPE NOT MADE