OR-331 A

Schlumberger

LDL-CNL-GR 1/500

CSU Field Log

COMPANY: AMOCO AUSTRALIA PETROLEUM CO. 329598

WELL: TILANA #1

FIELD: WILDCAT
RIG : DIAMOND M EPOC
SLAB: TASMANIA
NATION: AUSTRALIA
LOCATION: SHOT POINT 5199 ,
LINE 871-A-50

LATITUDE: 039 53'36.96"S
LONGITUDE: 145 58'42.2" E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM:
LOG MEASURED FROM: KB
22.3 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 22.3 M
DF: 22.0 M
GL: -79.9 M

DATE: 10 OCT 85
RUN NO: 1

OTHER SERVICES-
ISF-DDBHC-MS
HDT
WST
CST-GR

PROGRAM
TAPE NO:
28.2
SERVICE
ORDER NO:
DME851001

⑫

DEPTH-DRILLER: 3066.0 M
DEPTH-LOGGER: 3070.0 M
BTM. LOG INTERVAL: 3070.0 M
TOP LOG INTERVAL: 1651.5 M

CASING-DRILLER:	413.0 M	1651.0 M	
CASING-LOGGER:	413.0 M	1651.5 M	
CASING:	20 IN.	13 3/8 IN.	
WEIGHT:	133.000 LB/F	68.0000 LB/F	
BIT SIZE:	26 IN.	17 1/2 IN.	12 1/4 IN.
DEPTH:	416.0 M	1661.0 M	3066.0 M

TYPE FLUID IN HOLE: F/WTR GEL POLYMER
DENSITY: 9.30 LB/G
VISCOSITY: 57.0 S
PH: 11.6
FLUID LOSS: 5.5 C3
SOURCE OF SAMPLE: FLOWLINE
RM: .820 OHMM AT 110. DEGF
RMF: .921 OHMM AT 70.0 DEGF
RMC: 1.110 OHMM AT 70.0 DEGF
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: .425 OHMM AT 219. DEGF
RMF AT BHT: .314 OHMM AT 219. DEGF
RMC AT BHT: .378 OHMM AT 219. DEGF

TIME CIRC. STOPPED: 10:00 09/10
TIME LOGGER ON BTM.: 00:23 10/10

MAX. REC. TEMP: 219.0 DEGF

LOGGING UNIT NO: 822
LOGGING UNIT LOC: VEA
RECORDED BY: A. HALIM / A. SUSANTO
WITNESSED BY: C. E. REVILLA

REMARKS:

GR FAILED AT 2421M. FROM 2421M TO CASING SHOE
GR FROM "ISF-DDBHC" RUN PRESENTED.

EQUIPMENT NUMBERS-

DRS-C 2952	NSC-D 1735	PGD 987	GSR-J 6892
CNC-HA 360	CNB-AB 3021	SGC-SA 255	TCC-A 296
AMS 843	TCM-AB 16	NSM-A 2866	

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 28.2 FILE 0 10-OCT-85 13:44
DATA ACQUIRED NA

EVENT MARK SUMMARY:

5 cm

OUTPUT	INTERVAL BETWEEN PIPS	DEPTH TRACK EDGE
IHV	.100000 M3	LEFT EDGE

DRHO(G/C3) -.2500 .25000
BS (IN) 10.000 20.000
PEF 0.0 10.000
CALI(IN) 10.000 20.000
NPHI .45000 -.1500
GR (GAPI) 0.0 150.00
RHOB(G/C3) 1.9500 2.9500

CP 28.2 FILE 101 10-OCT-85 13:17
DATA ACQUIRED NA

CP 28.2 FILE 101 10-OCT-85 13:04
DATA ACQUIRED NA

TENS(LB) 7000.0 2000.0
DRHO(G/C3) -.2500 .25000
BS (IN) 10.000 20.000
PEF 0.0 10.000
CALI(IN) 10.000 20.000
NPHI .45000 -.1500
GR (GAPI) 0.0 150.00
RHOB(G/C3) 1.9500 2.9500

SENSOR MEASURE POINT TO TOOL ZERO

MTEM	11.89 METER	MRES	11.89 METER
STSG	-.28 METER	GR	9.83 METER
NCNL	7.24 METER	FCNL	7.24 METER
LITH	.79 METER	SCNL	-.28 METER
LS	.79 METER	LL	.79 METER
SS1	.64 METER	LU	.79 METER
CALI	.81 METER	SS2	.64 METER
NRAT	7.24 METER	TENS	-.28 METER

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
SHT	80.0000	DEGF	TD	3048.00	M
HC	CALI		PSNR	2.27300	
FD	1.00000	G/C3	MATR	LIME	
WMUD	9.20000	LB/G	MDEN	2.71000	G/C3
DHC	NONE		BFM	LIQU	
BS	12.2500	IN	BHS	OPEN	
PP	NORM		DO	0.0	M

TAPE NOT MADE

Schlumberger

LDL-CNL-GR 1/500

CSU Field Log