COMPANY: AMOCO AUSTRALIA PETROLEUM CO.
WELL: TILANA #1
FIELD: -
AREA: OTWAY BASIN
LOCATION: VICTORIA
LOCATION: 38 DEG 08' S
LOCATION: 142 DEG 48' E

PERM. DATUM: MEAN SEA LEVEL
LOG MEASURED FROM: KB 25.0 M ABOVE PERM. DATUM
DRL. MEASURED FROM: KELLY BUSHING

ELEVATION(S): KB: 25.0
DERRICK FLOOR: 0.0
GROUND/MUD LINE: -200.0
WATER DEPTH: 200.0

DATE: 27 OCT 84
RUN NO: ONE

DEPTH-DRILLER: 2000.0 M
DEPTH-LOGGER: 2000.0 M
BTM LOG INTERVAL: 2000.0 M
TOP LOG INTERVAL: 200.0 M

CASING-DRILLER: 13.375 @ 1000.0 M
CASING-LOGGER: 13.375 @ 1000.0 M
BIT SIZE: 12.250 IN FROM 1000.0 TO 2000.0 M
TYPE FLUID IN HOLE: KCL/POLYMER
DENSITY: 10.00 LB/G
VISCOSITY: 42.0 S
PH: 9.5
FLUID LOSS: 5.0 CC
SOURCE OF SAMPLE: FLOWLINE
RM @ MEAS TEMP: 0.220 @ 60.0 DEGF
RMF @ MEAS TEMP: 0.200 @ 60.0 DEGF
RMC @ MEAS TEMP: 0.300 @ 60.0 DEGF
RM @ BHT: 0.120 @ 200.0 DEGF
TIME CIRC. STOPPED: 14:30 HRS
TIME LOGGER ON BTM: 20:00 HRS
MAX. REC. TEMP.: 200.0 DEGF
EQUIPMENT NO.: 997
LOCATION: TILANA
RECORDED BY: P.WILLIS
WITNESSED BY: M.CLARKE

REMARKS:
A TOW BOARD WAS USED.
ALL DEPTHS REFERRED TO KB DATUM.
RUN 1 LOGGED WITH CALIPER.

EQUIPMENT NUMBERS:

UNIT NAME	UNIT NO	BASE OR LOCN	UNIT NAME	UNIT NO
DLL	3974	1	LSS	3974
CNL	3974	1		

THE DATA PRESENTED HERE WAS RECORDED ON ELECTRONIC EQUIPMENT MANUFACTURED BY SCHLUMBERGER AND SERVICED BY SCHLUMBERGER OFFSHORE SERVICES. WE DO NOT, HOWEVER, GUARANTEE THE ACCURACY OR CORRECTNESS OF INTERPRETATIONS AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

SP 200.0 | CALI 6 INCHES 16 | DT 150 US/F 50
-200.125 _M/DEP
-200.125 _M/DEP

SP 200.0 | CALI 6 INCHES 16 | DT 150 US/F 50
-200.125 _M/DEP
-200.125 _M/DEP

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
MDEN 2.5			CALI ATTN		
MATR SS			CALI MNEM		
MINV 1.05			CALI 6.0		
MN 1.5			CALI 16.0		
RXO 10.0			CALIBRATION		

TAPE NOT READ

SP 200.0 | CALI 6 INCHES 16 | DT 150 US/F 50
-200.125 _M/DEP
-200.125 _M/DEP